




Assignment Project Exam Help
Oracle Machines
<https://powcoder.com>

Beyond C.E. sets
Add WeChat powcoder



Assignment Project Exam Help

Co-hosted by Paul

<https://powcoder.com>

Add WeChat powcoder

From before

- C.e. sets are those a **computer** can list

Assignment Project Exam Help

- Computable: a computer can list them, and can also list their complements

<https://powcoder.com>

Add WeChat powcoder

- The set $K = \{x: \varphi_x(x) \downarrow\}$ is c.e. but not computable
- \bar{K} (the complement of K) is not c.e.

About c.e. sets

- We first defined a set to be c.e. if (means iff) it is empty or the range of a computable function
Assignment Project Exam Help
- We showed that a set is c.e. iff it is the range of a partial computable function
<https://powcoder.com>
Add WeChat powcoder
- We also showed that a set is c.e. iff it is the **domain** of a partial computable function

Proof:

Let A be a c.e. set

If A is empty, then A is the domain of the empty function given by the program which doesn't halt on any input

<https://powcoder.com>

If A is not empty, then it is the range of a computable function, say $A = \{f(0), f(1), f(2), \dots\}$.

Let $\varphi(x) = \mu y[f(y) = x]$. Then $\text{dom}(\varphi) = A$

Let's analyze the last definition of C.E.

- A is c.e. iff it is the domain of a p.c. function f .

Assignment Project Exam Help

- Given any x , if x is in A , then the $f(x) \downarrow$, and if x is not in A , then $f(x) \uparrow$

<https://powcoder.com>

Add WeChat powcoder

- So basically, we have a program that will confirm that YES if x is in A , and otherwise the program tells us nothing

Notation

- The domain of φ_e is denoted by W_e

Assignment Project Exam Help

- W_e is the e-th c.e. set

<https://powcoder.com>

Add WeChat powcoder

C.E. and \exists

- There is a strong relationship between c.e. and the existential quantifier

Assignment Project Exam Help

- If A is c.e., then for some e , x is in A iff $\exists s \varphi_{e,s}(x) \downarrow$

Where, roughly, $\varphi_{e,s}(x) \downarrow$ means that the computation halts within s steps (or stages).

- Note that $\{(e, s, x) : \varphi_{e,s}(x) \downarrow\}$ can be regarded as a relation $R(x_1, x_2, x_3)$

Computable Relations

- Recall, a binary relation over sets X, Y is a subset of the Cartesian product
$$X \times Y$$

Assignment Project Exam Help

- More generally, an n -ary relation over sets X_1, \dots, X_n is a subset of
$$X_1 \times \dots \times X_n$$

Add WeChat powcoder

- An n -ary relation on \mathbb{N} is one for which $X_1 = \dots = X_n = \mathbb{N}$
- A relation on \mathbb{N} is computable if it is computable as a set
- We say a relation is c.e. if it is c.e. as a set.

Example

- $R = \{(x, y, z) \in \mathbb{N}^3 : x < y \text{ and } z = 2x\}$

We have $R(1,2,2), R(0,3,0), R(10,11,20)$

But $\neg R(0,2,2), \neg R(0,0,0), \neg R(10,11,11)$

Here \neg means negation

- R is clearly computable. There's a program which when given any tuple (a, b, c) it can decide if $R(a, b, c)$ or $\neg R(a, b, c)$
- Note that we can regard relations as Boolean valued functions

- $R_2 = \{(x, e) \in \mathbb{N}^2: \varphi_e(x) \downarrow\}$

Not computable (why?)

Assignment Project Exam Help

<https://powcoder.com>

But it is c.e. because, for any given values a, b , if $R_2(a, b)$ then we can confirm that computably

Add WeChat powcoder

Special Cases

- Note that a function is a binary relation

Assignment Project Exam Help

- A non-empty subset of X is a unary (1-ary) relation on X .

<https://powcoder.com>

- There are 0-ary relations (TRUE and FALSE)

Add WeChat powcoder

- There is the empty relation \emptyset which is the same as FALSE (holds for nothing)

Deeper analysis of $\varphi_e(x) \downarrow$

- We assume $s > x$ and $s > e$ when we write $\varphi_{e,s}(x) \downarrow$

Assignment Project Exam Help

<https://powcoder.com>

- When we write $\varphi_{e,s}(x) \downarrow = y$, we assume that s is greater than x, e, y

Add WeChat powcoder

- Recall that the following ternary relation is computable
 $\{(e, s, x) : \varphi_{e,s}(x) \downarrow\}$

One can prove that:

A relation $R(x, y)$ is c.e. iff there exists a computable relation $C(a, x, y)$

such that for all x, y

$$R(x, y) \iff \exists a C(a, x, y)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Arithmetical Hierarchy

- We use Σ_1^0 to denote the class of relations (formulas) obtained as $\exists \bar{a} C(\bar{a}, \bar{x})$ using some computable relation C
Assignment Project Exam Help
- Π_1^0 denotes the class of relations (formulas) obtained as $\forall \bar{a} C(\bar{a}, \bar{x})$ using some computable relation C
<https://powcoder.com>
Add WeChat powcoder
- Note that if a set is Σ_1^0 then its complement is Π_1^0 , and vice versa

Going higher

- Π_2^0 denotes the class of relations (formulas) obtained as $\forall \bar{a} \exists \bar{b} C(\bar{a}, \bar{b}, \bar{x})$ using some computable relation C
Or equivalently $\forall \bar{a} D(\bar{a}, \bar{x})$ for some Σ_1^0 relation D
- Σ_2^0 denotes the class of relations (formulas) obtained as $\exists \bar{a} \forall \bar{b} C(\bar{a}, \bar{b}, \bar{x})$ using some computable relation C

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

In general

- Π_{n+1}^0 denotes the class of relations (formulas) obtained as $\forall \bar{a} D(\bar{a}, \bar{x})$ for some Σ_n^0 relation D
Assignment Project Exam Help
- Σ_{n+1}^0 denotes the class of relations (formulas) obtained as $\exists \bar{a} D(\bar{a}, \bar{x})$ for some Π_n^0 relation D
<https://powcoder.com>
Add WeChat powcoder
- Note that, for all n , $\Sigma_n^0 \cup \Pi_n^0 \subsetneq \Sigma_{n+1}^0 \cap \Pi_{n+1}^0$

- Recall we mentioned that

A relation $R(x, y)$ is c.e. iff there exists a computable relation $C(a, x, y)$ such that for all x, y

$$R(x, y) \Leftrightarrow \exists a C(a, x, y)$$

<https://powcoder.com>

- This means that C.E. = Σ_1^0
- BTW, Computable = $\Sigma_0^0 = \Pi_0^0$

The Normal Form Theorem for C.E. Sets

- The following are equivalent:

Assignment Project Exam Help

- A is c.e.

<https://powcoder.com>

- A is Σ_1^0

- $A = W_e$ for some $e \in \mathbb{N}$

Add WeChat powcoder

Relative Computability

- We have just seen that C.E. = Σ_1^0

Assignment Project Exam Help

- How about Σ_2^0 ? Or more generally, Σ_{n+1}^0 ?

<https://powcoder.com>

- Are they c.e. in some sense w.r.t. some higher level?

Add WeChat powcoder

- Indeed, it is all about the computable function which enumerates the set

Oracle Machines and Relative Computability

- Imagine a function which is computable but only after giving it certain knowledge

Assignment Project Exam Help

- Imagine its program which allows using the indicator function of some set A (not necessarily computable)

<https://powcoder.com>

Add WeChat powcoder

- Such a function is said to be (relatively) computable from A

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Turing Reducibility

- A set S is said to be Turing reducible to a set B ($S \leq_T B$) if the characteristic function of S is computable from B .
[Assignment Project Exam Help](https://powcoder.com)
- If $S \leq_T B$ and $S \geq_T B$, then we write $S \equiv_T B$ and say they are Turing equivalent
<https://powcoder.com>
Add WeChat powcoder
- \leq_T is a partial order, and \equiv_T is an equivalence relation

Turing Degrees

- The equivalence classes corresponding to \equiv_T are called the Turing degrees (often denoted by bold lowercase **a**, **b**, **c**, ..)
<https://powcoder.com>
- They are also known as degrees of unsolvability
Add WeChat: powcoder
- All computable sets have the same Turing degree (why?)

Structure of the set of Turing Degrees

- Partially ordered but not linearly ordered (there are incomparable degrees)

Assignment Project Exam Help

<https://powcoder.com>

- There is a smallest Turing degree which is the Turing degree of the empty set (which is also the Turing degree of any computable set)

Add WeChat powcoder

Notation

- P_e^A, Φ_e^A, W_e^A

Program with oracle A , p.c. function with oracle A , A -c.e. set

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How to get higher degrees? (the Jump operator)

- Given a set A , consider the halting set with respect to A :

$$A' = \{x \mid \exists y (x \leq y \wedge \phi_y^A(x) \downarrow)\} = \{x \mid x \in W_x^A\}$$

- This set is called the *jump* of A and we have that $A <_T A'$

<https://powcoder.com>
Add WeChat powcoder

- $\emptyset' = K$
- $A \equiv_T B$ implies $A' \equiv_T B'$
- A' is A -c.e. but not A -computable

Iterating the jump

- $\emptyset'', \emptyset''', \dots$

- $\emptyset^{(2)} = \emptyset''$

- $\emptyset^{(n)}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- $\deg(\emptyset) = \mathbf{0}$


Assignment Project Exam Help

- $\deg(A)'$ is defined as $\deg(A')$

<https://powcoder.com>

- $\deg(\emptyset^{(n)}) = \mathbf{0}^{(n)}$


Add WeChat powcoder




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
C.E./ Co-c.e.



Computable level



Other Reducibilities

- Note that Turing reducibility does not distinguish a set from its complement (for any set A , $A \equiv_T \bar{A}$)
[Assignment Project Exam Help](https://powcoder.com)
- But clearly both sets can be very different in terms of computability properties. Example: K and \bar{K}
<https://powcoder.com>
[Add WeChat powcoder](https://powcoder.com)
- Similar properties can be maintained by stronger reducibilities

m-reducibility (many-one reducibility)

- $A \leq_m B$ (A is m-reducible to B) if there exists a computable function f such that: for every $x \in \mathbb{N}$,

Assignment Project Exam Help

<https://powcoder.com>
 $x \in A \text{ iff } f(x) \in B$

Add WeChat powcoder