

Assignment Project Exam Help

Add WeChat powcoder

CSC373

Assignment Project Exam Help

Week 3: <https://powcoder.com> Dynamic Programming

Add WeChat powcoder

Nisarg Shah

Recap

Add WeChat powcoder

- Greedy Algorithms

- Interval scheduling
- Interval partitioning
- Minimizing lateness
- Huffman encoding
- ...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

5.4 Warning: Greed is Stupid

Assignment Project Exam Help

Add WeChat powcoder

If we're very very very very lucky, we can bypass all the recurrences and tables and so forth, and solve the problem using a *greedy* algorithm. The general greedy strategy is look for the best first step, take it, and then continue. While this approach seems very natural, it almost never works; optimization problems that can be solved correctly by a greedy algorithm are *very* rare. Nevertheless, for many problems that should be solved by dynamic programming, many students' first intuition is to apply a greedy strategy.

For example, a greedy algorithm for the edit distance problem might look for the longest common substring of the two strings, match up those substrings (since those substitutions don't cost anything), and then recursively look for the edit distances between the left halves and right halves of the strings. If there is no common substring—that is, if the two strings have no characters in common—the edit distance is clearly the length of the larger string. If this sounds like a stupid hack to you, pat yourself on the back. It isn't even *close* to the correct solution.

Assignment Project Exam Help

<https://powcoder.com>

Everyone should tattoo the following sentence on the back of their hands, right under all the rules about logarithms and big-Oh notation:

Add WeChat powcoder

**Greedy algorithms never work!
Use dynamic programming instead!**

What, never?

No, never!

What, *never*?


Well... hardly ever.⁶

Jeff Erickson on greedy algorithms...

Assignment Project Exam Help

The 1950s were not good years for mathematical research. We had a very interesting gentleman in Washington named Wilson. He was secretary of Defense, and he actually had a pathological fear and hatred of the word 'research'. I'm not using the term lightly; I'm using it precisely. His face would suffuse, he would turn red, and he would get violent if people used the term 'research' in his presence. You can imagine how he felt, then, about the term 'mathematical'. The RAND Corporation was employed by the Air Force, and the Air Force had Wilson as its boss, essentially. Hence, I felt I had to do something to shield Wilson and the Air Force from the fact that I was really doing mathematics inside the RAND Corporation. What title, what name, could I choose?

— Richard Bellman, on the origin of his term 'dynamic programming' (1984)



Richard Bellman's quote from Jeff Erickson's book

Assignment Project Exam Help

Dynamic Programming

Add WeChat powcoder

- Outline

- Breaking the problem down into simpler subproblems, solve each subproblem just once, and store their solutions.
- The next time the same subproblem occurs, instead of recomputing its solution, simply look up its previously computed solution.
- Hopefully, we save a lot of computation at the expense of modest increase in storage space.
- Also called “memoization”

- How is this different from divide & conquer?

Assignment Project Exam Help

Weighted Interval Scheduling

Add WeChat powcoder

- Problem

- Job j starts at time s_j and finishes at time f_j
- Each job j has a weight w_j
- Two jobs are compatible if they don't overlap
- **Goal:** find a set S of mutually compatible jobs with highest total weight $\sum_{j \in S} w_j$

- Recall: If all $w_j = 1$, then this is simply the interval scheduling problem from last week
 - Greedy algorithm based on earliest finish time ordering was optimal for this case

Assignment Project Exam Help

Recall: Interval Scheduling


Add WeChat powcoder

- What if we simply try to use it again?
 - Fails spectacularly!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Assignment Project Exam Help Weighted Interval Scheduling

- What if we use other orderings?
 - By weight: choose jobs with highest w_j first
 - Maximum weight per time: choose jobs with highest $w_j/(f_j - s_j)$ first
 - ... <https://powcoder.com>
- None of them
 - They're arbitrarily worse than the optimal solution
 - In fact, under a certain formalization, “no greedy algorithm” can produce any “decent approximation” in the worst case (beyond this course!)

Assignment Project Exam Help Weighted Interval Scheduling

• Convention

- Jobs are sorted by finish time: $f_1 \leq f_2 \leq \dots \leq f_n$
- $p[j]$ = largest index $i < j$ such that job i is compatible with job j (i.e. $f_i < s_j$)



Among jobs before job j , the ones compatible with it are precisely $1 \dots i$

E.g.

$$\begin{aligned} p[8] &= 1, \\ p[7] &= 3, \\ p[2] &= 0 \end{aligned}$$

Assignment Project Exam Help Weighted Interval Scheduling

- The DP approach

- Let OPT be an optimal solution

- Two options regarding job n :

- Option 1: Job n is in OPT

- Can't use incompatible jobs $\{p[n] + 1, \dots, n - 1\}$
- Must select optimal subset of jobs from $\{1, \dots, p[n]\}$

- Option 2: Job n is not in OPT

- Must select optimal subset of jobs from $\{1, \dots, n - 1\}$

- OPT is best of both options

- Notice that in both options, we need to solve the problem on a prefix of our ordering

Assignment Project Exam Help Weighted Interval Scheduling

- The DP approach

- $OPT(j)$ = max total weight of compatible jobs from $\{1, \dots, j\}$

- Base case: $OPT(0) = 0$

- Two cases regarding job j :

- Job j is selected: optimal weight is $w_j + OPT(p[j])$

- Job j is not selected: optimal weight is $OPT(j - 1)$

- Bellman equation:

$$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max\{OPT(j - 1), w_j + OPT(p[j])\} & \text{if } j > 0 \end{cases}$$

Assignment Project Exam Help

Brute Force Solution

Add WeChat powcoder

BRUTE-FORCE ($n, s_1, \dots, s_n, f_1, \dots, f_n, w_1, \dots, w_n$)

Sort jobs by finish time and renumber so that $f_1 \leq f_2 \leq \dots \leq f_n$.

Compute $p[1], p[2], \dots, p[n]$ via binary search.

RETURN COMPUTE-OPT(n).

<https://powcoder.com>

COMPUTE-OPT(j)

IF ($j = 0$)

 RETURN 0.

ELSE

 RETURN $\max \{ \text{COMPUTE-OPT}(j-1), w_j + \text{COMPUTE-OPT}(p[j]) \}$.

Assignment Project Exam Help

Brute Force Solution

Add WeChat powcoder

COMPUTE-OPT(j)

IF ($j = 0$)

RETURN 0.

ELSE

RETURN $\max \{ \text{COMPUTE-OPT}(j-1), w_j + \text{COMPUTE-OPT}(p[j]) \}.$

Add WeChat powcoder

• Q: Worst-case running time of COMPUTE-OPT(n)?

- a) $\Theta(n)$
- b) $\Theta(n \log n)$
- c) $\Theta(1.618^n)$
- d) $\Theta(2^n)$

Assignment Project Exam Help

Brute Force Solution

Add WeChat powcoder

- Brute force running time
 - It is possible that $p(j) = j - 1$ for each j
 - Calling COMPUTE-OPT($j - 1$) and COMPUTE-OPT($p[j]$) separately would take 2^n steps
 - We can slightly optimize:
 - If $p[j] = j - 1$, call it just once, else call them separately
 - Now, the worst case is when $p(j) = j - 2$ for each j
 - **Running time:** $T(n) = T(n - 1) + T(n - 2)$
 - Fibonacci, golden ratio, ... ☺
 - $T(n) = O(\varphi^n)$, where $\varphi \approx 1.618$

Assignment Project Exam Help

Dynamic Programming

Add WeChat powcoder

- Why is the runtime high?
 - Some solutions are being computed many, many times
 - E.g. if $p[5] = 3$, then $\text{COMPUTE-OPT}(5)$ calls $\text{COMPUTE-OPT}(4)$ and $\text{COMPUTE-OPT}(3)$
 - But $\text{COMPUTE-OPT}(4)$ in turn calls $\text{COMPUTE-OPT}(3)$ again
- Memoization trick
 - Simply remember what you've already computed, and re-use the answer if needed in future

Dynamic Program: Top-Down

Add WeChat powcoder

- Let's store $\text{COMPUTE-OPT}(j)$ in $M[j]$

$\text{TOP-DOWN}(n, s_1, \dots, s_n, f_1, \dots, f_n, w_1, \dots, w_n)$

Sort jobs by finish time and renumber so that $f_1 \leq f_2 \leq \dots \leq f_n$.

Compute $p[1], p[2], \dots, p[n]$ via binary search.

$M[0] \leftarrow 0$.  global array

RETURN $\text{M-COMPUTE-OPT}(n)$.

$\text{M-COMPUTE-OPT}(j)$

IF ($M[j]$ is uninitialized)

$M[j] \leftarrow \max \{ \text{M-COMPUTE-OPT}(j-1), w_j + \text{M-COMPUTE-OPT}(p[j]) \}$.

RETURN $M[j]$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic Program: Top-Down

Add WeChat powcoder

- **Claim:** This memoized version takes $O(n \log n)$ time
 - Sorting jobs takes $O(n \log n)$
 - It also takes $O(n \log n)$ to do n binary searches to compute $p(j)$ for each j
 - M-Compute-OPT(j) is called *at most once* for each j
 - Each such call takes $O(1)$ time, not considering the time taken by any subroutine calls
 - So M-Compute-OPT(n) takes only $O(n)$ time
 - Overall time is $O(n \log n)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic Program: Bottom-Up

Add WeChat powcoder

- Find an order in which to call the functions so that the sub-solutions are ready when needed

Assignment Project Exam Help

BOTTOM-UP($n, s_1, \dots, s_n, f_1, \dots, f_n, w_1, \dots, w_n$)

<https://powcoder.com>

Sort jobs by finish time and renumber so that $f_1 \leq f_2 \leq \dots \leq f_n$.

Compute $p[1], p[2], \dots, p[n]$.


Add WeChat powcoder

$M[0] \leftarrow 0.$

previously computed values

FOR $j = 1$ TO n

$M[j] \leftarrow \max \{ M[j-1], w_j + M[p[j]] \}.$



Top-Down vs Bottom-Up

Add WeChat powcoder

- Top-Down may be preferred...

- ...when not all sub-solutions need to be computed on some inputs

- ...because one does not need to think of the “right order” in which to compute sub-solutions

Assignment Project Exam Help

<https://powcoder.com>

- Bottom-Up may be preferred.

Add WeChat powcoder

- ...when all sub-solutions will anyway need to be computed

- ...because it is faster as it prevents recursive call overheads and unnecessary random memory accesses

- ...because sometimes we can free-up memory early

Assignment Project Exam Help

Optimal Solution

Add WeChat powcoder

- This approach gave us the optimal value
- What about the actual solution (subset of jobs)?
 - Idea: Maintain the optimal value and an optimal solution
 - So, we compute two quantities:

Assignment Project Exam Help

<https://powcoder.com>

$$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max\{OPT(j-1), w_j + OPT(p[j])\} & \text{if } j > 0 \end{cases}$$

Add WeChat powcoder

$$S(j) = \begin{cases} \emptyset & \text{if } j = 0 \\ S(j-1) & \text{if } j > 0 \wedge OPT(j-1) \geq w_j + OPT(p[j]) \\ \{j\} \cup S(p[j]) & \text{if } j > 0 \wedge OPT(j-1) < w_j + OPT(p[j]) \end{cases}$$

Assignment Project Exam Help

Optimal Solution

Add WeChat powcoder

$$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max\{OPT(j-1), v_j + OPT(p[j])\} & \text{if } j > 0 \end{cases}$$

$$S(j) = \begin{cases} \emptyset & \text{if } j = 0 \\ S(j-1) & \text{if } j > 0 \wedge OPT(j-1) \geq v_j + OPT(p[j]) \\ \{j\} \cup S(p[j]) & \text{if } j > 0 \wedge OPT(j-1) < v_j + OPT(p[j]) \end{cases}$$

Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder

This works with both top-down (memoization) and bottom-up approaches.

In this problem, we can do something simpler: just compute OPT first, and later compute S using only OPT .

Assignment Project Exam Help

Optimal Solution

Add WeChat powcoder

$$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max\{OPT(j-1), v_j + OPT(p[j])\} & \text{if } j > 0 \end{cases}$$

$$S(j) = \begin{cases} \perp & \text{if } j = 0 \\ L & \text{if } j > 0 \wedge OPT(j-1) \geq v_j + OPT(p[j]) \\ R & \text{if } j > 0 \wedge OPT(j-1) < v_j + OPT(p[j]) \end{cases}$$

Assignment Project Exam Help
<https://powcoder.com>

- Save space by storing only one bit of information for each j : which option yielded the max weight
 - To reconstruct the optimal solution, start with $j = n$
 - If $S(j) = L$, update $j \leftarrow j - 1$
 - If $S(j) = R$, add j to the solution and update $j \leftarrow p[j]$
 - If $S(j) = \perp$, stop
- Add WeChat powcoder

Optimal Substructure Property

Add WeChat powcoder

- Dynamic programming applies well to problems that have **optimal substructure property**
 - Optimal solution to a problem can be computed easily given optimal solution to subproblems
- Recall: **divide-and-conquer** also uses this property
 - Divide-and-conquer is a special case in which the subproblems don't "overlap"
 - So there's no need for memoization
 - In dynamic programming, two of the subproblems may in turn require access to solution to the same subproblem

<https://powcoder.com>

Add WeChat powcoder


Assignment Project Exam Help

Knapsack Problem

Add WeChat powcoder

- Problem

- n items: item i provides value $v_i > 0$ and has weight $w_i > 0$
- Knapsack has weight capacity W
- Assumption: W , v_i -s, and w_i -s are all integers
- Goal: pack the knapsack with a collection of items with highest total value given that their total weight is at most W



i	v_i	w_i
1	\$1	1 kg
2	\$6	2 kg
3	\$18	5 kg
4	\$22	6 kg
5	\$28	7 kg

knapsack instance
(weight limit $W = 11$)

A First Attempt

Add WeChat powcoder

- Let $OPT(w)$ = maximum value we can pack with a knapsack of capacity w
 - Goal: Compute $OPT(W)$
 - Claim? $OPT(w)$ must use at least one job j with weight $\leq w$ and then optimally pack the remaining capacity of $w - w_j$
 - Let $w^* = \min_j w_j$
 - $OPT(w) = \begin{cases} 0 & \text{if } w < w^* \\ \max_{j:w_j \leq w} v_j + OPT(w - w_j) & \text{if } w \geq w^* \end{cases}$
- This is wrong!
 - It might use an item more than once!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A Refined Attempt

Add WeChat powcoder

- $OPT(i, w)$ = maximum value we can pack using only items $1, \dots, i$ given capacity w

➤ Goal: Compute $OPT(n, W)$.

Assignment Project Exam Help

- Consider item i

➤ If $w_i > w$, then we can't choose i . Just use $OPT(i - 1, w)$

<https://powcoder.com>

➤ If $w_i \leq w$, there are two cases:

Add WeChat powcoder

○ If we choose i , the best is $v_i + OPT(i - 1, w - w_i)$

○ If we don't choose i , the best is $OPT(i - 1, w)$

$$OPT(i, w) = \begin{cases} 0 & \text{if } i = 0 \\ OPT(i - 1, w) & \text{if } w_i > w \\ \max \{ OPT(i - 1, w), v_i + OPT(i - 1, w - w_i) \} & \text{otherwise} \end{cases}$$

Running Time

Add WeChat powcoder

- Consider possible evaluations $OPT(i, w)$
 - $i \in \{1, \dots, n\}$
 - $w \in \{1, \dots, W\}$ (recall weights and capacity are integers)
 - There are $O(n \cdot W)$ possible evaluations of OPT
 - Each is evaluated at most once (memoization)
 - Each takes $O(1)$ time to evaluate
 - So the total running time is $O(n \cdot W)$
- Q: Is this polynomial in the input size?
 - A: No! But it's pseudo-polynomial.

What if...?

Add WeChat powcoder

- Note that this algorithm runs in polynomial time when the value of W is polynomially bounded in the length of the input

Assignment Project Exam Help

<https://powcoder.com>

- Q: What if instead of the weights being small integers, we were told that the values are small integers?

Add WeChat powcoder

- Then we can use a different dynamic programming approach!

Assignment Project Exam Help

A Different DP

Add WeChat powcoder

- $OPT(i, v)$ = minimum capacity needed to pack a total value of at least v using items $1, \dots, i$

➤ **Goal:** Compute $\max\{v : OPT(i, v) \leq W\}$

- Consider item i

➤ If we choose i , we need capacity $w_i + OPT(i - 1, v - v_i)$

➤ If we don't choose i , we need capacity $OPT(i - 1, v)$

$$OPT(i, v) = \begin{cases} 0 & \text{if } v \leq 0 \\ \infty & \text{if } v > 0, i = 0 \\ \min \left\{ w_i + OPT(i - 1, v - v_i), OPT(i - 1, v) \right\} & \text{if } v > 0, i > 0 \end{cases}$$

Assignment Project Exam Help

A Different DP

Add WeChat powcoder

- $OPT(i, v)$ = minimum capacity needed to pack a total value of at least v using items $1, \dots, i$
 - **Goal:** Compute $\max\{v : OPT(i, v) \leq W\}$
- This approach has running time $O(n \cdot V)$, where $V = v_1 + \dots + v_n$
- So we can get $O(nW)$ or $O(n \cdot V)$
- Can we remove the dependence on both V and W ?
 - Not likely.
 - Knapsack problem is NP-complete (we'll see later).

Assignment Project Exam Help

Looking Ahead: FPTAS

Add WeChat powcoder

- While we cannot hope to solve the problem exactly in time $O(\text{poly}(n, \log W, \log V))$...
 - For any $\epsilon > 0$, we can get a value that is within $1 + \epsilon$ multiplicative factor of the optimal value in time $O\left(\text{poly}\left(n, \log W, \log V, \frac{1}{\epsilon}\right)\right)$ <https://powcoder.com>
 - Such algorithms are known as fully polynomial-time approximation scheme (FPTAS)
 - **Core idea behind FPTAS for knapsack:**
 - Approximate all weights and values up to the desired precision
 - Solve knapsack on approximate input using DP

Assignment Project Exam Help

Single-Source Shortest Paths

Add WeChat powcoder

- Problem

- **Input:** A directed graph $G = (V, E)$ with edge lengths ℓ_{vw} on each edge (v, w) , and a source vertex s
- **Goal:** Compute the length of the shortest path from s to every vertex t

<https://powcoder.com>


- When $\ell_{vw} \geq 0$ for each (v, w) ...
 - Dijkstra's algorithm can be used for this purpose
 - But it fails when some edge lengths can be negative
 - What do we do in this case?

Assignment Project Exam Help

Single-Source Shortest Paths

Add WeChat powcoder

- Cycle length = sum of lengths of edges in the cycle
 - If there is a negative length cycle, shortest paths are not even well defined.
 - You can traverse the cycle arbitrarily many times to get arbitrarily “short” paths
- Assignment Project Exam Help
<https://powcoder.com>



Assignment Project Exam Help


Single-Source Shortest Paths

Add WeChat powcoder

- But if there are no negative cycles...
 - Shortest paths are well-defined even when some of the edge lengths may be negative
- **Claim:** With no negative cycles, there is always a shortest path from any vertex to any other vertex that is **simple**
- Consider the shortest $s \rightsquigarrow t$ path with the fewest edges among all shortest $s \rightsquigarrow t$ paths
- If it has a cycle, removing the cycle creates a path with fewer edges that is no longer than the original path

Optimal Substructure Property

- Consider a simple shortest $s \rightsquigarrow t$ path P
 - It could be just a single edge
 - But if P has more than one edges, consider u which immediately precedes t in the path
 - If $s \rightsquigarrow t$ is shortest, $s \rightsquigarrow u$ must be shortest as well and it must use one fewer edge than the $s \rightsquigarrow t$ path




Optimal Substructure Property

Add WeChat powcoder

- $OPT(t, i)$ = shortest path from s to t using at most i edges
- Then:
 - Either this path uses at most $i - 1$ edges $\Rightarrow OPT(t, i - 1)$
 - Or it uses i edges $\Rightarrow \min_u OPT(u, i - 1) + \ell_{ut}$

Add WeChat powcoder



Optimal Substructure Property

Add WeChat powcoder

- $OPT(t, i)$ = shortest path from s to t using at most i edges

- Then: Assignment Project Exam Help

➤ Either this path uses at most $i - 1$ edges $\Rightarrow OPT(t, i - 1)$

➤ Or it uses i edges $\Rightarrow \min_u OPT(u, i - 1) + \ell_{ut}$

Add WeChat powcoder

$$OPT(t, i) = \begin{cases} 0 & i = 0 \vee t = s \\ \infty & i = 0 \wedge t \neq s \\ \min \{ OPT(t, i - 1), \min_u OPT(u, i - 1) + \ell_{ut} \} & \text{otherwise} \end{cases}$$

➤ Running time: $O(n^2)$ calls, each takes $O(n)$ time $\Rightarrow O(n^3)$

➤ Q: What do you need to store to also get the actual paths?

Assignment Project Exam Help

Side Notes

Add WeChat powcoder

- Bellman-Ford-Moore algorithm

- Improvement over this DP
- Running time $O(mn)$ for n vertices and m edges
- Space complexity reduces to $O(m + n)$

year	worst case	discovered by
1955	$O(n^4)$	Shimbel
1956	$O(m n^2 W)$	Ford
1958	$O(m n^3)$	Bellman, Moore
1983	$O(n^{3/4} m \log W)$	Gabow
1989	$O(m n^{1/2} \log(nW))$	Gabow-Tarjan
1993	$O(m n^{1/2} \log W)$	Goldberg
2005	$O(n^{2.38} W)$	Sankowski, Yuster-Zwick
2016	$\tilde{O}(n^{10/7} \log W)$	Cohen-Mądry-Sankowski-Vladu
20xx	???	

single-source shortest paths with weights between $-W$ and W

Assignment Project Exam Help Maximum Length Paths?

- Can we use a similar DP to compute maximum length paths from s to all other vertices?

- This is well defined when there are no positive cycles, in which case, yes.

- What if there are positive cycles, but we want maximum length *simple* paths?

Assignment Project Exam Help Maximum Length Paths?

- What goes wrong?

- Our DP doesn't work because its path from s to t might use a path from s to u and edge from u to t
- But path from s to u might in turn go through t
- The path may no longer remain simple

- In fact, maximum length simple path is NP-hard
 - Hamiltonian path problem (i.e. is there a path of length $n - 1$ in a given undirected graph?) is a special case

Assignment Project Exam Help

All-Pairs Shortest Paths

Add WeChat powcoder

- Problem

- **Input:** A directed graph $G = (V, E)$ with edge lengths ℓ_{vw} on each edge (v, w) and no negative cycles
- **Goal:** Compute the length of the shortest path from all vertices s to all other vertices t

- Simple idea: Add WeChat powcoder

- Run single-source shortest paths from each source s
- Running time is $O(n^4)$
- Actually, we can do this in $O(n^3)$ as well

Assignment Project Exam Help

All-Pairs Shortest Paths

Add WeChat powcoder

- **Problem**

- **Input:** A directed graph $G = (V, E)$ with edge lengths ℓ_{vw} on each edge (v, w) and no negative cycles
- **Goal:** Compute the length of the shortest path from all vertices s to all other vertices t

- $OPT(u, v, k)$ = length of shortest simple path from u to v in which intermediate nodes from $\{1, \dots, k\}$
- **Exercise:** Write down the recursion formula of OPT such that given subsolutions, it requires $O(1)$ time
- **Running time:** $O(n^3)$ calls, $O(1)$ per call $\Rightarrow O(n^3)$

Assignment Project Exam Help

Chain Matrix Product

Add WeChat powcoder

- Problem

- **Input:** Matrices M_1, \dots, M_n where the dimension of M_i is $d_{i-1} \times d_i$
- **Goal:** Compute $M_1 \cdot M_2 \cdot \dots \cdot M_n$

<https://powcoder.com>

- But matrix multiplication is associative

- $A \cdot (B \cdot C) = (A \cdot B) \cdot C$
- So isn't the optimal solution going to call the algorithm for multiplying two matrices exactly $n - 1$ times?
- **Insight:** the time it takes to multiply two matrices depends on their dimensions

Assignment Project Exam Help

Chain Matrix Product

Add WeChat powcoder

- Assume

- We use the brute force approach for matrix multiplication
- So multiplying $p \times q$ and $q \times r$ matrices requires $p \cdot q \cdot r$ operations

<https://powcoder.com>

- Example: compute $M_1 \cdot M_2 \cdot M_3$

- M_1 is 5×10
- M_2 is 10×100
- M_3 is 100×50
- $(M_1 \cdot M_2) \cdot M_3 \rightarrow 5 \cdot 10 \cdot 100 + 5 \cdot 100 \cdot 50 = 30000$ ops
- $M_1 \cdot (M_2 \cdot M_3) \rightarrow 10 \cdot 100 \cdot 50 + 5 \cdot 10 \cdot 50 = 52500$ ops

Assignment Project Exam Help

Chain Matrix Product

Add WeChat powcoder

- Note

- Our input is simply the dimensions d_0, d_1, \dots, d_n (such that each M_i is $d_{i-1} \times d_i$) and not the actual matrices

Assignment Project Exam Help

- Why is DP right for this problem?

<http://thisproblem.com>

- Optimal substructure property
- Think of the final product computed, say $A \cdot B$
- A is the product of some prefix, B is the product of the remaining suffix
- For the overall optimal computation, each of A and B should be computed optimally

Add WeChat powcoder

Assignment Project Exam Help

Chain Matrix Product

Add WeChat powcoder

- $OPT(i, j)$ = min ops required to compute $M_i \cdot \dots \cdot M_j$

➤ Here, $1 \leq i \leq j \leq n$

➤ Q: Why do we not just care about prefixes and suffices?

- $(M_1 \cdot (M_2 \cdot M_3 \cdot M_4)) \cdot M_5 \Rightarrow$ need to know optimal solution for $M_2 \cdot M_3 \cdot M_4$

Add WeChat powcoder

$$OPT(i, j) = \begin{cases} 0 & i = j \\ \min\{OPT(i, k) + OPT(k + 1, j) + d_{i-1}d_kd_j : i \leq k < j\} & \text{if } i < j \end{cases}$$

➤ Running time: $O(n^2)$ calls, $O(n)$ time per call $\Rightarrow O(n^3)$


Assignment Project Exam Help

Chain Matrix Product

Add WeChat powcoder

This slide is not in the scope of the course

- Can we do better?
 - Surprisingly, yes. But not by a DP algorithm (that I know of)
 - Hu & Shing (1981) developed $O(n \log n)$ time algorithm by reducing chain matrix product to the problem of “optimally” triangulating a regular polygon



Polygon
representation of
(AB)C

Polygon
representation of
A(BC)

Source: Wikipedia

Example

- A is 10×30 , B is 30×5 , C is 5×60
- The cost of each triangle is the product of its vertices
- Want to minimize total cost of all triangles

Edit Distance

Add WeChat powcoder

- Edit distance (aka sequence alignment) problem
 - How similar are strings $X = x_1, \dots, x_m$ and $Y = y_1, \dots, y_n$?

Assignment Project Exam Help

<https://powcoder.com>

- Suppose we can **delete** or **replace** symbols
 - We can do these operations on any symbol in either string
 - How many deletions & replacements does it take to match the two strings?

Add WeChat powcoder

Edit Distance

Add WeChat powcoder

- **Example:** occurrence vs occurrence

o	c	u	r	r	a	n	c	e	-
o	c	c	u	r	r	e	n	c	e

6 replacements, 1 deletion

Add WeChat powcoder

o	c	-	u	r	r	a	n	c	e
o	c	c	u	r	r	e	n	c	e

1 replacement, 1 deletion

Edit Distance

Add WeChat powcoder

- Edit distance problem

- Input

- Strings $X = x_1, \dots, x_m$ and $Y = y_1, \dots, y_n$
 - Cost $d(a)$ of deleting symbol a
 - Cost $r(a, b)$ of replacing symbol a with b
 - Assume r is symmetric, so $r(a, b) = r(b, a)$

- Goal

- Compute the minimum total cost for matching the two strings

- Optimal substructure?

- Want to delete/replace at one end and recurse

Edit Distance

Add WeChat powcoder

- Optimal substructure

- **Goal:** match x_1, \dots, x_m and y_1, \dots, y_n
- Consider the last symbols x_m and y_n
- Three options:
 - Delete x_m , and optimally match x_1, \dots, x_{m-1} and y_1, \dots, y_n
 - Delete y_n , and optimally match x_1, \dots, x_m and y_1, \dots, y_{n-1}
 - Match x_m and y_n , and optimally match x_1, \dots, x_{m-1} and y_1, \dots, y_{n-1}
 - We incur cost $r(x_m, y_n)$
 - Extend the definition of r so that $r(a, a) = 0$ for any symbol a
- Hence in the DP, we need to compute the optimal solutions for matching x_1, \dots, x_i with y_1, \dots, y_j for all (i, j)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Edit Distance

Add WeChat powcoder

- $E[i, j]$ = edit distance between x_1, \dots, x_i and y_1, \dots, y_j
- Bellman equation

Assignment Project Exam Help

$$E[i, j] = \begin{cases} 0 & \text{if } i = j = 0 \\ d(y_j) + E[i, j-1] & \text{if } i = 0 \wedge j > 0 \\ d(x_i) + E[i-1, j] & \text{if } i > 0 \wedge j = 0 \\ \min\{A, B, C\} & \text{otherwise} \end{cases}$$

Add WeChat powcoder

where

$$A = d(x_i) + E[i-1, j], B = d(y_j) + E[i, j-1]$$

$$C = r(x_i, y_j) + E[i-1, j-1]$$

- $O(n \cdot m)$ time, $O(n \cdot m)$ space

Edit Distance

Add WeChat powcoder

$$E[i, j] = \begin{cases} 0 & \text{if } i = j = 0 \\ d(y_j) + E[i, j - 1] & \text{if } i = 0 \wedge j > 0 \\ d(x_i) + E[i - 1, j] & \text{if } i > 0 \wedge j = 0 \\ \min\{A, B, C\} & \text{otherwise} \end{cases}$$

where

$$A = d(x_i) + E[i - 1, j], B = d(y_j) + E[i, j - 1] \\ C = r(x_i, y_j) + E[i - 1, j - 1]$$

Add WeChat powcoder

- Space complexity can be reduced in bottom-up approach
 - While computing $E[\cdot, j]$, we only need to store $E[\cdot, j]$ and $E[\cdot, j - 1]$,
 - So the additional space required is $O(m)$
 - By storing two rows at a time instead, we can make it $O(n)$
 - Usually people include storage of inputs, so it's $O(n + m)$
 - But this is not enough if we want to compute the actual solution

Assignment Project Exam Help Hirschberg's Algorithm

This slide is not in the scope of the course

- The optimal solution can be computed in $O(n \cdot m)$ time and $O(n + m)$ space too!

Assignment Project Exam Help

Programming
Techniques

Editor

A Linear Space
Algorithm for
Computing Maximal
Common Subsequences

D.S. Hirschberg
Princeton University

The problem of finding a longest common subsequence of two strings has been solved in quadratic time and space. An algorithm is presented which will solve this problem in quadratic time and in linear space.

Key Words and Phrases: subsequence, longest common subsequence, string correction, editing

CR Categories: 3.63, 3.73, 3.79, 4.22, 5.25




Assignment Project Exam Help

Hirschberg's Algorithm

Add WeChat powcoder

This slide is not in the scope of the course

- Key idea nicely combines divide & conquer with DP
- Edit distance graph




Assignment Project Exam Help

Hirschberg's Algorithm

Add WeChat powcoder

This slide is not in the scope of the course

- Observation (can be proved by induction)
 - $E[i, j]$ = length of shortest path from $(0, 0)$ to (i, j)




Assignment Project Exam Help

Hirschberg's Algorithm

This slide is not in the scope of the course

- Lemma

- Shortest path from $(0,0)$ to (m,n) passes through $(q, n/2)$ where q minimizes length of shortest path from $(0,0)$ to $(q, n/2)$ + length of shortest path from $(q, n/2)$ to (m,n)




Assignment Project Exam Help

Hirschberg's Algorithm

This slide is not in the scope of the course

- Idea

- Find q using divide-and-conquer
- Find shortest paths from $(0,0)$ to $(q, n/2)$ and $(q, n/2)$ to (m,n) using DP



Assignment Project Exam Help

Application: Protein Matching

Add WeChat powcoder

	A	R	N	D	C	Q	E	G	H	I	L	K	M	F	P	S	T	W	Y	V
A	7	-3	-3	-3	-1	-2	-2	0	-3	-3	-3	-1	-2	-4	-1	2	0	-5	-4	-1
R	-3	9	-1	-3	-6	1	-1	-4	0	-5	-4	3	-3	-5	-3	-2	-2	-5	-4	-4
N	-3	-1	9	2	-5	0	-1	-1	1	-6	-6	0	-4	-6	-4	1	0	-7	-4	-5
D	-3	-3	2	10	-7	-1	2	-3	-2	-7	-7	-2	-6	-6	-3	-1	-2	-8	-6	-6
C	-1	-6	-5	-7	13	-3	-7	-6	-1	1	3	-1	3	-4	-6	-2	-2	-5	-5	-2
Q	-2	1	0	-1	-5	9	3	-4	1	-5	-4	2	-1	-5	-3	-1	-1	-4	-3	-4
E	-2	-1	-1	2	-7	3	8	-4	0	-6	-6	1	-4	-6	-2	-1	-2	-6	-5	-4
G	0	-4	-1	-3	-6	-4	-4	9	-4	-7	-7	3	-5	-6	-5	-1	-3	-6	-6	-6
H	-3	0	1	-2	-7	1	0	-4	12	-6	-5	-1	-4	-2	-4	-2	-3	-4	3	-5
I	-3	-5	-6	-7	-2	-5	-6	-7	-6	7	2	-5	2	-1	-5	-4	-2	-5	-3	4
L	-3	-4	-6	-7	-3	-4	-6	-7	-5	2	6	-4	3	0	-5	-4	-3	-4	-2	1
K	-1	3	0	-2	-6	2	1	-5	-1	5	-4	8	-3	-5	-2	-1	-1	-6	-4	-4
M	-2	-3	-4	-6	-3	-1	-4	-5	-4	2	3	-3	9	0	-4	-3	-1	-3	-3	1
F	-4	-5	-6	-6	-4	-5	-6	-6	-2	-1	0	-5	0	10	-6	-4	-4	0	4	-2
P	-1	-3	-4	-3	-6	-3	-2	-5	-4	-5	-5	-2	-4	-6	12	-2	-3	-7	-6	-4
S	2	-2	1	-1	-2	-1	-1	-1	-2	-4	-4	-1	-3	-4	-2	7	2	-6	-3	-3
T	0	-2	0	-2	-2	-1	-2	-3	-3	-2	-3	-1	-1	-4	-3	2	8	-5	-3	0
W	-5	-5	-7	-8	-5	-4	-6	-6	-4	-5	-4	-6	-3	0	-7	-6	-5	16	3	-5
Y	-4	-4	-4	-6	-5	-3	-5	-6	3	-3	-2	-4	-3	4	-6	-3	-3	3	11	-3
V	-1	-4	-5	-6	-2	-4	-4	-6	-5	4	1	-4	1	-2	-4	-3	0	-5	-3	7