

Function Theory

$\langle v: D \rightarrow b \rangle$ “map v in D to b ”

body (may use v)

domain, type (a bunch)

variable, parameter (a fresh name)


Assignment Project Exam Help

<https://powcoder.com>

$v: D$ is a local axiom within b

Add WeChat powcoder

$\langle n: nat \rightarrow n+1 \rangle$



Renaming

$$\langle n: \text{nat} \rightarrow n+1 \rangle = \langle m: \text{nat} \rightarrow m+1 \rangle$$

Domain

$$\Box f \quad \text{“domain of } f\text{”}$$

$$\Box \langle n: \text{nat} \rightarrow n+1 \rangle = \text{nat}$$

Assignment Project Exam Help

Application

<https://powcoder.com>

$$f x \quad \text{“} f \text{ applied to } x \text{” or “} f \text{ of } x \text{”}$$

$$f(x) \quad (f)x \quad f(x+1) \quad \neg x \quad \neg x$$

Add WeChat powcoder

$$\langle n: \text{nat} \rightarrow n+1 \rangle 3 = 3+1 = 4$$

two variables

$$\text{max} = \langle x: \text{xrat} \rightarrow \langle y: \text{xrat} \rightarrow \text{if } x \geq y \text{ then } x \text{ else } y \text{ fi} \rangle \rangle$$
$$\text{max } 3 = \langle y: \text{xrat} \rightarrow \text{if } 3 \geq y \text{ then } 3 \text{ else } y \text{ fi} \rangle$$
$$\text{max } 3 \ 5 = \text{if } 3 \geq 5 \text{ then } 3 \text{ else } 5 \text{ fi} = 5$$
$$\text{max}(3, 5) = \text{max } 3, \text{max } 5$$

predicate

Assignment Project Exam Help
function with binary result

$$\text{even} = \langle i: \text{int} \rightarrow i/2 \text{ int} \rangle$$

<https://powcoder.com>

relation

Add WeChat powcoder
function with predicate result

$$\text{divides} = \langle n: \text{nat}+1 \rightarrow \langle i: \text{int} \rightarrow i/n: \text{int} \rangle \rangle$$
$$\text{even} = \text{divides } 2$$

selective union

$f|g$ “ f otherwise g ”

$$\Box(f|g) = \Box f, \Box g$$

$$(f|g) x = \text{if } x: \Box f \text{ then } f x \text{ else } g x \text{ fi}$$

abbreviated function notations

Assignment Project Exam Help

<https://powcoder.com>

$$\langle x: xrat \rightarrow \langle y: xrat \rightarrow \text{if } x \geq y \text{ then } x \text{ else } y \text{ fi} \rangle \rangle = \langle x, y: xrat \rightarrow \text{if } x \geq y \text{ then } x \text{ else } y \text{ fi} \rangle$$

Add WeChat powcoder

$$\langle n: nat \rightarrow n+1 \rangle = \langle n \rightarrow n+1 \rangle$$

$$\langle n: 2 \rightarrow 3 \rangle = 2 \rightarrow 3 \quad \text{scope brackets go with variable}$$

$$\langle x: int \rightarrow \langle y: int \rightarrow x+3 \rangle \rangle = x+3 \quad ? \quad \text{but we can't apply it}$$

Scope and Substitution

local

bound, hidden, private

introduction is inside the expression (formal)

nonlocal

global, free, visible, public

introduction is outside the expression (formal or informal)

<https://powcoder.com>

$\langle x \rightarrow x \ y \ \rangle (x \ y)$

Add WeChat powcoder

Scope and Substitution

local

bound, hidden, private

introduction is inside the expression (formal)

nonlocal

global, free, visible, public

introduction is outside the expression (formal or informal)

Assignment Project Exam Help

<https://powcoder.com>

$$= \langle x \rightarrow x \rangle^3$$

Add WeChat powcoder

Scope and Substitution

local

bound, hidden, private

introduction is inside the expression (formal)

nonlocal

global, free, visible, public

introduction is outside the expression (formal or informal)

Assignment Project Exam Help

<https://powcoder.com>

$$\begin{aligned}
 & \langle y \rightarrow x \ y \ \langle x \rightarrow x \ y \ \rangle x \rangle x && \text{rename inner } x \text{ to } z \\
 = & \langle y \rightarrow x \ y \ \langle z \rightarrow z \ y \ \rangle x \ y \ \rangle x && \text{now apply} \\
 = & (\ x \ x \ \langle z \rightarrow z \ x \ \rangle \ x \ x \)
 \end{aligned}$$

Quantifiers

A quantifier is an operator that applies to a function.

It is defined from a two-operand symmetric associative operator.

$\forall p$ is defined from \wedge $\forall \langle r: rat \rightarrow r < 0 \vee r = 0 \vee r > 0 \rangle$

$\exists p$ is defined from \vee $\exists \langle n: nat \rightarrow n = 0 \rangle$

Σf is defined from $+$ $\Sigma \langle n: nat+1 \rightarrow 1/2^n \rangle$

Πf is defined from \times $\Pi \langle n: nat+1 \rightarrow (4 \times n^2) / (4 \times n^2 - 1) \rangle$

abbreviations

$\forall r: rat. r < 0 \vee r = 0 \vee r > 0$

$\Sigma n: nat+1. 1/2^n$

$\forall x, y: rat. x = y+1 \Rightarrow x > y = \forall x: rat. \forall y: rat. x = y+1 \Rightarrow x > y$

$\Sigma n, m: 0, ..10. n \times m = \Sigma n: 0, ..10. \Sigma m: 0, ..10. n \times m$

$$\forall v: null \cdot b = \top$$

$$\forall v: x \cdot b = \langle v: x \rightarrow b \rangle x$$

$$\forall v: A, B \cdot b = (\forall v: A \cdot b) \wedge (\forall v: B \cdot b)$$

$$\exists v: null \cdot b = \perp$$

$$\exists v: x \cdot b = \langle v: x \rightarrow b \rangle x$$

$$\exists v: A, B \cdot b = (\exists v: A \cdot b) \vee (\exists v: B \cdot b)$$

Assignment Project Exam Help

<https://powcoder.com>

$$\Sigma v: null \cdot n = 0$$

Add WeChat powcoder

$$\Sigma v: x \cdot n = \langle v: x \rightarrow n \rangle x$$

$$(\Sigma v: A, B \cdot n) + (\Sigma v: A' B \cdot n) = (\Sigma v: A \cdot n) + (\Sigma v: B \cdot n)$$

$$\Pi v: null \cdot n = 1$$

$$\Pi v: x \cdot n = \langle v: x \rightarrow n \rangle x$$

$$(\Pi v: A, B \cdot n) \times (\Pi v: A' B \cdot n) = (\Pi v: A \cdot n) \times (\Pi v: B \cdot n)$$

build your own

$$\text{MAX } x: \text{rat} \cdot 4 \times x - x^2 = 4$$

$$\text{MAX } v: \text{null} \cdot n = -\infty$$

$$\text{MAX } v: x \cdot n = \langle v: x \rightarrow n \rangle x$$

$$\text{MAX } v: A, B \cdot n = \max (\text{MAX } v: A \cdot n) (\text{MAX } v: B \cdot n)$$

Assignment Project Exam Help

<https://powcoder.com>

$$x \wedge \top = x$$

$$x \vee \perp = x$$

$$x + 0 = x$$

$$x \times 1 = x$$

$$\max x (-\infty) = x$$

Add WeChat powcoder

Solution Quantifier

$\S p$ is the (bunch of) solutions of predicate p

$\S v: \text{null} \cdot b = \text{null}$

$\S v: x \cdot b = \text{if } \langle v: x \rightarrow b \rangle x \text{ then } x \text{ else } \text{null} \text{ fi}$

$\S v: A, B \cdot b = (\S v: A \cdot b), (\S v: B \cdot b)$

Assignment Project Exam Help

<https://powcoder.com>

$\{ \S i: \text{int} \cdot i^2=4 \} = \{-2, 2\}$

$\{ \S n: \text{nat} \cdot n < 3 \} = \{0, ..3\}$

Add WeChat powcoder

An expression talks about its nonlocal variables.

Assignment Project Exam Help
 $\exists n: \text{nat} \cdot x = 2 \times n$

<https://powcoder.com>

Add WeChat ^{says} powcoder

“ x is an even natural”

Function Fine Points


partial:	sometimes no result
total:	always at least one result
deterministic:	always at most one result
nondeterministic:	sometimes more than one result

Assignment Project Exam Help

$\langle n: \text{nat} \cdot n, n+1 \rangle$ <https://powcoder.com> total and nondeterministic

Add WeChat powcoder

$\langle n: \text{nat} \cdot n, n+1 \rangle 3 = 3, 4$



distribution

$$(f, g) x = f x, g x$$

$$f(x, y) = f x, f y$$

$$\text{double} = \langle n: \text{nat} \rightarrow n+n \rangle$$

$$\text{double } 2 = 4$$

$$\text{double } (2, 3) = \text{double } 2, \text{double } 3 = 4, 6$$

$$\text{double } (2, 3) \neq (2, 3) + (2, 3) = 4, 5, 6$$

$$\text{tiny} = \langle S: \text{nat} \rightarrow \$S < 3 \rangle$$

$$\text{tiny } \{\text{null}\} = \top$$

$$\text{tiny } \{0, 1, 2, 3\} = \perp$$

$$\text{tiny } \text{null} = \text{null}$$

function inclusion

$$f: g = \Box g: \Box f \wedge \forall x: \Box g \cdot fx: gx$$

$$A \rightarrow B = \langle a: A \rightarrow B \rangle$$

$A \rightarrow B$ is a function whose domain is A and whose result is B .

$$f: A \rightarrow B = A: \Box f \wedge \forall a: A \cdot fa: B$$

$A \rightarrow B$ is all those functions whose domain is at least A and whose result is at most B .

Add WeChat powcoder

$A \rightarrow B$ is antimonotonic in A and monotonic in B .

$$suc: nat \rightarrow nat$$

function inclusion

$$= nat: \Box suc \wedge \forall n: nat \cdot suc\ n: nat$$

definition of suc

$$= nat: nat \wedge \forall n: nat \cdot n+1: nat$$

reflexivity and definition of nat

$$= \top$$

function inclusion

$$f: g = \Box g: \Box f \wedge \forall x: \Box g \cdot fx: gx$$

$$suc: nat \rightarrow nat$$

$$even: int \rightarrow bin$$

$$max: xrat \rightarrow xrat \rightarrow xrat$$

Assignment Project Exam Help

<https://powcoder.com>

$$A: B \wedge f: B \rightarrow C \wedge C: D \Rightarrow f: A \rightarrow D$$

Add WeChat powcoder

$$(0, \dots, 10): nat \wedge suc: nat \rightarrow nat \wedge nat: int \Rightarrow suc: (0, \dots, 10) \rightarrow int$$

$$\langle f: (0, \dots, 10) \rightarrow int \cdot \forall n: 0, \dots, 10 \cdot even (f n) \rangle suc$$

$$= \forall n: 0, \dots, 10 \cdot even (suc n)$$

$$= \perp$$

function equality

$$f = g \quad = \quad \Box f = \Box g \wedge \forall x: \Box f \cdot fx = gx$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

function composition

If $\neg f: \Box g$ then

$$\Box(g \circ f) = \S x: \Box f \circ x: \Box g$$

$$(g \circ f) x = g (f x)$$

$$\Box(\text{even} \circ \text{suc})$$

$$= \S x: \Box \text{suc} \circ \text{suc } x: \text{even}$$

$$= \S x: \text{nat} \cdot x+1: \text{int}$$

$$= \text{nat}$$

$$(\text{even} \circ \text{suc}) 3 = \text{even} (\text{suc } 3) = \text{even } 4 = \top$$

$$(\neg \text{suc}) 3 = \neg(\text{suc } 3) = \neg 4$$

$$(\neg \text{even}) 3 = \neg(\text{even } 3) = \neg \perp = \top$$

function composition

Suppose $x, y: int$

$f, g: int \rightarrow int$

$h: int \rightarrow int \rightarrow int$

Then

$$\begin{aligned} & h f x g y \\ = & (((h f) x) g) y \\ = & ((h (f x)) g) y \\ = & (h (f x)) (g y) \\ = & h (f x) (g y) \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

list as function

If $m: 0, \dots, \#L$ then

$$\langle n: 0, \dots, \#L \rightarrow Ln \rangle m = L m$$

function \approx list

application \approx indexing

Assignment Project Exam Help

function composition \approx list composition

$$- [3; 5; 2] = [-3; -5; -2]$$

$$suc [3; 5; 2] = [4; 6; 3]$$

$$1 \rightarrow 21 \mid [10; 11; 12] = [10; 21; 12]$$

$$\Sigma L = \Sigma n: 0, \dots, \#L \cdot Ln$$

limit

$f: \text{nat} \rightarrow \text{rat}$

$f_0; f_1; f_2; \dots$ is a sequence of rationals

$$(\text{MAX } m \cdot \text{MIN } n \cdot f(m+n)) \leq (\text{LIM } f) \leq (\text{MIN } m \cdot \text{MAX } n \cdot f(m+n))$$

Assignment Project Exam Help

$$\text{LIM } n \cdot 1/(n+1) = 0$$

$$-1 \leq (\text{LIM } n \cdot (-1)^n) \leq 1$$

$$(\text{MIN } f) \leq (\text{LIM } f) \leq (\text{MAX } f)$$

$$x_{\text{real}} = \text{LIM } (\text{nat} \rightarrow \text{rat})$$

limit

$p: \text{nat} \rightarrow \text{bin}$

$p_0; p_1; p_2; \dots$ is a sequence of binary values

$$\exists m. \forall n. p(m+n) \Rightarrow \text{LIM } p \Rightarrow \forall m. \exists n. p(m+n)$$

Assignment Project Exam Help

$$\exists m. \forall i. i \geq m \Rightarrow p_i \Rightarrow \text{LIM } p$$

<https://powcoder.com>

$$\exists m. \forall i. i \geq m \Rightarrow \neg p_i \Rightarrow \neg \text{LIM } p$$

Add WeChat powcoder

$$\text{LIM } n. 1/(n+1) = 0 \quad = \quad \perp$$