

Computational Linguistics

CSC 2501 / 485
Fall 2018

9A

Assignment Project Exam Help

9A. Mildly Context Sensitive Grammar Formalisms

<https://powcoder.com>

Add WeChat powcoder

Gerald Penn

Department of Computer Science, University of Toronto

Based on slides by David Smith, Dan Klein, Stephen Clark
and Eva Banik

Combinatory Categorical Grammar

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Combinatory Categorical Grammar (CCG)

- Categorical grammar (CG) is one of the oldest grammar formalisms
- *Combinatory Categorical Grammar* now well established and computationally well founded (Steedman, 1996, 2000)
- Account of syntax; semantics; productivity and information structure; automatic parsers; generation

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Combinatory Categorical Grammar (CCG)

- CCG is a lexicalized grammar
- An elementary syntactic structure – for CCG a lexical category – is assigned to each word in a sentence
walked: $S \backslash NP$ “give me an NP to my left and I return a sentence”
- A small number of rules define how categories can combine
- Rules based on the combinators from Combinatory Logic

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

CCG Lexical Categories

- Atomic categories: S , N , NP , PP , ... (not many more)
- Complex categories are built recursively from atomic categories and slashes, which indicate the directions of arguments
- Complex categories encode subcategorisation information
 - intransitive verb: S \NP *walked*
 - transitive verb: (S \NP)/NP *respected*
 - ditransitive verb: ((S \NP)/NP)/NP *gave*
- Complex categories can encode modification
 - PP nominal: (NP \NP)/NP
 - PP verbal: ((S \NP)\ (S \NP))/NP

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Simple CCG Derivation

$$\begin{array}{c}
 \textit{interleukin} - 10 \quad \textit{inhibits} \quad \textit{production} \\
 \hline
 \textit{NP} \quad (S \backslash \textit{NP}) / \textit{NP} \quad \textit{NP} \\
 \hline
 \textit{Add WeChat powcoder} \quad S \backslash \textit{NP} \\
 \hline
 \textit{S}
 \end{array}$$

> forward application
 < backward application

- > forward application
- < backward application

Function Application Schemata

- Forward ($>$) and backward ($<$) application:

Assignment Project Exam Help

$$X / Y \quad Y \Rightarrow X \quad (>)$$

<https://powcoder.com>

$$Y \quad X \backslash Y \Rightarrow X \quad (<)$$

Add WeChat powcoder


Classical Categorical Grammar

- 'Classical' Categorical Grammar only has application rules
- Classical Categorical Grammar is context free

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Classical Categorical Grammar

- 'Classical' Categorical Grammar only has application rules
- Classical Categorical Grammar is context free

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder

Extraction out of a Relative Clause

$\overline{\text{The}}$ $\overline{\text{company}}$ $\overline{\text{which}}$ $\overline{\text{Microsoft}}$ $\overline{\text{bought}}$
 NP/N N $(NP \backslash NP)/(S/NP)$ NP $(S \backslash NP)/NP$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Extraction out of a Relative Clause

The *company* *which* *Microsoft* *bought*
 $\overline{NP/N}$ \overline{N} $\overline{(NP \backslash NP)/(S/NP)}$ \overline{NP} $\overline{(S \backslash NP)/NP}$
 $\overline{S/(S \backslash \overline{NP})}^{>\mathbf{T}}$


Assignment Project Exam Help

<https://powcoder.com>

> **T** type-raising

Add WeChat powcoder

Extraction out of a Relative Clause




<https://powcoder.com>


Add WeChat powcoder

- > **T** type-raising
- > **B** forward composition

Extraction out of a Relative Clause



Extraction out of a Relative Clause



Forward Composition and Type-Raising

- Forward composition ($>_{\mathbf{B}}$):


$$X/Y \ Y/Z \Rightarrow X/Z \quad (>_{\mathbf{B}})$$

- Type-raising (\mathbf{T}):

$$\begin{aligned} X &\Rightarrow T/(T \setminus X) \quad (>_{\mathbf{T}}) \\ X &\Rightarrow T \setminus (T/X) \quad (<_{\mathbf{T}}) \end{aligned}$$

- Extra combinatory rules increase the weak generative power to mild context -sensitivity

“Non-constituents” in CCG – Right Node Raising




Assignment Project Exam Help

<https://powcoder.com>

> **T** type-raising

Add WeChat powcoder

“Non-constituents” in CCG – Right Node Raising




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- > **T** type-raising
- > **B** forward composition

“Non-constituents” in CCG – Right Node Raising




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


“Non-constituents” in CCG – Right Node Raising



Combinatory Categorical Grammar

- CCG is *mildly* context sensitive
- Natural language is provably non-context free
- Constructions in Dutch and Swiss German (Shieber, 1985) require more than context free power for their analysis
 - these have *crossing* dependencies (which CCG can handle)

Assignment Project Exam Help



CCG Semantics

- Categories encode argument sequences
 - Parallel syntactic combinator operations and lambda calculus semantic operations
- Assignment Project Exam Help
<https://powcoder.com>
 Add WeChat powcoder


$John \vdash NP : john'$

$shares \vdash NP : shares'$

$buys \vdash (S \backslash NP) / NP : \lambda x. \lambda y. buys' xy$

$sleeps \vdash S \backslash NP : \lambda x. sleeps' x$

$well \vdash (S \backslash NP) \backslash (S \backslash NP) : \lambda f. \lambda x. well' (fx)$



CCG Semantics

Left arg.	Right arg.	Operation	Result
$X/Y : f$	$Y : a$	Forward application	$X : f(a)$
$Y : a$	$X \backslash Y : f$	Backward application	$X : f(a)$
$X/Y : f$	$Y/Z : g$	Forward composition	$X/Z : \lambda x.f(g(x))$
$X : a$		Type raising	$T/(T \backslash X) : \lambda f.f(a)$

etc.

Tree Adjoining Grammar



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

TAG Building Blocks

- Elementary trees (of many depths)
- Substitution at ↓
Assignment Project Exam Help
- Tree Substitution Grammar equivalent to CFG
*<https://powcoder.com>
Add WeChat powcoder*







TAG Building Blocks

- Auxiliary trees for *adjunction*
- Adds extra power beyond CFG


Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Derivation Tree



Derived Tree



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Semantics

$Harry(x) \wedge likes(e, x, y) \wedge peanuts(y) \wedge passionately(e)$