

Computational Linguistics

CSC 2501 / 485
Fall 2018

8

Assignment Project Exam Help

8. Word sense disambiguation

<https://powcoder.com>

Add WeChat powcoder

Gerald Penn

Department of Computer Science, University of Toronto

Reading: Jurafsky & Martin: 20.1–5.

Word sense disambiguation

- Word sense disambiguation (WSD), lexical disambiguation, resolving lexical ambiguity, lexical ambiguity resolution.


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


How big is the problem?

- Most words of English have only one sense.
(62% in *Longman's Dictionary of Contemporary English*; 79% in WordNet.)
- But the others tend to have **several** senses.
(Avg 3.83 in LDOCE; 2.96 in WordNet.)
<https://powcoder.com>
- Ambiguous words are more frequently used
(In British National Corpus, 84% of instances have more than one sense in WordNet.)
Add WeChat powcoder
- Some senses are more frequent than others.



Words occurring in the British National Corpus are plotted on the horizontal axis in rank order by frequency in the corpus. Number of WordNet senses per word is plotted on the vertical axis. Each point represents a bin of 100 words and the average number of senses of words in the bin.

Edmonds, Philip. "Disambiguation, Lexical." *Encyclopedia of Language and Linguistics* (second edition), Elsevier, 2006, pp 607–623.



In each column, the senses are ordered by frequency, normalized per word, and averaged over all words with that number of senses.

Edmonds, Philip. "Disambiguation, Lexical." *Encyclopedia of Language and Linguistics* (second edition), Elsevier, 2006, pp 607–623.

Sense inventory of a word

- Dictionaries, WordNet list senses of a word.
- Often, no agreement on proper sense-division of words.
- Don't want sense-divisions to be too coarse-grained or too fine-grained.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Frequent criticism
of WordNet

trench (trɛnʃ) *n.* **1.** A deep furrow or ditch. **2.** A long, narrow ditch embanked with its own soil and used for concealment and protection in warfare. **3.** A long, steep-sided valley on the ocean floor. — **trench** *v.* **trenched, trench·ing, trench·es.** — *tr.* **1.** To

The American Heritage Dictionary of the English Language (3rd edition)

<https://powcoder.com>

trench /trɛntʃ/ *n* ditch dug in the ground, eg for drainage or to give troops shelter from enemy fire: *irrigation trenches* ○ *The workmen dug a trench for*

Oxford Advanced Learner's Dictionary (encyclopedic edition)

lit·ter (līt'ər) *n.* **1.a.** A disorderly accumulation of objects; a pile. **b.** Carelessly discarded refuse, such as wastepaper: *the litter in the streets after a parade.* **2.** The offspring produced at one birth by a multiparous mammal. See Synonyms at **flock**¹. **3.a.** Material, such as straw, used as bedding for animals. **b.** An absorbent material, such as granulated clay, for covering the floor of an animal's cage or excretory box. **4.** An enclosed or curtained couch mounted on shafts and used to carry a single passenger. **5.** A flat supporting framework, such as a piece of canvas stretched between parallel shafts, for carrying a disabled or dead person; a stretcher. **6.** The uppermost layer of the forest floor consisting chiefly of fallen leaves and other decaying organic matter. — **litter**

Assignment Project Exam Help

AHDEL

litter /'lɪtə(r)/ *n* **1** (a) [U] light rubbish (eg bits of paper, wrappings, bottles) left lying about, esp in a public place: *Please do not leave litter.* ⇨ article at ENVIRONMENT. (b) [sing] state of untidiness: *Her desk was covered in a litter of books and papers.* ○ *His room was a litter of old clothes, dirty crockery and broken furniture.* **2** [U] straw, etc used as bedding for animals. **3** [CGp] all the young born to an animal at one time: *a litter of puppies.* **4** [C] (a) type of stretcher(1). (b) (formerly) couch carried on men's shoulders or by animals as a means of transport.

OALD

What counts as the right answer?

- Often, no agreement on which sense a given word-token is.
- Some tokens seem to have two or more senses at the same time.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Which senses are these? 1

- *image*

1. a picture formed in the mind;
2. a picture formed of an object in front of a mirror or lens;
3. the general opinion about a person, organization, etc, formed or intentionally created in people's minds;

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

[and three other senses]

“... of the Garonne, which becomes an unforgettable *image*. This is a very individual film, mannered, ...”

Example from: Kilgarriff, Adam. “Dictionary word sense distinctions: An enquiry into their nature.” *Computers and the Humanities*, 26: 365–387, 1993. Definitions from *Longman Dictionary of Contemporary English*, 2nd edition, 1987.

Which senses are these? 2

- *distinction*

1. the fact of being different;
2. the quality of being unusually good; excellence.

Assignment Project Exam Help

“... before the war, shares with Rilke and Kafka the ***distinction*** of having origins which seem to escape ...”

<https://powcoder.com>

Add WeChat powcoder

Example from: Kilgarriff, Adam. “Dictionary word sense distinctions: An enquiry into their nature.” *Computers and the Humanities*, 26: 365–387, 1993. Definitions from *Longman Dictionary of Contemporary English*, 2nd edition, 1987.

What counts as the right answer?

- Therefore, hard to get a definitive sense-tagged corpus.
- And hard to get human baseline for performance. [Assignment Project Exam Help](#)
- Human annotators <https://powcoder.com> agree about 70–95% of the time. [Add WeChat powcoder](#)
[Depending on word, sense inventory, context size, discussions, etc.]

Baseline algorithms 1

- Assume that input is PoS-tagged. Why?
- *Obvious baseline algorithm:*
Pick most-likely sense (or pick one at random). Assignment Project Exam Help
- Accuracy: 39–62% <https://powcoder.com>
Add WeChat powcoder

Baseline algorithms 2

- *Simple tricks (1):*
Notice when ambiguous word is in unambiguous fixed phrase.
- ***private school*** *Assignment Project Exam Help* ***private eye***
(But maybe not *right in all right.*)
<https://powcoder.com>
Add WeChat powcoder

Baseline algorithms 3

- *Simple tricks (2):*
“One sense per discourse”:
A homonymous word is rarely used in more than one sense in the same text.
Assignment Project Exam Help
- If word occurs multiple times, ...
https://powcoder.com
- Not true for polysemy.
Add WeChat powcoder
- *Simple tricks (3):*
Lesk’s algorithm (see below).

“Context” 1

- Meaning of word in use depends on (determined by) its context.
 - Circumstantial context.
 - Textual context.
 - Complete text.
 - Sentence, paragraph.
 - Window of n words.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

“Context” 2

- Words of context are also ambiguous; need for mutual constraints; often ignored in practice.
- “One sense per collocation”.
[Assignment Project Exam Help](https://powcoder.com)
- Collocation: words that *tend* to co-occur together.
<https://powcoder.com>
Add WeChat powcoder

Selectional preferences

- Constraints imposed by one word meaning on another—especially verbs on nouns.

*Eagle Airways which has applied to **serve** New York ...
Plain old bean soup, **served** daily since the turn of the
century ...*

Assignment Project Exam Help

<https://powcoder.com>

*I don't mind washing **dishes** now and then.
Sprouted grains and seeds are used in preparing salads and
dishes such as chop suey.*

Add WeChat powcoder

*It was the most popular **dish served** in the Ladies' Grill.*

- Some words select more strongly than others.
see (weak) — *drink* (moderate) — *elapse* (strong)

Limitations of selectional preferences

- Negation:
 - *You can't **eat** good intentions.*
 - *It's nonsense to say that a **book** elapsed.*
 - *I am not a **crook**.* (Richard Nixon, 17 Nov 1973)
- Odd events:
 - <https://powcoder.com>
 - *Los Angeles secretary Jannene Swift **married** a 50-pound pet rock in a formal ceremony in Lafayette Park.* (Newspaper report)

Limitations of selectional preferences

- Metaphor:

*The issue was acute because the exiled Polish Government in London, supported in the main by Britain, was still competing with the new Lublin Government formed behind the Red Army. More time was spent in trying to **marry** these incompatibles than over any subject discussed at Yalta. ... The application of these formulae could not please both sides, for they really attempted to **marry** the impossible to the inevitable.*

Limitations of selectional preferences

- In practice, attempts to induce selectional preferences or to use them have not been very successful.
- Apply in only about 20% of cases, achieve about 50% accuracy. (Mihalcea 2006, McCarthy & Carroll 2003)
- At best, they are a coarse filter for other methods.

Lesk's algorithm 1

- Sense s_i of ambiguous word w is likely to be the intended sense if many of the words used in the dictionary definition of s_i are also used in the definitions of words in the context window.
- For each sense s_i of w , let D_i be the bag of words in its dictionary definition.
- *Bag of words*: unordered set of words in a string, excepting those that are very frequent (*stop list*).
- Let B be the bag of words of the dictionary definitions of *all* senses of all words $v \neq w$ in the context window of w . (Might also (or instead) include all v in B .)
- Choose the sense s_i that maximizes $overlap(D_i, B)$.

Lesk's algorithm Example

- ... the keyboard of the **terminal** was ...

terminal

1. a point on an electrical device at which electric current enters or leaves.
2. where transport vehicles load or unload passengers or goods.
3. an input-output device providing access to a **computer**.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

keyboard

1. set of keys on a piano or organ or typewriter or typesetting machine or **computer** or the like.
2. an arrangement of hooks on which keys or locks are hung.

Lesk's algorithm 2

- Many variants possible on what is included in D_i and B .
 - *E.g.*, include the examples in dictionary definitions.
 - *E.g.*, include [Assignment Project Exam Help](https://powcoder.com) manually tagged example texts.
 - PoS tags on definitions. <https://powcoder.com>
 - Give extra weight to infrequent words occurring in the bags. [Add WeChat powcoder](#)
- **Results:** Simple versions of Lesk achieve accuracy around 50–60%; Lesk plus simple smarts gets to nearly 70%.

Math revision: Bayes's rule

- $P(A | B) = \frac{P(A \wedge B)}{P(B)} = \frac{P(B | A) \cdot P(A)}{P(B)}$
- *Typical problem:* We have B , and want to know which A is now most likely.

Add WeChat powcoder

$$\begin{aligned}\operatorname{argmax}_A P(A | B) &= \operatorname{argmax}_A \frac{P(B | A) \cdot P(A)}{P(B)} \\ &= \operatorname{argmax}_A P(B | A) \cdot P(A)\end{aligned}$$

Supervised Bayesian methods 1

- Classify contexts according to which sense of each ambiguous word they tend to be associated with.
- Bayes decision rule: Pick sense, s_j , that is most probable in given context, $j = \operatorname{argmax}_i P(s_i | C)$.
- Bag-of-words model of context.
- For each sense s_k of w in the given context C , we know the **prior probability** $P(s_k)$ of the sense, but require its **posterior probability** $P(s_k|C)$.

Supervised Bayesian methods 2

- Want sense s' of word w in context C such that $P(s'|C) > P(s_k|C)$ for all $s_k \neq s'$.

$$\begin{aligned}s' &= \operatorname{argmax}_{s_k} P(s_k|C) \\&= \operatorname{argmax}_{s_k} \frac{P(C|s_k)P(s_k)}{P(C)} \\&= \operatorname{argmax}_{s_k} P(C|s_k)P(s_k) \\&= \operatorname{argmax}_{s_k} P(s_k) \prod_{v_j \text{ in } C} P(v_j|s_k)\end{aligned}$$

where ...

Supervised Bayesian methods 3

- ***Naïve Bayes assumption:*** Attributes v_j of context C of sense s_k of w are conditionally independent of one another. Hence

$$P(C|s_k) = \prod_{v_j \in C} P(v_j|s_k)$$

Add WeChat powcoder

Supervised Bayesian methods 4

$$P(s_k) = \frac{c(s_k)}{c(w)}$$

$$P(v_j | s_k) = \frac{c(v_j, s_k)}{c(s_k)}$$

and $c(v_j, s_k)$ is the number of times v_j occurs in the context window of s_k .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Training corpora for supervised WSD

- **Problem:** Need *large* training corpus with each ambiguous word tagged with its sense.
 - Expensive, time-consuming human work.
 - “Large” for a human is small for WSD training.
- Some sense-tagged corpora:
 - SemCor: 700K PoS-tagged tokens (200K WordNet-sense-tagged) of Brown corpus and a short novel.
 - Singapore DSO corpus: About 200 “interesting” word-types tagged in about 2M tokens of Brown corpus and *Wall Street Journal*.

Evaluation

- Systems based on naïve Bayes methods have achieved 62–72% accuracy for selected words with adequate training data.

(Màrquez et al 2006, Edmonds 2006)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Yarowsky 1995

Unsupervised decision-list learning

- ***Decision list***: ordered list of strong, specific clues to senses of homonym.*

<https://powcoder.com>

Add WeChat powcoder

*Yarowsky calls them “polysemous words”.

Decision list for *bass*:

LogL	Context	Sense
10.98	<i>fish</i> in $\pm k$ words	FISH
10.92	<i>striped bass</i>	FISH
9.70	<i>guitar</i> in $\pm k$ words	MUSIC
9.20	<i>bass player</i>	MUSIC
9.10	<i>piano</i> in $\pm k$ words	MUSIC
8.87	<i>sea bass</i>	FISH
8.49	<i>play bass</i>	MUSIC
8.31	<i>river</i> in $\pm k$ words	FISH
7.71	<i>on bass</i>	MUSIC
5.32	<i>bass are</i>	FISH

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Yarowsky 1995 Basic ideas

- Separate decision list learned for each homonym.
- Bootstrapped from seeds, very large corpus, heuristics. [Assignment Project Exam Help](#)
- One sense per *discourse*. <https://powcoder.com>
- One sense per *collocation*. [Add WeChat powcoder](#)
- Uses supervised classification algorithm to build decision-list.
- Training corpus: 460M words, mixed texts.

Yarowsky 1995 Method 1

- 1–2. Get data (instances of target word); choose seed rules; apply them.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


used to strain microscopic **plant life** from the
zonal distribution of **plant life** .
close-up studies of **plant life** and natural
too rapid growth of aquatic **plant life** in water
the proliferation of **plant** and animal **life**
establishment phase of the **plant** virus **life** cycle
that divide **life** into **plant** and animal kingdom
many dangers to **plant** and animal **life**
mammals . Animal and **plant life** are delicately
automated **manufacturing plant** in Fremont
vast **manufacturing plant** and distribution
chemical **manufacturing plant** , producing viscose
keep a **manufacturing plant** profitable without
computer **manufacturing plant** and adjacent
discovered at a St. Louis **plant manufacturing**
copper **manufacturing plant** found that they
copper wire **manufacturing plant** , for example
s cement **manufacturing plant** in Alpena

vinyl chloride monomer **plant** , which is
molecules found in **plant** and animal tissue
Nissan car and truck **plant** in Japan is
and Golgi apparatus of **plant** and animal cells
union responses to **plant** closures .
cell types found in the **plant** kingdom are
company said the **plant** is still operating
Although thousands of **plant** and animal species
animal rather than **plant** tissues can be

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder




Initial state after use of seed rules

Yarowsky 1995 Method 2

- 3. Iterate:
 - 3a. Create a new decision-list classifier:
supervised training with the data tagged so far.
Looks for ~~collocations~~ [Assignment Project Exam Help](#) as features for classification.
 - 3b. Apply new ~~classifier~~ <https://powcoder.com> to whole data set, tag
some new instances. [Add WeChat powcoder](#)
 - 3c. Optional: Apply one-sense-per-discourse rule
wherever one sense now dominates a text.



Intermediate state



Final state

Yarowsky 1995: Method 3

- 4. Stop when converged. (Optional: Apply one-sense-per-discourse constraint.)
- 5. Use final decision list for WSD.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Yarowsky 1995 Evaluation

- Experiments: 12 homonymous words.
 - 400–12,000 hand-tagged instances of each.
 - Baseline (most frequent sense) = 63.9%.
- Best results, avg 96.5% accuracy.
 - Base seed on dictionary definition; use one-sense-per-discourse heuristic.
 - As good as or better than supervised algorithm used directly on fully labelled data.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Yarowsky 1995 Discussion 1

- Strength of method:
 - The one-sense heuristics.
 - Use of precise lexical and positional information.
 - Huge training corpus. [Assignment Project Exam Help](https://powcoder.com)
 - Bootstrapping: <https://powcoder.com> Unsupervised use of supervised algorithm. [Add WeChat powcoder](#)
- Disadvantages:
 - Train each word separately.
 - Homonyms only. [Why?](#)

Yarowsky 1995 Discussion 2

- Not limited to regular words; e.g., in speech synthesis system:
 - / as fraction or date:
3/4 → “three-quarters” or “third of April”.
 - Roman number as cardinal or ordinal:
chapter VII → “chapter seven”;
Henry VII → “Henry the seventh”.

Yarowsky, David. “Homograph disambiguation in speech synthesis.” In Jan van Santen, Richard Sproat, Joseph Olive and Julia Hirschberg (eds.), *Progress in Speech Synthesis*. Springer-Verlag, pp. 159–175, 1996.