

## This time: learning from examples



- Learning agents
- Inductive learning
- Classification and support vector machines (SVM)
- Decision tree learning

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## What is learning?



- “Learning denotes changes in a system that ... enable a system to do the same task more efficiently the next time.” –Herbert Simon

## Assignment Project Exam Help

- “Learning is constructing or modifying representations of what is being experienced.” –Ryszard Michalski

## Add WeChat powcoder

- “Learning is making useful changes in our minds.” –Marvin Minsky

# Why study learning?

- Understand and improve efficiency of human learning
  - Use to improve methods for teaching and tutoring people (e.g., better computer-aided instruction)

Assignment Project Exam Help

- Discover new things or structure previously unknown
  - Examples: data mining, scientific discovery

<https://powcoder.com>

Add WeChat powcoder

- Fill in skeletal or incomplete specifications about a domain
  - Large, complex AI systems can't be completely built by hand and require dynamic updating to incorporate new information
  - Learning new characteristics expands the domain or expertise and lessens the "brittleness" of the system

- Build agents that can adapt to users, other agents, and their environment

## Two types of learning in AI

*Deductive:* Deduce rules/facts from already known rules/facts. (We have already dealt with this)

Assignment Project Exam Help

$$(A \Rightarrow B) \Rightarrow (A \Rightarrow C)$$

*Inductive:* Learn new rules/facts from a data set  $\mathcal{D}$

Add WeChat powcoder

$$\mathcal{D} = \{\mathbf{x}(n), y(n)\}_{n=1 \dots N} \Rightarrow (A \Rightarrow C)$$

We will be dealing with the latter, *inductive* learning, now

## Learning



- Learning is essential for unknown environments,
  - i.e., when designer lacks omniscience


Assignment Project Exam Help

- Learning is useful as a system construction method,
  - i.e., expose the agent to reality rather than trying to write it down

Add WeChat powcoder

- Learning modifies the agent's decision mechanisms to improve performance

## Learning agents



## Learning element



- Design of a learning element is affected by
  - Which components of the performance element are to be learned
  - What feedback is available to learn these components
  - What representation is used for the components

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Type of feedback:
  - **Supervised learning**: correct answers for each example
  - **Unsupervised learning**: correct answers not given
  - **Reinforcement learning**: occasional rewards

# Inductive learning

- Simplest form: learn a function from examples

$f$  is the **target function**

An **example** is a pair  $(x, f(x))$

Problem: find a **hypothesis**  $h$   
such that  $h \approx f$   
given a **training set** of examples

(This is a highly simplified model of real learning:

- Ignores prior knowledge
- Assumes examples are given)



## Inductive learning method


- Construct/adjust  $h$  to agree with  $f$  on training set
- ( $h$  is **consistent** if it agrees with  $f$  on all examples)

Assignment Project Exam Help

- E.g., curve fitting:

<https://powcoder.com>

Add WeChat powcoder



## Inductive learning method


- Construct/adjust  $h$  to agree with  $f$  on training set
- ( $h$  is **consistent** if it agrees with  $f$  on all examples)

Assignment Project Exam Help

- E.g., curve fitting:

<https://powcoder.com>

Add WeChat powcoder



## Inductive learning method


- Construct/adjust  $h$  to agree with  $f$  on training set
- ( $h$  is **consistent** if it agrees with  $f$  on all examples)

Assignment Project Exam Help

- E.g., curve fitting:

<https://powcoder.com>

Add WeChat powcoder



## Inductive learning method


- Construct/adjust  $h$  to agree with  $f$  on training set
- ( $h$  is **consistent** if it agrees with  $f$  on all examples)

Assignment Project Exam Help

- E.g., curve fitting:

<https://powcoder.com>


Add WeChat powcoder



## Inductive learning method

- Construct/adjust  $h$  to agree with  $f$  on training set
- ( $h$  is **consistent** if it agrees with  $f$  on all examples)

- E.g., curve fitting:




## Inductive learning method

- Construct/adjust  $h$  to agree with  $f$  on training set
- ( $h$  is **consistent** if it agrees with  $f$  on all examples)

Assignment Project Exam Help

- E.g., curve fitting:


<https://powcoder.com>



- Ockham's razor: prefer the simplest hypothesis consistent with data

# Learning to classify

- In many problems we want to learn how to classify data into one of several possible categories.
  - E.g., face recognition, etc. Here earthquake vs nuclear explosion:




## Problem: how to best draw the line?

- Many methods exist. One of the most popular ones is the support vector machine (SVM): Find the **maximum margin separator**, i.e., the one that is as far as possible from any example point.

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



**Figure 18.30** Support vector machine classification: (a) Two classes of points (black and white circles) and three candidate linear separators. (b) The maximum margin separator (heavy line), is at the midpoint of the **margin** (area between dashed lines). The **support vectors** (points with large circles) are the examples closest to the separator.




# Non-linear separability and SVM

- SVM can handle data that is not linearly separable using the so-called “kernel trick”: embed the data into a higher-dimensional space, in which it is linearly separable.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




# Non-linear separability and SVM

- Kernel: remaps from original 2 dimensions  $x_1$  and  $x_2$  to 3 new dimensions:  $f_1 = x_1^2$ ,  $f_2 = x_2^2$ ,  $f_3 = \sqrt{2}x_1x_2$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



**Figure 18.31** (a) A two-dimensional training set with positive examples as black circles and negative examples as white circles. The true decision boundary,  $x_1^2 + x_2^2 \leq 1$ , is also shown. (b) The same data after mapping into a three-dimensional input space  $(x_1^2, x_2^2, \sqrt{2}x_1x_2)$ . The circular decision boundary in (a) becomes a linear decision boundary in three dimensions. Figure 18.30(b) gives a closeup of the separator in (b).

(see textbook for details  
on how those new  
dimensions were chosen)

# Learning decision trees

In some other problems, a single A vs. B classification is not sufficient.  
For example:

**Problem:** decide whether to wait for a table at a restaurant, based on the following attributes:

1. Alternate: is there an alternative restaurant nearby?
2. Bar: is there a comfortable bar area to wait in?
3. Fri/Sat: is today Friday or Saturday?
4. Hungry: are we hungry?
5. Patrons: number of people in the restaurant (None, Some, Full)
6. Price: price range (\$, \$\$, \$\$\$)
7. Raining: is it raining outside?
8. Reservation: have we made a reservation?
9. Type: kind of restaurant (French, Italian, Thai, Burger)
10. WaitEstimate: estimated waiting time (0-10, 10-30, 30-60, >60)

# Attribute-based representations

- Examples described by **attribute values** (Boolean, discrete, continuous)
- E.g., situations where I will/won't wait for a table:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Example	Attributes											Target
	<i>Alt</i>	<i>Bar</i>	<i>Fri</i>	<i>Hun</i>	<i>Pat</i>	<i>Price</i>	<i>Rain</i>	<i>Res</i>	<i>Type</i>	<i>Est</i>	<i>Wait</i>	
$X_1$	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T	
$X_2$	F	F	F	T	Full	\$	F	F	Thai	30-60	F	
$X_3$	F	F	F	F	Some	\$	F	F	Burger	0-10	T	
$X_4$	T	F	T	T	Full	\$	F	F	Thai	10-30	T	
$X_5$	T	F	T	F	Full	\$\$\$	F	T	French	>60	F	
$X_6$	F	T	F	T	Some	\$	T	T	Italian	0-10	T	
$X_7$	F	F	F	F	None	\$	F	F	Burger	0-10	F	
$X_8$	F	F	F	T	Some	\$	T	T	Thai	0-10	T	
$X_9$	F	T	T	F	Full	\$	T	F	Burger	>60	F	
$X_{10}$	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F	
$X_{11}$	F	F	F	F	None	\$	F	F	Thai	0-10	F	
$X_{12}$	T	T	T	T	Full	\$	F	F	Burger	30-60	T	

- Classification of examples is **positive** (T) or **negative** (F)

# Decision trees

- One possible representation for hypotheses
- E.g., here is the “true” (designed manually by thinking about all cases) tree for deciding whether to wait:

Assignment Project Exam Help



- Could we learn this tree from examples instead of designing it by hand?

## Inductive learning of decision tree



- **Simplest:** Construct a decision tree with one leaf for every example = memory based learning.  
Not very good generalization.

<https://powcoder.com>

Add WeChat powcoder

## Inductive learning of decision tree

- **Simplest:** Construct a decision tree with one leaf for every example = memory based learning.  
Not very good generalization.
- **Advanced:** Split on each variable so that the purity of each split increases (i.e. either only yes or only no)
- Purity measured, e.g., with entropy

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Inductive learning of decision tree

- **Simplest:** Construct a decision tree with one leaf for every example = memory based learning.  
Not very good generalization.
- **Advanced:** Split on each variable so that the purity of each split increases (i.e. either only yes or only no)
- Purity measured, e.g., with entropy


$$\text{Entropy} = -P(\text{yes}) \ln[P(\text{yes})] - P(\text{no}) \ln[P(\text{no})]$$

General form: 
$$\text{Entropy} = - \sum_i P(v_i) \ln[P(v_i)]$$



# Expressiveness

- Decision trees can express any function of the input attributes.
- E.g., for Boolean functions, truth table row  $\rightarrow$  path to leaf:



- Trivially, there is a consistent decision tree for any training set with one path to leaf for each example (unless  $f$  nondeterministic in  $x$ ) but it probably won't generalize to new examples
- Prefer to find more **compact** decision trees

## Hypothesis spaces

How many distinct decision trees with  $n$  Boolean attributes?

= number of Boolean functions

= number of distinct truth tables with  $2^n$  rows =  $2^{2^n}$

- E.g., with 6 Boolean attributes, there are 18,446,744,073,709,551,616 possible trees

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Hypothesis spaces

How many distinct decision trees with  $n$  Boolean attributes?

= number of Boolean functions

= number of distinct truth tables with  $2^n$  rows =  $2^{2^n}$

- E.g., with 6 Boolean attributes, there are 18,446,744,073,709,551,616 trees

How many purely conjunctive hypotheses (say,  $H(x_1 \wedge x_2 \wedge \neg x_3)$ )?

- Each attribute can be in (positive), in (negative), or out  
⇒  $3^n$  distinct conjunctive hypotheses
- More expressive hypothesis space
  - increases chance that target function can be expressed
  - increases number of hypotheses consistent with training set  
⇒ may get worse predictions

# ID3 Algorithm



- A greedy algorithm for decision tree construction developed by Ross Quinlan circa 1987

## Assignment Project Exam Help

- Top-down construction of decision tree by recursively selecting “best attribute” to use at the current node in tree
  - Once attribute is selected for current node, generate child nodes, one for each possible value of selected attribute
  - Partition examples using the possible values of this attribute, and assign these subsets of the examples to the appropriate child node
  - Repeat for each child node until all examples associated with a node are either all positive or all negative

<https://powcoder.com>

Add WeChat powcoder

## Choosing the best attribute

- Key problem: choosing which attribute to split a given set of examples

### Assignment Project Exam Help

- Some possibilities are:
  - **Random:** Select any attribute at random
  - **Least-Values:** Choose the attribute with the smallest number of possible values
  - **Most-Values:** Choose the attribute with the largest number of possible values
  - **Max-Gain:** Choose the attribute that has the largest expected *information gain*—i.e., attribute that results in smallest expected size of subtrees rooted at its children
- The ID3 algorithm uses the Max-Gain method of selecting the best attribute

## Decision tree learning


- Aim: find a small tree consistent with the training examples
- Idea: (recursively) choose "most significant" attribute as root of (sub)tree

**Assignment Project Exam Help**  
**<https://powcoder.com>**  
**Add WeChat powcoder**

```
function DTL(examples, attributes, default) returns a decision tree
    if examples is empty then return default
    else if all examples have the same classification then return the classification
    else if attributes is empty then return MODE(examples)
    else
        best ← CHOOSE-ATTRIBUTE(attributes, examples)
        tree ← a new decision tree with root test best
        for each value  $v_i$  of best do
            examplesi ← {elements of examples with best =  $v_i$ }
            subtree ← DTL(examplesi, attributes − best, MODE(examples))
            add a branch to tree with label  $v_i$  and subtree subtree
        return tree
```

## Choosing an attribute

- Idea: a good attribute splits the examples into subsets that are (ideally) "all positive" or "all negative"



- *Patrons?* is a better choice

## Using information theory

Note:

When using  $\ln()$ , entropy is in nats

When using  $\log_2()$ , entropy is in bits

- To implement `Choose-Attribute` in the DTL algorithm

- Information Content (Entropy):

Assignment Project Exam Help

$$I(P(v_1), \dots, P(v_n)) = \sum_{i=1}^n -P(v_i) \log_2 P(v_i)$$

<https://powcoder.com>

- For a training set containing  $p$  positive examples and  $n$  negative examples:

Add WeChat powcoder

$$I\left(\frac{p}{p+n}, \frac{n}{p+n}\right) = -\frac{p}{p+n} \log_2 \frac{p}{p+n} - \frac{n}{p+n} \log_2 \frac{n}{p+n}$$



# Information theory 101

- Information theory sprang almost fully formed from the seminal work of Claude E. Shannon at Bell Labs
  - A Mathematical Theory of Communication, *Bell System Technical Journal*, 1948.
- Intuitions
  - Common words (a, the, dog) are shorter than less common ones (parliamentarian, foreshadowing)
  - In Morse code, common (probable) letters have shorter encodings
- Information is measured in minimum number of bits needed to store or send some information
- Wikipedia: The measure of data, known as information entropy, is usually expressed by the average number of bits needed for storage or communication

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Information theory 101

- Information is measured in bits
- Information conveyed by message depends on its probability

Assignment Project Exam Help

- With  $n$  equally probable possible *messages*, the probability  $p$  of each is  $1/n$
- Information conveyed by message is  $-\log(p) = \log(n)$ 
  - e.g., with 16 messages, then  $\log(16) = 4$  and we need 4 bits to identify/send each message

https://powcoder.com  
Add WeChat powcoder

- Given probability distribution for  $n$  messages  $P = (p_1, p_2, \dots, p_n)$ , the information conveyed by distribution (aka *entropy* of  $P$ ) is:

$$I(P) = -(p_1 \log(p_1) + p_2 \log(p_2) + \dots + p_n \log(p_n))$$

probability of msg 2

info in msg 2

## Information theory II

Note:

When using  $\ln()$ , entropy is in nats

When using  $\log_2()$ , entropy is in bits

- Information conveyed by distribution (a.k.a. *entropy* of P):

$$I(P) = -(p_1 \cdot \log(p_1) + p_2 \cdot \log(p_2) + \dots + p_n \cdot \log(p_n))$$

## Assignment Project Exam Help

- Examples:

- If P is (0.5, 0.5) then  $I(P) = -0.5 \cdot \log(0.5) - 0.5 \cdot \log(0.5) = 1$

- If P is (0.67, 0.33) then  $I(P) = -(2/3 \cdot \log(2/3) + 1/3 \cdot \log(1/3)) = 0.92$

- If P is (1, 0) then  $I(P) = -1 \cdot \log(1) - 0 \cdot \log(0) = 0$

- The more uniform the probability distribution, the greater its information: More information is conveyed by a message telling you which event actually occurred
- Entropy is the average number of bits/message needed to represent a stream of messages

## Information gain

- A chosen attribute  $A$  divides the training set  $E$  into subsets  $E_1, \dots, E_v$  according to their values for  $A$ , where  $A$  has  $v$  distinct values.

### Assignment Project Exam Help

$$remainder(A) = \sum_{i=1}^v \frac{p_i + n_i}{p + n} I\left(\frac{p_i}{p_i + n_i}, \frac{n_i}{p_i + n_i}\right)$$

- Information Gain (IG) or reduction in entropy from the attribute test:

$$IG(A) = I\left(\frac{p}{p + n}, \frac{n}{p + n}\right) - remainder(A)$$

- Choose the attribute with the largest IG

## Information gain

For the training set,  $p = n = 6$ ,  $I(6/12, 6/12) = 1$  bit

Consider the attributes *Patrons* and *Type* (and others too):

$$IG(Patrons) = 1 - \left[ \frac{2}{12} I\left(\frac{1}{2}, \frac{1}{2}\right) + \frac{4}{12} I\left(\frac{1}{2}, \frac{1}{2}\right) + \frac{6}{12} I\left(\frac{2}{3}, \frac{1}{3}\right) \right] = 0.541 \text{ bits}$$

$$IG(Type) = 1 - \left[ \frac{2}{12} I\left(\frac{1}{2}, \frac{1}{2}\right) + \frac{2}{12} I\left(\frac{1}{2}, \frac{1}{2}\right) + \frac{4}{12} I\left(\frac{2}{3}, \frac{1}{3}\right) + \frac{4}{12} I\left(\frac{2}{3}, \frac{1}{3}\right) \right] = 0 \text{ bits}$$


*Patrons* has the highest IG of all attributes and so is chosen by the DTL algorithm as the root

## Decision tree learning example

Note:

When using  $\ln()$ , entropy is in nats

When using  $\log_2()$ , entropy is in bits




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	T	F	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	T	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	F	T	T	F	Full	\$	F	F	Burger	30-60	T

$$\text{Entropy} = \frac{6}{12} \left[ -\left(\frac{3}{6}\right) \ln\left(\frac{3}{6}\right) - \left(\frac{3}{6}\right) \ln\left(\frac{3}{6}\right) \right] + \frac{6}{12} \left[ -\left(\frac{3}{6}\right) \ln\left(\frac{3}{6}\right) - \left(\frac{3}{6}\right) \ln\left(\frac{3}{6}\right) \right] = 0.30$$

$$\text{Entropy decrease} = 0.30 - 0.30 = 0$$

NOTE: These examples use  $\ln(.)$  and not  $\log_2(.)$  like previous slides  
decisions are the same since both logs are linearly related

# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	F	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	F	T	T	T	Full	\$	F	F	Burger	30-60	T

$$\text{Entropy} = \frac{6}{12} \left[ -\left(\frac{3}{6}\right) \ln \left(\frac{3}{6}\right) - \left(\frac{3}{6}\right) \ln \left(\frac{3}{6}\right) \right] + \frac{6}{12} \left[ -\left(\frac{3}{6}\right) \ln \left(\frac{3}{6}\right) - \left(\frac{3}{6}\right) \ln \left(\frac{3}{6}\right) \right] = 0.30$$

$$\text{Entropy decrease} = 0.30 - 0.30 = 0$$

# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	F	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	T	T	T	F	Full	\$	F	F	Burger	30-60	T

$$\text{Entropy} = \frac{5}{12} \left[ -\left(\frac{2}{5}\right) \ln\left(\frac{2}{5}\right) - \left(\frac{3}{5}\right) \ln\left(\frac{3}{5}\right) \right] + \frac{7}{12} \left[ -\left(\frac{4}{7}\right) \ln\left(\frac{4}{7}\right) - \left(\frac{3}{7}\right) \ln\left(\frac{3}{7}\right) \right] = 0.29$$

$$\text{Entropy decrease} = 0.30 - 0.29 = 0.01$$



# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	F	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	T	T	T	F	Full	\$	F	F	Burger	30-60	T

$$\text{Entropy} = \frac{7}{12} \left[ -\left(\frac{5}{7}\right) \ln\left(\frac{5}{7}\right) - \left(\frac{2}{7}\right) \ln\left(\frac{2}{7}\right) \right] + \frac{5}{12} \left[ -\left(\frac{1}{5}\right) \ln\left(\frac{1}{5}\right) - \left(\frac{4}{5}\right) \ln\left(\frac{4}{5}\right) \right] = 0.24$$

$$\text{Entropy decrease} = 0.30 - 0.24 = 0.06$$

# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	F	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	T	T	T	T	Full	\$	F	F	Burger	30-60	T

$$\text{Entropy} = \frac{4}{12} \left[ -\left(\frac{2}{4}\right) \ln\left(\frac{2}{4}\right) - \left(\frac{2}{4}\right) \ln\left(\frac{2}{4}\right) \right] + \frac{8}{12} \left[ -\left(\frac{4}{8}\right) \ln\left(\frac{4}{8}\right) - \left(\frac{4}{8}\right) \ln\left(\frac{4}{8}\right) \right] = 0.30$$

$$\text{Entropy decrease} = 0.30 - 0.30 = 0$$

# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	T	F	Some	\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	T	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	T	T	T	F	Full	\$	F	F	Burger	30-60	T

$$\text{Entropy} = \frac{5}{12} \left[ -\left(\frac{3}{5}\right) \ln\left(\frac{3}{5}\right) - \left(\frac{2}{5}\right) \ln\left(\frac{2}{5}\right) \right] + \frac{7}{12} \left[ -\left(\frac{3}{7}\right) \ln\left(\frac{3}{7}\right) - \left(\frac{4}{7}\right) \ln\left(\frac{4}{7}\right) \right] = 0.29$$

$$\text{Entropy decrease} = 0.30 - 0.29 = 0.01$$

# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	T	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	F	T	T	F	Full	\$	F	F	Burger	30-60	T

$$\begin{aligned}
 \text{Entropy} &= \frac{2}{12} \left[ -\left(\frac{0}{2}\right) \ln\left(\frac{0}{2}\right) - \left(\frac{2}{2}\right) \ln\left(\frac{2}{2}\right) \right] + \frac{4}{12} \left[ -\left(\frac{4}{4}\right) \ln\left(\frac{4}{4}\right) - \left(\frac{0}{4}\right) \ln\left(\frac{0}{4}\right) \right] \\
 &+ \frac{6}{12} \left[ -\left(\frac{2}{6}\right) \ln\left(\frac{2}{6}\right) - \left(\frac{4}{6}\right) \ln\left(\frac{4}{6}\right) \right] = 0.14
 \end{aligned}$$

$$\text{Entropy decrease} = 0.30 - 0.14 = 0.16$$

# Decision tree learning example




Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	T	F	None	\$	T	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	F	T	F	T	Full	\$	F	F	Burger	30-60	T

$$\begin{aligned}
 \text{Entropy} &= \frac{6}{12} \left[ -\left(\frac{3}{6}\right) \ln\left(\frac{3}{6}\right) - \left(\frac{3}{6}\right) \ln\left(\frac{3}{6}\right) \right] + \frac{2}{12} \left[ -\left(\frac{2}{2}\right) \ln\left(\frac{2}{2}\right) - \left(\frac{0}{2}\right) \ln\left(\frac{0}{2}\right) \right] \\
 &+ \frac{4}{12} \left[ -\left(\frac{1}{4}\right) \ln\left(\frac{1}{4}\right) - \left(\frac{3}{4}\right) \ln\left(\frac{3}{4}\right) \right] = 0.23
 \end{aligned}$$

$$\text{Entropy decrease} = 0.30 - 0.23 = 0.07$$

# Decision tree learning example




Example	Attributes										Target	
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait	
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T	
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F	
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T	
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T	
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F	
X <sub>6</sub>	F	T	T	T	Some	\$\$\$	T	T	Italian	0-10	T	
X <sub>7</sub>	F	T	T	F	None	\$	T	F	Burger	0-10	F	
X <sub>8</sub>	F	F	F	T	Some	\$	T	T	Thai	0-10	T	
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F	
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F	
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F	
X <sub>12</sub>	F	T	T	F	Full	\$	F	F	Burger	30-60	T	

Add WeChat powcoder

$$\text{Entropy} = \frac{2}{12} \left[ -\left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) - \left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) \right] + \frac{2}{12} \left[ -\left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) - \left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) \right] \\ + \frac{4}{12} \left[ -\left(\frac{2}{4}\right) \ln\left(\frac{2}{4}\right) - \left(\frac{2}{4}\right) \ln\left(\frac{2}{4}\right) \right] + \frac{4}{12} \left[ -\left(\frac{2}{4}\right) \ln\left(\frac{2}{4}\right) - \left(\frac{2}{4}\right) \ln\left(\frac{2}{4}\right) \right] = 0.30$$

$$\text{Entropy decrease} = 0.30 - 0.30 = 0$$

# Decision tree learning example



Example	Attributes										Target
	Alt	Bar	Fri	Hun	Pat	Price	Rain	Res	Type	Est	WillWait
X <sub>1</sub>	T	F	F	T	Some	\$\$\$	F	T	French	0-10	T
X <sub>2</sub>	T	F	F	T	Full	\$	F	F	Thai	30-60	F
X <sub>3</sub>	F	T	F	F	Some	\$	F	F	Burger	0-10	T
X <sub>4</sub>	T	F	T	T	Full	\$	F	F	Thai	10-30	T
X <sub>5</sub>	T	F	T	F	Full	\$\$\$	F	T	French	>60	F
X <sub>6</sub>	F	T	F	T	Some	\$\$\$	T	T	Italian	0-10	T
X <sub>7</sub>	F	T	F	F	None	\$	F	F	Burger	0-10	F
X <sub>8</sub>	F	F	F	T	Some	\$	T	T	Thai	0-10	T
X <sub>9</sub>	F	T	T	F	Full	\$	T	F	Burger	>60	F
X <sub>10</sub>	T	T	T	T	Full	\$\$\$	F	T	Italian	10-30	F
X <sub>11</sub>	F	F	F	F	None	\$	F	F	Thai	0-10	F
X <sub>12</sub>	F	T	F	T	Full	\$	F	F	Burger	30-60	T

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

$$\text{Entropy} = \frac{6}{12} \left[ -\left(\frac{4}{6}\right) \ln\left(\frac{4}{6}\right) - \left(\frac{2}{6}\right) \ln\left(\frac{2}{6}\right) \right] + \frac{2}{12} \left[ -\left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) - \left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) \right] \\ + \frac{2}{12} \left[ -\left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) - \left(\frac{1}{2}\right) \ln\left(\frac{1}{2}\right) \right] + \frac{2}{12} \left[ -\left(\frac{0}{2}\right) \ln\left(\frac{0}{2}\right) - \left(\frac{2}{2}\right) \ln\left(\frac{2}{2}\right) \right] = 0.24$$


$$\text{Entropy decrease} = 0.30 - 0.24 = 0.06$$

## Decision tree learning example







## Decision tree learning example



# Decision tree learning example



## Decision tree learning example



Induced tree (from examples)


Cannot make it more complex  
than what the data supports.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Demo



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## How do we know it is correct?

How do we know that  $h \approx f$ ?

(Hume's Problem of Induction)


- Try  $h$  on a new assignment of examples  
(cross validation)

<https://powcoder.com>

...and assume the "principle of uniformity", i.e. the result we get on this test data should be indicative of results on future data. Causality is constant.

Learning curve for the decision tree algorithm on 100 randomly generated examples in the restaurant domain.

The graph summarizes 20 trials.




# Cross-validation

Use a “validation set”.

Assignment Project Exam Help

$$E_{gen} \approx E_{val}$$



$E_{val}$

<https://powcoder.com>

Add WeChat powcoder

Split your data set into two parts, one for training your model and the other for validating your model.

The error on the validation data is called “validation error”

$(E_{val})$


# K-Fold Cross-validation

More accurate than using only one validation set.

$$E_{gen} \approx \langle E_{val} \rangle = \frac{1}{K} \sum_{k=1}^K E_{val}(k)$$

<https://powcoder.com>


Add WeChat powcoder





## Example contd.

- Decision tree learned from the 12 examples:



- Substantially simpler than “true” tree---a more complex hypothesis isn’t justified by small amount of data

## Summary



- Learning needed for unknown environments, lazy designers
- Learning agent = performance element + learning element
- For supervised learning, the aim is to find a simple hypothesis approximately consistent with training examples
- Decision tree learning using information gain
- Learning performance = prediction accuracy measured on test set

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder