

Analysis of Algorithms

V. Adamchik

CSCI 570

Lecture 6

University of Southern California

Assignment Project Exam Help

<https://powcoder.com>
Divide-And-Conquer Algorithms

Add WeChat powcoder

Reading: chapter 5

Divide and Conquer Algorithms



- A divide-and-conquer algorithm consists of
- dividing a problem into smaller subproblems
 - solving (recursively) each subproblem
 - then combining solutions to subproblems to get solution to original problem

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Binary Search


Given a sorted array of size n :

- compare the search item with the middle
- if it's less, search in the lower half
- if it's greater, search in the upper half
- if it's equal or the entire array has been searched, terminate.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



linear
 n
 $n-1$
 $n-2$
 \vdots

binary
 n
 $n/2$
 $n/4$
 \vdots
 $\Omega(n)$


Mergesort

divides an unsorted list into two equal or nearly equal sub lists

sorts each of the sub lists by calling itself recursively, and then

merges the two sub lists together to form a sorted list

Add WeChat powcoder




$$T(n) = 2 \cdot T\left(\frac{n}{2}\right) + O(1) + O(n)$$

$$T(1) = 1$$

8 3 4 1 6 5 2 7

dividing



merge

1 2 3 4 5 6 7 8

D&C Recurrences

Suppose $T(n)$ is the number of steps in the worst case needed to solve the problem of size n .

We define the runtime complexity $T(n)$ by a recurrence equation.

<https://powcoder.com>

Binary Search: $T(n) = 1 + T\left(\frac{n}{2}\right) + O(1) + O(1)$
split. comp.

MergeSort: $T(n) = 2 \cdot T\left(\frac{n}{2}\right) + O(1) + O(n)$
dividing split merge

D&C Recurrences

Suppose $T(n)$ is the number of steps in the worst case needed to solve the problem of size n .


Let us divide a problem into $a \geq 1$ subproblems, each of which is of the input size n/b where $b > 1$.

The total complexity $T(n)$ is obtained by

$$T(n) = a \cdot T(n/b) + f(n)$$

Here $f(n)$ is a complexity of combining subproblem solutions (including complexity of *dividing* step).


Mergesort: tree of recursive calls



Tree of recursive calls

$$T(n) = a \cdot T(n/b) + f(n)$$

$$T(1) = O(1)$$



height

$$\log_b n$$

Counting leaves

$$h = \text{height}$$

$$T(n) = a \cdot T(n/b) + f(n)$$

$$h = \log_b n$$

Assignment Project Exam Help

$$a^h = a^{\log_b n}$$

<https://powcoder.com>

Add WeChat powcoder

$$\log_b n = \frac{\log_a n}{\log_a b}$$

Discussion Problem 1

① Draw a recursive tree for:


Assignment Project Exam Help
 $T(n) = 2T(n/3) + O(1)$

$T(1) = 1$
<https://powcoder.com>

$a=2; b=3; f(n)=O(1)$
Add WeChat powcoder

② and compute the total work $T(n)$.

Solution



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1

2

4

...

sum it up

$$n^{\log_3 2} = O(n^{\log_3 2})$$

verify!

leaves: $n^{\log_b a} = n^{\log_3 2}$

$$T(n) = 1 + 2 + 4 + \dots + 2^{b-1}$$

internal nodes
it depends on $f(n)$

leaves
free of $f(n)$

The Master Theorem

The master method provides a straightforward ("cookbook") method for solving recurrences of the form


Assignment Project Exam Help

$$T(n) = a \cdot T(n/b) + f(n)$$

<https://powcoder.com>

Add WeChat powcoder

where $a \geq 1$ and $b > 1$ are constants and $f(n)$ is a positive function.



The Master Theorem

$$T(n) = a \cdot T(n/b) + f(n), \quad \begin{matrix} \nearrow, 0 & \text{constants} \\ a \geq 1 \text{ and } b > 1 \end{matrix}$$

Let $c = \log_b a$.

Assignment Project Exam Help

Case 1: (only leaves)

if $f(n) = O(n^{c-\epsilon})$, then $T(n) = \Theta(n^c)$ for some $\epsilon > 0$.
<https://powcoder.com>

Add WeChat powcoder

Case 2: (all nodes) Merge sort ($k=0$)

if $f(n) = \Theta(n^c \log^k n)$, $k \geq 0$, then $T(n) = \Theta(n^c \log^{k+1} n)$
 $\uparrow !!$ $\uparrow !!!$

Case 3: (only internal nodes)

if $f(n) = \Omega(n^{c+\epsilon})$, then $T(n) = \Theta(f(n))$ for some $\epsilon > 0$.

Discussion Problem 2

Solve the recurrence by the Master Theorem:

$$T(n) = 16 T(n/4) + 5n^3$$

$$a=16$$
$$b=4$$

Assignment Project Exam Help

$$c = \log_b a = \log_4 16 = 2$$

<https://powcoder.com>

Add WhatsApp powcoder

$$T(n) = a \cdot T(n/b) + f(n)$$

Case 1: if $f(n) = O(n^{c-\epsilon})$, then $T(n) = \Theta(n^c)$

Case 2: if $f(n) = \Theta(n^c \log^k n)$, then $T(n) = \Theta(n^c \log^{k+1} n)$

Case 3: if $f(n) = \Omega(n^{c+\epsilon})$, then $T(n) = \Theta(f(n))$

where $c = \log_b a$.

Discussion Problem 3

Solve the recurrence by the Master Theorem:

case 1

$$1. A(n) = 3 A(n/3) + 15$$

leaves $f(n)$
 $O(n)$ $O(1)$, $A(n) = \Theta(n)$

case 3

$$2. B(n) = 4 B(n/2) + n^3$$

Assignment Project Exam Help

<https://powcoder.com>

leaves $f(n)$
 $O(n^2)$ $O(n^3)$, $B(n) = \Theta(n^3)$

case 2, $k=0$

$$3. C(n) = 4 C(n/2) + n^2$$

Add WeChat powcoder

$C(n) = \Theta(n^2 \log n)$

$$4. D(n) = 4 D(n/2) + n$$

$D(n) = \Theta(n^2)$


case 2 with $k=1$

$$5. E(n) = 4 E(n/2) + n^2 \log n$$

$E(n) = \Theta(n^2 \log^2 n)$

Integer Multiplication

$a + b$



Given two n -digit integers a and b , compute $a \times b$.

Brute force solution: $O(n^2)$ bit operations.

154517766 = 15451 $\cdot 10^4$ + 7766
 n digits $\frac{n}{2}$ digits $\frac{n}{2}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{array}{r} 1234 \\ \times 1111 \\ \hline 1234 \\ 1234 \\ 1234 \\ 1234 \\ \hline 1370974 \end{array}$$

$$\begin{aligned} a \cdot b &= (x_{\frac{n}{2}} \cdot 10^{\frac{n}{2}} + x_0) \cdot (y_{\frac{n}{2}} \cdot 10^{\frac{n}{2}} + y_0) = \\ &= x_{\frac{n}{2}} y_{\frac{n}{2}} 10^n \oplus (x_{\frac{n}{2}} y_0 \oplus x_0 y_{\frac{n}{2}}) 10^{\frac{n}{2}} \oplus x_0 y_0 \end{aligned}$$

$\frac{n}{2}$ bits $\frac{n}{2}$ bits base $O(1)$ new write additions base $O(1)$ $O(\frac{n}{2}) \approx O(n)$

$$T(n) = 4 \cdot T\left(\frac{n}{2}\right) + O(n)$$

$$T(n) = \Theta(n^2)$$

case 1

1961 Karatsuba's algorithm

Consider the product of two integers

$$(x_1 \cdot 10^{n/2} + x_0) \cdot (y_1 \cdot 10^{n/2} + y_0)$$

Assignment Project Exam Help

$$x_0 y_1 + x_1 y_0 = (x_0 + y_1) \cdot (x_1 + y_0) - x_0 y_0 - x_1 y_1$$

<https://powcoder.com>

$$a \cdot b = x_1 y_1 10^n + [x_0 y_1 + x_1 y_0] 10^{n/2} + x_0 y_0$$

This has 3 multiplications..

$$T(n) = 3 \cdot T\left(\frac{n}{2}\right) + O(n), \quad T(n) = \Theta\left(n^{\log_3 3}\right)$$
$$T(n) = \Theta(n^{1.58})$$

Discussion Problem 4

FFT
 $O(n \log n)$

Consider another divide and conquer algorithm for integer multiplication. The key idea is to divide a large integer into **3 parts** (rather than 2) of size approximately $n/3$ and then multiply those parts. What would be the runtime complexity of this multiplication?

Assignment Project Exam Help

154 | 5177 | 66
 $\frac{n}{3}$

<https://powcoder.com>
 Add WeChat powcoder

Rechr. equation: $T(n) = 9T\left(\frac{n}{3}\right) + O(n)$


1962, Cook from MIT
 he reduced 9 to 5
 multiplications.

$$T(n) = O(n^2)$$

$T(n) = O(n^{\log_3 5})$ better than Karatsuba's

Discussion Problem 5

Design a new Mergesort algorithm in which instead of splitting the input array in half we split it in the ratio 1:3. What is the runtime complexity of this algorithm?




Assignment Project Exam Help

do not apply the MT
<https://powcoder.com>

Recurrence: $T(n) = T\left(\frac{n}{4}\right) + T\left(\frac{3n}{4}\right) + O(n)$
Add WeChat powcoder

$$T(n) = \Theta(?)$$



and so b^h
 leaves: $O(1)$

$T(h) = h \cdot \text{height}$

$$\left. \begin{aligned} h \cdot \log_4 h &\leq T(h) \leq h \cdot \log_{\frac{4}{3}} h \\ c_2 \cdot h \cdot \log n &\leq T(h) \leq c_1 \cdot h \cdot \log n \end{aligned} \right\} \begin{matrix} T(h) \\ \Theta(h \log h) \end{matrix}$$

Discussion Problem 6

There are 2 sorted arrays A and B of size n each. Design a D&C algorithm to find the median of the array obtained after merging the above 2 arrays (i.e. array of length 2n). Discuss its runtime complexity

Assignment Project Exam Help

Input: A and B

A = [1, 3, 5, 16, 18, 21, 30]

B = [2, 13, 17, 20, 23, 29, 35]

<https://powcoder.com>

Add WhatsApp powcoder

AUB = [1, 2, 3, 5, 13, 16, 17, 18, 20, 21, 23, 29, 30, 35]

① NO D&C : $O(n)$ by merging 2 sorted arrays.

② D&C : $O(\log n)$ clue!! binary search

$$A' = [16, 18, 21, 30] \quad \text{Input size: } n/2$$

$$B' = [2, 13, 17, 20]$$

$$A'' = [16, 18, 21] \quad \text{Input size } n/4$$

$$B'' = [13, 17, 20]$$

and <https://powcoder.com>

Recurrence: $T(n) = 2T\left(\frac{n}{2}\right) + O(1)$
 same as binary search

$$T(n) = O(\log n)$$

Assignment Project Exam Help

Add WeChat powcoder

CPU for integer multiplication

GPU \rightarrow Matrix Multiplication

NVIDIA
TPU
Google tensor

gaming, ML, crypto, ...

$$C = A \times B, \text{ size } n \times n$$

$$\begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} \begin{pmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{pmatrix} = \begin{pmatrix} a_{11}b_{11} + a_{12}b_{21} & a_{11}b_{12} + a_{12}b_{22} \\ a_{21}b_{11} + a_{22}b_{21} & a_{21}b_{12} + a_{22}b_{22} \end{pmatrix}$$

Runtime: $O(n \cdot n) = O(n^2)$

$$n \times n \xrightarrow{O(n^2)} n \times n$$

$$(a_{11}, a_{12}) \cdot (b_{11}, b_{21}) \in O(n)$$

Matrix Multiplication

The usual rules of matrix multiplication holds for
block matrices

Assignment Project Exam Help

$$\begin{pmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{pmatrix} \begin{pmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{pmatrix} = \begin{pmatrix} A_{11}B_{11} + A_{12}B_{21} & A_{11}B_{12} + A_{12}B_{22} \\ A_{21}B_{11} + A_{22}B_{21} & A_{21}B_{12} + A_{22}B_{22} \end{pmatrix}$$

<https://powcoder.com>

Add WeChat powcoder

addition
 $O(n^2)$



Algorithm

Let $n = 2^k$ and $M(A, B)$ denote the matrix product

1. if A is 1×1 matrix, return $a_{11} * b_{11}$.

2. write

$$A = \begin{pmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{pmatrix} \quad B = \begin{pmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{pmatrix}$$

<https://powcoder.com>

where A_{ij} and B_{ij} are $n/2 \times n/2$ matrices.

3. Compute $C_{ij} = M(A_{i1}, B_{1j}) + M(A_{i2}, B_{2j})$

4. Return

$$\begin{pmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{pmatrix}$$

$$T(n) = 8T\left(\frac{n}{2}\right) + O(n^2), \quad T(n) = \Theta(n^3)$$

1968, Strassen's Algorithm

How many additions? 18

$$\begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix} \begin{pmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{pmatrix} = \begin{pmatrix} s_1 + s_2 - s_4 + s_6 & s_4 - s_5 \\ s_6 + s_7 & s_2 - s_3 + s_5 - s_7 \end{pmatrix}$$

$a_{21}b_{11} + a_{22}b_{21}$

$s_1 = (a_{12} - a_{22})(b_{21} + b_{22})$ Assignment Project Exam Help It takes 7 multiplications

$s_2 = (a_{11} + a_{22})(b_{11} + b_{12})$ <https://powcoder.com>

$s_3 = (a_{11} - a_{21})(b_{11} + b_{12})$

$s_4 = (a_{11} + a_{12})b_{22}$

$s_5 = a_{11}(b_{12} - b_{22})$

$s_6 = a_{22}(b_{21} - b_{11})$

$s_7 = (a_{21} + a_{22})b_{11}$

Add WeChat powcoder

$T(n) = 7 \cdot T\left(\frac{n}{2}\right) + O(n^2)$

$T(n) = \Theta(n^{\log_2 7})$

$T(n) = \Theta(n^{2.8})$

$s_6 + s_7 = a_{22}(b_{21} - b_{11}) + b_{11}(a_{21} + a_{22}) =$
 $= a_{22}b_{21} - \cancel{a_{22}b_{11}} + b_{11}a_{21} + \cancel{b_{11}a_{22}}$

Fast Matrix Multiplication

1969, Strassen $O(n^{2.808})$.

1978, Pan $O(n^{2.796})$

1979, Bini $O(n^{2.78})$

1981, Schonhage $O(n^{2.548})$

1981, Pan $O(n^{2.522})$

1982, Romani $O(n^{2.517})$

1982, Coppersmith and Winograd $O(n^{2.494})$

1986, Strassen $O(n^{2.479})$

1989, Coppersmith and Winograd $O(n^{2.376})$

2010, Stothers $O(n^{2.374})$

2011, Williams $O(n^{2.3728642})$

2014, Le Gall $O(n^{2.3728639})$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

NSA

library

theoretical-!!

Discussion Problem 7

You are given an unsorted array of ALL integers in the range $[0, \dots, 2^k - 1]$ except for one integer, denoted the missing number by M .

Assignment Project Exam Help

Describe a divide-and-conquer to find the missing number M , and discuss its the worst-case runtime complexity in terms of $n = 2^k$.

<https://powcoder.com>

Add WeChat powcoder

$k=3$ $[0, 1, 2, 3, 4, 5, 6, 7]$

Input: array of integers

Goal: split the input

input: $[5, 6, 7, 1, 2, 3, 5]$

$A = [A_1, A_2]$

$M \in A_1?$

$M \in A_2?$

What number is missed?

size n

~~100~~

000

~~111~~

001

011

~~101~~

~~110~~



size $\frac{n}{2}$

000

001

010

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$M = 010$

missing number starts with 0
followed by 1

Runtime: $T(n) = 1 \cdot T(\frac{n}{2}) + \underbrace{O(n)}_{\text{traverse the input}}$
 $T(n) = \Theta(n)$

Finding the Maximum Subsequence Sum

Given an array $A[0, \dots, n-1]$ of integers, design a D&C algorithm that finds a subarray $A[i, \dots, j]$ such that $A[i] + A[i+1] + \dots + A[j]$ is the maximum.

Assignment Project Exam Help

41

42

For example,

<https://powcoder.com>

$A = \{3, -4, 5, -2, -2, 6, -3, 5, -3, 2\}$

Add WeChat powcoder

Output: $\{5, -2, -2, 6, -3, 5\}$

Sum = $5 - 2 - 2 + 6 - 3 + 5 = 9$

Finding the Maximum Subsequence Sum (MSS)

3, -4, 5, -2, -2, 6, -3, 5, -3, 2

A_1 A_2

Assignment Project Exam Help.

$(l_1, r_1, max_1) = MSS(A_1);$ recursive
<https://powcoder.com>

$(l_2, r_2, max_2) = MSS(A_2);$ recursive
Add WeChat powcoder

$(l_3, r_3, max_3) = \underline{span}(A_1 \cup A_2);$ iterative

return $MAX(max_1, max_2, max_3);$

Finding the Maximum Subsequence Sum (MSS)

A_1 A_2

3, -4, 5, -2, -2, 6, -3, 5, -3, 2

Implementation of $span$

Assignment Project Exam Help

-2 must be a part of $span$

6 must be a part of $span$

<https://powcoder.com>

Compute partial sums

0, -3, $\left[1, -4, -2 \right]$ 6, 3, 8, 5, 7

Find the max sequence, $max_3 = 9$

Runtime: $T(n) = 2 \cdot T\left(\frac{n}{2}\right) + O(n)$

$span$