

Analysis of Algorithms

V. Adamchik

CSCI 570

Lecture 11

University of Southern California

Assignment Project Exam Help

<https://powcoder.com>
NP-Completeness
Add WeChat powcoder

Reading: chapter 9

In 1935 Alan Turing described a model of computation, known today as the Turing Machine (TM).



A problem P is *computable* (or *decidable*) if it can be solved by a Turing machine that halts on every input.

Assignment Project Exam Help

<https://powcoder.com>

Alan Turing (1936, age 22)

Add WeChat powcoder

We say that P has an *algorithm*.

Turing Machines were adopted in the 1960's, years after his death.

High Level Example of a Turing Machine

The machine that takes a binary string and appends 0 to the left side of the string.


Input: #10010Δ

Output: #010010Δ

- leftmost char

Δ - rightmost char

Transition on each edge
read,write,move (L or R)



The Church-Turing Thesis

"Any natural / reasonable notion of computation can be simulated by a TM."

~~This is not a theorem.~~
Assignment Project Exam Help

~~http://powcoder.com~~
Is it...an observation?

Add WeChat powcoder
...a definition?
...a hypothesis?

...a law of nature?

...a philosophical statement?

Everyone believes it.

No counterexample yet.

Undecidable Problems

Undecidable means that there is no computer program that always gives the correct answer: it may give the wrong answer or run forever without giving any answer.

Assignment Project Exam Help

<https://powcoder.com>

The halting problem is the problem of deciding whether a given Turing machine halts when presented with a given input.

Add WeChat powcoder

Turing's Theorem:

The Halting Problem is not decidable.

Super-Turing computation

In 1995 Hava Siegelmann proposed
Artificial Recurrent Neural Networks (ARNN).

Assignment Project Exam Help
She proved mathematically that ARNNs have
computational powers that extend the TM.
<https://powcoder.com>

Add WeChat powcoder
She claims that ARNNs can "compute" Turing
non-computable functions.

As of today the statement is not proven nor disproven.

Runtime Complexity

Let M be a Turing Machine that halts on all inputs.

Assume we compute the running time purely as a function of the length of the input string.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Definition: The running complexity is the function

$f : \mathbb{N} \rightarrow \mathbb{N}$ such that $f(n)$ is the maximum number of steps that M uses on any input of length n .

P and NP complexity classes

P = set of problems that can be solved in polynomial time by a deterministic TM.

<https://powcoder.com>

Add WeChat powcoder

NP = set of problems for which solution can be verified in polynomial time by a deterministic TM.

Polynomial Reduction: $Y \leq_p X$

To reduce a decision problem Y to a decision problem X (we write $Y \leq_p X$) we want a function f that maps Y to X such that:

1) f is a polynomial time computable

2) $\forall y \in Y$ (y is instance of Y) is YES
if and only if $f(y) \in X$ is YES.

If we cannot solve Y , we cannot solve X .

We use this to prove NP completeness: knowing that Y is hard, we prove that X is at least as hard as Y .

$$Y \leq_p X$$

If we can solve X in polynomial time,
we can solve Y in polynomial time.

Assignment Project Exam Help

<https://powcoder.com>

Examples:

Add WeChat powcoder

Bipartite Matching \leq_p Max-Flow

Circulation \leq_p Max-Flow

$$Y \leq_p X$$

If we can solve X , we can solve Y .

The contrapositive of the statement "if A , then B " is "if not B , then not A ".

Assignment Project Exam Help

<https://powcoder.com>
If we cannot solve Y , we cannot solve X .

Add WeChat powcoder

Knowing that Y is hard, we prove that X is harder.

In plain form: X is at least as hard as Y .

Two ways of using $Y \leq_p X$

1) X is easy

If we can solve X in polynomial time,
we can solve Y in polynomial time.

<https://powcoder.com>

Add WeChat powcoder

2) Y is hard

Then X is at least as hard as Y

NP-Hard and NP-Complete

X is *NP-Hard*, if $\forall Y \in \text{NP}$ and $Y \leq_p X$.

Assignment Project Exam Help

<https://powcoder.com>


X is *NP-Complete* if X is NP-Hard and $X \in \text{NP}$.

Add WeChat powcoder

Venn Diagram ($P \neq NP$)

NPH problems do not have to be in NP.

NPC problems are the most difficult NP problems.



It's not known if NPC problems can be solved by a *deterministic* TM in polynomial time.

NP-Completeness Proof Method


To show that X is NP-Complete:

- 1) Show that X is in NP
- 2) Pick a problem Y , known to be an NP-Complete
- 3) Prove $Y \leq_p X$ (reduce Y to X)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Boolean Satisfiability Problem (SAT)

A propositional logic formula is built from variables, operators AND (conjunction, \wedge), OR (disjunction, \vee), NOT (negation, \neg), and parentheses:

Assignment Project Exam Help

$(X_1 \vee \neg X_3) \wedge (X_1 \vee \neg X_2 \vee X_4 \vee X_5) \wedge \dots$

<https://powcoder.com>

A formula is said to be satisfiable if it can be made TRUE by assigning appropriate logical values (TRUE, FALSE) to its variables.

Add WeChat powcoder

A formula is in conjunctive normal form (CNF) if it is a conjunction of clauses.

A **literal** is a variable or its negation.

A **clause** is a disjunction of literals.

Cook-Levin Theorem (1971)

Theorem. CNF SAT is NP-complete.


Assignment Project Exam Help

No proof... <https://powcoder.com>

Cook received a Turing Award for his work.

You are not responsible for knowing the proof.

Reduction



Dick Karp (1972)

Karp introduced the now standard methodology for proving problems to be NP-Complete.

He received a Turing Award for his work (1985).


Independent Set

Given a graph, we say that a subset of vertices is "independent" if no two of them are joined by an edge.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Independent Set

Optimization Version:

Given a graph, find the largest independent set.

Assignment Project Exam Help

Decision Version: <https://powcoder.com>

Given a graph and a number k , does the graph contains an independent set of size k ?
Add WeChat powcoder

Optimization vs. Decision

Optimization vs. Decision Problems

If one can solve an optimization problem (in polynomial time), then one can answer the decision version (in polynomial time)

Assignment Project Exam Help

Conversely, by doing binary search on the bound b , one can transform a polynomial time answer to a decision version into a polynomial time algorithm for the corresponding optimization problem

<https://powcoder.com>

Add WeChat powcoder

In that sense, these are essentially equivalent. However, they belong to two different complexity classes.

Independent Set is NP Complete

Given a graph and a number k , does the graph contains an independent set of size k ?

Is it in NP? [Assignment Project Exam Help](https://powcoder.com)

We need to show we can verify a solution in polynomial time.

[Add WeChat powcoder](https://powcoder.com)

Given a set of vertices, we can easily count them and then verify that any two of them are not joined by an edge.

Independent Set is NP Complete

Given a graph and a number k , does the graph contains an independent set of size at least k ?

Is it in NP-hard? [Assignment Project Exam Help](#)

<https://powcoder.com>
We need to pick Y such that $Y \leq_p \text{IndSet}$ for $\forall Y \in \text{NP}$
[Add WeChat powcoder](#)

Reduce from 3-SAT.

3-SAT is SAT where each clause has at most 3 literals.

$3SAT \leq_p \text{IndSet}$


We construct a graph G that will have an independent set of size k iff the 3-SAT instance with k clauses is satisfiable.

Assignment Project Exam Help

For each clause $(X \vee Y \vee Z)$ we will be using a special gadget:

<https://powcoder.com>
Add WeChat powcoder

Next, we need to connect gadgets.







As an example, consider the following instance:

$$(X \vee Y \vee Z) \wedge (X \vee \neg Y \vee Z) \wedge (\neg X \vee Y \vee \neg Z) \wedge (\neg X \vee \neg Y)$$

$3SAT \leq_p IndSet$

$$(X \vee Y \vee Z) \wedge (X \vee \neg Y \vee Z) \wedge (\neg X \vee Y \vee \neg Z) \wedge (\neg X \vee \neg Y)$$




Add WeChat powcoder

How do we connect gadgets?

Claim:

$3SAT \leq_p IndSet$


$$(X \vee Y \vee Z) \wedge (X \vee \neg Y \vee Z) \wedge (\neg X \vee Y \vee \neg Z) \wedge (\neg X \vee \neg Y)$$



Proof. \Rightarrow)

$3SAT \leq_p IndSet$

$$(X \vee Y \vee Z) \wedge (X \vee \neg Y \vee Z) \wedge (\neg X \vee Y \vee \neg Z) \wedge (\neg X \vee \neg Y)$$



Proof. \Leftarrow)





Vertex Cover

Given $G=(V,E)$, find the smallest $S \subset V$ s.t. every edge is incident to vertices in S .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Vertex Cover

Theorem: for a graph $G=(V,E)$, S is an independent set if and only if $V-S$ is a vertex cover

Proof. \Rightarrow) Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Vertex Cover

Theorem: for a graph $G=(V,E)$, S is a independent set if and only if $V-S$ is a vertex cover

Proof. \Leftarrow) Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Vertex Cover in NP-Complete

Claim: a graph $G=(V,E)$ has an independent set of size at least k if and only if G has a vertex cover of size at most $V-k$.

Assignment Project Exam Help

Ind. Set \leq_p Vertex Cover

<https://powcoder.com>

Vertex Cover \leq_p Ind. Set

Add WeChat powcoder

Discussion Problem 1

Show that vertex cover remains NP-Complete even if the instances are restricted to graphs with only even degree vertices. Let us call this problem VC-even.

Assignment Project Exam Help

Prove: $VC \leq_p VC\text{-even}$

<https://powcoder.com>

Add WeChat powcoder

$$VC \leq_p VC\text{-even}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$VC \leq_p VC\text{-even}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Hamiltonian Cycle Problem

A Hamiltonian cycle (HC) in a graph is a cycle that visits each vertex exactly once.



Assignment Project Exam Help

Problem Statement: <https://powcoder.com>

Given a directed or undirected graph $G = (V, E)$. Find if the graph contains a Hamiltonian cycle.

We can prove it that HC problem is NP-complete by reduction from SAT, but we won't.

Discussion Problem 2

Assuming that finding a Hamiltonian Cycle (HC) in a graph is NP-complete, prove that finding a Hamiltonian Path is also NP-complete. HP is a path that visits each vertex exactly once and isn't required to return to its starting point.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder