

Analysis of Algorithms

V. Adamchik

CSCI 570

Lecture 7

University of Southern California

Assignment Project Exam Help

<https://powcoder.com>
Dynamic Programming

Add WeChat powcoder

Reading: chapter 6

Exam - I

Date: Thursday March 11

Time: starts at 5pm Pacific time

Locations: online, DEN Quiz

Practice: posted

Assignment Project Exam Help

TA Review: March 9 and March 10

<https://powcoder.com>

Add WeChat powcoder

Open book and notes

Use scratch paper

No internet searching

No talking to each other (chat, phone, messenger)

REVIEW QUESTIONS

1. (T/F) For a divide-and-conquer algorithm, it is possible that the dividing step takes asymptotically longer time than the combining step.
2. (T/F) A divide-and-conquer algorithm acting on an input size of n can have a lower bound less than $\Theta(n \log n)$.
3. (T/F) There exist some problems that can be efficiently solved by a divide-and-conquer algorithm but cannot be solved by a greedy algorithm.
4. (T/F) It is possible for a divide-and-conquer algorithm to have an exponential runtime.
5. (T/F) A divide-and-conquer algorithm is always recursive.
6. (T/F) The master theorem can be applied to the following recurrence:
 $T(n) = 1.2 T(n/2) + n$.
7. (T/F) The master theorem can be applied to the following recurrence:
 $T(n) = 9 T(n/3) - n^2 \log n + n$.
8. (T/F) Karatsuba's algorithm reduces the number of multiplications from four to three.
9. (T/F) The runtime complexity of mergesort can be asymptotically improved by recursively splitting an array into three parts (rather than into two parts).

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

10. (T/F) Two $n \times n$ matrices of integers are multiplied in $\Theta(n^2)$ time.
11. (Fill in the blank) Let A, B be two 2×2 matrices that are multiplied using the standard multiplication method and Strassen's method.
- a. Number of multiplications in the standard method: _____
 - b. Number of additions in the standard method: _____
 - c. Number of multiplications using Strassen's method: _____
 - d. Number of additions using Strassen's method: _____
12. (Fill in the blank) The space complexity of Strassen's algorithm is: _____.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fibonacci Numbers

Fibonacci number F_n is defined as the sum of two previous Fibonacci numbers:

Assignment Project Exam Help

$F_n = F_{n-1} + F_{n-2}$
<https://powcoder.com>

Add WhatsApp
 $F_0 = 0, F_1 = 1$
powcoder


Design a divide & conquer algorithm to compute Fibonacci numbers. What is its runtime complexity?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Overlapping Subproblems



Fibonacci Numbers: $F_n = F_{n-1} + F_{n-2}$

Memoization

```
int table[50]; //initialize to zero  
table[0] = table[1] = 1;
```

```
int fib(int n)  
{  
    if (table[n] != 0) return table[n];  
    else  
        table[n] = fib(n-1) + fib(n-2);  
  
    return table[n];  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Runtime complexity?

Tabulation

```
int table[n];
```

```
void fib(int n)
```

```
{
```

```
    table[0] = table[1] = 1;
```

```
    for(int k = 2; k < n; k++)
```

```
        table[k] = table[k-1] + table[k-2];
```

```
    return;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Two Approaches

```
int table[n];  
table[0] = table[1] = 1;
```

```
int fib(int n)  
{  
    if (table[n] != 0)  
        return table[n];  
    else  
        table[n] = fib(n-1) + fib(n-2);  
    return table[n];  
}
```

Memoization:
a top-down approach.

```
int table[n];
```

```
int[] fib(int n)  
{
```

```
    table[0] = table[1] = 1;  
    for(int k = 2; k < n; k++)  
        table[k] = table[k-1] + table[k-2];  
    return table;  
}
```

Tabulation:
a bottom-up approach.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic Programming

General approach: in order to solve a larger problem, we solve smaller subproblems and store their values in a table.

Assignment Project Exam Help

DP is applicable when the subproblems are greatly overlap. Compare with Mergesort.

<https://powcoder.com>

Add WeChat powcoder

DP is not greedy either. DP tries every choice before solving the problem. It is much more expensive than greedy.

DP can be implemented by means of memoization or tabulation.

Dynamic Programming

Optimal substructure means that the solution can be obtained by the combination of optimal solutions to its subproblems. Such optimal substructures are usually described recursively.

<https://powcoder.com>

Overlapping subproblems means that the space of subproblems must be small, so an algorithm solving the problem should solve the same subproblems over and over again.

Dynamic Programming

The term dynamic programming was originally used in the 1950s by Richard Bellman.

The term computer (dated from 1613) meant a person performing mathematical calculations.

<https://powcoder.com>

In the 30-50s those early computers were mostly women who used painstaking calculations on paper and later punch cards.

The earliest human computers



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Who put a man to the moon?

0-1 Knapsack Problem

Given a set of n unbreakable unique items, each with a weight w_k and a value v_k , determine the subset of items such that the total weight is less or equal to a given knapsack capacity W and the total value is as large as possible.



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Decision Tree

$$x_k = \begin{cases} 1, \text{item } k \text{ selected} \\ 0, \text{item } k \text{ not selected} \end{cases}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Subproblems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Recurrence Formula

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Tracing the Algorithm

$n = 4, W = 5$

(weight, value) = (2,3), (3,4), (4,5), (5,6)

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

	0	1	2	3	4	5	← knapsack
0	0	0	0	0	0	0	
1	0						
1,2	0						
1,2,3	0						
1,2,3,4	0						


↑ items

Pseudo-code

```
int knapsack(int W, int w[], int v[], int n) {  
    int Opt[n+1][W+1];  
    for (k = 0; k <= n; k++) {  
        for (x = 0; x <= W; x++) {  
            if (k==0 || x==0) Opt[k][x] = 0;  
            if (w[x] > x) Opt[k][x] = Opt[k-1][x];  
            else  
                Opt[k][x] = max( v[k] + Opt[k-1][x - w[k-1]],  
                                Opt[k-1][x] );  
        }  
    }  
    return Opt[n][W];  
}
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Complexity



Runtime Complexity?

Space Complexity?

Pseudo-Polynomial Runtime

Definition. A numeric algorithm runs in pseudo-polynomial time if its running time is polynomial in the numeric value of the input, but is exponential in the length of the input.

0-1 Knapsack is pseudo-polynomial algorithm, $T(n) = \Theta(n \cdot W)$

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 2

The table built in the algorithm does not show the optimal items, but only the maximum value. How do we find which items give us that optimal value?

$n = 4, W = 5$

(weight, value) = (2, 3), (3, 4), (4, 5), (5, 6)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

DP Approach

solve using the following four steps:

1. Define (in plain English) subproblems to be solved.
2. Write the recurrence relation for subproblems.
3. Write pseudo-code to compute the optimal value.
4. Compute the runtime of the above DP algorithm in terms of the input size.

Discussion Problem 3

You are to compute the **minimum** number of coins needed to make change for a given amount **m**. Assume that we have an unlimited supply of coins. All denominations d_k are sorted in ascending order:

Assignment Project Exam Help
 $1 = d_1 < d_2 < \dots < d_n$

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Longest Common Subsequence

We are given string S_1 of length n , and string S_2 of length m .

Our goal is to produce their longest common subsequence. <https://powcoder.com>

A subsequence is a subset of elements in the sequence taken in order (with strictly increasing indexes.) Or you may think as removing some characters from one string to get another.

Intuition

A B A Z D C

Assignment Project Exam Help

B A C B A D

<https://powcoder.com>

Add WeChat powcoder

Subproblems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Recurrence

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example $S = \text{ABAZDC}$
 $T = \text{BACBAD}$

		B	A	C	B	A	D
	0	0	0	0	0	0	0
A	0						
B	0						
A	0						
Z	0						
D	0						
C	0						

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Pseudo-code

```
int LCS(char[] S1, int n, char[] S2, int m)
```

```
{
```

```
int table[n+1, m+1];
```

```
table[0...n, 0] = table[0, 0...m] = 0; //init
```

```
for(i = 1; i <= n; i++)
```

```
    for(j = 1; j <= m; j++)
```

```
        if (S1[i] == S2[j]) table[i, j] = 1 + table[i-1, j-1]
```

```
        else
```

```
            table[i, j] = max(table[i, j-1], table[i-1, j]);
```

```
return table[n, m];
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How much space do we need?

		B	A	C	B	A	D
	0	0	0	0	0	0	0
A	0	0	1	1	1	1	1
B	0	1	1	1	2	2	2
A	0	1	2	2	2	3	3
Z	0	1	2	2	2	3	3
D	0	1	2	2	2	3	4
C	0	1	2	3	3	3	4

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How do we find the common sequence?

	0	0	0	0	0	0	0
	0	0	1	1	1	1	1
	0	1	1	1	2	2	2
	0	1	2	2	2	3	3
	0	1	2	2	2	3	3
	0	1	2	2	2	3	4
	0	1	2	3	3	3	4

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 4

A subsequence is **palindromic** if it reads the same left and right. Devise a DP algorithm that takes a string and returns the length of the longest palindromic subsequence (not necessarily contiguous)

· **Assignment Project Exam Help**

For example, the string

<https://powcoder.com>
QRAECCETCAURP

has several palindromic subsequences. RACECAR is one of them.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 5

You are to plan the spring 2022 schedule of classes. Suppose that you can sign up for as many classes as you want, and you'll have infinite amount of energy to handle all the classes, but you cannot have any time conflict between the lectures. Also assume that the problem reduces to planning your schedule of one particular day. Thus, consider one particular day of the week and all the classes happening on that day: c_1, \dots, c_n . Associated with each class c_i is a start time s_i and a finish time f_i and you also assign a score v_i to that class based on your interests and your program requirement. Assume $s_i < f_i$. You would like to choose a set of courses C for that day to maximize the total score. Devise an algorithm for planning your schedule.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder