

# Analysis of Algorithms

V. Adamchik

CSCI 570

Lecture 4

University of Southern California

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Greedy Algorithms

Reading: chapter 3 and 4

# Intuition: a kind of heaps

We want to create a heap with a better amortized complexity of insertion. This example will demonstrate that binary heaps do not provide a better upper bound for the worst-case complexity.

Insert  $7, 6, 5, 4, 3, 2, 1$  into an empty binary min-heap.



<https://powcoder.com>

Add WeChat powcoder

Total # of swaps in a sorted sequence

$$\sum_{k=0}^{\log n - 1} k \cdot 2^k = O(n \log n) \quad | \quad AC(insert) = O(\log n)$$

# heap ordering prop. Binomial Trees $B_k$

The binomial tree  $B_k$  is defined as

1.  $B_0$  is a single node
- 2.  $B_k$  is formed by joining two  $B_{k-1}$  trees

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


$B_0$




$B_1$



$B_2$



$B_3$



Binomial  
numbers

1

3

3

1

$2^0$

$2^1$

$2^2$

$2^3$

# Binomial Heaps

Queue

A binomial heap is a collection (a linked list) of at most  $\lceil \log n \rceil$  binomial trees (of unique rank) in increasing order of size where each tree has a heap ordering property.


min-heap

Assignment Project Exam Help

cannot have

<https://powcoder.com>

Add WeChat powcoder.



$O(\log n)$  trees  
same as the  
# of bits

LL:  $\Delta \leftrightarrow \Delta \leftrightarrow \Delta \leftrightarrow \Delta$

## Discussion Problem 1






Given a sequence of numbers: 3, 5, 2, 8, 1, 5, 2, 7.

Draw a binomial heap by inserting the above numbers reading them from left to right

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Discussion Problem 2

binary number

How many binomial trees does a binomial heap with 25 elements contain? What are the ranks of those trees?

Assignment Project Exam Help

$$25_2 = (16 + 8 + 1)_2 = \underbrace{1}_{B_4} \underbrace{1}_{B_3} \underbrace{0}_{B_2} \underbrace{0}_{B_1} \underbrace{1}_{B_0}$$

<https://powcoder.com>

$$N_2 = \text{bits}$$

$\# \text{ of bin. trees} = O(\log N) \leftarrow \# \text{ of bin. trees}$

Add WeChat powcoder

Insertion into a heap?  
is a binary addition

$$\begin{array}{r} + 11001 \\ \hline 11010 = 26_2 \\ \text{B}_4 \text{ B}_3 \text{ B}_1 \end{array}$$

# Insertion

What is its worst-case runtime complexity?

$$15_2 = 1111$$

$$\begin{array}{r} 1111 \\ + \quad 1 \\ \hline 10000 \end{array}$$

$$O(\log n)$$

Assignment Project Exam Help

<https://powcoder.com>


What is its amortized runtime complexity?

lecture 2.

$$O(1)$$

Add WeChat powcoder

Accounting Method, 2 tokens



# Building: Binomial vs Binary Heaps

online algo

The cost of inserting  $n$  elements into a binary heap, one after the other, is  $\Theta(n \log n)$  in the worst-case.

Assignment Project Exam Help

offline algo

If  $n$  is known in advance, we run heapify, so a binary heap can be constructed in time  $\Theta(n)$ .

<https://powcoder.com>

Add WhatsApp [powcoder](https://powcoder.com)


The cost of inserting  $n$  elements into a binomial heap, one after the other, is  $\Theta(n)$  (amortized cost), even if  $n$  is not known in advance.



find  $H_{in} = O(1)$

## deleteMin()

$9 \leftrightarrow 12 \leftrightarrow 6 \leftrightarrow 8$   
 merge      14



$B_K$   
has  $K$  children

Decrease Key  
5  
percolate  
up  
 $O(\log n)$

## deleteMin()

Algo:

1. delete the min,  $O(1)$
2. move subtrees to the top level
3. traverse a collection of merged trees of the same rank,  $O(\log n)$

Runtime Complexity,  $O(\log n)$

4. update the min pointer,  $O(\log n)$

$O(n)$  for binary heap

$O(\log n)$  for binomial heap

### Discussion Problem 3

Devise an algorithm for merging two binomial heaps and discuss its complexity. Merge  $B_0 B_1 B_2 B_4$  with  $B_1 B_4$ .

Algo:

Assignment Project Exam Help

10111

10010

1. merge two LL,  $O(1)$
2. traverse and merge binomial trees of the same rank,  $O(\log n)$

<https://powcoder.com>

Add WeChat powcoder

$$\begin{array}{r} + \quad 10111 \\ + \quad 10010 \\ \hline 101001 \\ B_5 \quad B_3 \quad B_0 \end{array}$$

$$LL: B_0 \leftrightarrow B_3 \leftrightarrow B_5$$

# Heaps

"lazy"  
Binomial heap  
↑

	Binary	Binomial	Fibonacci
findMin	$\Theta(1)$	$\Theta(1)$ <sup>pointer</sup>	
deleteMin	$\Theta(\log n)$	$\Theta(\log n)$	
insert	$\Theta(\log n)$	$\Theta(1)$ (ac)	
decreaseKey	$\Theta(\log n)$	$\Theta(\log n)$ ?	$O(1)$ ac
merge	$\Theta(n)$	$\Theta(\log n)$	

ac - amortized cost.

see slide 9.

# Lazy vs. Eager algorithms

## FIBONACCI HEAPS

Idea: relaxed (lazy) binomial heaps

Goal: decreaseKey in  $O(1)$  ac.

It allows trees of the same rank  
and those trees are not binomial  
trees.

CLRS textbook

The algorithm is outside of the scope of this course.

# Heaps

	Binary	<u>Binomial</u>	Fibonacci
findMin	$\Theta(1)$	$\Theta(1)$	$\Theta(1)$
<u>deleteMin</u>	$\Theta(\log n)$	$\Theta(\log n)$	$O(\log n)$ (ac)
<u>insert</u>	$\Theta(\log n)$	$\Theta(1)$ (ac)	$\Theta(1)$
<u>decreaseKey</u>	$\Theta(\log n)$	$\Theta(\log n)$	$\Theta(1)$ (ac)
merge	$\Theta(n)$	$\Theta(\log n)$	$\Theta(1)$ (ac)

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

easy

# decreaseKey: example

Suppose we want to change 11 to 5.



# Greedy Algorithms

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




$$40 = 25 + 10 + 5$$

# The Money Changing Problem

We are to make a change of \$0.40 using US currency and assuming that there is an unlimited supply of coins.

penny, nickel, dime, ...




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

greedy algo  
 $O(h)$

quad tree  
brute-force: consider all choices  
 $O(4^h)$  exponential



# SubOptimal solution

Greedy Algorithm does not always yield the global optimal solution.

denominations: 1, 5, 10, 20, 25, 50, 100

Assignment Project Exam Help

greedy:  $40 = 25 + 10 + 5$

<https://powcoder.com>


OPT:  $40 = 20 + 20$

Add WeChat powcoder

# What is Greedy Algorithm?

There is no formal definition...

- It is used to solve optimization problems
- It makes a local optimal choice at each step
- $\rightarrow$  Earlier decisions are never undone
- $\rightarrow$  Do not always yield optimal solutions



# Elements of the greedy strategy

There is no guarantee that such a greedy algorithm exists, however a problem to be solved must obey the following two common properties:

Assignment Project Exam Help

<https://powcoder.com>

greedy-choice property

and


Add WeChat powcoder

optimal substructure.

Proof. induction, contradiction


# Scheduling Problem

There is a set of  $n$  requests. Each request  $i$  has a starting time  $s(i)$  and finish time  $f(i)$ . Assume that all requests are equally important and  $s(i) \leq f(i)$ . Our goal is to develop a greedy algorithm that finds the largest compatible (non-overlapping) subset of requests.




# How do we choose requests?

1. Sort by starting time,  $s(i)$



ALG: ~~2~~ of requests 1  
OPT: 2 (B & C)

2. Sort by  $f(i) - s(i)$ , shortest first



ALG: 1 (C)  
OPT: 2 (A & B)

3. Sort by finish time,  $f(i)$

first example: C, A

second example: B, A

Goal:  $k=m$

Proof

ALG:  $i_1, i_2, \dots, i_k$

OPT:  $j_1, j_2, \dots, j_m$

Prove  $f(i_r) \leq f(j_r)$ , for  $\forall r \leq k$

by induction

OPT. substructure

Assignment Project Exam Help

Base case:  $r=1$ ,  $f(i_1) \leq f(j_1)$ , it holds

<https://powcoder.com>

IH:  $f(i_{r-1}) \leq f(j_{r-1})$ , for  $(r-1)$  request

Add WeChat powcoder

IS: prove it for  $r$ -th request

$$f(i_{r-1}) \leq f(j_{r-1}) \leq s(j_r)$$

IH

cannot overlap

Prove  $K=m$   
Proof by contradiction.

ALF:  $i$   
OPT:  $j$

Assume  $K < m$ . conclude  $\exists j_{K+1}$

$\left\{ \begin{array}{l} f(j_K) \leq s(j_{K+1}) \\ f(i_K) \leq f(j_K) \end{array} \right.$  compatible  
by induction

<https://powcoder.com>

$f(i_K) \leq s(j_{K+1})$  Add WeChat powcoder  
does not overlap

It means that  $j_{K+1}$   
with  $i_1, i_2, \dots, i_K$   
ALF will choose  $j_{K+1}$ . Contradiction.



## Discussion Problem 4

Let's consider a long, quiet country road with houses scattered very sparsely along it. We can picture the road as a long line segment, with an eastern endpoint and a western endpoint. You want to place cell phone base stations at certain points along the road so that every house is within four miles of one of the base stations.


Assignment Project Exam Help

<https://powcoder.com>

Give an efficient algorithm that achieves this goal and uses as few base stations as possible.

Add WeChat powcoder

INPUT:  
seq. of houses  
 $h_1, h_2, \dots, h_k$



Algorithm:

1. Sort the sequence of houses (west to east)

2.  repeat

Complexity: given  $n$  houses.  $O(n \log n)$

Proof of the correctness.

ALG:  $s_1, s_2, \dots, s_n$  OPT:  $t_1, t_2, \dots, t_m$

<https://powcoder.com>

INDUCTION

Add WeChat powcoder

Base case: for one house it is true

IH: assume for  $c-1$  houses

IH: prove it for  $c$  houses

$s_1, s_2, \dots, s_{c-1}, \Delta$



Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder

$OPT \text{ size} \geq ALG \text{ size}$

Brute-force: find 4LL spanning trees, find min  
exponential The Minimum Spanning Tree

Find a spanning tree of the minimum total weight.

$$MST = 1 + 2 + 3 + 4 + 6 + 7 = 23$$

Algo:


Assignment Project Exam Help

1. sort edges,  $O(E \log E)$


2. process edges in ascending order

2a. make sure that ~~A~~ cycle,  $O(V)$

Runtime:  $O(E \log E + E \cdot V)$



# ATT $O(E \log E + E \cdot V)$ Kruskal's Algorithm



Assume that you do not sort edges  
 Runtime:  $O(E \cdot E + E \cdot V)$

# T/F Questions

---

F 1. Every graph has a spanning tree.

F 2. A Minimum Spanning Tree is unique.

F 3. Kruskal's algorithm can fail in the presence of negative cost edges.

Assignment Project Exam Help

<https://www.powcoder.com>

Add WeChat powcoder

# Discussion Problem 5

You are given a graph  $G$  with all distinct edge costs. Let  $T$  be a minimum spanning tree for  $G$ . Now suppose that we replace each edge cost  $c_e$  by its square,  $c_e^2$ , thereby creating a new graph  $G_1$  with the different distinct costs. Prove or disprove whether  $T$  is still an MST for this new graph  $G_1$ .

Assignment Project Exam Help

<https://powcoder.com>

$$MST(G) = T$$

$$MST(G_1) = ?$$

FALSE  
Add WeChat powcoder

$$\text{if } c_e \geq 0, MST(G) = MST(G_1)$$


Proof. sorting order does not change.

# Discussion Problem 6

You are given a minimum spanning tree  $T$  in a graph  $G = (V, E)$ . Suppose we add a new edge (without introducing any new vertices) to  $G$  creating a new graph  $G_1$ . Devise a linear time algorithm to find an MST in  $G_1$ .


Assignment Project Exam Help

$$MST(F) = T, \quad MST(F_1) = ?$$



<https://powcoder.com>

Add WeChat powcoder



- Algorithm:  $(b, d)$
1. add that new edge to  $T$ ,  $O(1)$
  2. traverse the cycle  $(d, b, a)$ , delete the largest edge,  $O(V)$



# Prim's Algorithm

heap of vertices  
first step:




insert vertices  
delete Min  
decrease Key for  
updating edges

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



$(c, e) = 3$   
 $(d, e) = 5$

# Complexity of Prim's Algorithm

Also:

1. deleteMin  $O(\log V)$   
on each vertex  $O(V \cdot \log V)$
2. decreaseKey  $O(\log V)$   
update each edge  $O(E \cdot \log V)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$O(V \cdot \log V + E \cdot \log V)$ , binary heap

$O(V \cdot \log V + E)$ , Fibonacci heap