

Analysis of Algorithms

V. Adamchik

CSCI 570

Lecture 10

University of Southern California

Assignment Project Exam Help

<https://powcoder.com>
Linear Programming

Add WeChat powcoder

Reading: chapter 8

Linear Programming

In this lecture we describe linear programming that is used to express a wide variety of different kinds of problems. LP can solve the max-flow problem and the shortest distance, find optimal strategies in games, and many other things.

<https://powcoder.com>

We will primarily discuss the setting and how to code up various problems as linear programs.

Add WeChat powcoder

Solving by Reduction

Formally, to reduce a problem Y to a problem X (we write $Y \leq_p X$) we want a function f that maps Y to X such that:

Assignment Project Exam Help

- f is a polynomial time computable
- \forall instance $y \in Y$ is solvable if and only if $f(y) \in X$ is solvable.

<https://powcoder.com>

Add WeChat powcoder

A Production Problem

A company wishes to produce two types of souvenirs: type-A will result in a profit of \$1.00, and type-B in a profit of \$1.20.

To manufacture a type-A souvenir requires 2 minutes on machine I and 1 minute on machine II.

A type-B souvenir requires 1 minute on machine I and 3 minutes on machine II.

There are 3 hours available on machine I and 5 hours available on machine II.

How many souvenirs of each type should the company make in order to maximize its profit?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A Production Problem

	Type-A	Type-B	Time Available
Profit/Unit	\$1.00	\$1.20	
Machine I	2 min	1 min	180 min
Machine II	1 min	3 min	300 min

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A Linear Program

We want to maximize the objective function


subject to the system of inequalities:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A Production Problem



We need to find the feasible point that is farthest in the "objective" direction

Fundamental Theorem

If a linear programming problem has a solution, then it must occur at a vertex, or corner point, of the feasible set S .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

If the objective function P is optimized at two adjacent vertices of S , then it is optimized at every point on the line segment joining these vertices, in which case there are **infinitely** many solutions to the problem.

Existence of Solution

Suppose we are given a LP problem with a feasible set S and an objective function P . There are 3 cases to consider

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Standard LP form

We say that a maximization linear program with n variables is in standard form if for every variable x_k we have the inequality $x_k \geq 0$ and all other m linear inequalities. A LP in standard form is written as

$$\max (c_1x_1 + \dots + c_nx_n)$$

subject to

$$a_{11}x_1 + \dots + a_{1n}x_n \leq b_1$$

$$\vdots$$

$$a_{m1}x_1 + \dots + a_{mn}x_n \leq b_m$$

$$x_1 \geq 0, \dots, x_n \geq 0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Standard LP in Matrix Form

The vector c is the column vector (c_1, \dots, c_n) .

The vector x is the column vector (x_1, \dots, x_n) .

The matrix A is the $n \times m$ matrix of coefficients of the left-hand sides of the inequalities, and

$b = (b_1, \dots, b_m)$ is the vector of right-hand sides of the inequalities.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{array}{ll} \max & (c^T x) \\ \text{subject to} & \\ & Ax \leq b \\ & x \geq 0 \end{array}$$

Exercise: Convert to Matrix Form

$$\max(x_1 + 1.2 x_2)$$

$$2x_1 + x_2 \leq 180$$

$$x_1 + 3x_2 \leq 300$$

$$x_1 \geq 0$$

$$x_2 \geq 0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Algorithms for LP

The standard algorithm for solving LPs is the **Simplex Algorithm**, due to **Dantzig**, 1947.

Assignment Project Exam Help

This algorithm starts by finding a vertex of the polytope, and then moving to a neighbor with increased cost as long as this is possible. By linearity and convexity, once it gets stuck it has found the optimal solution.

<https://powcoder.com>

Add WeChat powcoder

Unfortunately simplex does not run in polynomial time it does well in practice, but poorly in theory.

Algorithms for LP

In 1974 **Khachian** has shown that LP could be done in polynomial time by something called the **Ellipsoid Algorithm** (but it tends to be fairly slow in practice).

Assignment Project Exam Help

<https://powcoder.com>

In 1984, **Karmarkar** discovered a faster polynomial-time algorithm called "**interior-point**". While simplex only moves along the outer faces of the polytope, "interior-point" algorithm moves inside the polytope.

MATLAB

<https://www.mathworks.com/help/optim/ug/linprog.html>

linprog

Linear programming solver

Finds the minimum of a problem specified by

$$\min_x f^T x \text{ such that } \begin{cases} A \cdot x \leq b, \\ A_{eq} \cdot x = b_{eq}, \\ lb \leq x \leq ub. \end{cases}$$

f , x , b , b_{eq} , lb , and ub are vectors and A and A_{eq} are matrices.

Description

$x = \text{linprog}(f, A, b)$ solves $\min f^T x$ such that $A \cdot x \leq b$.

$x = \text{linprog}(f, A, b, A_{eq}, b_{eq})$ includes equality constraints $A_{eq} \cdot x = b_{eq}$. Set $A = []$ and $b = []$ if no inequalities exist.

$x = \text{linprog}(f, A, b, A_{eq}, b_{eq}, lb, ub)$ defines a set of lower and upper bounds on the design variables, x , so that the solution is always in the range $lb \leq x \leq ub$. Set $A_{eq} = []$ and $b_{eq} = []$ if no equalities exist.

Discussion Problem 1

A cargo plane can carry a maximum weight of 100 tons and a maximum volume of 60 cubic meters. There are three materials to be transported, and the cargo company may choose to carry any amount of each, up to the maximum available limits given below.

Assignment Project Exam Help

<https://powcoder.com>

	Density	Volume	Price
Material 1	2 tons/m ³	40 m ³	\$1,000 per m ³
Material 2	1 tons/m ³	30 m ³	\$2,000 per m ³
Material 3	3 tons/m ³	20 m ³	\$12,000 per m ³

Add WeChat powcoder

Write a linear program that optimizes revenue within the constraints.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 2

There are n people and n jobs. You are given a cost matrix, C , where c_{ij} represents the cost of assigning person i to do job j . You need to assign all the jobs to people and also only one job to a person. You also need to minimize the total cost of your assignment. Write a linear program that minimizes the total cost of your assignment.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 3

Convert the following LP to standard form

$$\max (5x_1 - 2x_2 + 9x_3)$$

Assignment Project Exam Help

$$3x_1 + x_2 + 4x_3 = 8$$

<https://powcoder.com>

$$2x_1 + 7x_2 - 6x_3 \leq 4$$

$$x_1 \leq 0, x_3 \geq 1$$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 4

Explain why LP cannot contain constraints in the form of *strong* inequalities.

$$\max(7x_1 - x_2 + 5x_3)$$

$$x_1 + x_2 + 4x_3 < 8$$

$$3x_1 - x_2 + 2x_3 > 3$$

$$2x_1 + 5x_2 - x_3 \leq -7$$

$$x_1, x_2, x_3 \geq 0$$


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exercise: Max-Flow as LP

Write a max-flow problem as a linear program.





Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Exercise: Shortest Path as LP

Write a shortest st-path problem as a linear program.





Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 5

Write a 0-1 Knapsack Problem as a linear program.

Given n items with weights w_1, w_2, \dots, w_n and values v_1, v_2, \dots, v_n .
Put these items in a knapsack of capacity W to get the maximum total value.

Assignment Project Exam Help

<http://powcoder.com>

Add WeChat powcoder

$$\text{Given } \sum_{k=1}^m w_k \leq W$$

$$\text{optimize } \sum_{k=1}^m v_k \rightarrow \max$$

Knapsack as LP

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dual LP

Assignment Project Exam Help
To every linear program there is
a dual linear program

<https://powcoder.com>

Add WeChat powcoder



Duality

Definition. The dual of the standard (primal) maximum problem

$$\max c^T x$$

$$Ax \leq b \text{ and } x \geq 0$$

Assignment Project Exam Help

<https://powcoder.com>

is defined to be the standard minimum problem

Add WeChat powcoder

$$\min b^T y$$

$$A^T y \geq c \text{ and } y \geq 0$$

Exercise: duality

Consider the LP:

$$\max(7x_1 - x_2 + 5x_3)$$

$$x_1 + x_2 + 4x_3 \leq 8$$

Assignment Project Exam Help

$$3x_1 - x_2 + 2x_3 \leq 3$$

$$2x_1 + 5x_2 - x_3 \leq -7$$

<https://powcoder.com>

$$x_1, x_2, x_3 \geq 0$$

Add WeChat powcoder

Write the dual problem.

$$\max (c^T x)$$

$$A x \leq b$$

$$x \geq 0$$

primal LP



$$\min (b^T y)$$

$$A^T y \geq c$$

$$y \geq 0$$

dual LP

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

From Primal to Dual

Consider the max LP constraints

$$a_{11}x_1 + \dots + a_{1n}x_n \leq b_1$$

Assignment Project Exam Help

$$a_{m1}x_1 + \dots + a_{mn}x_n \leq b_m$$

<https://powcoder.com>

Add WeChat powcoder

- 1) Multiply each equation by a new variable $y_k \geq 0$.
- 2) Add up those m equations.
- 3) Collect terms wrt to x_k .
- 4) Choose y_k in a way such that $A^T y \geq c$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Weak Duality

$$\begin{array}{l} \max (c^T x) \\ A x \leq b \\ x \geq 0 \end{array}$$

primal linear
program



$$\begin{array}{l} \min (b^T y) \\ A^T y \geq c \\ y \geq 0 \end{array}$$

dual linear
program

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Weak Duality. The optimum of the dual is an upper bound to the optimum of the primal.

$$\text{opt}(\text{primal}) \leq \text{opt}(\text{dual})$$

Weak Duality

$$\begin{array}{l} \max (c^T x) \\ Ax \leq b \\ x \geq 0 \end{array}$$



$$\begin{array}{l} \min (b^T y) \\ A^T y \geq c \\ y \geq 0 \end{array}$$

Assignment Project Exam Help

Theorem (The weak duality)

<https://powcoder.com>

Let P and D be primal and dual LP correspondingly.

If x is a feasible solution for P and y is a feasible solution for D, then $c^T x \leq b^T y$.

Add WeChat powcoder

Proof (in matrix form).

Weak Duality: $\text{opt}(\text{primal}) \leq \text{opt}(\text{dual})$

Corollary 1. If a standard problem and its dual are both feasible, then both are feasible bounded.

Assignment Project Exam Help

<https://powcoder.com>

Corollary 2. If one problem has an unbounded solution, then the dual of that problem is infeasible.

Strong Duality

$$\begin{array}{l} \max (c^T x) \\ Ax \leq b \\ x \geq 0 \end{array}$$



$$\begin{array}{l} \min (b^T y) \\ A^T y \geq c \\ y \geq 0 \end{array}$$

Assignment Project Exam Help

<https://powcoder.com>

Theorem (The strong duality)

Let P and D be primal and dual LP correspondingly.

If P and D are feasible, then $c^T x = b^T y$.

The proof of this theorem is beyond the scope of this course.

Possibilities for the Feasibility

$$\max (c^T x)$$

$$A x \leq b$$

$$x \geq 0$$

$$\min (b^T y)$$

$$A^T y \geq c$$

$$y \geq 0$$

Assignment Project Exam Help

P \ D	F.B.	F.U.	I.
F.B.			
F.U.			
I.			

<https://powcoder.com>

Add WeChat powcoder

feasible bounded - F.B.

feasible unbounded - F.U.

infeasible - I.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Discussion Problem 6

Consider the LP:

$$\max(3x_1 + 8x_2 + x_3)$$

$$x_1 + 4x_2 - 2x_3 \leq 20$$

$$x_1 + x_2 + x_3 \geq 7$$

$$x_2 + x_3 = 3$$

$$x_2 \geq -1$$

$$x_3 \leq 5$$

Write the dual problem.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Finding the Dual in Equality Form

$$\begin{array}{l} \max (c^T x) \\ Ax = b \\ x \geq 0 \end{array}$$



$$\begin{array}{l} \min (b^T y) \\ A^T y \leq c \end{array}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Very often linear programs are encountered in equality form $Ax = b$. A problem can be transformed into inequality form by replacing each equation by two inequalities.

$$\begin{array}{l} Ax \leq b \\ -Ax \leq -b \end{array}$$

The dual can then be found by applying the definition of the dual to this problem. Let y^+ and y^- be the dual variables associated with each of the above inequality.

Finding the Dual in Equality Form

$$\max (c^T x)$$

$$A x = b$$

$$x \geq 0$$

Assignment Project Exam Help

$$\max (c^T x)$$

$$A x \leq b$$

$$-A x \leq -b$$

$$x \geq 0$$

<https://powcoder.com>

Add WeChat powcoder



$$\min (b^T y^+ - b^T y^-)$$

$$A^T y^+ - A^T y^- \geq c$$

$$y^+ \geq 0, y^- \geq 0$$

$$\min (b^T (y^+ - y^-))$$

$$A^T (y^+ - y^-) \geq c$$

$$y^+ \geq 0, y^- \geq 0$$

Nonlinear Optimization

$$\max f(x_1, x_2, \dots, x_n)$$

$$h_i(x_1, x_2, \dots, x_n) \leq 0, i = 1, \dots, m$$

$$x_k \geq 0, k = 1, \dots, n$$

Add WeChat powcoder

Here **f** and/or **h** are nonlinear functions.

The problem is solved using Lagrange multipliers.