

Rotation around an arbitrary axis

Euler's theorem: Any rotation or sequence of rotations around a point is equivalent to a single rotation around an axis that passes through the point.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

What does the matrix look like?

Rotation around an arbitrary axis through the origin

Axis: \mathbf{u}

Point: P

Angle: β

Approach (one of many):

1. *Two rotations to align \mathbf{u} with x -axis (arbitrary choice)*


2. *Do x -roll by β*

3. *Undo the alignment*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Derivation

1. $R_z(-\phi)R_y(\theta)$

2. $R_x(\beta)$

3. $R_y(-\theta)R_z(\phi)$


Altogether:

$$R_y(-\theta)R_z(\phi) R_x(\beta) R_z(-\phi)R_y(\theta)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Derivation

1. $R_z(-\phi)R_y(\theta)$

2. $R_x(\beta)$

3. $R_y(-\theta)R_z(\phi)$

Altogether:

$$R_y(-\theta)R_z(\phi) R_x(\beta) R_z(-\phi)R_y(\theta)$$

Parameters:

$$\cos(\theta) = u_x / \sqrt{u_x^2 + u_z^2}$$

$$\sin(\theta) = u_z / \sqrt{u_x^2 + u_z^2}$$


$$\sin(\phi) = u_y / |\mathbf{u}|$$

$$\cos(\phi) = \sqrt{u_x^2 + u_z^2} / |\mathbf{u}|$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Derivation

1. $R_z(-\phi)R_y(\theta)$

$$\cos(\theta) = u_x / \sqrt{u_x^2 + u_z^2}$$

2. $R_x(\beta)$

$$\sin(\theta) = u_z / \sqrt{u_x^2 + u_z^2}$$

3. $R_y(-\theta)R_z(\phi)$

$$\sin(\phi) = u_y / |\mathbf{u}|$$

$$\cos(\phi) = \sqrt{u_x^2 + u_z^2} / |\mathbf{u}|$$

Altogether:

$$R_y(-\theta)R_z(\phi) R_x(\beta) R_z(-\phi)R_y(\theta)$$


Exercise:

Derive the matrix for rotation around an axis that does not pass through the origin

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Properties of affine transformations

1. *Preservation of affine combinations of points.*
2. *Preservation of lines and planes.*
3. *Preservation of parallelism of lines and planes.*
4. *Relative ratios on a line are preserved.*
5. *Affine transformations are composed of elementary ones.*

Assignment Project Exam Help

<https://powcoder.com>

And WeChat: powcoder

Affine Combinations of Points

Assignment Project Exam Help

$$W = a_1P_1 + a_2P_2$$

$$T(W) = T(a_1P_1 + a_2P_2) = a_1T(P_1) + a_2T(P_2)$$

Add WeChat powcoder

Proof: from linearity of matrix multiplication

$$MW = M(a_1P_1 + a_2P_2) = a_1MP_1 + a_2MP_2$$

Preservations of Lines and Planes

Line:

$$L(t) = (1 - t)P_1 + tP_2$$

$$T(L(t)) = (1 - t)T(P_1) + tT(P_2)$$

Plane

$$Pl(s, t) = (1 - s - t)P_1 + tP_2 + sP_3$$

$$T(Pl(s, t)) = (1 - s - t)T(P_1) + tT(P_2) + sT(P_3)$$

Proof: Direct consequence of previous property

Preservation of Parallelism for Lines and Planes

$L(t) = P + t\mathbf{u}$ Assignment Project Exam Help

<https://powcoder.com>

$$ML = M(P + t\mathbf{u}) = MP + M(t\mathbf{u}) \rightarrow$$

$$ML = MP + t(M\mathbf{u})$$


$M\mathbf{u}$ independent of P .

Similarly for planes.

Rigid body transformation

Combination of a translation and a rotation

- Preserve lines, angles and distances
- 6 Degrees of freedom in 3D



General form of 3D affine transformations

Rotation, Scaling,
Shear

Translation

Assignment Project Exam Help

<https://powcoder.com>
Add WeChat powcoder

$$\begin{pmatrix} m_{11} & m_{12} & m_{13} & m_{14} \\ m_{21} & m_{22} & m_{23} & m_{24} \\ m_{31} & m_{32} & m_{33} & m_{34} \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Transforming Points and Vectors

- Points

$$\begin{pmatrix} Q_x \\ Q_y \\ Q_z \\ 1 \end{pmatrix} = \begin{pmatrix} m_{11} & m_{12} & m_{13} & m_{14} \\ m_{21} & m_{22} & m_{23} & m_{24} \\ m_{31} & m_{32} & m_{33} & m_{34} \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ P_z \\ 1 \end{pmatrix}$$

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

- Vectors

$$\begin{pmatrix} w_x \\ w_y \\ w_z \\ 0 \end{pmatrix} = \begin{pmatrix} m_{11} & m_{12} & m_{13} & m_{14} \\ m_{21} & m_{22} & m_{23} & m_{24} \\ m_{31} & m_{32} & m_{33} & m_{34} \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} v_x \\ v_y \\ v_z \\ 0 \end{pmatrix}$$

Advanced concepts

Generalized shears

Decomposition of 2D AT:

2D : $M = T \text{ Sh } S \text{ R}$

3D: $M = T \text{ S } R \text{ Sh}_1 \text{ Sh}_2$

Rotations in 3D

Gimbal lock

Quaternions

Exponential maps

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Transformations of Coordinate systems

Coordinate systems consist of vectors and an origin (point), therefore we can transform them just like any other group of points and vectors

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Alternative way to think of transformations:


- Transformations as a change of basis

Reminder: Coordinate systems

Coordinate Assignment Project Exam Help
system: $(\mathbf{a}, \mathbf{b}, \mathbf{c}, \theta)$

<https://powcoder.com>

Add WeChat powcoder



$$\mathbf{v} = (v_1, v_2, v_3) \rightarrow \mathbf{v} = v_1 \mathbf{a} + v_2 \mathbf{b} + v_3 \mathbf{c}$$

$$P = (p_1, p_2, p_3) \rightarrow P - \theta = p_1 \mathbf{a} + p_2 \mathbf{b} + p_3 \mathbf{c}$$

$$P = \theta + p_1 \mathbf{a} + p_2 \mathbf{b} + p_3 \mathbf{c}$$

Reminder: The homogeneous representation of points and vectors


$$\mathbf{v} = v_1\mathbf{a} + v_2\mathbf{b} + v_3\mathbf{c} \rightarrow \mathbf{v} = (\mathbf{a}, \mathbf{b}, \mathbf{c}, \theta) \begin{pmatrix} v_1 \\ v_2 \\ v_3 \\ 0 \end{pmatrix}$$

Assignment Project Exam Help

<https://powcoder.com>

$$P = \theta + p_1\mathbf{a} + p_2\mathbf{b} + p_3\mathbf{c} \rightarrow P = (\mathbf{a}, \mathbf{b}, \mathbf{c}, \theta) \begin{pmatrix} p_1 \\ p_2 \\ p_3 \\ 1 \end{pmatrix}$$

Add WeChat powcoder



Transformation as a change of CS

Assume a coordinate system A and a point P


$$P_A = (a, b, c)_A \rightarrow$$

$$P_A = a\mathbf{x} + b\mathbf{y} + c\mathbf{z} + O$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Transformation as a change of CS

$$P_A = (a, b, c, 1)_A \rightarrow$$

$$P_A = a\mathbf{x} + b\mathbf{y} + c\mathbf{z} + O$$

Transform with \mathbf{M}

$$Q_A = \mathbf{M}P_A \rightarrow Q_A = (a, e, f, 1)_A$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Transformation as a change of CS

$$P_A = (a, b, c, 1)_A \rightarrow$$

$$P_A = a\mathbf{x} + b\mathbf{y} + c\mathbf{z} + O$$


Transform with \mathbf{M}

$$Q_A = \mathbf{M}P_A \rightarrow Q_A = (d, e, f, 1)_A$$

Using the full form of P_A

$$Q_A = \mathbf{M}P_A = \mathbf{M}(a\mathbf{x}_A + b\mathbf{y}_A + c\mathbf{z}_A + O_A) \rightarrow$$

$$Q = a(\mathbf{M}\mathbf{x}) + b(\mathbf{M}\mathbf{y}) + c(\mathbf{M}\mathbf{z}) + \mathbf{M}O$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Transformation as a change of CS

$$P_A = (a, b, c, 1)_A \rightarrow$$

$$P_A = a\mathbf{x} + b\mathbf{y} + c\mathbf{z} + O$$

Transform with \mathbf{M}

$$Q_A = \mathbf{M}P_A \rightarrow Q_A = (d, e, f, 1)_A$$

Using the full form of P_A

$$Q_A = \mathbf{M}P_A = \mathbf{M}(a\mathbf{x}_A + b\mathbf{y}_A + c\mathbf{z}_A + O_A)$$

$$Q = a(\mathbf{M}\mathbf{x}) + b(\mathbf{M}\mathbf{y}) + c(\mathbf{M}\mathbf{z}) + \mathbf{M}O$$

We define coordinate system B :


$$\mathbf{u} = \mathbf{M}\mathbf{x}, \quad \mathbf{v} = \mathbf{M}\mathbf{y}, \quad \mathbf{w} = \mathbf{M}\mathbf{z}, \quad G = \mathbf{M}O$$

Which means:

$$Q = a\mathbf{u} + b\mathbf{v} + c\mathbf{w} + G$$

Notice that by definition:

$$Q_B = (a, b, c, 1)_B$$




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Transformation as a change of CS

So interpretation one:



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$P_A = (a, b, c, 1)_A \rightarrow$$

$$P_A = a\mathbf{x} + b\mathbf{y} + c\mathbf{z} + O$$

Transform with \mathbf{M}

$$Q_A = \mathbf{M}P_A \rightarrow Q_A = (d, e, f, 1)_A$$

Transformation as a change of CS

So interpretation two:

$$P_A = (a, b, c, 1)_A \rightarrow$$

$$P = a\mathbf{x} + b\mathbf{y} + c\mathbf{z} + G$$


Transform CS A with M into CS B

$$\mathbf{u} = M\mathbf{x}, \quad \mathbf{v} = M\mathbf{y}, \quad \mathbf{w} = M\mathbf{z}, \quad G = MO$$

The point maintains its coordinates but with respect to the new CS B

$$Q_B = (a, b, c, 1)_B$$

In other words the point is fixed with respect to the moving CS



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Transformation as a change of CS

So we have:

$$P_A = (a, b, c, 1), \quad Q_A = (d, e, f, 1),$$

$$Q_B = (a, b, c, 1), \quad Q_A = \mathbf{M}P_A$$

Which means


$$Q_A = \mathbf{M}P_A \rightarrow Q_A = \mathbf{M}Q_B$$

Let's show explicitly the coordinates of each side of the matrix


$$Q_A = {}_A\mathbf{M}_B Q_B$$

Remember, the same matrix transforms CS A into CS B, e.g.

$$\mathbf{u}_A = {}_A\mathbf{M}_B \mathbf{x}_A$$



Transformation as a change of CS



Fixed point: $Q = (a, b, c, 1)$

We can repeat the process for system B and C ignoring A

$CS_C = T(CS_B) : \mathbf{i}_B = {}_B\mathbf{M}_C \mathbf{u}_B, \mathbf{j}_B = {}_B\mathbf{M}_C \mathbf{u}_j$ etc


and

$$Q_B = {}_B\mathbf{M}_C Q_C$$

Then chain them all together:

$$Q_A = {}_A\mathbf{M}_B {}_B\mathbf{M}_C Q_C$$

Chain of CS




Chain or hierarchy of CS (frames): $A \rightarrow B \rightarrow C$

Represented by the matrix relationships:

$$Q_B = {}_B\mathbf{M}_C Q_C, \quad Q_A = {}_A\mathbf{M}_B Q_B, \quad Q_A = {}_A\mathbf{M}_B {}_B\mathbf{M}_C Q_C$$

Chain can be reformulated



Chain or hierarchy of CS (frames): $A \rightarrow B \rightarrow C$


Represented by the matrix relationships:

$$Q_B = {}_B\mathbf{M}_C Q_C, \quad Q_A = {}_A\mathbf{M}_B Q_B, \quad Q_A = {}_A\mathbf{M}_B {}_B\mathbf{M}_C Q_C$$

Reformulate chain $B \rightarrow A \rightarrow C$

Represented by the matrix relationships:.... ?

Chain can be reformulated



Add WeChat powcoder

Chain or hierarchy of CS (frames): $A \rightarrow B \rightarrow C$

$$Q_B = {}_B\mathbf{M}_C Q_C, \quad Q_A = {}_A\mathbf{M}_B Q_B, \quad Q_A = {}_A\mathbf{M}_B {}_B\mathbf{M}_C Q_C$$


Reformulate chain $B \rightarrow A \rightarrow C$

$$Q_B = {}_B\mathbf{M}_A Q_A, \quad Q_A = {}_A\mathbf{M}_C Q_C, \quad Q_B = {}_B\mathbf{M}_A {}_A\mathbf{M}_C Q_C$$

remember: Non-trivial affine transformations can be inverted

$${}_B\mathbf{M}_A = ({}_A\mathbf{M}_B)^{-1}, \quad {}_A\mathbf{M}_C = {}_A\mathbf{M}_B {}_B\mathbf{M}_C$$

Exercise



Chain: $A \rightarrow B \rightarrow C$

$$Q_B = {}_B\mathbf{M}_C Q_C, \quad Q_A = {}_A\mathbf{M}_B Q_B, \quad Q_A = {}_A\mathbf{M}_{BB}\mathbf{M}_C Q_C$$

Chain $B \rightarrow A \rightarrow C$

$$Q_B = {}_B\mathbf{M}_A Q_A, \quad Q_A = {}_A\mathbf{M}_C Q_C, \quad Q_B = {}_B\mathbf{M}_{AA}\mathbf{M}_C Q_C$$

$${}_B\mathbf{M}_A = ({}_A\mathbf{M}_B)^{-1}, \quad {}_A\mathbf{M}_C = {}_A\mathbf{M}_{BB}\mathbf{M}_C$$

What is ${}_C\mathbf{M}_A$?

More details and derivations

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Transforming CS1 into CS2

- Using an affine matrix M

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Transforming CS1 into CS2

- Using an affine matrix M

Transform each element of the frame:

$$O'_{CS1} = T(O_{CS1}) = T((0, 0, 0, 1)) = M[0 \ 0 \ 0 \ 1]^T$$

$$\mathbf{i}'_{CS1} = T(\mathbf{i}_{CS1}) = T((1, 0, 0, 0)) = M[1 \ 0 \ 0 \ 0]^T$$

$$\mathbf{j}'_{CS1} = T(\mathbf{j}_{CS1}) = T((0, 1, 0, 0)) = M[0 \ 1 \ 0 \ 0]^T$$


$$\mathbf{k}'_{CS1} = T(\mathbf{k}_{CS1}) = T((0, 0, 1, 0)) = M[0 \ 0 \ 1 \ 0]^T$$

The following hold by definition:

$$O'_{CS2} = (0, 0, 0, 1)_{CS2}, \quad \mathbf{i}'_{CS2} = (1, 0, 0, 0)_{CS1} \cdots$$

Also remember that:

$$\mathbf{i}_{CS1} = (0, 0, 0, 0)_{CS1} \text{ means } \mathbf{i}_{CS1} = 1\mathbf{i}_{CS1} + 0\mathbf{j}_{CS1} + 0\mathbf{k}_{CS1} + 0O_{CS1}$$



Transforming CS1 into CS2

- Using an affine matrix M

Transform each element of the frame:

$$O'_{CS1} = T(O_{CS1}) = T((0, 0, 0, 1)) = M[0 \ 0 \ 0 \ 1]^T$$

$$\mathbf{i}'_{CS1} = T(\mathbf{i}_{CS1}) = T((1, 0, 0, 0)) = M[1 \ 0 \ 0 \ 0]^T$$

$$\mathbf{j}'_{CS1} = T(\mathbf{j}_{CS1}) = T((0, 1, 0, 0)) = M[0 \ 1 \ 0 \ 0]^T$$

$$\mathbf{k}'_{CS1} = T(\mathbf{k}_{CS1}) = T((0, 0, 1, 0)) = M[0 \ 0 \ 1 \ 0]^T$$

The following hold by definition:

$$O'_{CS2} = (0, 0, 0, 1), \mathbf{i}'_{CS2} = (1, 0, 0, 0) \dots$$


The following hold by definition for a point P in the space:

$$P_{CS1} = (a, b, c, 1)_{CS1} = a\mathbf{i}_{CS1} + b\mathbf{j}_{CS1} + c\mathbf{k}_{CS1} + O_{CS1}$$

$$P_{CS2} = (d, e, f, 1)_{CS2} = d\mathbf{i}'_{CS2} + e\mathbf{j}'_{CS2} + f\mathbf{k}'_{CS2} + O'_{CS2}$$

$$P_{CS1} = (a, b, c, 1)_{CS1} = d\mathbf{i}'_{CS1} + e\mathbf{j}'_{CS1} + f\mathbf{k}'_{CS1} + O'_{CS1}$$

$$P_{CS2} = (d, e, f, 1)_{CS2} = a\mathbf{i}_{CS2} + b\mathbf{j}_{CS2} + c\mathbf{k}_{CS2} + O_{CS2}$$



Both systems are equivalent.
There is nothing special about CS1

Transforming CS1 into CS2

- What is the relationship between P in CS2 and P in CS1 if $CS2 = T(CS1)$ and T is an affine transformation represented by matrix M?

Notation and what we know:

$$P_{CS1} = (a, b, c, 1)^T$$


$$P_{CS2} = (d, e, f, 1)^T$$

$$O' = T(O), \quad i' = T(i), \quad j' = T(j), \quad k' = T(k)$$

Reminder:

$$O'_{CS2} = (0, 0, 0, 1), \quad O'_{CS1} = T((0, 0, 0, 1)) = M \mathbf{0}$$

$$i'_{CS2} = (1, 0, 0, 0), \quad i'_{CS1} = T((1, 0, 0, 0))$$



Derivation

In any frame $P = d\mathbf{i}' + e\mathbf{j}' + f\mathbf{k}' + O'$ so in CS1 $P_{CS1} = d\mathbf{i}'_{CS1} + e\mathbf{j}'_{CS1} + f\mathbf{k}'_{CS1} + O'_{CS1}$

We know that $(\mathbf{i}, \mathbf{j}, \mathbf{k}, O) = T((\mathbf{i}', \mathbf{j}', \mathbf{k}', O'))$

All vectors below are in frame CS1 so for example $\mathbf{i} = (1, 0, 0, 0)$

$$P_{CS1} = dT(\mathbf{i}) + eT(\mathbf{j}) + fT(\mathbf{k}) + T(O) = d(\mathbf{M}\mathbf{i}) + e(\mathbf{M}\mathbf{j}) + f(\mathbf{M}\mathbf{k}) + \mathbf{M}O$$

$$= d(\mathbf{M} \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}) + e(\mathbf{M} \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}) + f(\mathbf{M} \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}) + \mathbf{M} \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$$

$$= \mathbf{M} \begin{bmatrix} d \\ 0 \\ 0 \\ 0 \end{bmatrix} + \mathbf{M} \begin{bmatrix} 0 \\ e \\ 0 \\ 0 \end{bmatrix} + \mathbf{M} \begin{bmatrix} 0 \\ 0 \\ f \\ 0 \end{bmatrix} + \mathbf{M} \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$$

$$= \mathbf{M} \left(\begin{bmatrix} d \\ 0 \\ 0 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ e \\ 0 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ f \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix} \right) = \mathbf{M} \begin{bmatrix} d \\ e \\ f \\ 1 \end{bmatrix}$$

P in CS1 vs P in CS2


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$P_{CS1} = M P_{CS2}$$

$$\begin{pmatrix} a \\ b \\ c \\ 1 \end{pmatrix} = M \begin{pmatrix} d \\ e \\ f \\ 1 \end{pmatrix}$$



Successive transformations of the Coordinate System

CS1 → CS2 → CS3

T1

T2


Assignment Project Exam Help

<https://powcoder.com>

Working backwards:

$$P_{CS2} = M_2 P_{CS3} \rightarrow \begin{pmatrix} d \\ e \\ f \\ 1 \end{pmatrix} = M_2 \begin{pmatrix} g \\ h \\ m \\ 1 \end{pmatrix}$$

$$P_{CS1} = M_1 P_{CS2} \rightarrow \begin{pmatrix} a \\ b \\ c \\ 1 \end{pmatrix} = M_1 \begin{pmatrix} d \\ e \\ f \\ 1 \end{pmatrix} = M_1 M_2 \begin{pmatrix} g \\ h \\ m \\ 1 \end{pmatrix}$$



Transformations as a change of basis

Another way of approaching the issue of relating two coordinate systems

Assignment Project Exam Help


<https://powcoder.com>

Similar to the previous one but from a different point of view

Add WeChat powcoder

Transformations as a change of basis

We know the basis of CS2 with respect to CS1 i.e.:



$$\mathbf{i}'_{CS1} = (i'_x, i'_y, i'_z)$$

$$\mathbf{j}'_{CS1} = (j'_x, j'_y, j'_z)$$

$$\mathbf{k}'_{CS1} = (k'_x, k'_y, k'_z)$$

$$\mathbf{O}'_{CS1} = (O'_x, O'_y, O'_z)$$

Can we find the matrix M that transforms points from CS2 to CS1?


$$P_{CS1} = MP_{CS2}$$

Transformations as a change of basis

We know the basis vectors and we know that

$$P_{CS1} = M P_{CS2}$$

Assignment Project Exam Help



What is M with respect to the basis vectors?

<https://powcoder.com>

$$P_{CS2} = a\mathbf{i}'_{CS2} + b\mathbf{j}'_{CS2} + c\mathbf{k}'_{CS2} + O'_{CS2} = a \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} + b \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix} + c \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

Add WeChat powcoder

$$P_{CS1} = a\mathbf{i}'_{CS1} + b\mathbf{j}'_{CS1} + c\mathbf{k}'_{CS1} + O'_{CS1} = a \begin{bmatrix} i'_x \\ i'_y \\ i'_z \\ 1 \end{bmatrix} + b \begin{bmatrix} j'_x \\ j'_y \\ j'_z \\ 1 \end{bmatrix} + c \begin{bmatrix} k'_x \\ k'_y \\ k'_z \\ 1 \end{bmatrix} + \begin{bmatrix} O'_x \\ O'_y \\ O'_z \\ 1 \end{bmatrix}$$

$$P_{CS1} = \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ 1 \end{bmatrix} = M P_{CS2}$$

Transformations as a change of basis

- Note that this is actually the matrix that transforms CS1 into CS2 with respect to CS1

Assignment Project Exam Help


- Sanity check: <https://powcoder.com>

$$M_{\mathbf{x}_{CS1}} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} = \begin{bmatrix} i'_x \\ i'_y \\ i'_z \\ 0 \end{bmatrix} = \mathbf{i}'_{CS1}$$

Similarly

$$M_{\mathbf{y}_{CS1}} = \mathbf{j}'_{CS1}, \quad M_{\mathbf{z}_{CS1}} = \mathbf{k}'_{CS1}, \quad M_{O_{CS1}} = O'_{CS1}$$

Transformations as a change of basis



$$P_{CS1} = M P_{CS2}$$

Assignment Project Exam Help

$$P_{CS1} = \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ 1 \end{bmatrix} = M P_{CS2}$$


That is:

We can view transformations as a change of coordinate system

So really this matrix operation has two interpretations

*Mathematically equivalent
but conceptually different*

Assignment Project Exam Help



<https://powcoder.com>


Add WeChat powcoder

$$P_{CS1} = \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ 1 \end{bmatrix} = M P_{CS2}$$

A. Transformation in a single coordinate system

Ignore CS2:

- Point $(x, y, z, 1)$ in CS1 is transformed to point $P' = (x', y', z', 1)$ in CS1 by a transformation represented by M




Add WeChat powcoder

$$P'_{CS1} = \begin{bmatrix} x' \\ y' \\ z' \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = M P_{CS1}$$

A. Transformation in a single coordinate system

Ignore CS2:

- Point $(x, y, z, 1)$ in CS1 is transformed to point $P = (x', y', z', 1)$ in CS1 by a transformation represented by M
- The transformation happens wrt to CS1




$$P'_{CS1} = \begin{bmatrix} x' \\ y' \\ z' \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = M P_{CS1}$$

B. Transformation of Coordinate System (change of basis)

Interpretation two:

- CS1 is transformed to CS2 through a transformation and the point remains fixed with respect to CS2




Add WeChat powcoder

$$P_{CS1} = \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ 1 \end{bmatrix} = M P_{CS2}$$

B. Transformation of Coordinate System (change of basis)

Interpretation two:

- CS1 is transformed to CS2 through a transformation and the point remains fixed with respect to CS2




Add WeChat powcoder

$$P_{CS1} = \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ 1 \end{bmatrix} = M P_{CS2}$$

B. Transformation of Coordinate System (change of basis)

Interpretation two:

- CS1 is transformed to CS2 through a transformation and the point remains fixed with respect to CS2



Add WeChat powcoder


$$P_{CS1} = \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} i'_x & j'_x & k'_x & O'_x \\ i'_y & j'_y & k'_y & O'_y \\ i'_z & j'_z & k'_z & O'_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ 1 \end{bmatrix} = M P_{CS2}$$

Transforming a point through transforming coordinate systems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Transforming a point through transforming coordinate systems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Transforming a point through transforming coordinate systems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Example


In 2D homogeneous coordinates

Assignment Project Exam Help

$$P = [1, 1, 1]^T$$

<https://powcoder.com>

Add WeChat powcoder



Example


Transformation $T(1,0)$: M

$$P' = M[1,1,1]^T = MP = [2,1,1]^T$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Example

Equivalently

Transformation $T(1,0)$: M on CSA

$$P_A = {}_A M_B P$$

$$P = [1, 1, 1]^T$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Conceptual difference: the local coordinates of P stay the same, the local system changes and becomes CSB.

In other words we transformed system A and P along with it.


However the fixed coordinates of P are now in CSB

Example

Transformation $T(1,0)$: M on CSA

$$P_A = {}_A M_B P$$

Next transformation? <https://powcoder.com>




Example


Two choices!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$P_A = {}_A M_B P$$





Example

After the last matrix $T(1,0)$: ${}^B M_C$

This transformation now happens in
CSB

$$P_A = {}^A M_B {}^B M_C P$$



Hierarchy of systems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example


We now have 3 systems we can work in

$$P_A = {}_A M_{BB} M_{CP}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat  powcoder



Hierarchy of systems

Example

Let's rotate in CSB by $R(z, 45)$:

After the matrix $R(z, 45)$ is inserted



$$P_A = {}_A M_{BB} M_C P$$

$$P_A = {}_A M_{BB} (R(z, 45)_{B'B'} M_C) P$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Hierarchy of systems

Example

Same matrix here $R(z,45)$:

$$P_A = {}_A M_{BB} M_{CP}$$



After the matrix $R(z,45)$ is inserted

$$P_A = {}_A R(z,45) {}_{A'} M_{BB} M_{CP}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Hierarchy of systems

Main point

Interpreting a transformation matrix

Assignment Project Exam Help

- $P_A = {}^A M_B P_B$
transforms a point within system A, from its current location to a new one

<https://powcoder.com>

Add WeChat powcoder

- $P_A = {}^A M_B P_B$
transforms system A into B. Right of matrix M we talk in B coordinates. Left of matrix M we talk in A coordinates

Rule of thumb

Transforming a point P:

Transformations: T_1, T_2, T_3

Matrix: $M = M_3 \times M_2 \times M_1$

Point transformed by: MP

Successive transformations happen with respect to the same CS

Transforming a CS

Transformations: T_1, T_2, T_3

Matrix: $M = M_1 \times M_2 \times M_3$

A point has original coordinates MP

Each transformations happens with respect to the new CS

The **last** coordinate system (right most) represents the **first** transformation applied to the point

Rule of thumb

To find the transformation matrix that transforms P from CSB coordinates to CSA coordinates, we find the sequence of transformations that align CSA to CSB accumulating matrices from left to right.

Assignment Project Exam Help

<https://powcoder.com>

Add WhatsApp powcoder

Explanation of this rule

If we think transforming systems, M takes CS A from the left and produces B on the right.

Assignment Project Exam Help


$\overrightarrow{A^M B}$

Transformation M: $A^M B$

<https://powcoder.com>

After this transformation we talk in B coordinates (right side).

Add WeChat powcoder



If we think about points then we move the other way. M takes B on the right and produces the A coordinates on the left:

$\overleftarrow{A^M B}$

Explanation of this rule

Take this simple example where to produce B we translate A by 1 on x axis.


Assignment Project Exam Help

$$P_B = (1,1) \quad P_A = (2,1)$$

Transformation M: ${}_A M_B$

<https://powcoder.com>

Add WeChat powcoder



If we move A by +1 to transform it into B then the coordinates of P with respect to the new system are shortened by 1 (B is closer to P than A by 1). So if we want to transform the coordinates of P from B to A we need to add 1 in x. Exactly what we need to do to transform system A to B.