


All transformations



Line Rendering Algorithm

Compute \mathbf{M}_{mod}

Compute $\mathbf{M}^{-1}_{\text{cam}}$

Compute $\mathbf{M}_{\text{modelview}} = \mathbf{M}^{-1}_{\text{cam}} \mathbf{M}_{\text{mod}}$

Compute \mathbf{M}_O

Compute \mathbf{M}_P // disregard \mathbf{M}_P here and below for orthographic-only case

Compute $\mathbf{M}_{\text{proj}} = \mathbf{M}_O \mathbf{M}_P$

Compute \mathbf{M}_{VP}

Compute $\mathbf{M} = \mathbf{M}_{VP} \mathbf{M}_{\text{proj}} \mathbf{M}_{\text{modelview}}$

for each line segment i between vertices P_i and Q_i do

$P = \mathbf{M}P_i$; $Q = \mathbf{M}Q_i$

drawline(P_x/h_P , P_y/h_P , Q_x/h_Q , Q_y/h_Q) // h_P, h_Q are the 4th coordinates of P, Q

end for

3D Clipping

Keep what is visible

We can clip

1. in the WCS

What are the six plane equations?

2. in the CCS

Usually done here(!)


Clipping in homogeneous coordinates 4D

volume bounded by 3D planes

Still simple and efficient

3. In the NDCS


Singularity at $P_z = 0$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



In any case we must clip against planes

Orthographic view volume

Planes in viewing coordinates

Normals pointing inside

left: $x - \text{left} = 0$


right: $-x + \text{right} = 0$

bottom: $y - \text{bottom} = 0$

top: $-y + \text{top} = 0$

front: $-z - \text{near} = 0$

back: $z + \text{far} = 0$



Perspective View volume

Planes in viewing coordinates

Normals pointing inside

left: $x + \text{left} * z / \text{near} = 0$


right: $-x - \text{right} * z / \text{near} = 0$

top: $-y - \text{top} * z / \text{near} = 0$

bottom: $y + \text{bottom} * z / \text{near} = 0$

front: $-z - \text{near} = 0$

back: $z + \text{far} = 0$



Clipping in NDCS (Aside)

Normalized view volume

- Constant planes
- Lines in VCS lines NDCS

Problem



- Z coordinate loses its sign

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

VCS	$(1, 0, -2)$	$(0, 0, 2)$
CCS	$(1, 0, 2/3, 2)$	$(0, 0, -6, -2)$
NDCS	$(1/2, 0, 1/3)$	$(0, 0, 3)$



Clipping in CCS (Aside)

We'll define the clipping region in CCS by first looking at the clipping region in NDCS:

$$-1 \leq x/w \leq 1$$



This means that in CCS, we have:

$$-w \leq x \leq w$$

Similarly for y, z

<https://powcoder.com>

Add WeChat powcoder





Example (Aside)

The perspective transformation creates

$W = -z$

Assignment Project Exam Help

<https://powcoder.com>
Add WeChat powcoder



Typo: they should have different z


unclipped CCS
P1(-2,0,-1,3)
P2(-3,1,-1,2)

clipped CCS
P1(-2,0,-1,3)
P2(-2.5,0.5,-1,2.5)

unclipped NDCS
P1(-0.67,0,-0.33)
P2(-1.5,0.5,-0.5)

clipped NDCS
P1(-0.67,0,-0.33)
P2(-1,0.2,-0.4)

So far our Pipeline



Rasterization

- The rasterizer outputs the location of fragments, i.e. pixel size screen elements. We can consider a fragment as pixel in most cases but they are not exactly equivalent.
<https://powcoder.com>
- The programmable fragment shader computes the colors of the fragments and how they affect the corresponding pixel
Add WeChat powcoder

Representations for lines and Curves

Line (in 2D)

- Explicit
- Implicit

$$y = \frac{dy}{dx}(x - x_0) + y_0$$

Assignment Project Exam Help

$$F(x, y) = (x - x_0)dy - (y - y_0)dx$$

<https://powcoder.com>

if $F(x, y) = 0$ then (x, y) is on line

$F(x, y) > 0$ (x, y) is below line

$F(x, y) < 0$ (x, y) is above line

Add WeChat powcoder

- Parametric

$$x(t) = x_0 + t(x_1 - x_0)$$

$$y(t) = y_0 + t(y_1 - y_0)$$

$$t \in [0, 1]$$

$$P(t) = P_0 + t(P_1 - P_0), \text{ or}$$

$$P(t) = (1 - t)P_0 + tP_1$$

Circle

- Explicit

Assignment Project Exam Help
 $y = \pm \sqrt{r^2 - x^2}; \quad |x| \leq r$

- Implicit

<https://powcoder.com>
 $x^2 + y^2 = r^2$

Add WeChat powcoder
 $F(x, y) = x^2 + y^2 - r^2$

if $F(x, y) = 0$ then (x, y) is on circle
 $F(x, y) > 0$ (x, y) is outside
 $F(x, y) < 0$ (x, y) is inside

- Parametric

$$\begin{aligned} x(\theta) &= r \cos(\theta) \\ y(\theta) &= r \sin(\theta) \\ \theta &\in [0, 2\pi] \end{aligned}$$

Rasterization



Primitives must be rasterized

- Mathematical form --> Set of finite size pixels

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Line rasterization




FIGURE 10.23 Drawing a straight-line-segment.



Line rasterization

Desired properties

- Straight
- Pass through end points
- Smooth
- Independent of end point order
- Uniform brightness
- Brightness independent of slope
- Efficient




FIGURE 10.23 Drawing a straight-line-segment.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Straightforward Implementation

Line between two points

$(x_1, y_1), (x_2, y_2)$

$$y(x) = y_1 + \frac{y_2 - y_1}{x_2 - x_1} (x - x_1)$$

Straightforward Implementation

Line between two points (slope < 45)

Round points then:

Assignment Project Exam Help

DrawLine(int x1,int y1,int x2,int y2)

<https://powcoder.com>

{

float y;

Add WeChat powcoder

int x;

for (x=x1; x<=x2; x++) {

y = y1 + (x-x1)*(y2-y1)/(x2-x1)

SetPixel(x, Round(y));

}

}

Better Implementation

How can we improve this algorithm?

```
DrawLine(int x1,int y1,int x2,int y2)
```

```
{
```

```
    float y;
```

```
    int x;
```

```
    for (x=x1; x<=x2; x = x + 1){
```

```
         $y = y1 + (x-x1)*(y2-y1)/(x2-x1)$ 
```

```
        SetPixel(x, Round(y) );
```

```
    }
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Better Implementation

```
DrawLine(int x1,int y1,int x2,int y2)
```

```
{
```

```
    float y,m; Assignment Project Exam Help
```

```
    int x;
```

```
    dx = x2-x1 ; https://powcoder.com
```

```
    dy = y2-y1 ;
```

```
    m = dy/ (float) dx ; Add WeChat powcoder
```

```
    for (x=x1; x<=x2; x = x + 1) {
```

```
        y = y1 + m*(x-x1) ;
```

```
        SetPixel(x, Round(y) );
```

```
    }
```

```
}
```

Even Better Implementation: Incremental

```
DrawLine(int x1,int y1,int x2,int y2)
```

```
{
```

```
    float y,m;
```

```
    int x;
```

```
    dx = x2-x1 ;
```

```
    dy = y2-y1 ;
```

```
    m = dy/ (float) dx;
```

```
    y = y1 + 0.5 ;
```

```
    for (x=x1; x<=x2; x = x + 1) {
```

```
        SetPixel(x, Floor(y) );
```

```
        y = y + m ;
```

```
    }
```

```
}
```

```
//  $y(x) = mx + d \rightarrow y(x+1) = y(x) + m$ 
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Midpoint algorithm (Bresenham) (ASIDE)


Line in the first quadrant ($0 < \text{slope} < 45 \text{ deg}$)

Implicit function:

$$F(x,y) = xdy - ydx + e,$$

$dx, dy > 0$ and $dy/dx \leq 1.0$;

- Current choice $P = (x, y)$.
- How do we choose next of P , $P' = (x+1, y')$?



Midpoint algorithm (Bresenham) (ASIDE)

Line in the first quadrant ($0 < \text{slope} < 45 \text{ deg}$)

Implicit function:

$$F(x,y) = xdy - ydx + e,$$

$dx, dy > 0$ and $dy/dx \leq 1, 0$;


- Current choice $P = (x,y)$.
- How do we choose next of P , $P' = (x+1, y')$?

If($F(M) = F(x+1, y+0.5) < 0$)

M above line so E

else

M below line so NE



Midpoint algorithm (Bresenham)

DrawLine(int x1, float y1, int x2, float y2, int color)

{

int x,y,dx,dy;

y = Round(y1);

for (x=x1; x<=x2; x++) {

SetPixel(x, y);

if (F(x+1,y+0.5)>0) {

y = y + 1 ;

}


}

}

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Can we compute F in a smart way?


- We are at pixel (x,y) we evaluate F at $M = (x+1,y+0.5)$ and $E=(x+1,y)$ or $NE=(x+1,y+1)$ accordingly.

(Reminder: $F(x,y) = xdy - ydx + c$)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Can we compute F in a smart way?

- We are at pixel (x,y) we evaluate F at $M = (x+1,y+0.5)$ and $E=(x+1,y)$ or $NE=(x+1,y+1)$ accordingly.

(Reminder: $F(x,y) = xdy - ydx + c$)

Assignment Project Exam Help


- If we chose E for $x+1$ the next criteria will be at M' :

$$F(x+2,y+0.5) = [(x+1)dy + dy] - (y+0.5)dx + c \rightarrow$$

$$F(x+2,y+0.5) = F(x+1,y+0.5) + dy \rightarrow$$

$$F_E = F + dy = F + dF_E$$

Add WeChat powcoder



Can we compute F in a smart way?

- We are at pixel (x,y) we evaluate F at $M = (x+1,y+0.5)$ and $E=(x+1,y)$ or $NE=(x+1,y+1)$ accordingly.

(Reminder: $F(x,y) = xdy - ydx + c$)

- If we chose E for $x+1$ the next criteria will be at M' :

$$F(x+2,y+0.5) = (x+1)dy + dy - (y+0.5)dx + c \rightarrow$$

$$F(x+2,y+0.5) = F(x+1,y+0.5) + dy \rightarrow$$

$$F_E = F + dy$$

- If we chose NE then the next criteria will be at M'' :


$$F(x+2,y+1+0.5) =$$

$$F(x+1,y+0.5) + dy - dx \rightarrow$$

$$F_{NE} = F + dy - dx$$

<https://powcoder.com>

Add WeChat powcoder



Can we compute F in a smart way?

- We are at pixel (x,y) we evaluate F at $M = (x+1,y+0.5)$ and $E=(x+1,y)$ or $NE=(x+1,y+1)$ accordingly.

(Reminder: $F(x,y) = xdy - ydx + c$)

Assignment Project Exam Help

- If we chose E for $x+1$ the next criteria will be at M' :


<https://powcoder.com>

$$F_E = F + dy$$

Add WeChat powcoder

- If we chose NE then the next criteria will be at M'' :

$$F_{NE} = F + dy - dx$$



Criterion update

Update

$$F_E = F + dy = F + dF_E$$

$$F_{NE} = F + dy - dx = F + dF_{NE}$$

Starting value?

Line equation: $F(x,y) = xdy - ydx + c$


Assume line starts at pixel (x_0, y_0)

$$\begin{aligned} F_{\text{start}} &= F(x_0+1, y_0+0.5) = (x_0+1)dy - (y_0+0.5)dx + c = \\ &= (x_0dy - y_0dx + c) + dy - 0.5dx = F(x_0, y_0) + dy - 0.5dx. \end{aligned}$$

(x_0, y_0) belongs on the line so: $F(x_0, y_0) = 0$

Therefore:

$$F_{\text{start}} = dy - 0.5dx$$



Criterion update (Integer version)

Update

$$F_{\text{start}} = dy - 0.5dx$$

$$F_E = F + dy = F + dF_E$$

$$F_{NE} = F + dy - dx = F + dF_{NE}$$

Everything is integer

Multiply by 2 $\rightarrow F_{\text{start}} = 2dy - dx$

$$dF_E = 2dy$$

$$dF_{NE} = 2(dy - dx)$$

Midpoint algorithm

```
DrawLine(int x1, float y1, int x2, float y2, int color)
```

```
{  
    int x,y,dx,dy,dE, dNE;  
    dx = x2-x1 ;  
    dy = y2-y1 ;  
    d = 2*dy-dx ; // initialize d  
    dE = 2*dy ;  
    dNE = 2*(dy-dx) ;  
    y = Round(y1) ;  
    for (x=x1; x<=x2; x++)  
        SetPixel(x, y, color );  
        if (d>0) { // chose NE  
            d = d + dNE ;  
            y = y + 1 ;  
        } else { // chose E  
            d = d + dE ;  
        }  
    }  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Incremental algorithms for polynomials (ASIDE)

General form of a polynomial of degree n :

Assignment Project Exam Help

$$F(x) = a_n x^n + a_{n-1} x^{n-1} + \cdots + a_1 x + a_0, a_n \neq 0$$

$Q^{n-1}(x)$
Add WeChat powcoder

or

$$F(x) = a_n x^n + Q^{n-1}(x), \quad a_n \neq 0$$

Incremental algorithms for polynomials

$$F(x) = a_n x^n + Q^{n-1}(x), a_n \neq 0$$

$$F(x+d) = a_n (x+d)^n + Q^{n-1}(x+d) = a_n (x+d)^n + P^{n-1}(x)$$

$$= a_n \sum_{k=0}^n \binom{n}{k} x^{n-k} d^k + P^{n-1}(x)$$

$$= a_n \sum_k \left(\frac{n!}{k!(n-k)!} \right) x^{n-k} d^k + P^{n-1}(x)$$

$$= a_n x^n + \sum_{k=1}^n \left(\frac{n!}{k!(n-k)!} \right) x^{n-k} d^k + P^{n-1}(x)$$

$$= a_n x^n + R^{n-1}(x) + P^{n-1}(x)$$

$$= a_n x^n + G^{n-1}(x)$$

N-order differences (ASIDE)

Polynomial forms

$$F(x) = a_n x^n + Q^{n-1}(x), a_n \neq 0$$
$$F(x+d) = a_n (x+d)^n + Q^{n-1}(x+d)$$

First order differences

<https://powcoder.com>

$$\Delta F = F(x+d) - F(x) = a_n (x+d)^n + Q^{n-1}(x+d) - a_n x^n - Q^{n-1}(x) = D_1^{n-1}(x)$$

Add WeChat powcoder

Second order differences

$$\Delta^2 F(x) = \Delta F(x+d) - \Delta F(x) = D_2^{n-2}(x)$$

\vdots

n -order Differences

$$\Delta^n F(x) = \Delta^{n-1} F(x+d) - \Delta^{n-1} F(x) = D_n^0 = c$$

N-order difference update

Computing the polynomial incrementally from the differences

$$F(x) = a_n x^n + Q^{n-1}(x), a_n \neq 0$$

$$F(x+d) = a_n x^n + G^{n-1}(x)$$

<https://powcoder.com>

$$F(x+d) = F(x) + \Delta^1 F(x)$$

$$\Delta F(x+d) = \Delta F(x) + \Delta^2 F(x)$$

$$\Delta^2 F(x+d) = \Delta^2 F(x) + \Delta^3 F(x)$$

\vdots

$$\Delta^{n-1} F(x+d) = \Delta^{n-1} F(x) + \Delta^n F(x)$$

$$\Delta^n F(x+d) = c$$

Example: $y = x^2$

$$y(x + d) = x^2 + 2xd + d^2 = y(x) + 2xd + d^2$$

$$\rightarrow y(x + d) = y(x) + \Delta y(x)$$

$$\text{where } \Delta y(x) = 2xd + d^2$$

$$\Delta y(x + d) = 2(x + d)d + d^2 = \Delta y(x) + 2d^2$$

$$\rightarrow \Delta y(x + d) = \Delta y(x) + \Delta^2 y(x)$$

$$\text{where } \Delta^2 y(x) = 2d^2$$

The incremental algorithm to compute $y = x^2$ (END ASIDE)

```
computePar(int d)
```

```
{
```

```
    float y = 0;
```

```
    int x = 0 ;
```

```
    DY = d^2 ; // at x = 0
```

```
    DDY = 2*d;
```

```
    for( x = 0 ; x < X_MAX ; x++ ) {
```

```
        printf("d, %f", x,y) ;
```

```
        y = y + DY ;
```

```
        DY = DY + DDY ;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Polygons

Collection of points connected with lines

- Vertices: v_1, v_2, v_3, v_4

- Edges:

$$e_1 = v_1v_2$$

$$e_2 = v_2v_3$$


$$e_3 = v_3v_4$$

$$e_4 = v_4v_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





Polygons

- Open / closed
- Planar / non-planar
- Filled / wireframe
- Convex / concave
- Simple / non-simple

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Triangles


The most common primitive

- Convex
- Planar
- Simple

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Reminder

Plane equations

Implicit

$$F(x, y, z) = Ax + By + Cz + D = \vec{N} \cdot \vec{P} + D$$

Points on Plane $F(x, y, z) = 0$

Parametric

$$\text{Plane}(s, t) = P_0 + s(P_1 - P_0) + t(P_2 - P_0)$$

P_0, P_1, P_2 not colinear


or

$$\text{Plane}(s, t) = (1 - s - t)P_0 + sP_1 + tP_2$$

$$\text{Plane}(s, t) = P_0 + sV_1 + tV_2 \text{ where } V_1, V_2 \text{ basis vectors}$$

Explicit

$$z = -(A/C)x - (B/C)y - D/C, \quad C \neq 0$$



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Point normal form

Plane equation

$$F(x, y, z) = Ax + By + Cz + D = \vec{N} \cdot \vec{P} + D$$

Points on Plane $F(x, y, z) = 0$



Observation : Let's take an arbitrary vector \vec{u} that lies on the plane which can be defined by two points e.g. P_1, P_2 on the plane.

$$\vec{u} = P_2 - P_1$$

$$\left. \begin{array}{l} \vec{N} \cdot P_1 + D = 0 \\ \vec{N} \cdot P_2 + D = 0 \end{array} \right\} \Rightarrow \vec{N} \cdot (P_2 - P_1) = 0 \Rightarrow \vec{N} \cdot \vec{u} = 0 \Rightarrow \boxed{\vec{N} \perp \vec{u}}$$

Computing point normal form from 3 Points

$$F(x, y, z) = Ax + By + Cz + D = \mathbf{N} \cdot \mathbf{P} + D$$

Points on Plane $F(x, y, z) = 0$

First way :

$$\mathbf{N} \cdot \mathbf{P}_0 + D = 0$$

$$\mathbf{N} \cdot \mathbf{P}_1 + D = 0$$


$$\mathbf{N} \cdot \mathbf{P}_2 + D = 0$$

$$|\mathbf{N}| = 1 \text{ (arbitrary choice)}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Second way :

\mathbf{N} is normal to F

Let's find a normal vector :

$$\mathbf{N} = (\mathbf{P}_1 - \mathbf{P}_0) \times (\mathbf{P}_2 - \mathbf{P}_0)$$

Compute D :

$$D = -\mathbf{N} \cdot \mathbf{P}_0$$

Intersection of line and plane

Implicit equation for the plane:

$$F(P) = \mathbf{N} \cdot P + D$$

Parametric equation for the line from P_a to P_b :

$$L(t) = P_a + t(P_b - P_a)$$

Plug $L(t)$ in $F(P)$ and solve for $t = t_i$:


$$\mathbf{N} \cdot [P_a + t_i(P_b - P_a)] = -D$$

If $\mathbf{N} \cdot (P_a - P_b) = 0$ then zero or infinite solutions (how?). Otherwise,

$$t_i = \frac{-D - \mathbf{N} \cdot P_a}{\mathbf{N} \cdot P_b - \mathbf{N} \cdot P_a} = \frac{-F(P_a)}{F(P_b) - F(P_a)}$$

Finally, evaluate $L(t_i)$ for the intersection point P_i :

$$P_i = P_a + \frac{-F(P_a)}{F(P_b) - F(P_a)}(P_b - P_a) = \frac{P_a F(P_b) - P_b F(P_a)}{F(P_b) - F(P_a)}$$



Polygons in OpenGL

New versions ONLY TRIANGLES

Vertices have attributes (position, normal, color, etc)

- Arrays of floats: `GLfloat positions[] = { ... } ;`
- Indexed Arrays (Element Arrays)


<https://powcoder.com>
Add WeChat powcoder

Special functionality to store and interpret the arrays

- Vertex Buffer Objects
- Vertex Array Objects
- We will see the details later

Indexed Face Sets

OpenGL element arrays



faces	vertex list	vertex list
#		# x,y,z
0	0, 2, 3, 1	0 0, 1, 1
1	1, 3, 7, 5	1 1, 1, 1
2	5, 7, 6, 4	2 0, 0, 1
3	4, 6, 2, 0	3 1, 0, 1
4	4, 0, 1, 5	4 0, 1, 0
5	2, 6, 7, 3	5 1, 1, 0
		6 0, 0, 0
		7 1, 0, 0

- The **ordering** of the vertices in the faces should be consistent (clock wise or counter-clockwise)
- In OpenGL it defines the orientation (front or back) of the surface (not the normal! -- confusing, I know)

Vertex attributes

Generic attributes (user defined)


Commonly defined attributes

Assignment Project Exam Help

- Position
- Normal vector
- Color
- Texture coordinates

<https://powcoder.com>

Add WeChat powcoder



- Position has slightly special status, in the sense that a vertex shader must output a position

Computing the normal of a polygon

One way:

$$N = (V_{n-1} - V_0) \times (V_1 - V_0)$$

Assignment Project Exam Help


Newell's method

$$N_x = \sum_{i=0}^{n-1} (y_i - y_{next(i)})(z_i + z_{next(i)})$$

$$N_y = \sum_{i=0}^{n-1} (z_i - z_{next(i)})(x_i + x_{next(i)})$$

$$N_z = \sum_{i=0}^{n-1} (x_i - x_{next(i)})(y_i + y_{next(i)})$$

where $next(j) = (j + 1) \bmod n$



<https://powcoder.com>

Add WeChat powcoder

Normalize to get unit normal

Transformation of normal vectors


Given an affine transformation M

- Is the new normal the M -transformed version of the original normal, i.e. $n' = Mn$?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Transformation of normal vectors

Given an affine transformation M


- If $\text{dot}(n, v) = 0$ does it mean that $\text{dot}(Mn, Mv) = 0$?
- In other words is the new normal the M -transformed version of the original normal?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- NOT in general
 - *Non uniform scale*
 - *Shear*




Transformation of normal vectors

$\mathbf{n} = (n_x, n_y, n_z, 0)^T$ normal to S

$\mathbf{v} = (v_x, v_y, v_z, 0)^T$ tangent to S

$S' = MS$, *Assignment Project Exam Help*



$$\mathbf{n} \cdot \mathbf{v} = \mathbf{n}^T \mathbf{v} = 0$$

$$\mathbf{n}^T \mathbf{v} = 0 \rightarrow \mathbf{n}^T I \mathbf{v} = 0 \rightarrow \mathbf{n}^T (M^{-1} M) \mathbf{v} = 0$$

$$\rightarrow (\mathbf{n}^T M^{-1})(M \mathbf{v}) = 0 \rightarrow (M^{-T} \mathbf{n})^T (M \mathbf{v}) = 0$$

$$\rightarrow (M^{-T} \mathbf{n}) \cdot (M \mathbf{v}) = 0$$

So: $\mathbf{n}' = M^{-T} \mathbf{n}$

The inverse transpose M^{-T} of the Modelview Matrix must be given to the shaders for transforming normals

Transformation of normal vectors



Note:

Add WeChat powcoder

- If M is pure rotation then $M^{-T} = M$
- Vectors do not translate so we can and should consider only the top left 3×3 part of the matrix in this process

Normalization

Unit normals may not stay unit after transformation.

Assignment Project Exam Help

- Transformation includes scale or shear

<https://powcoder.com>

Add WeChat powcoder

Polygon Rasterization (for OpenGL, only triangles)


We can render triangles in three different ways

- As points: that is, only the vertices
- As lines: that is only the edges
- As filled in: all interior points

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Polygon Rasterization (for OpenGL, only triangles)

We can render triangles in three different ways

- As points: that is, only the vertices


Rasterize produces the screen coordinates of the vertices



<https://powcoder.com>


- As lines: that is, only the edges

Rasterize produces 3 lines using line scan conversion



- As filled in: all interior points

...coming up



Polygon Rasterization (for OpenGL, only triangles)

Scan conversion

shade pixels lying within a closed polygon efficiently.



Algorithm

- For each row of pixels define a *scanline* through their centers
- intersect each scanline with all edges
- sort intersections in x
- calculate parity of intersections to determine in/out
- fill the 'in' pixels

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Note

During rasterization

- Pixels centers are considered at integer values (n,k)
- Therefore scanlines are of the form:
 $y = k, k \in (1, 2, \dots)$
- Also, $x = n, n \in (1, 2, \dots)$







Special cases (ASIDE)

- Horizontal edges can be excluded
- Vertices lying on scanlines

— Change in sign of $y_i - y_{i+1}$:
count twice

— No change: shorten edge
by one scanline



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Efficiency?

Many intersection tests can be eliminated by taking advantage of coherence between adjacent scanlines.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Edges that intersect scanline y are likely to intersect $y+1$
- x changes predictably from scanline y to $y+1$

$$y = mx + a \rightarrow x = 1/m(y - a) \rightarrow x(y+1) = x(y) + 1/m$$



Attributes of Interior pixels?

- We only have attributes for vertices
- What about the other points of the triangle
- E.g. Colors:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- Most common approach: interpolation

Interpolating information along a 2D line


Forms and relationships

- Parametric from

$$x = (1 - t)x_1 + tx_2, \quad t \in [0, 1]$$

$$y = (1 - t)y_1 + ty_2,$$

$$I = (1 - t)I_1 + tI_2.$$



- Using ratios (for $y_1 \neq y_2$)

$$\frac{I(t_a) - I(t_b)}{y(t_a) - y(t_b)} = \frac{I_1 - I_2}{y_1 - y_2}, \quad \forall t_a, t_b : t_a \neq t_b$$

- Choosing t_a and t_b we can get efficient incremental versions:

$$\frac{I_{y+1} - I_y}{(y + 1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \rightarrow I_{y+1} = I_y + \frac{I_1 - I_2}{y_1 - y_2}$$


- Similarly for x

constant along line

Bilinear Interpolation of Information during scanconversion

Color, Normal, Texture coordinates

- Two levels of interpolation
- Along edges (green)
- Along scan-line (red)
- Remember pixel centres at integer values
- First scan-line $y = 0$, second $y = 1, \dots$
- Pixels along scanline y :
 $(x_1, y), (x_1 + 1, y), (x_1 + 2, y), \dots$
- Incremental approach on both levels



Bilinear Interpolation of Information during scanconversion

Two levels of interpolation

Assignment Project Exam Help

Right edge (1, 2)


$$\frac{I_{r,y+1} - I_{r,y}}{(y+1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \rightarrow I_{r,y+1} = I_{r,y} + \frac{I_1 - I_2}{y_1 - y_2} (y+1 - y)$$

Left edge (1, 3)

$$\frac{I_{l,y+1} - I_{l,y}}{(y+1) - y} = \frac{I_1 - I_3}{y_1 - y_3} \rightarrow I_{l,y+1} = I_{l,y} + \frac{I_1 - I_3}{y_1 - y_3} (y+1 - y)$$

Along a scan line

$$\frac{I_{x+1} - I_x}{(x+1) - x} = \frac{I_r - I_l}{x_r - x_l} \rightarrow I_{x+1} = I_x + \frac{I_r - I_l}{x_r - x_l} (x+1 - x)$$




Bilinear Interpolation of Information during scanconversion

Color, Normal, Texture coordinates

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Right edge (1, 2)

$$\frac{I_{r,y+1} - I_{r,y}}{(y+1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \rightarrow I_{r,y+1} = I_{r,y} + \frac{I_1 - I_2}{y_1 - y_2}$$

Left edge (1, 3)

$$\frac{I_{l,y+1} - I_{l,y}}{(y+1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \rightarrow I_{l,y+1} = I_{l,y} + \frac{I_1 - I_2}{y_1 - y_2}$$

Along a scan line

$$\frac{I_{x+1} - I_x}{(x+1) - x} = \frac{I_r - I_l}{x_r - x_l} \rightarrow I_{x+1} = I_x + \frac{I_r - I_l}{x_r - x_l}$$

Incremental interpolation during scanconversion

Color, Normal, Texture coordinates

Assignment Project Exam Help

<https://powecoder.com>
Add WeChat powecoder

Right edge (1,2):


$$\frac{I_{r,(y+1)} - I_{r,y}}{(y+1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \Rightarrow I_{r,(y+1)} = I_{r,y} + \frac{I_1 - I_2}{y_1 - y_2} (y+1 - y)$$

Left Edge (1,3):

$$\frac{I_{l,(y+1)} - I_{l,y}}{(y+1) - y} = \frac{I_1 - I_3}{y_1 - y_3} \Rightarrow I_{l,(y+1)} = I_{l,y} + \frac{I_1 - I_3}{y_1 - y_3} (y+1 - y)$$

Along scanline:

$$\frac{I_{(x+1)} - I_x}{(x+1) - x} = \frac{I_r - I_l}{x_r - x_l} \Rightarrow I_{(x+1)} = I_x + \frac{I_r - I_l}{x_r - x_l} (x+1 - x)$$



How does WebGL support this?

Vertex shader:

- varying vec4 vcolor

Assignment Project Exam Help

Fragment shader

<https://powcoder.com>

- varying vec4 vcolor

Add WeChat powcoder


Rasterizer knows to interpolate

- vcolor

Z-buffer algorithm

Although part of the positions the z-value can be viewed as a special attribute of a vertex

- for each polygon in model
- project vertices of polygon onto viewing plane
- for each pixel inside the projected polygon
- calculate pixel colour
- calculate pixel z-value
- compare pixel z-value to value stored for pixel in z-buffer
- if pixel is closer, draw it in frame-buffer and z-buffer
- end
- end



Depth Test

- `gl.enable(gl.DEPTH_TEST) ;`
- `gl.disable(gl.DEPTH_TEST) ;`
- `void gl.depthFunc(func) ;`
- `func` specifies the depth comparison function:
`gl.NEVER, gl.LESS,`
`gl.EQUAL, gl.LEQUAL, gl.GREATER, gl.NOT_EQUAL, gl.GEQUAL, gl.`
`ALWAYS`
- The default value is `gl.LESS`: test passes if the incoming depth value is less than the stored one.
- Size of the z-buffer: `canvas.height * canvas.width` floats

Z-fighting


Common problem with depth test based systems

- Intersections
- Overlaps
- Rendering highlights on top of geometry

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Polygon Offset

- `gl.enable(gl.POLYGON_OFFSET_FILL) ;`
`gl.enable(gl.POLYGON_OFFSET_LINE) ;`
`gl.enable(gl.POLYGON_OFFSET_POINT) ;`

Assignment Project Exam Help

- `void gl.polygonOffset(GLfloat factor, GLfloat units) ;`

<https://powcoder.com>

Add WeChat powcoder

- Offsetting the z-values before depth comparison
- Useful for rendering hidden-line images, for applying decals to surfaces, and for rendering solids with highlighted edges
- see online manual

Depth Value Functions (aside)

- `void gl.depthRangef(gl.FLOAT nearVal, gl.FLOAT farVal);`

Assignment Project Exam Help

- After clipping and division by w , depth coordinates range from -1 to 1, corresponding to the near and far clipping planes. `gl.depthRange` specifies a linear mapping of the normalized depth coordinates in this range to window depth coordinates. Regardless of the actual depth buffer implementation, window coordinate depth values are treated as though they range from 0 through 1 (like color components). Thus, the values accepted by `gl.depthRange` are both clamped to this range before they are accepted.
- The setting of (0,1) maps the near plane to 0 and the far plane to 1. With this mapping, the depth buffer range is fully utilized.

Pixel Region filling algorithms

Scan convert boundary


Fill in regions

Assignment Project Exam Help

<https://powcoder.com>

2D paint programs

Add WeChat powcoder



<http://www.cs.unc.edu/~mcmillan/comp136/Lecture8/areaFills.html>

BoundaryFill

```
boundaryFill(int x, int y, int fill, int boundary) {  
    if ((x < 0) || (x >= raster.width)) return;  
    if ((y < 0) || (y >= raster.height)) return;  
    int current = raster.getPixel(x, y);  
    if ((current != boundary) & (current != fill)) {  
        raster.setPixel(fill, x, y);  
        boundaryFill(x+1, y, fill, boundary);  
        boundaryFill(x, y+1, fill, boundary);  
        boundaryFill(x-1, y, fill, boundary);  
        boundaryFill(x, y-1, fill, boundary);  
    }  
}
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Flood Fill

```
public void floodFill(int x, int y, int fill, int old)
```

```
{
```

```
    if ((x < 0) || (x >= raster.width)) return;
```

```
    if ((y < 0) || (y >= raster.height)) return;
```

```
    if (raster.getPixel(x, y) == old) {
```

```
        raster.setPixel(fill, x, y);
```

```
        floodFill(x+1, y, fill, old);
```

```
        floodFill(x, y+1, fill, old);
```

```
        floodFill(x-1, y, fill, old);
```

```
        floodFill(x, y-1, fill, old);
```


```
    }
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Adjacency


4-connected

8 connected

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Polygon clipping (2D): Aside

Sutherland-Hodgeman

Assignment Project Exam Help




for each side of clipping window

for each edge of polygon


output points based upon the
following table

<https://powcoder.com>

Add WeChat powcoder



case #	first point	second point	output point(s)
1	inside	inside	second point
2	inside	outside	intersection point
3	outside	outside	none
4	outside	inside	intersection point and second point




case #	first point	second point	output point(s)
1	inside	inside	second point
2	inside	outside	intersection point
3	outside	outside	none
4	outside	inside	intersection point and second point

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



original: 1,2,3,4,5,1

clip L: 1,2,A,B,4,5,1

clip B: 1,2,A,B,C,D,5,1

clip R: 1,2,A,B,C,E,F,1

clip T: (same)

Outcodes for trivial reject/accept

[Hill 389] A vertex outcode consists of four bits: TBRL, where:

T is set if $y > \text{top}$,

B is set if $y < \text{bottom}$,

R is set if $x > \text{right}$, and

L is set if $x < \text{left}$.

Trivial accept: all vertices are inside
(all outcodes are 0000, bitwise OR)

Trivial reject: all vertices are outside
with respect to any given
side (bitwise AND is not 0000)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

