

Elementary Affine Transformations

Any affine transformation is equivalent to a combination of four elementary affine transformations

- Translation
- Scaling
- Rotation
- Shear

<https://powcoder.com>

Add WeChat powcoder

Translation

$$Q = P + d \begin{pmatrix} T_x & T_y \end{pmatrix}^T$$


<https://powcoder.com>

$$Q_x = P_x + T_x$$

Add WeChat powcoder

$$Q_y = P_y + T_y$$

$$\begin{pmatrix} Q_x \\ Q_y \\ 1 \end{pmatrix} = \begin{pmatrix} 1 & 0 & T_x \\ 0 & 1 & T_y \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ 1 \end{pmatrix}$$




Scaling around the origin


Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

$$\begin{pmatrix} Q_x \\ Q_y \\ 1 \end{pmatrix} = \begin{pmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ 1 \end{pmatrix}$$

Uniform : $s_x = s_y$



Rotation around the origin



Assignment Project Exam Help

$$Q_x = \cos\theta P_x - \sin\theta P_y$$
$$Q_y = \sin\theta P_x + \cos\theta P_y$$

Add WeChat powcoder

$$\begin{pmatrix} Q_x \\ Q_y \\ 1 \end{pmatrix} = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ 1 \end{pmatrix}$$

Shear around the origin

In the x-direction

$$Q_x = P_x + aP_y$$


$$Q_y = P_y$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{pmatrix} Q_x \\ Q_y \\ 1 \end{pmatrix} = \begin{pmatrix} 1 & a & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ 1 \end{pmatrix}$$



Zero point

All elementary affine transformations have one or more
'zero' or 'identity' points **except translation**

Assignment Project Exam Help

$$F(P) = P$$

<https://powcoder.com>

Add WeChat powcoder

What are these points for Shear(), Scale() and
Rotate() ?

Inverse of a Transformation

Cramer's rule or we can be smarter

- Inverse transformation: $Q = MP$, $P = M^{-1}Q$

Assignment Project Exam Help

<https://powcoder.com>



Inverse of Translation

$$Q = T(d)P \rightarrow P = T(-d)Q$$

Assignment Project Exam Help
<https://powcoder.com>

$$\begin{pmatrix} 1 & 0 & T_x \\ 0 & 1 & T_y \\ 0 & 0 & 1 \end{pmatrix}^{-1} = \begin{pmatrix} 1 & 0 & -T_x \\ 0 & 1 & -T_y \\ 0 & 0 & 1 \end{pmatrix}$$

Add WeChat
powcoder

Inverse of Scaling

$$Q = S(s)P \xrightarrow{\text{Assignment Project Exam Help}} P \equiv S(1/s_x, 1/s_y)Q$$

<https://powcoder.com>

$$\begin{pmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{pmatrix} \xrightarrow{\text{Add WeChat powcoder}} \begin{pmatrix} 1/s_x & 0 & 0 \\ 0 & 1/s_y & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

Inverse of Rotation

$$Q = R(\theta)P \rightarrow P = R(-\theta)Q$$

Assignment Project Exam Help

$$\begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}^{-1} = \begin{pmatrix} \cos\theta & \sin\theta & 0 \\ -\sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

<https://powcoder.com>

Add WeChat powcoder

Inverse of a Shear in x

$$Q = Sh_x(a) P \xrightarrow{\text{Assignment Project Exam Help}} P \equiv Sh_x(-a) Q$$

<https://powcoder.com>

$$\begin{pmatrix} 1 & a & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}^{-1} \xrightarrow{\text{Add WeChat powcoder}} \begin{pmatrix} 1 & -a & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

Composing 2D Affine Transformations

Composing two affine transformations produces an affine transformation

Assignment Project Exam Help

$$Q = T_2(T_1(P))$$

<https://powcoder.com>

In matrix form:

Add WeChat powcoder

$$Q = M_2(M_1 P) = (M_2 M_1)P = MP$$

Which transformation happens first?

Main Points

Any affine transformation can be performed as series of elementary transformations.

Assignment Project Exam Help

<https://powcoder.com>

Affine transformations are the main modeling tool in graphics.

Add WeChat powcoder

Make sure you understand the order.

Examples

Reflection

Rotation about an arbitrary pivot point

Assignment Project Exam Help


Scaling around an arbitrary point

Reflection about a tilted line

Add WeChat powcoder


Example of 2D transformation

Rotate around an arbitrary point O by -90 degrees:



Rotate around an arbitrary point


Rotate around an arbitrary point O by -90 degrees:



Rotate around an arbitrary point


We know how to rotate around the origin

Assignment Project Exam Help




Rotate around an arbitrary point

...but that is not what we want to do!




So what do we do?



Transform it to a known case

Translate(-Ox,-Oy)

Assignment Project Exam Help




Second step: Rotation

Translate(-Ox,-Oy)

Rotate(-90)

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder


Final: Put everything back

Translate(-Ox,-Oy)

Assignment Project Exam Help
Rotate(-90)

Translate(Ox,Oy)
<https://powcoder.com>


Add WeChat powcoder



Rotation about arbitrary point

IMPORTANT!: Order

$$M = T(Ox, Oy)R(-90)T(-Ox, -Oy)$$



Affine Transformations in 3D

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Affine Transformations in 3D

General form

Assignment Project Exam Help

$$\begin{pmatrix} Q_x \\ Q_y \\ Q_z \\ 1 \end{pmatrix} = \begin{pmatrix} m_{11} & m_{12} & m_{13} & m_{14} \\ m_{21} & m_{22} & m_{23} & m_{24} \\ m_{31} & m_{32} & m_{33} & m_{34} \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ P_z \\ 1 \end{pmatrix}$$

Elementary 3D Affine Transformations

Translation

$$\begin{pmatrix} Q_x \\ Q_y \\ Q_z \\ 1 \end{pmatrix} = \begin{pmatrix} 1 & 0 & 0 & T_x \\ 0 & 1 & 0 & T_y \\ 0 & 0 & 1 & T_z \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ P_z \\ 1 \end{pmatrix}$$

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Scaling Around the Origin

$$\begin{pmatrix} Q_x \\ Q_y \\ Q_z \\ 1 \end{pmatrix} = \begin{pmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ P_z \\ 1 \end{pmatrix}$$

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- Uniform scaling: $s_x = s_y = s_z$

Shear around the origin

Along x-axis

Assignment Project Exam Help

$$\begin{pmatrix} Q_x \\ Q_y \\ Q_z \\ 1 \end{pmatrix} = \begin{pmatrix} 1 & a & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ P_z \\ 1 \end{pmatrix}$$

https://powcoder.com
Add WeChat powcoder

3 DRotation

Various representations

Assignment Project Exam Help
Decomposition into axis
rotations (x-roll, y-roll, z-roll)
<https://powcoder.com>

Add WeChat powcoder

CCW positive assumption


Reminder 2D z-rotation

$$Q_x = \cos\theta P_x - \sin\theta P_y$$

$$Q_y = \sin\theta P_x + \cos\theta P_y$$

$$\begin{pmatrix} Q_x \\ Q_y \\ 1 \end{pmatrix} = \begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} P_x \\ P_y \\ 1 \end{pmatrix}$$

Three axis to rotate around



Z-roll

$$Q_x = \cos\theta P_x - \sin\theta P_y$$

$$Q_y = \sin\theta P_x + \cos\theta P_y$$

$$Q_z = P_z$$

Add WeChat powcoder

$$R_z(\theta) = \begin{pmatrix} \cos(\theta) & -\sin(\theta) & 0 & 0 \\ \sin(\theta) & \cos(\theta) & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

X-roll

Cyclic indexing

$x \rightarrow y \rightarrow z \rightarrow x \rightarrow y$

Assignment Project Exam Help

$$\begin{bmatrix} x \\ y \\ z \end{bmatrix} \rightarrow \begin{bmatrix} x \\ y \\ z \\ x \\ y \end{bmatrix}$$

$Q_y = \cos\theta P_y - \sin\theta P_z$

$Q_z = \sin\theta P_y + \cos\theta P_z$
Add WeChat powcoder
 $Q_x = P_x$

$$R_x(\theta) = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos(\theta) & -\sin(\theta) & 0 \\ 0 & \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Y-roll

$$\begin{bmatrix} x \\ y \\ z \end{bmatrix} \rightarrow \begin{bmatrix} x \\ y \\ z \\ x \\ y \end{bmatrix}$$

Assignment Project Exam Help

<https://powcoder.com>

$$Q_z = \cos\theta P_z - \sin\theta P_x$$

$$Q_x = \sin\theta P_z + \cos\theta P_x$$

$$Q_y = P_y$$

$$R_y(\theta) = \begin{pmatrix} \cos(\theta) & 0 & \sin(\theta) & 0 \\ 0 & 1 & 0 & 0 \\ -\sin(\theta) & 0 & \cos(\theta) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Inversion of transformations

Translation: $T^{-1}(a, b, c) = T(-a, -b, -c)$

Rotation: $R_{\text{Assignment Project Exam Help}}^{-1}(b) = R_{\text{Assignment Project Exam Help}}(-b)$

Scaling: $S_{\text{https://powcoder.com}}^{-1}(sx, sy, sz) = S(1/sx, 1/sy, 1/sz)$

Shearing: $Sh_{\text{Add WeChat powcoder}}^{-1}(a) = Sh(-a)$

Inverse of Rotations

Pure rotation only, no scaling or shear.

Assignment Project Exam Help

$$M = \begin{pmatrix} m_{11} & m_{12} & m_{13} \\ m_{21} & m_{22} & m_{23} \\ m_{31} & m_{32} & m_{33} \end{pmatrix}$$

$$M^{-1} = M^T$$

Composition of 3D Affine Transformations

The composition of affine transformations is an affine transformation.

Assignment Project Exam Help

Any 3D affine transformation can be performed as a series of elementary affine transformations.

Add WeChat powcoder

Composite 3D Rotation around origin

$$R = R_z(\theta_3)R_y(\theta_2)R_x(\theta_1)$$

Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder
The order is important !!

It is often convenient to use other representations for 3D rotations....

Gimbal lock

$$R(\theta_1, \theta_2, \theta_3) = R_z(\theta_3)R_y(\theta_2)R_x(\theta_1)$$

$$\begin{pmatrix} \cos(\theta_3) & -\sin(\theta_3) & 0 & 0 \\ \sin(\theta_3) & \cos(\theta_3) & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} \cos(\theta_2) & 0 & \sin(\theta_2) & 0 \\ 0 & 1 & 0 & 0 \\ -\sin(\theta_2) & 0 & \cos(\theta_2) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos(\theta_1) & -\sin(\theta_1) & 0 \\ 0 & \sin(\theta_1) & \cos(\theta_1) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Assignment Project Exam Help

<https://powcoder.com>

$$R(\theta_1, 90^\circ, \theta_3) = R_z(\theta_3)R_y(90^\circ)R_x(\theta_1)$$

Add WeChat powcoder

$$\begin{pmatrix} \cos(\theta_3) & -\sin(\theta_3) & 0 & 0 \\ \sin(\theta_3) & \cos(\theta_3) & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos(\theta_1) & -\sin(\theta_1) & 0 \\ 0 & \sin(\theta_1) & \cos(\theta_1) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} =$$

$$\begin{pmatrix} \cos(\theta_3) & -\sin(\theta_3) & 0 & 0 \\ \sin(\theta_3) & \cos(\theta_3) & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 0 & \sin(\theta_1) & \cos(\theta_1) & 0 \\ 0 & \cos(\theta_1) & -\sin(\theta_1) & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Loss of degree of freedom

$$R(\theta_1, 90^\circ, \theta_3) = \begin{pmatrix} \cos(\theta_3) & -\sin(\theta_3) & 0 & 0 \\ \sin(\theta_3) & \cos(\theta_3) & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 0 & \sin(\theta_1) & \cos(\theta_1) & 0 \\ 0 & \cos(\theta_1) & -\sin(\theta_1) & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} =$$

$$\begin{pmatrix} 0 & \cos(\theta_3)\sin(\theta_1) - \sin(\theta_3)\cos(\theta_1) & \cos(\theta_3)\cos(\theta_1) + \sin(\theta_3)\sin(\theta_1) & 0 \\ 0 & \cos(\theta_3)\cos(\theta_1) + \sin(\theta_3)\sin(\theta_1) & -\cos(\theta_3)\sin(\theta_1) + \sin(\theta_3)\cos(\theta_1) & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} =$$

$$\begin{pmatrix} 0 & \sin(\theta_1 - \theta_3) & \cos(\theta_1 - \theta_3) & 0 \\ 0 & \cos(\theta_1 - \theta_3) & -\sin(\theta_1 - \theta_3) & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} =$$

$$\begin{pmatrix} 0 & \sin(\theta) & \cos(\theta) & 0 \\ 0 & \cos(\theta) & -\sin(\theta) & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} = R(\theta) \quad (\theta_1, \theta_3) \rightarrow \theta = (\theta_1 - \theta_3)$$

Rotation around an arbitrary axis

Euler's theorem: Any rotation or sequence of rotations around a point is equivalent to a single rotation around an axis that passes through the point.

<https://powcoder.com>

Add WeChat powcoder

What does the matrix look like?