

Illumination



Determining and Object's Appearance

Ultimately, we're interested in modeling **light transport** in scene


- Light is emitted from light sources and interacts with surfaces
- on impact with an object, some is reflected and some is absorbed
- distribution of reflected light determines "finish" (matte, glossy, ...)
- composition of light arriving at eye determines what we see

Assignment Project Exam Help

<https://powcoder.com>

Let's focus on the local interaction of light with single surface point

Add WeChat powcoder



Modeling Light Sources

In general, light sources have a very complex structure

- incandescent light bulbs, the sun, CRT monitors, ...

To simplify things, we'll focus on **point light sources** for now

- light source is a single infinitesimal point
- emits light equally in all directions (**isotropic** illumination)
- outgoing light is set of rays originating at light point

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Basic Local Illumination Model

We're only interested in light that finally arrives at view point

- a function of the light & viewing positions
- and local surface reflectance


Assignment Project Exam Help

<https://powcoder.com>

Characterize light using RGB triples

- can operate on each channel separately

Add WeChat powcoder



Given a point, compute intensity of reflected light


Local Illumination physics

Law of reflection and Snell's law of refraction


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



What are we trying to model ?



- Keep things simple and computationally efficient
- Sufficient expressive power for a wide range of materials

Diffuse Reflection


This is the simplest kind of reflection

- also called **Lambertian** reflection
- models dull, matte surfaces — materials like chalk

Ideal diffuse reflection


- scatters incoming light equally in all directions
- identical appearance from all viewing directions
- reflected intensity depends only on direction of light source

Light is reflected according to Lambert's Law



Lambert's Law for Diffuse Reflection

Purely diffuse object




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$I = I_L k_d \cos \theta$$

$$= I_L k_d (\mathbf{n} \cdot \mathbf{L})$$



I : resulting intensity


I_L : light source intensity

k_d : (diffuse) surface reflectance coefficient

$$k_d \in [0,1]$$

θ : angle between normal & light direction

Lambert's cosine law



Specular Reflection


Diffuse reflection is nice, but many surfaces are shiny

- their appearance changes as the viewpoint moves
- they have glossy **specular highlights** (or specularities)
- because they reflect light coherently, in a preferred direction

<https://powcoder.com>


A mirror is a perfect specular reflector

- incoming ray reflected about normal direction
- nothing reflected in any other direction




Most surfaces are imperfect specular reflectors

- reflect rays in cone about perfect reflection direction



How do we model specular reflection?



We want a

- simple,
- efficient,
- and intuitive

model

Phong Illumination Model


$$I = I_L k_d \cos \theta + I_L k_s \cos^n \phi$$
$$= I_L k_d (\mathbf{n} \cdot \mathbf{L}) + I_L k_s (\mathbf{r} \cdot \mathbf{v})^n$$

One particular specular reflection model

- quite common in practice
- it is purely empirical
- there's *no physical basis* for it

<https://powcoder.com>

Add WeChat powcoder



I : resulting intensity

I_L : light source intensity

k_s : (specular) surface reflectance coefficient

$$k_s \in [0, 1]$$

ϕ : angle between viewing & reflection direction

n : "shininess" factor

Computing R


- Convention L towards light
- n, R, L unit vectors

$$R = (n \cdot L)n + S$$

$$S = (n \cdot L)n - L$$

substituting we get

$$R = 2(n \cdot L)n - L$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Computing R

- Convention L towards light
- $\mathbf{n}, \mathbf{R}, \mathbf{L}$ unit vectors


$$\mathbf{R} = (\mathbf{n} \cdot \mathbf{L})\mathbf{n} + \mathbf{S}$$

$$\mathbf{S} = (\mathbf{n} \cdot \mathbf{L})\mathbf{n} - \mathbf{L}$$


substituting we get

$$\mathbf{R} = 2(\mathbf{n} \cdot \mathbf{L})\mathbf{n} - \mathbf{L}$$

Sanity check: we can visualize what we computed for R as the dotted vector



The effect of the exponent n



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Comparison

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



Examples of Phong Specular Model

Diffuse only



*Diffuse + Specular
(shininess 5)*



*Diffuse + Specular
(shininess 50)*



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


The Blinn-Torrance Specular Model

Agrees better with experimental results

Halfway vector H between L, V

$$I_s = I_i K_{spec} (H \cdot N)^n$$

$$I_s = I_i K_{spec} \cos^n(\alpha)$$



It measures how far from the normal N, H is, which is somewhat similar to how far from the V, R is.

Advantages of the Blinn Specular Model


- Theoretical basis
- No need to compute reflective direction R
- $N \cdot H$ cannot be negative if $N \cdot L > 0$ and $N \cdot V > 0$
- If the light is directional and we have orthographic projection then $N \cdot H$ constant

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$H = \frac{L + V}{\|L + V\|}$$




The Ambient Glow

So far, areas not directly illuminated by any light appear black

- this tends to look rather unnatural
- in the real world, there's lots of ambient light

To compensate, we invent new light source

- assume there is a constant ambient "glow"
- this ambient glow is *purely fictitious*



Just add in another term to our illumination equation

$$I = I_L k_d \cos \theta + I_L k_s \cos^n \phi + I_a k_a$$


I_a : ambient light intensity

k_a : (ambient) surface reflectance coefficient

Our Three Basic Components of Illumination



Diffuse



Specular



Ambient

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Combined for the Final Result : ADS - Lighting



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Lights and materials

$$\text{ObjectColor}_r = I_r = I_{a,r} K_{a,r} + I_{i,r} K_{\text{diff},r} (N \cdot L) + I_{i,r} K_{\text{spec},r} (R \cdot V)^n$$

$$\text{ObjectColor}_g = I_g = I_{a,g} K_{a,g} + I_{i,g} K_{\text{diff},g} (N \cdot L) + I_{i,g} K_{\text{spec},g} (R \cdot V)^n$$

$$\text{ObjectColor}_b = I_b = I_{a,b} K_{a,b} + I_{i,b} K_{\text{diff},b} (N \cdot L) + I_{i,b} K_{\text{spec},b} (R \cdot V)^n$$

Material properties: <https://powcoder.com>

$$K_a, K_{\text{diff}}, K_{\text{spec}}, n$$

Add WeChat powcoder

Light properties

$$I_a, I_{\text{diff}}, I_{\text{spec}}$$

Questions

*If you shine red light (1,0,0) to a white object
what color does the object appear to have?*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Questions

If you shine red light (1,0,0) to a white object what color does the object appear to have?

Assignment Project Exam Help

<https://powcoder.com>

- Red: $\sim(1,0,0) * (1,1,1) = \sim(1,0,0)$
- May not be exactly (1,0,0) but it would be a shade of red

Add WeChat powcoder

Questions

What if you shine red light $(1,0,0)$ to a green object $(0,1,0)$?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Questions

What if you shine red light $(1,0,0)$ to a green object $(0,1,0)$?

Assignment Project Exam Help

<https://powcoder.com>

- Object will look black

Add WeChat powcoder

Questions

What is the color of the highlight?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Questions

What is the color of the highlight?

Assignment Project Exam Help

<https://powcoder.com>

- For non-metallic materials it is the color of the light
- For certain metallic materials it is the color of the material

Add WeChat powcoder

Special cases

$$\text{ObjectColor}_r = I_r = I_{a,r} K_{a,r} + I_{i,r} K_{\text{diff},r} (N \cdot L) + I_{i,r} K_{\text{spec},r} (R \cdot V)^n$$

$$\text{ObjectColor}_g = I_g = I_{a,g} K_{a,g} + I_{i,g} K_{\text{diff},g} (N \cdot L) + I_{i,g} K_{\text{spec},g} (R \cdot V)^n$$

$$\text{ObjectColor}_b = I_b = I_{a,b} K_{a,b} + I_{i,b} K_{\text{diff},b} (N \cdot L) + I_{i,b} K_{\text{spec},b} (R \cdot V)^n$$

<https://powcoder.com>

- What should be done if $V_b > 1$?

Add WeChat powcoder

Special cases

$$\text{ObjectColor}_r = I_r = I_{a_r} K_{a_r} + I_{i_r} K_{\text{diff}_r} (N \cdot L) + I_{i_r} K_{\text{spec}_r} (R \cdot V)^n$$

$$\text{ObjectColor}_g = I_g = I_{a_g} K_{a_g} + I_{i_g} K_{\text{diff}_g} (N \cdot L) + I_{i_g} K_{\text{spec}_g} (R \cdot V)^n$$

$$\text{ObjectColor}_b = I_b = I_{a_b} K_{a_b} + I_{i_b} K_{\text{diff}_b} (N \cdot L) + I_{i_b} K_{\text{spec}_b} (R \cdot V)^n$$

<https://powcoder.com>

- What should be done if $I_b > 1$?
- This is an important issue that falls under the general notion of tone mapping.
- - Clamp the value of I to one. Problem? $(10, 1, 1) \rightarrow (1, 1, 1)$
 - Scale so that maximum becomes 1? $(10, 1, 1) \rightarrow (1, 0.1, 0.1)$
 - Scale non-linearly?

Special cases

$$\text{ObjectColor}_r = I_r = I_{a_r}K_{a_r} + I_{i_r}K_{\text{diff}_r}(N \cdot L) + I_{i_r}K_{\text{spec}_r}(R \cdot V)^n$$

$$\text{ObjectColor}_g = I_g = I_{a_g}K_{a_g} + I_{i_g}K_{\text{diff}_g}(N \cdot L) + I_{i_g}K_{\text{spec}_g}(R \cdot V)^n$$

$$\text{ObjectColor}_b = I_b = I_{a_b}K_{a_b} + I_{i_b}K_{\text{diff}_b}(N \cdot L) + I_{i_b}K_{\text{spec}_b}(R \cdot V)^n$$

<https://powcoder.com>

- What should be done if $N \cdot L < 0$?
Clamp the value of I to zero or flip the normal.

Special cases

$$\text{ObjectColor}_r = I_r = I_{a_r} K_{a_r} + I_{i_r} K_{\text{diff}_r} (N \cdot L) + I_{i_r} K_{\text{spec}_r} (R \cdot V)^n$$

$$\text{ObjectColor}_g = I_g = I_{a_g} K_{a_g} + I_{i_g} K_{\text{diff}_g} (N \cdot L) + I_{i_g} K_{\text{spec}_g} (R \cdot V)^n$$

$$\text{ObjectColor}_b = I_b = I_{a_b} K_{a_b} + I_{i_b} K_{\text{diff}_b} (N \cdot L) + I_{i_b} K_{\text{spec}_b} (R \cdot V)^n$$

<https://powcoder.com>

- How can we handle multiple light sources?
Sum the intensity of the individual contributions.

Shading Polygons: Flat Shading

Illumination equations are evaluated at surface locations

- so where do we apply them?

Assignment Project Exam Help

We could just do it once per polygon

- fill every pixel covered by polygon with the resulting color

https://powcoder.com
Add WeChat powcoder




Apply the ADS model in the vertex shader

Tell the rasterizer not to interpolate per pixel (-- keyword “flat” find out the details on your own)

Shading Polygons: Gouraud Shading

Alternatively, we could evaluate at every vertex

- compute color for each covered pixel
- linearly interpolate colors over polygon



Misses details that don't fall on vertex

- specular highlights, for instance

Apply the ADS lighting model in the vertex shader
Default interpolation

Shading Polygons: Phong Shading

Don't just interpolate colors over polygons

Assignment Project Exam Help


Interpolate surface normal over polygon

- evaluate illumination equation at each pixel

<https://powcoder.com>

Add WeChat powcoder

Apply ADS, in the fragment
shader with the interpolated
normal per pixel



Summarizing the Shading Model

We describe local appearance with illumination equations

- consists of a sum of set of components — light is additive
- treat each wavelength independently
- currently: diffuse, specular, and ambient terms

Assignment Project Exam Help


<https://powcoder.com>

$$I = I_L k_d \cos \theta + I_L k_s \cos^n \phi + I_a k_a$$


Add WeChat powcoder

Must shade every pixel covered by polygon

- flat shading: constant color
- Gouraud shading: interpolate corner colors
- Phong shading: interpolate corner normals



Examples of Phong Illuminated materials



IMPORTANT:

Which coordinate system?

In which system do we normally do the lighting calculations

Assignment Project Exam Help

- Viewing coordinate system

<https://powcoder.com>

Add WeChat powcoder

Shader based ADS Lighting

Per vertex

Per pixel



Per vertex ADS lighting

Vertex Shader applies the Phong illumination model per vertex

Fragment shader receives the interpolated colour from the rasterizer

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Per vertex ADS lighting

Vertex Shader

```
// Parameters
attribute vec4 vPosition;
attribute vec3 vNormal;
attribute vec4 vColor;
attribute vec2 vTexCoord;

uniform vec4 ambientProduct, diffuseProduct, specularProduct;
uniform vec4 lightPosition;
uniform float shininess;

varying vec4 fColor;
```

Per vertex ADS lighting

Vertex Shader

```
uniform vec4 ambientProduct, diffuseProduct, specularProduct;  
uniform vec4 lightPosition;  
uniform float shininess;
```

```
void  
main()  
{  
    // Transform vertex position into eye coordinates  
    vec3 pos = (modelViewMatrix * vPosition).xyz;  
  
    // Transform vertex normal into eye coordinates  
    vec3 N = normalize( (normalMatrix*vec4(vNormal,0.0)).xyz);  
  
    // Outputs  
    fColor = ads(pos, lightPosition.xyz, N); // Anything interesting  
                                              // about light's position?  
    gl_Position = projectionMatrix * modelViewMatrix*vPosition ;  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Homework

Modify what is needed so that the light is stationary in the word coordinate system

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Per vertex ADS lighting

Vertex Shader

```
vec4 ads(vec3 pos, vec3 lpos, vec3 N) {  
    vec3 L = normalize(lpos - pos) ;  
    vec3 V = normalize(-pos) ;    // why?  
    vec3 R = reflect(-L, N) ;  
  
    // Compute terms in the illumination equation  
    vec4 ambient = ambientProduct;  
    float Kd = max( dot(L, N), 0.0 );  
  
    vec4 diffuse = vec4(0.0, 0.0, 0.0, 1.0);  
    vec4 specular = vec4(0.0, 0.0, 0.0, 1.0);  
    diffuse = Kd*diffuseProduct;  
    float Ks = pow( max(dot(R, V), 0.0), shininess );  
    specular = Ks * specularProduct;  
  
    if( dot(L, N) < 0.0 ) {  
        specular = vec4(0.0, 0.0, 0.0, 1.0);  
    }  
    vec4 color = ambient + diffuse + specular;  
    color.a = 1.0 ;    // WHY??  
    return color ;  
}
```

Per vertex ADS lighting

Fragment Shader

```
varying vec4 fColor;
```

```
void
```

```
main()
```

```
{
```

```
    gl_FragColor = fColor;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Per fragment ADS lighting

Vertex shader outputs the necessary information to the fragment shader

Assignment Project Exam Help

<https://powcoder.com>

Fragment Shader receives the interpolated information and applies the Phong illumination model per fragment

Add WeChat powcoder

What is this “necessary” information?

Per fragment ADS lighting

Vertex shader outputs the necessary information to the fragment shader

Assignment Project Exam Help

Fragment Shader receives the interpolated information and applies the Phong illumination model per fragment

<https://powcoder.com>

Add WeChat powcoder

What is this “necessary” information?

- Remember the fragment shader does not have access to vertex attributes

Per fragment ADS lighting

Vertex Shader

```
attribute vec4 vPosition;  
attribute vec3 vNormal;  
attribute vec4 vColor;
```

Assignment Project Exam Help

<https://powcoder.com>

```
uniform mat4 modelViewMatrix;  
uniform mat4 normalMatrix;  
uniform mat4 projectionMatrix;  
uniform vec4 lightPosition;
```

Add WeChat powcoder

```
varying vec3 fPos ; // vertex position in eye coords  
varying vec3 fLpos ; // light position in eye coords  
varying vec3 fN ;    // vertex normal in eye coords
```

```
void main() {
```

Per fragment ADS lighting

Vertex Shader

```
varying vec3 fPos ; // vertex position in eye coords
varying vec3 fLpos ; // light position in eye coords
varying vec3 fN ; // vertex normal in eye coords
```

```
void main() {
    // Transform vertex position into eye coordinates
    fPos = (modelViewMatrix * vPosition).xyz;

    //transform normal in eye coordinates
    fN = normalize( (normalMatrix*vec4(vNormal,0.0)).xyz);
    // pass through light position
    fLpos = lightPosition.xyz ;

    // Transform vertex position in clip coordinates
    gl_Position = projectionMatrix * modelViewMatrix * vPosition;
}
```

Per fragment ADS lighting

Fragment Shader

```
precision mediump float;
```

```
uniform vec4 ambientProduct, diffuserProduct, specularProduct;  
uniform float shininess;
```

```
varying vec3 fPos ;
```

```
varying vec3 fLpos ;
```

```
varying vec3 fN ;
```

```
varying vec2 fTexCoord ;
```

```
void main() {
```

```
    gl_FragColor = ads(fPos, fLpos, fN) ;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Per fragment ADS lighting

Fragment Shader

// EXACTLY the same as in the case of per vertex ADS

```
vec4 ads(vec3 pos, vec3 lpos, vec3 N) {  
    vec3 L = normalize(lpos - pos);  
    vec3 V = normalize(-pos); // why?  
    vec3 R = reflect(-L, N);  
  
    // Compute terms in the illumination equation  
    vec4 ambient = ambientProduct;  
    float Kd = max(dot(L, N), 0.0);  
  
    vec4 diffuse = vec4(0.0, 0.0, 0.0, 1.0);  
    vec4 specular = vec4(0.0, 0.0, 0.0, 1.0);  
    diffuse = Kd*diffuseProduct;  
    float Ks = pow(max(dot(R, V), 0.0), shininess);  
    specular = Ks * specularProduct;  
  
    if(dot(L, N) < 0.0) {  
        specular = vec4(0.0, 0.0, 0.0, 1.0);  
    }  
    vec4 color = ambient + diffuse + specular;  
    color.a = 1.0;  
    return color;  
}
```

Homework

What do you need to do to support multiple lights?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

What Have We Ignored?

Some local phenomena

- shadows — every point is illuminated by every light source
- attenuation — intensity falls off with square of distance to light
- transparent objects — light can be transmitted through surface

Global illumination

- reflections of objects in other objects
- indirect diffuse light — ambient term is just a hack

Realistic surface detail

- can make an orange sphere
- but it doesn't have the texture of the real fruit

Realistic light sources

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder