

Polymorphic Higher-Order Programming

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

CSI 3120

Amy Felty

University of Ottawa

slides copyright 2017, 2018, 2019, 2020

Author David Walker, updated by Amy Felty

permission granted to reuse these slides for non-commercial educational purposes

Some Design & Coding Rules

- *Laziness* can be a really good force in design.
- Never write the same code twice.
 - factor out the common bits into a reusable procedure.
 - better, use someone else's (well-tested, well-documented, and well-maintained) procedure.
- Why is this a good idea?
 - why don't we just cut-and-paste snippets of code using the editor instead of creating new functions?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Some Design & Coding Rules

- *Laziness* can be a really good force in design.
- Never write the same code twice.
 - factor out the common bits into a reusable procedure.
 - better, use someone else's (well-tested, well-documented, and well-maintained) procedure.
- Why is this a good idea?
 - why don't we just cut-and-paste snippets of code using the editor instead of creating new functions?
 - find and fix a bug in one copy, have to fix in all of them.
 - decide to change the functionality, have to track down all of the places where it gets used.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Factoring Code in OCaml

Consider these definitions:

```
let rec inc_all (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> (hd+1)::(inc_all tl)
```

Assignment Project Exam Help

<https://powcoder.com>

```
let rec square_all (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> (hd*hd)::(square_all tl)
```

Add WeChat powcoder

Factoring Code in OCaml

Consider these definitions:

```
let rec inc_all (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> (hd+1)::(inc_all tl)
```

Assignment Project Exam Help

<https://powcoder.com>

```
let rec square_all (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> (hd*hd)::(square_all tl)
```

Add WeChat powcoder

The code is almost identical – factor it out!

Factoring Code in OCaml

A *higher-order* function captures the recursion pattern:

```
let rec map (f:int->int) (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> f hd :: map f tl
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Factoring Code in OCaml

A *higher-order* function captures the recursion pattern:

```
let rec map (f:int->int) (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> f hd :: map f tl
```

Assignment Project Exam Help

<https://powcoder.com>

Uses of the function:

Add WeChat powcoder

```
let inc x = x+1  
let inc_all xs = map inc xs
```

Factoring Code in OCaml

A *higher-order* function captures the recursion pattern:

```
let rec map (f:int->int) (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> f hd :: map f tl
```

Assignment Project Exam Help

<https://powcoder.com>

Uses of the function:

Add WeChat powcoder

Writing little
functions like inc
just so we can call
map is a pain.

```
let inc x = x+1  
let inc_all xs = map inc xs  
  
let square y = y*y  
let square_all xs = map square xs
```


Factoring Code in OCaml

A *higher-order* function captures the recursion pattern:

```
let rec map (f:int->int) (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> f hd :: map f tl
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Uses of the function:

```
let inc_all xs = map (fun x -> x + 1) xs  
  
let square_all xs = map (fun y -> y * y) xs
```

We can use an
anonymous
function
instead.

Originally,
Church wrote
this function
using λ instead
of **fun**:
($\lambda x. x+1$) or
($\lambda y. y*y$)

Here's an annoying thing

```
let rec map (f:int->int) (xs:int list) : int list =  
  match xs with  
  | [] -> []  
  | hd::tl -> (f hd)::(map f tl);;
```

Assignment Project Exam Help

What if I want to increment a list of floats?

<https://powcoder.com>

Alas, I can't just call this map. It works on ints!

Add WeChat powcoder

Here's an annoying thing

```
let rec map (f:int->int) (xs:int list) : int list =  
  match xs with  
    | [] -> []  
    | hd::tl -> (f hd)::(map f tl);;
```

Assignment Project Exam Help

What if I want to increment a list of floats?

<https://powcoder.com>

Alas, I can't just call this map. It works on ints!

Add WeChat powcoder

```
let rec mapfloat (f:float->float) (xs:float list) :  
  float list =  
  match xs with  
    | [] -> []  
    | hd::tl -> (f hd)::(mapfloat f tl);;
```

Turns out

```
let rec map f xs =
```

```
  match xs with
```

```
  | [] -> []
```

```
  | hd::tl -> (f hd)::(map f tl)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
let ints = map (fun x -> x + 1) [1; 2; 3; 4]
```

```
let floats = map (fun x -> x +. 2.0) [3.1415; 2.718]
```

```
let strings = map String.uppercase_ascii ["sarah"; "joe"]
```

Type of the undecorated map?

```
let rec map f xs =  
  match xs with  
  | [] -> []  
  | hd::tl -> (f hd)::(map f tl)  
  
map : ('a -> 'b) -> 'a list -> 'b list
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Type of the undecorated map?

```
let rec map f xs =  
  match xs with  
  | [] -> []  
  | hd::tl -> (f hd)::(map f tl)  
  
map : ('a -> 'b) -> 'a list -> 'b list
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

We often use greek letters like α or β to represent type variables.

Read as:

- for any types 'a and 'b,
- if you give map a function from 'a to 'b,
- it will return a function
 - which when given a list of 'a values
 - returns a list of 'b values.

We can say this explicitly

```
let rec map (f:'a -> 'b) (xs:'a list) : 'b list =  
  match xs with  
  | [] -> []  
  | hd::tl -> (f hd)::(map f tl)
```

map : ('a -> 'b) -> 'a list -> 'b list

<https://powcoder.com>

The OCaml compiler is smart enough to figure out that this is the *most general* type that you can assign to the code.

We say map is *polymorphic* in the types 'a and 'b – just a fancy way to say map can be used on any types 'a and 'b.

Java generics derived from ML-style polymorphism (but added after the fact and more complicated due to subtyping)

Summary

- Map is a *higher-order function* that captures a very common *recursion pattern*
- We can write clear, terse, reusable code by exploiting:
 - higher-order functions
 - anonymous functions
 - first-class functions
 - polymorphism

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder