

Static Program Analysis

Assignment Project Exam Help

Part 5 – widening and narrowing

<https://powcoder.com>

Add WeChat powcoder

<http://cs.au.dk/~amoeller/spa/>

Anders Møller & Michael I. Schwartzbach
Computer Science, Aarhus University

Interval analysis

- Compute upper and lower bounds for integers
- Possible applications:
 - array bounds checking
 - integer representation
 - ...

Assignment Project Exam Help

<https://powcoder.com>

- Lattice of intervals:

Add WeChat powcoder

$$\text{Interval} = \text{lift}(\{ [l, h] \mid l, h \in N \wedge l \leq h \})$$


where

$$N = \{-\infty, \dots, -2, -1, 0, 1, 2, \dots, \infty\}$$

and intervals are ordered by inclusion:

$$[l_1, h_1] \sqsubseteq [l_2, h_2] \text{ iff } l_2 \leq l_1 \wedge h_1 \leq h_2$$

The interval lattice



bottom element here interpreted as “not an integer”

Interval analysis lattice

- The total lattice for a program point is

$$L = \text{Vars} \rightarrow \text{Interval}$$

that provides bounds for each (integer) variable

- If using the worklist solver that initializes the worklist with only the *entry* node, use the lattice *lift*(L)
 - bottom value of *lift*(L) represents “unreachable program point”
 - bottom value of L represents “maybe reachable, but all variables are non-integers”

- This lattice has *infinite height*, since the chain

$$[0, 0] \sqsubseteq [0, 1] \sqsubseteq [0, 2] \sqsubseteq [0, 3] \sqsubseteq [0, 4] \dots$$

occurs in *Interval*

Interval constraints

- For assignments:

$$\llbracket x = E \rrbracket = JOIN(v)[x \rightarrow eval(JOIN(v), E)]$$

<https://powcoder.com>

- For all other nodes:

$$\llbracket v \rrbracket = JOIN(v)$$

where $JOIN(v) = \sqcup_{w \in pred(v)} \llbracket w \rrbracket$

Evaluating intervals

- The *eval* function is an *abstract evaluation*:
 - $eval(\sigma, x) = \sigma(x)$
 - $eval(\sigma, intconst) = [intconst, intconst]$
 - $eval(\sigma, E_1 \text{ op } E_2) = \overline{op}(eval(\sigma, E_1), eval(\sigma, E_2))$
- Abstract arithmetic operators:
 - $\overline{op}([l_1, h_1], [l_2, h_2]) =$

$$\left[\min_{x \in [l_1, h_1], y \in [l_2, h_2]} x \text{ op } y, \max_{x \in [l_1, h_1], y \in [l_2, h_2]} x \text{ op } y \right]$$
- Abstract comparison operators (could be improved):
 - $\overline{op}([l_1, h_1], [l_2, h_2]) = [0, 1]$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

not trivial to implement!

Fixed-point problems

- The lattice has infinite height, so the fixed-point algorithm does not work ☹

Assignment Project Exam Help

- In L^n , the sequence of approximants

$f^i(\perp, \perp, \dots, \perp)$

<https://powcoder.com>
Add WeChat powcoder

is not guaranteed to converge

- (Exercise: give an example of a program where this happens)
- Restricting to 32 bit integers is not a practical solution
- *Widening* gives a useful solution...

Widening

- Introduce a *widening* function $\omega: L^n \rightarrow L^n$ so that

$$(\omega \circ f)^i(\perp, \perp, \dots, \perp)$$


Assignment Project Exam Help

converges on a fixed-point that is a safe
approximation of each $f^i(\perp, \perp, \dots, \perp)$

Add WeChat powcoder

- i.e. the function ω coarsens the information

Turbo charging the iterations



Widening for intervals


- The function ω is defined pointwise on L^n
- Parameterized with a fixed finite subset $B \subset N$
 - must contain $-\infty$ and ∞ (to retain the \perp element)
 - typically seeded with all integer constants occurring in the given program
- Idea: Find the nearest enclosing allowed interval
- On single elements from *Interval* :

$$\omega([a, b]) = [\max\{i \in B \mid i \leq a\}, \min\{i \in B \mid b \leq i\}]$$

$$\omega(\perp) = \perp$$

Divergence in action

```
y = 0;  
x = 7;  
x = x+1;  
while (input) {  
    x = 7;  
    x = x+1;  
    y = y+1;  
}
```



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

```
[x → ⊥, y → ⊥]  
[x → [8, 8], y → [0, 1]]  
[x → [8, 8], y → [0, 2]]  
[x → [8, 8], y → [0, 3]]  
...
```

Widening in action

```
y = 0;  
x = 7;  
x = x+1;  
while (input) {  
    x = 7;  
    x = x+1;  
    y = y+1;  
}
```



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$[x \rightarrow \perp, y \rightarrow \perp]$
$[x \rightarrow [7, \infty], y \rightarrow [0, 1]]$
$[x \rightarrow [7, \infty], y \rightarrow [0, 7]]$
$[x \rightarrow [7, \infty], y \rightarrow [0, \infty]]$

$B = \{-\infty, 0, 1, 7, \infty\}$

Correctness of widening

- Widening works when:
 - ω is an *extensive* and *monotone* function, and
 - $\omega(L)$ is a *finite-height* lattice
- Safety: $\forall i: f^i(\perp, \perp, \dots, \perp) \sqsubseteq (\omega \circ f)^i(\perp, \perp, \dots, \perp)$
since f is monotone and ω is extensive
- $\omega \circ f$ is a monotone function $\omega(L) \rightarrow \omega(L)$
so the fixed-point exists
- Almost “correct by definition”!
- When used in the worklist algorithm, it suffices to apply widening on back-edges in the CFG

Assignment Project Exam Help

<https://powcoder.com>

And WeChat powcoder

Narrowing

- Widening generally shoots over the target
- *Narrowing* may improve the result by applying f
- Define:

$$fix = \bigsqcup f^i(\perp, \perp, \dots, \perp) \quad fix\omega = \bigsqcup (\omega \circ f)^i(\perp, \perp, \dots, \perp)$$

then $fix \sqsubseteq fix\omega$


- But we also have that

$$fix \sqsubseteq f(fix\omega) \sqsubseteq fix\omega$$

so applying f again may improve the result and remain sound!


- This can be iterated arbitrarily many times
 - may diverge, but safe to stop anytime

Backing up



Narrowing in action

```
y = 0;  
x = 7;  
x = x+1;  
while (input) {  
    x = 7;  
    x = x+1;  
    y = y+1;  
}
```



$[x \rightarrow \perp, y \rightarrow \perp]$
 $[x \rightarrow [7, \infty], y \rightarrow [0, 1]]$
 $[x \rightarrow [7, \infty], y \rightarrow [0, 7]]$
 $[x \rightarrow [7, \infty], y \rightarrow [0, \infty]]$
...
 $[x \rightarrow [8, 8], y \rightarrow [0, \infty]]$

$B = \{-\infty, 0, 1, 7, \infty\}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Correctness of (repeated) narrowing

- $f(\text{fix}\omega) \sqsubseteq \omega(f(\text{fix}\omega)) = (\omega \circ f)(\text{fix}\omega) = \text{fix}\omega$
since ω is extensive
 - by induction we also have, for all i :
 $f^{i+1}(\text{fix}\omega) \sqsubseteq f^i(\text{fix}\omega) \sqsubseteq \text{fix}\omega$
– i.e. $f^{i+1}(\text{fix}\omega)$ is at least as precise as $f^i(\text{fix}\omega)$
- $\text{fix} \sqsubseteq \text{fix}\omega$ hence $f(\text{fix}) = \text{fix} \sqsubseteq f(\text{fix}\omega)$
by monotonicity of f
 - by induction we also have, for all i :
 $\text{fix} \sqsubseteq f^i(\text{fix}\omega)$
– i.e. $f^i(\text{fix}\omega)$ is a sound approximation of fix

More powerful widening

- Defining the widening function based on constants occurring in the given program may not work

```
f(x) = if (x < 100) then x - 10 else f(f(x + 11));  
var r;  
if (x < 100) {  
    r = x - 10;  
} else {  
    r = f(f(x + 11));  
}  
return r;  
}
```

https://en.wikipedia.org/wiki/McCarthy_91_function

- Note: this example requires interprocedural analysis...

More powerful widening

- A *widening* is a function $\nabla: L \times L \rightarrow L$ that is extensive in both arguments and satisfies the following property:
for all increasing chains $z_0 \sqsubseteq z_1 \sqsubseteq \dots$,
the sequence $y_0 = z_0, \dots, y_{i+1} = y_i \nabla z_{i+1}, \dots$ converges
(i.e. stabilizes after a finite number of steps)
- Now replace the basic fixed point solver by computing
 $x_0 = \perp, \dots, x_{i+1} = x_i \nabla F(x_i), \dots$ until convergence

More powerful widening for interval analysis

Extrapolates unstable bounds to B:

$$\perp \nabla y = y$$

$$x \nabla \perp = x$$

$$[a_1, b_1] \nabla [a_2, b_2] =$$

[if $a_1 \leq a_2$ then a_1 else $\max\{i \in B \mid i \leq a_2\}$,
if $b_2 \leq b_1$ then b_1 else $\min\{i \in B \mid b_2 \leq i\}$]

The ∇ operator on L is then defined pointwise down to individual intervals

For the small example program, we now get the same result as with simple widening plus narrowing (but now without using narrowing)