

Static Program Analysis

Assignment Project Exam Help

Part 3 – lattices and fixpoints

<https://powcoder.com>

Add WeChat powcoder

<http://cs.au.dk/~amoeller/spa/>

Anders Møller & Michael I. Schwartzbach
Computer Science, Aarhus University

Flow-sensitivity

- Type checking is (usually) *flow-insensitive*:
 - statements may be permuted without affecting typability
 - constraints are naturally generated from *AST nodes*
- Other analyses must be *flow-sensitive*:
 - the order of statements affects the results
 - constraints are naturally generated from *control flow graph nodes*


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Sign analysis

- Determine the sign (+, -, 0) of all expressions
- The *Sign* lattice:



the terminology
will be defined
later – this is just
an appetizer...


- States are modeled by the map lattice $Vars \rightarrow Sign$
where $Vars$ is the set of variables in the program

Implementation: `TIP/src/tip/analysis/SignAnalysis.scala`

Generating constraints

```
1 var a,b;  
2 a = 42;  
3 b = a + input;  
4 a = a - b;
```

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder

$$x_1 = [a \mapsto \top, b \mapsto \top]$$

$$x_2 = x_1[a \mapsto 42]$$

$$x_3 = x_2[b \mapsto x_2(a) + \text{input}]$$

$$x_4 = x_3[a \mapsto x_3(a) - x_3(b)]$$

Sign analysis constraints

- The variable $\llbracket v \rrbracket$ denotes a map that gives the sign value for all variables at the program point *after* node v

- For variable declarations:

$$\llbracket \text{var } x_1, \dots, x_n \rrbracket = \text{JOIN}(v)[x_1 \mapsto T, \dots, x_n \mapsto T]$$

- For assignments:

$$\llbracket x = E \rrbracket = \text{JOIN}(v)[x \mapsto \text{eval}(\text{JOIN}(v), E)]$$

- For all other nodes:

$$\llbracket v \rrbracket = \text{JOIN}(v)$$

$$\text{where } \text{JOIN}(v) = \bigsqcup_{w \in \text{pred}(v)} \llbracket w \rrbracket$$

← combines information from predecessors
(explained later...)

Evaluating signs

- The *eval* function is an *abstract evaluation*:
 - $eval(\sigma, x) = \sigma(x)$
 - $eval(\sigma, int(x)) = sign(int(x))$
 - $eval(\sigma, E_1 \text{ op } E_2) = \overline{op}(eval(\sigma, E_1), eval(\sigma, E_2))$
- $\sigma: Vars \rightarrow Sign$ is an abstract state
- The *sign* function gives the sign of an integer
- The \overline{op} function is an abstract evaluation of the given operator

Abstract operators

+	\perp	0	-	+	T
\perp	\perp	\perp	\perp	\perp	\perp
0	\perp	0	-	+	T
-	\perp	-	-	T	T
+	\perp	+	T	+	T
T	\perp	T	T	T	T

-	\perp	0	-	+	T
\perp	\perp	\perp	\perp	\perp	\perp
0	\perp	0	+	-	T
-	\perp	-	T	-	T
+	\perp	+	+	T	T
T	\perp	T	T	T	T

*	\perp	0	-	+	T
\perp	\perp	\perp	\perp	\perp	\perp
0	\perp	0	0	0	0
-	\perp	0	+	-	T
+	\perp	0	-	+	T
T	\perp	0	T	T	T

Assignment Project Exam Help

<https://powcoder.com>

/	\perp	0	-	+	T
\perp	\perp	\perp	\perp	\perp	\perp
0	\perp	\perp	0	0	T
-	\perp	\perp	T	T	T
+	\perp	\perp	T	T	T
T	\perp	\perp	T	T	T

Add > WeChat powcoder

>	\perp	0	-	+	T
\perp	\perp	\perp	\perp	\perp	\perp
0	\perp	0	+	0	T
-	\perp	0	T	0	T
+	\perp	+	+	T	T
T	\perp	T	T	T	T


==	\perp	0	-	+	T
\perp	\perp	\perp	\perp	\perp	\perp
0	\perp	+	0	0	T
-	\perp	0	T	0	T
+	\perp	0	0	T	T
T	\perp	T	T	T	T

(assuming the subset of TIP with only integer values)

Increasing precision

- Some loss of information:
 - $(2 > 0) == 1$ is analyzed as T
 - $+ / +$ is analyzed as T, since e.g. $\frac{1}{2}$ is rounded down
- Use a richer lattice for better precision:


<https://powcoder.com>
Add WeChat powcoder



- Abstract operators are now 8×8 tables

Partial orders

- Given a set S , a partial order \sqsubseteq is a binary relation on S that satisfies:
 - reflexivity: $\forall x \in S: x \sqsubseteq x$
 - transitivity: $\forall x, y, z \in S: x \sqsubseteq y \wedge y \sqsubseteq z \Rightarrow x \sqsubseteq z$
 - anti-symmetry: $\forall x, y \in S: x \sqsubseteq y \wedge y \sqsubseteq x \Rightarrow x = y$
- Can be illustrated by a Hasse diagram (if finite)



Upper and lower bounds

- Let $X \subseteq S$ be a subset
- We say that $y \in S$ is an *upper* bound ($X \sqsubseteq y$) when

$$\forall x \in X: x \sqsubseteq y$$

- We say that $y \in S$ is a *lower* bound ($y \sqsubseteq X$) when

$$\forall x \in X: y \sqsubseteq x$$

- A *least* upper bound $\sqcup X$ is defined by

$$X \sqsubseteq \sqcup X \wedge \forall y \in S: X \sqsubseteq y \Rightarrow \sqcup X \sqsubseteq y$$

- A *greatest* lower bound $\sqcap X$ is defined by

$$\sqcap X \sqsubseteq X \wedge \forall y \in S: y \sqsubseteq X \Rightarrow y \sqsubseteq \sqcap X$$

Lattices


- A (complete) *lattice* is a partial order where $\sqcup X$ and $\sqcap X$ exist for all $X \subseteq S$

Assignment Project Exam Help


- A lattice must have
 - a unique largest element, $\top = \sqcup S$ (exercise)
 - a unique smallest element, $\perp = \sqcap S$
- If S is a finite set, then it defines a lattice iff
 - \top and \perp exist in S
 - $x \sqcup y$ and $x \sqcap y$ exist for all $x, y \in S$ ($x \sqcup y$ is notation for $\sqcup \{x, y\}$)

Implementation: `TIP/src/tip/lattices/`

These partial orders are lattices




These partial orders are *not* lattices



The powerset lattice

- Every finite set A defines a lattice $(2^A, \subseteq)$ where
 - $\perp = \emptyset$
 - $\top = A$
 - $x \sqcup y = x \cup y$
 - $x \sqcap y = x \cap y$




Lattice height

- The *height* of a lattice is the length of the longest path from \perp to \top
- The lattice $(2^A, \subseteq)$ has height $|A|$

<https://powcoder.com>

Add WeChat powcoder



Map lattice

- If A is a set and L is a lattice, then we obtain the map lattice:

Assignment Project Exam Help

$$A \rightarrow L = \{ [a_1 \mapsto x_1, a_2 \mapsto x_2, \dots] \mid A = \{a_1, a_2, \dots\} \wedge x_1, x_2, \dots \in L \}$$

Add WeChat powcoder

ordered pointwise

Example $A \rightarrow L$ where

- A is the set of program variables
- L is the *Sign* lattice

- \sqcup and \sqcap can be computed pointwise
- $height(A \rightarrow L) = |A| \cdot height(L)$

Product lattice

- If L_1, L_2, \dots, L_n are lattices, then so is the *product*:

$$L_1 \times L_2 \times \dots \times L_n = \{ (x_1, x_2, \dots, x_n) \mid x_i \in L_i \}$$

<https://powcoder.com>

where \sqsubseteq is defined pointwise

Add WeChat powcoder


- Note that \sqcup and \sqcap can be computed pointwise
- $height(L_1 \times L_2 \times \dots \times L_n) = height(L_1) + \dots + height(L_n)$

Example:

each L_i is the map lattice $A \rightarrow L$ from the previous slide,
and n is the number of CFG nodes

Flat lattice

- If A is a set, then $flat(A)$ is a lattice:



- $height(flat(A)) = 2$

Lift lattice

- If L is a lattice, then so is $\text{lift}(L)$, which is:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- $\text{height}(\text{lift}(L)) = \text{height}(L) + 1$

Sign analysis constraints, revisited

- The variable $\llbracket v \rrbracket$ denotes a map that gives the sign value for all variables at the program point *after* node v

Assignment Project Exam Help

- $\llbracket v \rrbracket \in States$ where $States = Vars \rightarrow Sign$

<https://powcoder.com>

- For variable declarations:

$$\llbracket \text{var } x_1, \dots, x_n \rrbracket = JOIN(v)[x_1 \mapsto T, \dots, x_n \mapsto T]$$

- For assignments:

$$\llbracket x = E \rrbracket = JOIN(v)[x \mapsto eval(JOIN(v), E)]$$

- For all other nodes:

$$\llbracket v \rrbracket = JOIN(v)$$

$$\text{where } JOIN(v) = \bigsqcup_{w \in pred(v)} \llbracket w \rrbracket$$

← combines information from predecessors

```

var a,b,c;
a = 42;
b = 87;
if (input) {
  c = a + b;
} else {
  c = a - b;
}

```

Generating constraints



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
\llbracket entry \rrbracket &= \perp \\
\llbracket var\ a,\ b,\ c \rrbracket &= \llbracket entry \rrbracket [a \mapsto T, b \mapsto T, c \mapsto T] \\
\llbracket a = 42 \rrbracket &= \llbracket var\ a,\ b,\ c \rrbracket [a \mapsto +] \\
\llbracket b = 87 \rrbracket &= \llbracket a = 42 \rrbracket [b \mapsto +] \\
\llbracket input \rrbracket &= \llbracket b = 87 \rrbracket \\
\llbracket c = a + b \rrbracket &= \llbracket input \rrbracket [c \mapsto \llbracket input \rrbracket(a) + \llbracket input \rrbracket(b)] \\
\llbracket c = a - b \rrbracket &= \llbracket input \rrbracket [c \mapsto \llbracket input \rrbracket(a) - \llbracket input \rrbracket(b)] \\
\llbracket exit \rrbracket &= \llbracket c = a + b \rrbracket \sqcup \llbracket c = a - b \rrbracket
\end{aligned}$$

using l.u.b. \longrightarrow

Constraints

- From the program being analyzed, we have constraint variables $x_1, \dots, x_n \in L$ and a collection of constraints:

$$x_1 = f_1(x_1, \dots, x_n)$$

$$x_2 = f_2(x_1, \dots, x_n)$$

...

$$x_n = f_n(x_1, \dots, x_n)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Note that L^n is
a product lattice



- These can be collected into a single function $f: L^n \rightarrow L^n$:

$$f(x_1, \dots, x_n) = (f_1(x_1, \dots, x_n), \dots, f_n(x_1, \dots, x_n))$$

- How do we find the least (i.e. most precise) value of x_1, \dots, x_n such that $x_1, \dots, x_n = f(x_1, \dots, x_n)$ (if that exists)???

Monotone functions

- A function $f: L \rightarrow L$ is *monotone* when
$$\forall x, y \in L: x \sqsubseteq y \Rightarrow f(x) \sqsubseteq f(y)$$
- A function with several arguments is monotone if it is monotone in each argument
- Monotone functions are closed under composition
- As functions, \sqcup and \sqcap are both monotone (exercises)
- $x \sqsubseteq y$ can be interpreted as “x is at least as precise as y”
- When f is monotone:
“more precise input cannot lead to less precise output”

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Monotonicity for the sign analysis

Example, constraints for assignments:

$$\llbracket x = E \rrbracket = JOIN(v)[x \mapsto eval(JOIN(v), E)]$$

- The \sqcup operator and map updates are monotone
- Compositions preserve monotonicity (exercises)
- Are the abstract operators monotone?
- Can be verified by a tedious inspection:
 - $\forall x, y, x' \in L: x \sqsubseteq x' \Rightarrow x \overline{\text{op}} y \sqsubseteq x' \overline{\text{op}} y$
 - $\forall x, y, y' \in L: y \sqsubseteq y' \Rightarrow x \overline{\text{op}} y \sqsubseteq x \overline{\text{op}} y'$

Kleene's fixed-point theorem

$x \in L$ is a *fixed-point* of $f: L \rightarrow L$ iff $f(x)=x$

In a lattice with finite height, every monotone function f has a *unique least fixed-point*:

Add WeChat powcoder

$$\text{fix}(f) = \bigsqcup_{i \geq 0} f^i(\perp)$$

Proof of existence

- Clearly, $\perp \sqsubseteq f(\perp)$
- Since f is monotone, we also have $f(\perp) \sqsubseteq f^2(\perp)$
- By induction, $f(\perp) \sqsubseteq f^{i-1}(\perp)$
- This means that $\perp \sqsubseteq f(\perp) \sqsubseteq f^2(\perp) \sqsubseteq \dots \sqsubseteq f^i(\perp)$
is an increasing chain
- L has finite height, so for some k : $f^k(\perp) = f^{k+1}(\perp)$
- If $x \sqsubseteq y$ then $x \sqcup y = y$ (exercise)
- So $\text{fix}(f) = f^k(\perp)$

Proof of unique least

- Assume that x is another fixed-point: $x = f(x)$
- Clearly, $\perp \sqsubseteq x$
- By induction, $f(\perp) \sqsubseteq f^i(x) = x$
- In particular, $f(x) = f^k(\perp) \sqsubseteq x$, i.e. $\text{fix}(f)$ is least
- Uniqueness then follows from anti-symmetry

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Computing fixed-points

The time complexity of $fix(f)$ depends on:


- the height of the lattice
- the cost of computing f
- the cost of testing equality

```
x =  $\perp$ ;  
do {  
  t = x;  
  x = f(x);  
} while (x  $\neq$  t);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Implementation: `TIP/src/tip/solvers/FixpointSolvers.scala`

Summary: lattice equations

- Let L be a lattice with finite height

- A *equation system* is of the form.

$$x_1 = f_1(x_1, \dots, x_n)$$

$$x_2 = f_2(x_1, \dots, x_n)$$

...

$$x_n = f_n(x_1, \dots, x_n)$$

where x_i are variables and each $f_i: L^n \rightarrow L$ is monotone

- Note that L^n is a product lattice

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Solving equations

- Every equation system has a *unique least solution*, which is the least fixed-point of the function $f: L^n \rightarrow L^n$ defined by

$$f(x_1, \dots, x_n) = (f_1(x_1, \dots, x_n), \dots, f_n(x_1, \dots, x_n))$$

- A solution is always a fixed-point (for any kind of equation)
- The least one is the most precise

Solving inequations

- A *inequation system* is of the form

$$x_1 \sqsubseteq f_1(x_1, \dots, x_n) \qquad x_1 \sqsupseteq f_1(x_1, \dots, x_n)$$

$$x_2 \sqsubseteq f_2(x_1, \dots, x_n) \qquad \text{or} \qquad x_2 \sqsupseteq f_2(x_1, \dots, x_n)$$

...

$$x_n \sqsubseteq f_n(x_1, \dots, x_n) \qquad x_n \sqsupseteq f_n(x_1, \dots, x_n)$$

- Can be solved by exploiting the facts that

$$x \sqsubseteq y \Leftrightarrow x = x \sqcap y$$

and

$$x \sqsupseteq y \Leftrightarrow x = x \sqcup y$$

Monotone frameworks

John B. Kam, Jeffrey D. Ullman: Monotone Data Flow Analysis Frameworks. Acta Inf. 7: 305-317 (1977)

- A CFG to be analyzed, nodes $\text{Nodes} = \{v_1, v_2, \dots, v_n\}$
- A finite-height lattice L of possible answers
 - fixed or parametrized by the given program
- A constraint variable $\llbracket v \rrbracket \in L$ for every CFG node v
- A dataflow constraint for each syntactic construct
 - relates the value of $\llbracket v \rrbracket$ to the variables for other nodes
 - typically a node is related to its neighbors
 - the constraints must be monotone functions:
$$\llbracket v_i \rrbracket = f_i(\llbracket v_1 \rrbracket, \llbracket v_2 \rrbracket, \dots, \llbracket v_n \rrbracket)$$

Monotone frameworks

- Extract all constraints for the CFG
- Solve constraints using the fixed-point algorithm:
 - we work in the lattice L^n where L is a lattice describing abstract states
 - computing the least fixed-point of the combined function:
$$f(x_1, \dots, x_n) = (f_1(x_1, \dots, x_n), \dots, f_n(x_1, \dots, x_n))$$
- This solution gives an answer from L for each CFG node

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Generating and solving constraints



Conceptually, we separate constraint generation from constraint solving, but in implementations, the two stages are typically interleaved

Lattice points as answers



Conservative approximation...

The naive algorithm

```
x = ( $\perp$ ,  $\perp$ , ...,  $\perp$ );
```

```
do {
```

```
    t = x;
```

```
    x = f(x);
```

```
} while (x  $\neq$  t);
```

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

- Correctness ensured by the fixed point theorem
- Does not exploit any special structure of L^n or f
(i.e. $x \in L^n$ and $f(x_1, \dots, x_n) = (f_1(x_1, \dots, x_n), \dots, f_n(x_1, \dots, x_n))$)

Implementation: SimpleFixpointSolver

Example: sign analysis

```
ite(n) {  
  var f;  
  f = 1;  
  while (n>0) {  
    f = f*n;  
    n = n-1;  
  }  
  return f;  
}
```



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Note: some of the constraints are mutually recursive in this example

(We shall later see how to improve precision for the loop condition)

The naive algorithm

	$f^0(\perp, \perp, \dots, \perp)$	$f^1(\perp, \perp, \dots, \perp)$...	$f^k(\perp, \perp, \dots, \perp)$
1	$f_1^0(\perp, \perp, \dots, \perp)$	$f_1^1(\perp, \perp, \dots, \perp)$...	$f_1^k(\perp, \perp, \dots, \perp)$
2	\perp	$f_2^1(\perp, \perp, \dots, \perp)$...	$f_2^k(\perp, \perp, \dots, \perp)$
...
n	\perp	$f_n^1(\perp, \perp, \dots, \perp)$...	$f_n^k(\perp, \perp, \dots, \perp)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Computing each new entry is done using the previous column

- Without using the entries in the current column that have already been computed!
- And many entries are likely unchanged from one column to the next!

Chaotic iteration

Recall that $f(x_1, \dots, x_n) = (f_1(x_1, \dots, x_n), \dots, f_n(x_1, \dots, x_n))$

```
x1 = ⊥; ... xn = ⊥;  
while ((x1, ..., xn) ≠ f(x1, ..., xn)) {  
    pick i nondeterministically such  
    that xi ≠ fi(x1, ..., xn)  
    xi = fi(x1, ..., xn);  
}
```

We now exploit the special structure of L^n
– may require a higher number of iterations,
but less work in each iteration

Correctness of chaotic iteration

- Let x^j be the value of $x=(x_1, \dots, x_n)$ in the j 'th iteration of the naive algorithm
- Let \underline{x}^j be the value of $\underline{x}=(\underline{x}_1, \dots, \underline{x}_n)$ in the j 'th iteration of the chaotic iteration algorithm
- By induction in j , show $\forall j: \underline{x}^j \sqsubseteq x^j$
- Chaotic iteration eventually terminates at a fixed point
- It must be identical to the result of the naive algorithm since that is the least fixed point

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Towards a practical algorithm

- Computing $\exists i : \dots$ in chaotic iteration is not practical
- Idea: predict i from the analysis and the structure of the program
<https://powcoder.com>
- Example:
In sign analysis, when we have processed a CFG node v , process $\text{succ}(v)$ next

The worklist algorithm (1/2)

- Essentially a specialization of chaotic iteration that exploits the special structure of f

Assignment Project Exam Help

- Most right-hand sides of f_i are quite sparse:
 - constraints on CFG nodes do not involve all others

<https://powcoder.com>

Add WeChat powcoder

- Use a map:

$$dep: \text{Nodes} \rightarrow 2^{\text{Nodes}}$$

that for $v \in \text{Nodes}$ gives the variables w where v occurs on the right-hand side of the constraint for w

The worklist algorithm (2/2)

```
x1 = ⊥; ... xn = ⊥;  
W = {v1, ..., vn};  
while (W ≠ ∅) {  
    vi = w.removeNext();  
    y = fi(x1, ..., xn);  
    if (y ≠ xi) {  
        for (vj ∈ dep(vi)) w.add(vj);  
        xi = y;  
    }  
}
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder


Implementation: SimpleWorklistFixpointSolver

Further improvements

- Represent the worklist as a priority queue
 - find clever heuristics for priorities

Assignment Project Exam Help

- Look at the graph of dependency edges:
 - build strongly-connected components
 - solve constraints bottom-up in the resulting DAG




Transfer functions

- The constraint functions in dataflow analysis usually have this structure:

$$\llbracket v \rrbracket = t_v(JOIN(v))$$

where $t_v: States \rightarrow States$ is called the **transfer function** for v



- Example:

$$\begin{aligned} \llbracket x = E \rrbracket &= JOIN(v)[x \mapsto eval(JOIN(v), E)] \\ &= t_v(JOIN(v)) \end{aligned}$$

where

$$t_v(s) = s[x \mapsto eval(s, E)]$$

Sign Analysis, continued...

- Another improvement of the worklist algorithm:
 - only add the entry node to the worklist initially
 - then let dataflow propagate through the program according to the constraints...

Assignment Project Exam Help

- Now, what if the constraint rule for variable declarations was:

$$\llbracket \text{var } x_1, \dots, x_n \rrbracket = \text{JOIN}(v)[x_1 \mapsto \perp, \dots, x_n \mapsto \perp]$$

(would make sense if we treat “uninitialized” as “no value” instead of “any value”)

- Problem: iteration would stop before the fixpoint!
- Solution: replace $\text{Vars} \rightarrow \text{Sign}$ by $\text{lift}(\text{Vars} \rightarrow \text{Sign})$
(allows us to distinguish between “unreachable” and “all variables are non-integers”)
- This trick is also useful for context-sensitive analysis! (later...)

Implementation: `worklistFixpointSolverWithReachability, MapLiftLatticeSolver`