

EBU7240

Computer Vision

Assignment Project Exam Help

- Detection: Pedestrian detection - <https://powcoder.com>

Add WeChat powcoder

Semester 1, 2021

Changjae Oh

Outline

- Overview
- Dalal-Triggs (pedestrian detection)
 - Histogram of Oriented Gradients
 - Learning with SVM


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Object Detection

- Focus on **object search**: "Where is it?"
- Build templates that differentiate **object patch** from **background patch**



Challenges in modeling the object class



Illumination



Object pose



'Clutter'



Occlusions



Intra-class
appearance



Viewpoint

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Challenges in modeling the non-object class


True
Detections



Bad
Localization



Confused with
Similar Object



Misc. Background



Confused with
Dissimilar Objects



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Object Detection Design challenges


- **How to efficiently search for likely objects**
 - Even simple models require searching hundreds of thousands of positions and scales.
- **Feature design and scoring**
 - How should appearance be modeled?
 - What features correspond to the object?
- **How to deal with different viewpoints?**
 - Often train different models for a few different viewpoints

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

General Process of Object Detection



Specifying an object model

1. Statistical Template in Bounding Box

- Object is some (x, y, w, h) in image
- Features defined with respect to bounding box coordinates


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Image



Template Visualization

Specifying an object model



2. Articulated parts model

- Object is configuration of parts
- Each part is detectable

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Specifying an object model

3. Hybrid template/parts model


Detections



<https://powcoder.com>

Add WeChat powcoder

Template Visualization



root filters
coarse resolution


part filters
finer resolution

deformation
models

Specifying an object model

4. 3D-ish model

- Object is collection of 3D planar patches under affine transformation



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Specifying an object model

4. Deformable 3D model

- Object is a parameterized space of shape/pose/deformation of class of 3D object

Assignment Project Exam Help

<https://powcoder.com>

Learning a Model:
Add WeChat powcoder

2) Shape Training


Why not just pick the most complex model?

- Inference is harder
 - More parameters
 - Harder to 'fit' (infer / optimize fit)
 - Longer computation


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



General Process of Object Detection



Generating hypotheses

1. 2D template model / sliding window

- Test patch at each location and scale



Generating hypotheses

1. 2D template model / sliding window

- Test patch at each location and scale



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Note – Template did not change size





Each window is separately classified




Generating hypotheses

2. Region-based proposal


- Arbitrary bounding box + image 'cut' segmentation



General Process of Object Detection




General Process of Object Detection



Resolving detection scores


1. Non-max suppression



Resolving detection scores

2. Context/reasoning


- Via geometry
- Via known information or prior distributions
- Non-max suppression



(g) Car Detections: Local



(h) Ped Detections: Local



Hoiem et al. 2006

Dalal Triggs: Person detection with HOG & linear SVM



Histograms of Oriented Gradients for Human Detection, [Navneet Dalal](#), [Bill Triggs](#), International Conference on Computer Vision & Pattern Recognition - June 2005

Statistical Template

- Object model = sum of scores of features at fixed positions!



$$+3 -2 -2 -1 -2.5 = -0.5 \stackrel{?}{>} 7.5$$

Assignment Project Exam Help

<https://powcoder.com> Non-object

Add WeChat powcoder



$$+4 +1 +0.5 +3 +0.5 = 10.5 \stackrel{?}{>} 7.5$$

Object

Example: Dalal-Triggs pedestrian detector





Assignment Project Exam Help

1. Extract fixed-sized (64x128 pixel) window at each position and scale
2. Compute HOG (histogram of gradient) features within each window
3. Score the window with a linear SVM classifier
4. Perform non-maxima suppression to remove overlapping detections with lower scores

<https://powcoder.com>


Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- **Tested with**

- RGB
 - LAB
 - Grayscale
- } Slightly better performance vs. grayscale


Assignment Project Exam Help

<https://powcoder.com>

- **Gamma Normalization and Compression**

- Square root
 - Log
- } Very slightly better performance vs. no adjustment

Add WeChat powcoder



Outperforms

-1	0	1
----	---	---

centered

-1	1
----	---

uncentered

1	-8	0	8	-1
---	----	---	---	----

cubic-corrected

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


0	1
-1	0

diagonal

-1	0	1
-2	0	2
-1	0	1



Sobel







Histogram of Oriented Gradients


Orientation: 9 bins (for unsigned angles 0-180)



Histograms over $k \times k$ pixel cells




- Votes weighted by magnitude
- Bilinear interpolation between cells



Normalize with respect to surrounding cells

Rectangular HOG (R-HOG)



Assignment Project Exam Help

How to normalize?


<https://powcoder.com>

Add WeChat powcoder


- Concatenate all cell responses from neighboring blocks into vector.
- Normalize vector.
- Extract responses from cell of interest.
- Do this 4x for each neighbor set in 2x2.

$$f = \frac{v}{\sqrt{\|v\|_2^2 + e^2}}$$

e is a small constant
(to remove div. by zero on empty bins)



X=



Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder

$$\# \text{ features} = 15 \times 7 \times 9 \times 4 = 3780$$


orientations

cells

normalizations by
neighboring cells




pos w neg w
Training data classes



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$0.16 = w^T x - b$$

$$\text{sign}(0.16) = 1$$

\Rightarrow pedestrian

Strengths/Weaknesses of Statistical Template Approach

- **Strengths**

- Works very well for non-deformable objects with canonical orientations: faces, cars, pedestrians
- Fast detection

Assignment Project Exam Help

<https://powcoder.com>

- **Weaknesses**

- Not so well for highly deformable objects or "stuff"
- Not robust to occlusion
- Requires lots of training data

Add WeChat powcoder

EBU7240

Computer Vision

Assignment Project Exam Help

- Detection2: Face detection - <https://powcoder.com>

Add WeChat powcoder

Semester 1, 2021

Changjae Oh

Outline

- Overview
- Viola-Jones (face detection)
 - Boosting for learning
 - Decision trees

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Consumer application: Apple iPhoto

- Things iPhoto thinks are faces





This person tried to unlock your Phone

2016/07/23 15:51

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Challenges of face detection

- **Sliding window = tens of thousands of location/scale evaluations**
 - One megapixel image has $\sim 10^6$ pixels, and a comparable number of candidate face locations
- **Faces are rare: 0–10 per image**
 - For computational efficiency, spend as little time as possible on the non-face windows
- **For 1 Mpix, to avoid having a false positive in every image, our false positive rate has to be less than 10^{-6}**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Viola/Jones Face Detector

- A seminal approach to real-time object detection.
- Training is slow, but detection is very fast
- Key ideas:
 1. Integral images for fast feature evaluation
 2. Boosting for feature selection
 3. Attentional cascade for fast non-face window rejection

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

P. Viola and M. Jones. [Rapid object detection using a boosted cascade of simple features](#). CVPR 2001.

P. Viola and M. Jones. [Robust real-time face detection](#). IJCV 57(2), 2004.

1. Integral images for fast feature evaluation

- The integral image computes a value at each pixel (x,y) that is the sum of all pixel values above and to the left of (x,y) , inclusive.




Assignment Project Exam Help

- This can quickly be computed in one pass through the image.
$$I_{\Sigma}(x,y) = \sum_{\substack{x' \leq x \\ y' \leq y}} i(x',y')$$
- 'Summed area table'


<https://powcoder.com>

Add WeChat powcoder

Computing the integral image



Computing the integral image



- Cumulative row sum: $s(x, y) = s(x-1, y) + i(x, y)$
- Integral image: $ii(x, y) = ii(x, y-1) + s(x, y)$


Python: `ii = np.cumsum(i)`

Computing sum within a rectangle

- Let A, B, C, D be the values of the image at the corners of a rectangle

- The sum of original image values within the rectangle can be computed as:

- $\text{sum} = A - B - C + D$




<https://powcoder.com>

Add WeChat powcoder

Only 3 additions are required
for any size of rectangle!


Integral Images

- `ii = cumsum(cumsum(im, 1), 2)`



$ii(x, y)$ = Sum of the values in the grey region

Add WeChat powcoder



SUM within Rectangle D is
 $ii(4) - ii(2) - ii(3) + ii(1)$

Integral Images- example

- Find the integral image of the figure below and computer the sum of pixels in the grey region based on the integral image.

1	2	3	4	5
1	1	1	2	6
1	6	0	5	2
1	3	6	5	1
1	2	0	1	3

1	3	6	10	15
2	5	9	15	26
3	12	18	27	40
4	16	26	42	56
5	19	29	46	63

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

$$\begin{aligned} & ii(4) - ii(2) - ii(3) + ii(1) \\ &= 42 - 10 - 4 + 1 \end{aligned}$$

Features that are fast to compute

- “Haar-like features”


- Differences of sums of intensity
- Computed at different positions and scales within sliding window




Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Two-rectangle features





Three-rectangle features



Etc.

Image Features

“Rectangle filters”




B


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



C




D

$$\begin{aligned} \text{Value} &= \sum(\text{pixels in white area}) \\ &\quad - \sum(\text{pixels in black area}) \end{aligned}$$


Example

Source



Add WeChat

Result



Computing a rectangle feature



But these features are rubbish...!

Yes, individually they are 'weak classifiers'

• *Jargon: 'feature' and 'classifier' are used interchangeably here.
Also with 'learner'.*

Assignment Project Exam Help


But, what if we combine thousands of them...

Add WeChat powcoder


-1 +1



Two-rectangle features




Three-rectangle features



Etc.

How many features are there?

- For a 24×24 detection region, the number of possible rectangle features is ~160,000!



How many features are there?

- For a 24×24 detection region, the number of possible rectangle features is ~160,000!
- At test time, it is impractical to evaluate the entire feature set.
[Assignment Project Exam Help](https://powcoder.com)
- Can we learn a 'strong classifier' using just a small subset of all possible features?
<https://powcoder.com>
Add WeChat powcoder

2. *Boosting* for feature selection


Initially, weight each training example equally.

Weight = size of point

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



2. *Boosting* for feature selection


In each boosting round:

Find the weak classifier, trained for each feature, that achieves the lowest *weighted* training error.

Raise the weights of training examples misclassified by current weak classifier.

Weak
Classifier 1

Round 1:




Boosting illustration

In each boosting round:

Find the weak classifier,
trained for each feature,
that achieves the lowest
weighted training error.

Raise the weights of
training examples
misclassified by
current weak classifier.

Round 1:



Boosting illustration


In each boosting round:

Find the weak classifier, trained for each feature, that achieves the lowest *weighted* training error.

Raise the weights of training examples misclassified by current weak classifier.

Weak
Classifier 2

Round 2:




Boosting illustration

In each boosting round:

Find the weak classifier,
trained for each feature,
that achieves the lowest
weighted training error.

Raise the weights of
training examples
misclassified by
current weak classifier.

Round 2:




Boosting illustration

In each boosting round:

Find the weak classifier, trained for each feature, that achieves the lowest *weighted* training error.

Raise the weights of training examples misclassified by current weak classifier.




Boosting illustration

Compute final classifier as linear combination of all weak classifier.

Weight of each classifier is directly proportional to its accuracy.

Round 3:



Exact formulas for re-weighting and combining weak learners depend on the particular boosting scheme (e.g., AdaBoost).

Boosting for face detection

- **First two features selected by boosting:**

- The first feature measures the difference in intensity between the region of the eyes and a region across the upper cheeks. The feature capitalizes on the observation that the eye region is often darker than the cheeks.
- The second feature compares the intensities in the eye regions to the intensity across the bridge of the nose.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



The two features are shown in the top row and then overlaid on a typical training face in the bottom row.

Feature selection with boosting

- Create a large pool of features (180K)
- Select discriminative features that work well together

Final strong learner

$$h(\mathbf{x}) = \text{sign} \left(\sum_{j=1}^M \alpha_j h_j(\mathbf{x}) \right)$$

Weak learner

Learner weight

Assignment Project Exam Help

https://powcoder.com

window

- “Weak learner” = feature + threshold + ‘polarity’

Add WeChat powcoder

$$h_j(\mathbf{x}) = \begin{cases} -s_j & \text{if } f_j < \theta_j \\ s_j & \text{otherwise} \end{cases}$$

value of rectangle feature

threshold

‘polarity’ = black or white region flip $\longrightarrow s_j \in \pm 1$

- Choose weak learner that minimizes error on the weighted training set, then reweight

Boosting: Pros and Cons

- **Advantages of boosting**

- Integrates classifier training with feature selection
- Complexity of training is linear instead of quadratic in the number of training examples
- Flexibility in the choice of weak learners, boosting scheme
- Testing is fast

Assignment Project Exam Help


<https://powcoder.com>

- **Disadvantages**

- Needs many training examples
- Training is slow

Add WeChat powcoder

Cascade for Fast Detection




Fast classifiers early in cascade which reject many negative examples but detect almost all positive examples.

Slow classifiers later, but most examples don't get there.

Attentional cascade


- Chain classifiers that are progressively more complex and have lower false positive rates:



Attentional cascade

- The detection rate and the false positive rate of the cascade are found by multiplying the respective rates of the individual stages
- A detection rate of 0.9 and a false positive rate on the order of 10^{-6} can be achieved by a 10-stage cascade if each stage has a detection rate of 0.99 ($0.99^{10} \approx 0.9$) and a false positive rate of about 0.30 ($0.3^{10} \approx 6 \times 10^{-6}$)

Add WeChat powcoder



Training the cascade

- Set target detection and false positive rates for each stage
- Keep adding features to the current stage until its target rates have been met
 - Need to lower boosting threshold to maximize detection (as opposed to minimizing total classification error)
 - Test on a validation set <https://powcoder.com>
- If the overall false positive rate is not low enough, then add another stage
- Use false positives from current stage as the negative training examples for the next stage

The implemented system

- **Training Data**

- 5000 faces
 - All frontal, rescaled to 24x24 pixels
- 300 million non-faces
 - 9500 non-face images
- Faces are normalized
 - Scale, translation

- **Many variations**

- Across individuals
- Illumination
- Pose



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Viola-Jones details

- **38 stages with 1, 10, 25, 50 ... features**
 - 6061 total used out of 180K candidates
 - 10 features evaluated on average
- **Training Examples**
 - 4916 positive examples
 - 10000 negative examples collected after each stage
- **Scanning**
 - Scale detector rather than image
 - Scale steps = 1.25 (factor between two consecutive scales)
 - Translation $1 \times \text{scale}$ (# pixels between two consecutive windows)
- **Non-max suppression: average coordinates of overlapping boxes**
- **Train 3 classifiers and take vote**


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Viola-Jones Results

Speed = 15 FPS (in 2001)




Add WeChat powcoder

Detector \ False detections							
	10	31	50	65	78	95	167
Viola-Jones	76.1%	88.4%	91.4%	92.0%	92.1%	92.9%	93.9%
Viola-Jones (voting)	81.1%	89.7%	92.1%	93.1%	93.1%	93.2 %	93.7%
Rowley-Baluja-Kanade	83.2%	86.0%	-	-	-	89.2%	90.1%
Schneiderman-Kanade	-	-	-	94.4%	-	-	-
Roth-Yang-Ahuja	-	-	-	-	(94.8%)	-	-

MIT + CMU face dataset

Boosting for face detection

- A 200-feature classifier can yield 95% detection rate and a false positive rate of 1 in 14084




Output of Face Detector on Test Images




Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder



Summary: Viola/Jones detector

- Rectangle features
- Integral images for fast computation
- Boosting for feature selection
- Attentional cascade for fast rejection of negative windows

<https://powcoder.com>

Add WeChat powcoder