

EBU7240

Computer Vision

- Tracking: Image Alignment -

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Semester 1, 2021

Changjae Oh

Content

- Motion Estimation (Review of EBU6230 content)
- Image Alignment
- Kanade-Lucas-Tomasi (KLT) Tracking
- Mean-shift Tracking

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Objectives

- To review **Lucas-Kanade optical flow** in EBU6230
- To understand **Lucas-Kanade image alignment**
- To understand the **relationship** between Lucas-Kanade optical flow and image alignment
- To understand **Kanade-Lucas-Tomasi tracker**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Content

- Motion Estimation (Review of EBU6230 content)
- Image Alignment
- Kanade-Lucas-Tomasi (KLT) Tracking
- Mean-shift Tracking

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Motion Estimation: Gradient method

- Brightness consistency constraint

$$H(x, y, t) = I(x + \Delta x, y + \Delta y, t + \Delta t)$$

- small motion: (Δx and Δy are less than 1 pixel)
 - suppose we take the Taylor series expansion of I :

$$I(x + \Delta, y + \Delta y, t + \Delta t) = I(x, y, t) + \frac{\partial I}{\partial x} \Delta x + \frac{\partial I}{\partial y} \Delta y + \frac{\partial I}{\partial t} \Delta t + \text{higher order terms}$$

$$I(x + \Delta, y + \Delta y, t + \Delta t) \approx I(x, y, t) + \frac{\partial I}{\partial x} \Delta x + \frac{\partial I}{\partial y} \Delta y + \frac{\partial I}{\partial t} \Delta t$$

Gradient method

- Spatio-temporal constraint

Assignment Project Exam Help
$$\frac{\partial I}{\partial x} V_x + \frac{\partial I}{\partial y} V_y + \frac{\partial I}{\partial t} = 0$$
<https://powcoder.com>

Add WeChat powcoder

- This equation introduces one constraint only
 - Where the motion vector of a pixel has 2 components (parameters)
 - A second constraints is necessary to solve the system

Aperture problem

- The aperture problem
 - stems from the need to solve one equation with two unknowns, which are the two components of optical flow
 - it is not possible to estimate both components of the optical flow from the local spatial and temporal derivatives
- By applying a constraint
 - the optical flow field changes smoothly in a small neighborhood it is possible to estimate both components of the optical flow if the spatial and temporal derivatives of the image intensity are available

<https://powcoder.com>

Add WeChat powcoder

Solving the aperture problem

- How to get more equations for a pixel?
- By applying a constraint
 - the optical flow field changes smoothly in a small neighborhood
it is possible to estimate both components of the optical flow
if the spatial and temporal derivatives of the image
intensity are available
- Lucas–Kanade method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Gradient method

- The Lucas–Kanade method assumes that the displacement of the image contents between two nearby instants (frames) is small

$$\begin{aligned} I_x(q_1)V_x + I_y(q_1)V_y &= -I_t(q_1) \\ I_x(q_2)V_x + I_y(q_2)V_y &= -I_t(q_2) \\ &\dots \\ I_x(q_n)V_x + I_y(q_n)V_y &= -I_t(q_n) \end{aligned}$$

Assignment Project Exam Help
...<https://powcoder.com>
Add WeChat powcoder

- Matrix form

$$A = \begin{bmatrix} I_x(q_1) & I_y(q_1) \\ I_x(q_2) & I_y(q_2) \\ \dots & \dots \\ I_x(q_n) & I_y(q_n) \end{bmatrix} \quad v = \begin{bmatrix} V_x \\ V_y \end{bmatrix} \quad b = \begin{bmatrix} -I_t(q_1) \\ -I_t(q_2) \\ \dots \\ -I_t(q_n) \end{bmatrix}$$

Gradient method

- Prob: we have more equations than unknowns

$$A v = b \longrightarrow \text{minimize } \|A v - b\|^2$$

- Solution: solve least squares problem

$$(A^T A) v = A^T b$$

- minimum least squares solution given by solution of:

$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} V_x \\ V_y \end{bmatrix} = \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

- The summations are over all n pixels in the $K \times K$ window
- This technique was first proposed by Lukas & Kanade (1981)

Lucas-Kanade flow


$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} V_x \\ V_y \end{bmatrix} = - \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

Assignment Project Exam Help

- When is this solvable?
 - $\mathbf{A}^T \mathbf{A}$ should be invertible
 - $\mathbf{A}^T \mathbf{A}$ should not be too small due to noise
 - eigenvalues λ_1 and λ_2 of $\mathbf{A}^T \mathbf{A}$ should not be too small
 - $\mathbf{A}^T \mathbf{A}$ should be well-conditioned
 - λ_1 / λ_2 should not be too large (λ_1 = larger eigenvalue)
- Recall the Harris corner detector: $M = \mathbf{A}^T \mathbf{A}$ is the second moment matrix

Interpreting the eigenvalues

Classification of image points using eigenvalues of the second moment matrix:



Uniform region



- gradients have small magnitude
- small λ_1 , small λ_2
- system is ill-conditioned

Edge



- gradients have one dominant direction
- large λ_1 , small λ_2
- system is ill-conditioned

High-texture or corner region




- gradients have different directions, large magnitudes
- large λ_1 , large λ_2
- system is well-conditioned

Content

- Motion Estimation (Review of EBU6230 content)
- **Image Alignment**
- Kanade-Lucas-Tomasi (KLT) Tracking
- Mean-shift Tracking **Assignment Project Exam Help**


<https://powcoder.com>

Add WeChat powcoder





How can I find



in the image?



Idea #1: Template Matching



Slow, global solution

Idea #2: Pyramid Template Matching



Faster, locally optimal

Idea #3: Model refinement

(when you have a good initial solution)



Fastest, locally optimal

Some notation before we get into the math...

2D image transformation

$$\mathbf{W}(\mathbf{x}; \mathbf{p})$$

2D image coordinate

$$\mathbf{x} = \begin{bmatrix} x \\ y \end{bmatrix}$$

Parameters of the transformation

$$\mathbf{p} = \{p_1, \dots, p_N\}$$

Warped image

$$I(\mathbf{x}') = I(\mathbf{W}(\mathbf{x}; \mathbf{p}))$$

Pixel value at a coordinate

Translation

$$\mathbf{W}(\mathbf{x}; \mathbf{p}) = \begin{bmatrix} x + p_1 \\ y + p_2 \end{bmatrix}$$

$$= \begin{bmatrix} 1 & 0 & p_1 \\ 0 & 1 & p_2 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

transform coordinate

Affine

$$\mathbf{W}(\mathbf{x}; \mathbf{p}) = \begin{bmatrix} p_1x + p_2y + p_3 \\ p_4x + p_5y + p_6 \end{bmatrix}$$

$$= \begin{bmatrix} p_1 & p_2 & p_3 \\ p_4 & p_5 & p_6 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

affine transform coordinate

can be written in matrix form when linear
affine warp matrix can also be 3x3 when last row is [0 0 1]

Image alignment

- Problem definition

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

$$\min_{\mathbf{p}} \sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p})) - T(\mathbf{x})]^2$$

warped image template image

Find the warp parameters \mathbf{p} such that the SSD is minimized

Image alignment

Find the warp parameters \mathbf{p} such that the SSD is minimized




Image alignment

- Problem definition

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

$$\min_{\mathbf{p}} \sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p})) - T(\mathbf{x})]^2$$

warped image template image

Find the warp parameters \mathbf{p} such that the SSD is minimized

How could you find a solution to this problem?

Image alignment

This is a non-linear (quadratic) function of a non-parametric function!

(Function I is non-parametric)

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder
Hard to optimize

$$\min_p \sum_x [I(W(x; p)) - T(x)]^2$$

What can you do to make it easier to solve?

*assume good initialization,
linearized objective and update incrementally*

Lucas-Kanade alignment

(pretty strong assumption)

If you have a good initial guess \mathbf{p} ...

$$\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p})) - T(\mathbf{x})]^2$$

can be written as...

$$\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p} + \Delta \mathbf{p})) - T(\mathbf{x})]^2$$

(a small incremental adjustment)
(this is what we are solving for now)

Lucas-Kanade alignment

This is **still** a non-linear (quadratic) function of a non-parametric function!

(Function I is non-parametric)

Assignment Project Exam Help

$$\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p} + \Delta \mathbf{p})) - T(\mathbf{x})]^2$$

https://powcoder.com
Add WeChat powcoder

How can we linearize the function I for a really small perturbation of \mathbf{p} ?

Taylor series approximation!

Lucas-Kanade alignment

Multivariable Taylor Series Expansion
(First order approximation)

$$f(x, y) \approx f(a, b) + f_x(a, b)(x - a) + f_y(a, b)(y - b)$$

Assignment Project Exam Help

Recall: $\mathbf{x}' = \mathbf{W}(\mathbf{x}; \mathbf{p})$

<https://powcoder.com>

$$I(\mathbf{W}(\mathbf{x}; \mathbf{p} + \Delta \mathbf{p})) \approx I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \frac{\partial I(\mathbf{W}(\mathbf{x}; \mathbf{p}))}{\partial \mathbf{p}} \Delta \mathbf{p}$$

Add WeChat powcoder

chain rule

$$= I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \frac{\partial I(\mathbf{W}(\mathbf{x}; \mathbf{p}))}{\partial \mathbf{x}'} \frac{\partial \mathbf{W}(\mathbf{x}; \mathbf{p})}{\partial \mathbf{p}} \Delta \mathbf{p}$$

short-hand

$$= I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p}$$

↑
↑
short-hand


Lucas-Kanade alignment

$$\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p} + \Delta\mathbf{p})) - T(\mathbf{x})]^2$$

Assignment Project Exam Help

<https://powcoder.com>

By linear approximation,
Add WeChat powcoder

$$\sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta\mathbf{p} - T(\mathbf{x}) \right]^2$$


Now, the function is a linear function of the unknowns

Lucas-Kanade alignment

The Jacobian $\frac{\partial \mathbf{W}}{\partial \mathbf{p}}$

(A matrix of partial derivatives)

$$\mathbf{x} = \begin{bmatrix} x \\ y \end{bmatrix}$$

$$\partial \mathbf{W} = \begin{bmatrix} W_x(x, y) \\ W_y(x, y) \end{bmatrix}$$

$$\frac{\partial \mathbf{W}}{\partial \mathbf{p}} = \begin{bmatrix} \frac{\partial W_x}{\partial p_1} & \frac{\partial W_x}{\partial p_2} & \dots & \frac{\partial W_x}{\partial p_N} \\ \frac{\partial W_y}{\partial p_1} & \frac{\partial W_y}{\partial p_2} & \dots & \frac{\partial W_y}{\partial p_N} \end{bmatrix}$$

Rate of change of the warp

Affine transform

$$\mathbf{W}(\mathbf{x}, \mathbf{p}) = \begin{bmatrix} p_1 x + p_3 y + p_5 \\ p_2 x + p_4 y + p_6 \end{bmatrix}$$

$$\frac{\partial W_x}{\partial p_1} = x \quad \frac{\partial W_x}{\partial p_2} = 0 \quad \dots$$

$$\frac{\partial W_y}{\partial p_1} = 0 \quad \dots$$

$$\frac{\partial \mathbf{W}}{\partial \mathbf{p}} = \begin{bmatrix} x & 0 & y & 0 & 1 & 0 \\ 0 & x & 0 & y & 0 & 1 \end{bmatrix}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Lucas-Kanade alignment

Diagram illustrating the Lucas-Kanade alignment formula with annotations:

Annotations and dimensions:

- warp function (2×1)
- Partial derivatives of warp function (2×6)
- template image intensity (scalar)
- warp parameters (6 for affine)
- image gradient (1×2)
- incremental warp (6×1)
- pixel coordinate (2×1)
- image intensity (scalar)

Formula:

$$\sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - T(\mathbf{x}) \right]^2$$

Watermark text:

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Summary: Lucas-Kanade alignment

Problem:

$$\min_p \sum_x [I(\mathbf{W}(x; p)) - T(x)]^2$$

warped image template image

Difficult non-linear optimization problem

Assignment Project Exam Help

Strategy:

<https://powcoder.com>

$$\sum_x [I(\mathbf{W}(x; p + \Delta p)) - T(x)]^2$$

Add WeChat powcoder

Assume known approximate solution
Solve for increment

$$\sum_x \left[I(\mathbf{W}(x; p)) + \nabla I \frac{\partial \mathbf{W}}{\partial p} \Delta p - T(x) \right]^2$$

Taylor series approximation
Linearize

then solve for Δp

Lucas-Kanade alignment - Solver

Assignment Project Exam Help

Ok, so how do we solve this?

<https://powcoder.com>

$$\min_{\Delta \mathbf{p}} \sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - T(\mathbf{x}) \right]^2$$

Add WeChat powcoder

Lucas-Kanade alignment - Solver

$$\min_{\Delta \mathbf{p}} \sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - T(\mathbf{x}) \right]^2$$

Assignment Project Exam Help
(moving terms around)

$$\min_{\Delta \mathbf{p}} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - \{T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))\} \right]^2$$

vector of
constants

vector of
variables

constant

Have you seen this form of optimization problem before?

Lucas-Kanade alignment - Solver

$$\min_{\Delta \mathbf{p}} \sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - T(\mathbf{x}) \right]^2$$

Assignment Project Exam Help

$$\min_{\Delta \mathbf{p}} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - \{T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))\} \right]^2$$

<https://powcoder.com>

Add WeChat powcoder

constant

variable

constant

Looks like

$$\mathbf{Ax} - \mathbf{b}$$

How do you solve this?

Lucas-Kanade alignment - Solver

Least squares approximation

$$\hat{x} = \arg \min_x ||Ax - b||^2 \text{ is solved by } x = (A^\top A)^{-1} A^\top b$$

Applied to our task:

$$\min_{\Delta p} \sum_x \left[\nabla I \frac{\partial \mathbf{W}}{\partial p} \Delta p - \{T(x) - I(\mathbf{W}(x; p))\} \right]^2$$

Add WeChat powcoder

$$\Delta p = H^{-1} \sum_x \left[\nabla I \frac{\partial \mathbf{W}}{\partial p} \right]^\top [T(x) - I(\mathbf{W}(x; p))] \quad \text{after applying} \quad x = (A^\top A)^{-1} A^\top b$$

$$\text{where } H = \sum_x \left[\nabla I \frac{\partial \mathbf{W}}{\partial p} \right]^\top \left[\nabla I \frac{\partial \mathbf{W}}{\partial p} \right] \quad A^\top A$$

Lucas-Kanade alignment - Solver

Solve:

$$\min_{\mathbf{p}} \sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p})) - T(\mathbf{x})]^2$$

warped image
template image

Difficult non-linear optimization problem

Strategy:

$$\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p} + \Delta \mathbf{p})) - T(\mathbf{x})]^2$$

Assume known approximate solution
Solve for increment

$$\sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - T(\mathbf{x}) \right]^2$$

Taylor series approximation
Linearize

Solution:

$$\Delta \mathbf{p} = H^{-1} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top [T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$$

Solution to least square
s approximation

$$H = \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]$$

Hessian

Called Gauss-Newton gradient decent non-linear optimization!

Lucas-Kanade alignment - Algorithm

1. Warp image $I(\mathbf{W}(\mathbf{x}; \mathbf{p}))$

2. Compute error image $[T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$

3. Compute gradient $\nabla I(\mathbf{x}')$ \mathbf{x} : coordinates of the warped image
(gradients of the warped image)

<https://powcoder.com>

4. Evaluate Jacobian $\frac{\partial \mathbf{W}}{\partial \mathbf{p}}$
Add WeChat powcoder

5. Compute Hessian H
$$H = \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]$$

6. Compute $\Delta \mathbf{p}$
$$\Delta \mathbf{p} = H^{-1} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top [T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$$

7. Update parameters $\mathbf{p} \leftarrow \mathbf{p} + \Delta \mathbf{p}$

Lucas-Kanade alignment - Algorithm

1. Warp image $I(\mathbf{W}(\mathbf{x}; \mathbf{p}))$

2. Compute error image $[T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$

3. Compute gradient $\nabla I(\mathbf{x}')$

<https://powcoder.com>

4. Evaluate Jacobian $\frac{\partial \mathbf{W}}{\partial \mathbf{p}}$

Add WeChat powcoder


5. Compute Hessian H

$$H = \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^{\top} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]$$

6. Compute $\Delta \mathbf{p}$

$$\Delta \mathbf{p} = H^{-1} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^{\top} [T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$$

7. Update parameters $\mathbf{p} \leftarrow \mathbf{p} + \Delta \mathbf{p}$



L-K motion estimation vs L-K image alignment?

- Relationships

$$\min_{\mathbf{p}} \sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p})) - T(\mathbf{x})]^2$$

Assignment Project Exam Help

- Lucas-Kanade motion estimation (what we learned in EBU6230) can be seen as a special case of the Lucas-Kanade image alignment with a translational warp model

Add WeChat powcoder

Translation

$$\begin{aligned} \mathbf{W}(\mathbf{x}; \mathbf{p}) &= \begin{bmatrix} x + p_1 \\ y + p_2 \end{bmatrix} \\ &= \begin{bmatrix} 1 & 0 & p_1 \\ 0 & 1 & p_2 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix} \end{aligned}$$

transform coordinate

Affine

$$\begin{aligned} \mathbf{W}(\mathbf{x}; \mathbf{p}) &= \begin{bmatrix} p_1 x + p_2 y + p_3 \\ p_4 x + p_5 y + p_6 \end{bmatrix} \\ &= \begin{bmatrix} p_1 & p_2 & p_3 \\ p_4 & p_5 & p_6 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix} \end{aligned}$$

affine transform coordinate

Content

- Motion Estimation (Review of EBU6230 content)
- Image Alignment
- Kanade-Lucas-Tomasi (KLT) Tracking
- Mean-shift Tracking

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://www.youtube.com/watch?v=rwljkECpY0M>

Feature-based tracking

- Up to now, we've been aligning entire images
 - but we can also track just small image regions too

- Questions to solve tracking
 - How should we select features?
 - How should we track them from frame to frame?

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

KLT-tracker: history



Lucas



Kanade

An Iterative Image Registration Technique
with an Application to Stereo Vision.

1981



<https://powcoder.com>

Add WeChat powcoder



Kanade

Tomasi


Detection and Tracking of Feature Points.

1991

The original KLT algorithm



Tomasi



Shi

Good Features to Track.

1994

KLT-tracker: history

Kanade-Lucas-Tomasi

Assignment Project Exam Help

<https://powcoder.com>

How should we track them from frame to frame?

Lucas-Kanade

Method for aligning
(tracking) an image patch

How should we select features?

Tomasi-Kanade

Method for choosing the
best feature (image patch)
for tracking

Add WeChat powcoder

What are good features for tracking?
Assignment Project Exam Help

Intuitively, we want to avoid smooth regions
and edges.
But is there a more principled way to define
good features?

What are good features for tracking?
Assignment Project Exam Help

<https://powcoder.com>
Can be derived from the tracking algorithm

Add WeChat powcoder
'A feature is good if it can be tracked well'

Recall: Lucas-Kanade image alignment

error function (SSD) $\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p})) - T(\mathbf{x})]^2$

incremental update $\sum_{\mathbf{x}} [I(\mathbf{W}(\mathbf{x}; \mathbf{p} + \Delta \mathbf{p})) - T(\mathbf{x})]^2$

linearize $\sum_{\mathbf{x}} \left[I(\mathbf{W}(\mathbf{x}; \mathbf{p})) + \nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \Delta \mathbf{p} - T(\mathbf{x}) \right]^2$

Gradient update $\Delta \mathbf{p} = H^{-1} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top [T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$

$$H = \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]$$

Update $\mathbf{p} \leftarrow \mathbf{p} + \Delta \mathbf{p}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Hessian matrix

Stability of gradient decent iterations depends on ...

$$\Delta \mathbf{p} = H^{-1} \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^{\top} [T(\mathbf{x}) - I(\mathbf{W}(\mathbf{x}; \mathbf{p}))]$$

Inverting the Hessian <https://powcoder.com>

$$H = \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^{\top} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]$$

When does the inversion fail?

H is singular. But what does that mean?

Hessian matrix

Above the noise level

$$\lambda_1 \gg 0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Well-conditioned

both Eigenvalues have similar magnitude

Hessian matrix

Concrete example: Consider translation model

$$\mathbf{W}(\mathbf{x}; \mathbf{p}) = \begin{bmatrix} x + p_1 \\ y + p_2 \end{bmatrix} \quad \frac{\mathbf{W}}{\partial \mathbf{p}} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$


Hessian

Assignment Project Exam Help


$$\begin{aligned} H &= \sum_{\mathbf{x}} \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right]^\top \left[\nabla I \frac{\partial \mathbf{W}}{\partial \mathbf{p}} \right] \\ &= \sum_{\mathbf{x}} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} I_x \\ I_y \end{bmatrix} \begin{bmatrix} I_x & I_y \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \\ &= \begin{bmatrix} \sum_{\mathbf{x}} I_x I_x & \sum_{\mathbf{x}} I_y I_x \\ \sum_{\mathbf{x}} I_x I_y & \sum_{\mathbf{x}} I_y I_y \end{bmatrix} \quad \leftarrow \text{when is this singular?} \end{aligned}$$

How are the eigenvalues related to image content?


Interpreting eigenvalues



Interpreting eigenvalues



Interpreting eigenvalues



What are good features for tracking?
Assignment Project Exam Help

<https://powcoder.com>
 $\min(\lambda_1, \lambda_2) > \lambda$

Add WeChat powcoder
'big Eigenvalues means good for tracking'

KLT algorithm

1. Find corners satisfying $\min(\lambda_1, \lambda_2) > \lambda$
2. For each corner compute displacement to next frame using the Lucas-Kanade method
3. Store displacement of each corner, update corner position
4. (optional) Add more corner points every M frames using 1
5. Repeat 2 to 3 (4)
6. Returns long trajectories for each corner point

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

EBU7240

Computer Vision

Assignment Project Exam Help

- <https://powcoder.com> -

Add WeChat powcoder

Semester 1, 2021

Changjae Oh

Content

- Motion Estimation (Review of EBU6230 content)
- Image Alignment
- Kanade-Lucas-Tomasi (KLT) Tracking
- **Mean-shift Tracking** Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)

Assignment Project Exam Help

Pick a point

<https://powcoder.com>

Add WeChat powcoder




Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)

Draw a window




Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)

Compute the
(weighted) **mean**



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)

Shift the window



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)

Compute the **mean**



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm


Fukunaga & Hostetler (1975)



Mean Shift Algorithm

A 'mode seeking' algorithm

Fukunaga & Hostetler (1975)



Mean-Shift Algorithm

Initialize \mathbf{x} place we start

While $v(\mathbf{x}) > \epsilon$ shift values becomes really small

Assignment Project Exam Help

1. Compute mean-shift

<https://powcoder.com>

$$m(\mathbf{x}) = \frac{\sum_s K(\mathbf{x}, \mathbf{x}_s) \mathbf{x}_s}{\sum_s K(\mathbf{x}, \mathbf{x}_s)}$$

[Add WeChat powcoder](https://powcoder.com)

compute the 'mean'

$$\mathbf{v}(\mathbf{x}) = m(\mathbf{x}) - \mathbf{x}$$

compute the 'shift'

2. Update $\mathbf{x} \leftarrow \mathbf{x} + \mathbf{v}(\mathbf{x})$ update the point

Mean-Shift Tracking

Given a set of points:

$$\{\mathbf{x}_s\}_{s=1}^S, \quad \mathbf{x}_s \in \mathcal{R}^d$$

and a kernel:

<https://powcoder.com>

$$K(\mathbf{x}, \mathbf{x}_s) = g\left(\frac{\|\mathbf{x} - \mathbf{x}_s\|^2}{h}\right)$$

Find the mean sample point:

$$\mathbf{x}$$

Mean-Shift Algorithm

Initialize \mathbf{x}

place we start

While $v(\mathbf{x}) > \epsilon$

shift values beco

Assignment Project Exam Help

1. Compute mean-shift

$$m(\mathbf{x}) = \frac{\sum_s K(\mathbf{x}, \mathbf{x}_s) \mathbf{x}_s}{\sum_s K(\mathbf{x}, \mathbf{x}_s)}$$

Add WeChat powecoder

$$v(\mathbf{x}) = m(\mathbf{x}) - \mathbf{x}$$

2. Update $\mathbf{x} \leftarrow \mathbf{x} + v(\mathbf{x})$

compute the 'mean'

compute the 'shift'

update the point

Gaussian Noise Removal: Bilateral Filtering


Bilateral filter for grayscale image

- One of the most popular filters with various applications
- Considers both spatial and intensity distances

$$O(i, j) = \sum_{s=-a}^a \sum_{t=-b}^b w(s, t) I(i + s, j + t)$$

$$w(s, t) = \frac{1}{W(i, j)} \exp\left(-\frac{s^2}{2\sigma_s^2} - \frac{t^2}{2\sigma_t^2}\right) \exp\left(-\frac{(I(i, j) - I(i + s, j + t))^2}{2\sigma_r^2}\right)$$

$$W(i, j) = \sum_{m=-a}^a \sum_{n=-b}^b \exp\left(-\frac{m^2}{2\sigma_s^2} - \frac{n^2}{2\sigma_t^2}\right) \exp\left(-\frac{(I(i, j) - I(i + m, j + n))^2}{2\sigma_r^2}\right)$$



- This can be rewritten as:

$$O_p = \frac{1}{W_p} \sum_{q \in N_p} G_{\sigma_s}(|p - q|) G_{\sigma_r}(|I_p - I_q|) I_q$$

$$W_p = \sum_{q \in N_p} G_{\sigma_s}(|p - q|) G_{\sigma_r}(|I_p - I_q|)$$


Assignment Project Exam Help

Everything up to now has been about
<https://powcoder.com>
distributions over samples...

Add WeChat powcoder

Dealing with Images

Pixels for a lattice, spatial density is the same everywhere!



What can we do?

Dealing with Images

same

Consider a set of points: $\{\mathbf{x}_s\}_{s=1}^S \quad \mathbf{x}_s \in \mathcal{R}^d$

Associated weights: $w(\mathbf{x}_s)$

<https://powcoder.com>

Sample mean: $m(\mathbf{x}) = \frac{\sum_s K(\mathbf{x}, \mathbf{x}_s) w(\mathbf{x}_s) \mathbf{x}_s}{\sum_s K(\mathbf{x}, \mathbf{x}_s) w(\mathbf{x}_s)}$

same

Mean shift: $m(\mathbf{x}) - \mathbf{x}$

Mean-Shift Algorithm (for images)

Initialize \mathbf{x}

While $v(\mathbf{x}) > \epsilon$

Assignment Project Exam Help

1. Compute mean-shift

<https://powcoder.com>


$$m(\mathbf{x}) = \frac{\sum_s K(\mathbf{x}, \mathbf{x}_s) w(\mathbf{x}_s) \mathbf{x}_s}{\sum_s K(\mathbf{x}, \mathbf{x}_s) w(\mathbf{x}_s)}$$

Add WeChat powcoder


$$v(\mathbf{x}) = m(\mathbf{x}) - \mathbf{x}$$

2. Update $\mathbf{x} \leftarrow \mathbf{x} + v(\mathbf{x})$


For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight




For images, each pixel is point with a weight



For images, each pixel is point with a weight



For images, each pixel is point with a weight



Mean-Shift procedure

- Simple Mean Shift procedure:

- Compute mean shift vector
- Translate the Kernel window by $m(x)$

Initialize \mathbf{x}


While $v(\mathbf{x}) > \epsilon$

1. Compute mean-shift

$$m(\mathbf{x}) = \frac{\sum_s K(\mathbf{x}, \mathbf{x}_s) w(\mathbf{x}_s) \mathbf{x}_s}{\sum_s K(\mathbf{x}, \mathbf{x}_s) w(\mathbf{x}_s)}$$

$$v(\mathbf{x}) = m(\mathbf{x}) - \mathbf{x}$$

2. Update $\mathbf{x} \leftarrow \mathbf{x} + v(\mathbf{x})$




Assignment Project Exam Help

Finally... <https://powcoder.com> mean shift tracking in video!

Add WeChat powcoder

Mean shift tracking in video

Goal: find the best candidate location in frame 2



Frame 1

Frame 2

Use the mean shift algorithm
to find the best candidate location

Non-rigid object tracking



hand tracking

Non-rigid object tracking


Compute a descriptor for the target



Target

Non-rigid object tracking

Search for similar descriptor in neighborhood in next frame



Non-rigid object tracking


Compute a descriptor for the new target



Target

Non-rigid object tracking

Search for similar descriptor in neighborhood in next frame



Assignment Project Exam Help

<https://powcoder.com>

How do we model the target and candidate regions?

Add WeChat powcoder

Modelling the target



M-dimensional **target** descriptor

$$\mathbf{q} = \{q_1, \dots, q_M\}$$

(centered at target center)


<https://powcoder.com>

a 'fancy' (confusing) way to write a weighted histogram

$$q_m = C \sum_n k(\|\mathbf{x}_n\|^2) \delta[b(\mathbf{x}_n) - m]$$

Annotations for the equation:

- C : Normalization factor
- \sum_n : sum over all pixels
- $k(\|\mathbf{x}_n\|^2)$: function of inverse distance (weight)
- δ : Kronecker delta function
- $b(\mathbf{x}_n)$: quantization function
- m : bin ID



A normalized
color histogram
(weighted by distance)

Modelling the candidate

M-dimensional **candidate** descriptor

$$\mathbf{p}(\mathbf{y}) = \{p_1(\mathbf{y}), \dots, p_M(\mathbf{y})\}$$



(centered at location \mathbf{y})

<https://powcoder.com>

a weighted histogram at \mathbf{y}

$$p_m = C_h \sum_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right) \delta[b(\mathbf{x}_n) - m]$$

bandwidth



Similarity between the target and candidate

Distance function

$$d(\mathbf{y}) = \sqrt{1 - \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]}$$

Assignment Project Exam Help
Bhattacharyya Coefficient


$$\rho(\mathbf{y}) \equiv \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] = \sum_m \sqrt{p_m(\mathbf{y}) q_m}$$

<https://powcoder.com>

Just the Cosine distance between two unit vectors

Add WeChat powcoder


$$\rho(\mathbf{y}) = \cos \theta_{\mathbf{y}} = \frac{\mathbf{p}(\mathbf{y})^\top \mathbf{q}}{\|\mathbf{p}\| \|\mathbf{q}\|} = \sum_m \sqrt{p_m(\mathbf{y}) q_m}$$



Assignment Project Exam Help

Now we can compute the similarity between a
target and multiple candidate regions

<https://powcoder.com>
Add WeChat powcoder




image

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



similarity over image




we want to find this peak


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



image



similarity over image

Objective function

$$\min_{\mathbf{y}} d(\mathbf{y}) \quad \text{same as} \quad \max_{\mathbf{y}} \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]$$

Assignment Project Exam Help

Assuming a good initial guess

<https://powcoder.com>

Add WeChat powcoder

Linearize around the initial guess (Taylor series expansion)

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0) q_m} + \frac{1}{2} \sum_m p_m(\mathbf{y}) \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}}$$

function at specified value derivative

Objective function

Linearized objective

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0) q_m} + \frac{1}{2} \sum_m p_m(\mathbf{y}) \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}}$$

Assignment Project Exam Help

<https://powcoder.com>

$$p_m = C_h \sum_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right) \delta[b(\mathbf{x}_n) - m]$$

Remember
definition of this?

Add WeChat powcoder

Fully expanded

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0) q_m} + \frac{1}{2} \sum_m \left\{ C_h \sum_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right) \delta[b(\mathbf{x}_n) - m] \right\} \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}}$$

Objective function

Fully expanded linearized objective

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0) q_m} + \frac{1}{2} \sum_m \left\{ C_h \sum_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right) \delta[b(\mathbf{x}_n) - m] \right\} \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}}$$

Assignment Project Exam Help

Moving terms around...
<https://powcoder.com>

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \underbrace{\frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0) q_m}}_{\text{Does not depend on unknown } \mathbf{y}} + \underbrace{\frac{C_h}{2} \sum_n w_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right)}_{\text{Weighted kernel density estimate}}$$

where $w_n = \sum_m \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}} \delta[b(\mathbf{x}_n) - m]$

Weight is bigger when $q_m > p_m(\mathbf{y}_0)$

Assignment Project Exam Help

OK, why are we doing all this math?

<https://powcoder.com>

Add WeChat powcoder

We want to maximize this

$$\max_{\mathbf{y}} \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]$$

Fully expanded linearized objective

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0)} q_m + \frac{C_h}{2} \sum_n w_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right)$$

$$\text{where } w_n = \sum_m \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}} \delta[b(\mathbf{x}_n) - m]$$

We want to maximize this

$$\max_{\mathbf{y}} \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]$$

only need to
maximize this!

Fully expanded linearized objective

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0)} q_m + \frac{C_h}{2} \sum_n w_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right)$$

doesn't depend on unknown \mathbf{y}

$$\text{where } w_n = \sum_m \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}} \delta[b(\mathbf{x}_n) - m]$$

We want to maximize this

$$\max_{\mathbf{y}} \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]$$

Assignment Project Exam Help

only need to
maximize this!

<https://powcoder.com>
Fully expanded linearized objective

$$\rho[\mathbf{p}(\mathbf{y}), \mathbf{q}] \approx \frac{1}{2} \sum_m \sqrt{p_m(\mathbf{y}_0)} q_m + \frac{C_h}{2} \sum_n w_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right)$$

Add WeChat powcoder

doesn't depend on unknown \mathbf{y}

$$\text{where } w_n = \sum_m \sqrt{\frac{q_m}{p_m(\mathbf{y}_0)}} \delta[b(\mathbf{x}_n) - m]$$

what can we use to solve this weighted KDE?

Mean Shift Algorithm!

$$\frac{C_h}{2} \sum_n w_n k \left(\left\| \frac{\mathbf{y} - \mathbf{x}_n}{h} \right\|^2 \right)$$

Assignment Project Exam Help

the new sample of mean of this KDE is
<https://powcoder.com>

Add WeChat powcoder

$$\mathbf{y}_1 = \frac{\sum_n \mathbf{x}_n w_n g \left(\left\| \frac{\mathbf{y}_0 - \mathbf{x}_n}{h} \right\|^2 \right)}{\sum_n w_n g \left(\left\| \frac{\mathbf{y}_0 - \mathbf{x}_n}{h} \right\|^2 \right)} \quad \text{(this was derived earlier)}$$

(new candidate location)

Mean-Shift Object Tracking

For each frame:

1. Initialize location y_0

Compute q

Compute $p(y_0)$

2. Derive weights w_n

3. Shift to new candidate location (mean shift) y_1

4. Compute $p(y_1)$

5. If $\|y_0 - y_1\| < \epsilon$ return

Otherwise $y_0 \leftarrow y_1$ and go back to 2

Mean-Shift Object Tracking: example


Compute a descriptor for the target



Target
 q

Mean-Shift Object Tracking: example

Search for similar descriptor in neighborhood in next frame



Target

Candidate

$$\max_{\mathbf{y}} \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]$$

Mean-Shift Object Tracking: example

Compute a descriptor for the new target




Target

q

Mean-Shift Object Tracking: example

Search for similar descriptor in neighborhood in next frame



Target

Candidate

$$\max_{\mathbf{y}} \rho[\mathbf{p}(\mathbf{y}), \mathbf{q}]$$

Examples



Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder



Modern trackers

Assignment Project Exam Help
Learning Multi-Domain Convolutional
<https://powcoder.com>
Neural Networks for Visual Tracking
Add WeChat powcoder

Hyeonseob Nam and Bohyung Han

From Mid-level to High-level ?



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder