

Cryptography Basics – Public Key Cryptography

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

ECEN 4133

FEB 4, 2021

Shared key limitations

Suppose Alice publishes data to lots of people, and they all want to verify integrity...

Can't share an integrity key with *everybody*, or else *anybody* could forge messages

Suppose Bob wants to receive data from lots of people, confidentially...

Schemes we've discussed would require a separate key shared with each person

[What to do?]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Public-key crypto

So far, encryption key == decryption key “**symmetric key crypto**”

New idea: Keys are distinct, and you can't find one from the other

Almost always used by splitting key-pair

Alice keeps one key private (“**private key**”)

Publishes the other key (“**public key**”)

<https://powcoder.com>
Add WeChat powcoder

Invented in 1976 by Diffie and Hellman (earlier by Clifford Cocks of British intelligence, in secret)

First popular public key algorithm: **RSA**

Rivest, Shamir, and Adleman 1978

Requirements for a public key crypto system to be secure

1. Computationally easy for B to generate a key pair: PU_b, PR_b
2. Computationally easy for sender A to generate the ciphertext for message M: $C=E(PU_b, M)$
3. Computationally easy for receiver B to decrypt the ciphertext: $M=D(PR_b, C)$
4. Computational infeasible to guess PR_b knowing PU_b .
5. Computational infeasible to recover M from PU_b and C.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

RSA

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



**A Method for Obtaining Digital
Signatures and Public-Key Cryptosystems**

R.L. Rivest, A. Shamir, and L. Adleman*

How RSA works

Key generation:

1. Pick large (say, 1024 bits) random primes p and q
2. Compute $N := pq$ (RSA uses multiplication mod N)
3. Pick e to be relatively prime to $(p-1)(q-1)$
4. Find d so that $ed \bmod (p-1)(q-1) = 1$
5. Finally: **Public key** is (e, N)
Private key is (d, N)

To encrypt: $E(x) = x^e \bmod N$

To decrypt: $D(x) = x^d \bmod N$

Why RSA works

“It works” theorem:

For all $0 < x < N$,

can show that $D(E(x)) = x$

Assignment Project Exam Help

Proof:

$$\begin{aligned} D(E(x)) &= (x^e \bmod pq)^d \bmod pq \\ &= x^{ed} \bmod pq \\ &= x^{a(p-1)(q-1)+1} \bmod pq \quad \text{for some } a \quad (\text{because } ed \bmod (p-1)(q-1) = 1) \\ &= (x^{(p-1)(q-1)})^a x \bmod pq \\ &= (x^{(p-1)(q-1)} \bmod pq)^a x \bmod pq \\ &= 1^a x \bmod pq \\ &\quad (\text{because of the fact that if } p, q \text{ are prime, then for all } 0 < x < N, \\ &\quad \quad x^{(p-1)(q-1)} \bmod pq = 1) \\ &= x \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

Is RSA secure?

Best known way to compute d from e
is factoring N into p and q .

Best known factoring algorithm:

General number field sieve

Takes more than polynomial time, but less than exponential time, to factor n -bit number.

(Still takes way too long if p, q are large enough and random.)

Fingers crossed...


but can't rule out a breakthrough!

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Signing with the public key for confidentiality or secrecy:



Does this provide integrity?

Signing with private key for integrity/authentication.



Does this provide confidentiality?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

RSA can be used for either confidentiality or integrity

RSA for confidentiality:

Encrypt with public key

Decrypt with private key

“your eyes only” message

Assignment Project Exam Help

RSA for integrity:

<https://powcoder.com>

Encrypt (“sign”) with private key

Decrypt (“verify”) with public key

called a **digital signature**

Add WeChat powcoder

[What if we want both confidentiality and integrity on the same message?]

Which of these provides both confidentiality and integrity?

Alice (A) wants to send a secret message M to Bob (B) so that Bob can verify that it comes from Alice.

Which one(s) is/are secure?

1. $E(E(M, PR_A), PU_B)$
2. $E(E(M, PU_B), PR_A)$
3. $C=E(M, PR_A) \quad t=E(H(C), PU_B)$
 - Send $C || t$
4. $C=E(M, PU_B) \quad t=E(H(C), PR_A)$
 - Send $C || t$

<https://powcoder.com>

Add WeChat powcoder

Review: Public-key Crypto

So far, encryption key == decryption key
“**symmetric key crypto**”

New idea: Keys are distinct.

RSA: $N := pq$

Public key is (e, N)

Private key is (d, N)

To encrypt: $E(x) = x^e \bmod N$
To decrypt: $D(x) = x^d \bmod N$

RSA for confidentiality:

Encrypt with public key
Decrypt with private key

*RSA for integrity (**digital signatures**):*

Encrypt (“sign”) with private key
Decrypt (“verify”) with public key

[Cautions?!]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

RSA drawback: Performance

Factor of 1000 or more slower than AES.

Dominated by exponentiation – cost goes up (roughly) as cube of key size.

Message must be shorter than N .

[How big should the RSA keys be?]

Assignment Project Exam Help

<https://powcoder.com>

Use in practice:

Encryption:

Use RSA to encrypt a random $x < N$, compute $k := \text{PRF}(x)$, encrypt message using a symmetric cipher and key k

Add WeChat powcoder

Signing:

Compute $v := \text{PRF}(m)$, use RSA to sign a carefully padded version of v (many gotchas!)

Almost always should use crypto libraries to get the details right

True or False?

Public-key encryption is a general-purpose technique that has made symmetric encryption obsolete

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

True or False?

Key distribution is trivial when using public-key encryption, compared to the cumbersome handshaking involved with key distribution centers for symmetric encryption.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Attacks against RSA

1. Brute force: trying all possible private keys
2. Mathematical attacks: factoring
3. Timing attacks: using the running time of decryption
4. Hardware-based fault attack: induce faults in hardware to generate digital signatures
5. Chosen plaintext attack on unpadded RSA

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exercise

Suppose Bob uses RSA crypto with a very large modulus n for which the factorization cannot be found in a reasonable amount of time.

Suppose Alice sends a message to Bob by representing each alphabet letter as an integer between 0 and 25 (A→0, ..., Z→25) and then encrypting each number separately using RSA with large e and large n .

Is this method secure?

If yes, why?

If not, how to efficiently attack this encryption method?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Solution

For a set of message block values $SM = \{0, 1, 2, \dots, 25\}$. The set of corresponding ciphertext block values $SC = \{0^e \bmod N, 1^e \bmod N, \dots, 25^e \bmod N\}$, and can be computed by everybody with the knowledge of the public key of Bob.

The most efficient attack is to compute $M^e \bmod N$ for all possible values of M , then create a look-up table with a ciphertext as an index and the corresponding plaintext as a value of the appropriate location in the table.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Two subtle “textbook” RSA problems:

1. For small e and m :
 $m^e \bmod N == m^e$
Trivial to decrypt!
2. If m is chosen from a small set, easy to confirm a ciphertext is a given message (anyone can encrypt!)
Chosen plaintext attack

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Solution: RSA Padding


Need to make sure m is as *large enough* to wrap around N (so can't take e -th root of ciphertext)

Need to *randomize* before encryption (so low-entropy plaintext can't be decrypted)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Other public key cryptography systems


RSA is popular, but not the only one:

- DSA – Digital Signature Algorithm
- ECDSA – Elliptic Curve Digital Signature Algorithm
 - Very small public keys: e.g. curve25519: 256-bits (32 bytes)
- Post-Quantum Cryptography:
 - Ring-LWE, NTRU, hash-based

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



So Far:

The Security Mindset

Message Integrity **Assignment Project Exam Help**

Confidentiality

Key Exchange

<https://powcoder.com>

Building a Secure Channel

Public Key Crypto

Add WeChat powcoder

Next Week:

Begin Web Security Unit

HTTPS: Secure channels for the web