

ECS 150 - GDB tutorial

Prof. Joël Porquet-Lupine

Assignment Project Exam Help

UC Davis - 2020/2021

<https://powcoder.com>

Add WeChat powcoder



GDB

GNU project

- Started by Richard Stallman in 1983
- Free software, mass collaboration project in response to proprietary UNIX
 - Copyleft license: GNU GPL
 - User programs: text editor (Emacs), compiler (GCC toolchain), debugger (GDB), and various utilities (ls, grep, awk, make, etc.)
 - Kernel: GNU Hurd

GDB

- GNU DeBugger
- Supports many languages
 - Including C and C++
- Inspection of program during execution
 - Execution flow
 - Data
- Helps finding errors like *segmentation fault*
- Read the fully-detailed manual: <https://sourceware.org/gdb/current/onlinedocs/gdb/>

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

GDB usage

Compilation flags

- Canonical compilation command line:

```
$ gcc [cflags] -o <output> <input>
```

- Optimize for speed (-O2)

```
$ gcc -Wall -Werror -O2 -o myprogram main.c
```

Assignment Project Exam Help

- Enable debugging support (-g)

```
$ gcc -Wall -Werror -g myprogram main.c
```

- Not recommended to use debugging along with optimizations
 - No optimization option is equivalent to -O0

<https://powcoder.com>

Add WeChat powcoder

GDB usage

Makefile digression

- During development, very useful to be able to debug your program
- For production, probably better to disable the debug support and activate all possible optimization support
 - Reduce size of the executable (can easily be by 50%!)
 - Increase performance (can also be by 50%!)

Makefile automation

```
ifeq ($(D),1)
CFLAGS += -g    # Enable debugging
else
CFLAGS += -O2   # Enable optimization
endif
```

Building mode

```
$ make D=1    # compile with debug support and no optimization
```

```
$ make        # compile with optimizations (production)
```

- Probably want to use `make clean` when changing building mode

GDB usage

Starting GDB

- Start GDB, specify the program to debug

```
$ gdb
...
(gdb) file myprogram
Reading symbols from myprogram...done.
(gdb)
```

- Or, start GDB with the program to debug as argument

```
$ gdb myprogram
...
Reading symbols from myprogram...done.
(gdb)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Running the program

- Without any argument:

```
(gdb) run
```

- With arguments:

```
(gdb) run argv1 argv2...
```

GDB usage

Interactive help

- GDB offers an interactive shell
 - History management
 - Auto-complete (with TAB)

In order to discover what you can do, just ask:

```
(gdb) help
```

```
List of classes of commands:
```

```
aliases -- Aliases of other commands
```

```
breakpoints -- Making program stop at certain points
```

```
...
```

```
(gdb) help breakpoints
```

```
Making program stop at certain points.
```

```
List of commands:
```

```
awatch -- Set a watchpoint for an expression
```

```
break -- Set breakpoint at specified location
```

```
...
```

```
(gdb) help break
```

```
Set breakpoint at specified location.
```

```
break [PROBE_MODIFIER] [LOCATION] [thread THREADNUM] [if CONDITION]
```

```
...
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

GDB usage

Possible scenarios

1. Program doesn't have bugs:

- It will run fine until completion

```
$ ./myprogram  
I worked, hurray!
```

2. *Best-case* scenario, regarding bugs:

- *Segmentation fault*

```
$ ./myprogram  
segmentation fault (core dumped) ./myprogram
```

3. *Worst-case* scenario:

- Doesn't crash but wrong result

```
$ ./myprogram  
I work??, ??rray!
```

- Bugs that don't trigger any segmentation fault
- In this case, you'll probably have to spend more time...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Segmentation faults

Example #1

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

size_t foo_len (const char *s)
{
    return strlen(s);
}

int main (int argc, char *argv[])
{
    char *a = NULL;

    printf ("size of a = %d\n", foo_len(a));

    return 0;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Execution

```
$ ./strlen-test
zsh: segmentation fault (core dumped) ./strlen-test
```


Segmentation faults

Run with GDB

- (After compiling the code with `-g`)

```
$ gdb ./strlen-test
(gdb) run
Starting program: /home/joel/tmp/test/strlen-test

Program received signal SIGSEGV, Segmentation fault.
0x00007ffff7abc446 in strlen () from /usr/lib/libc.so.6
(gdb)
```

Backtrace

- First thing to do when getting a *segfault*:
 - Understand what is the sequence of calls that brought us there

```
(gdb) backtrace      # use just 'bt'
#0  0x00007ffff7abc446 in strlen () from /usr/lib/libc.so.6
#1  0x000000000040055e in foo_len(s=0x0) at strlen-test.c:7
#2  0x0000000000400583 in main (argc=1, argv=0x7ffff7fd788) at strlen-test.c:14
```

Investigate

- `foo_len()` is supposed to receive a pointer
- Here it receives `0` (aka `NULL`)
- Looks like this `NULL` pointer probably gets dereferenced in `strlen()`...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Segmentation faults

Fix...

- Here, the problem is fairly obvious

```
size_t foo_len (const char *s)
{
    return strlen(s);
}

int main (int argc, char *argv[])
{
    char *a = "This is a valid string";

    printf ("size of a = %d\n", foo_len(a));

    return 0;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

And, celebrate!

```
$ ./strlen-test
size of a = 22
```

Segmentation faults

Better fix

- Prevent the same bug from happening again

```
size_t foo_len (const char *s)
{
    assert(s && "String cannot be NULL here!");
    return strlen(s);
}
```

```
int main (int argc, char *argv[])
{
    char *a = NULL;

    printf ("size of a = %d\n", foo_len(a));

    return 0;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
$ ./strlen-test
strlen-test: strlen-test.c:8: foo_len:
Assertion `s && "String cannot be NULL here!"' failed.
```

Segmentation faults

Example #2

```
#include<stdio.h>
#include<stdlib.h>

const static int len = 10;

int main(void)
{
    int *tab;
    unsigned int i,

    tab = malloc(len * sizeof(int));
    for (i = len - 1; i >= 0; i--)
        tab[i] = i;

    free(tab);
    return 0;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Execution

```
$ ./tablen-test
segmentation fault (core dumped) ./tablen-test
```

Segmentation faults

Run GDB

```
$ gdb ./tablen-test
(gdb) run
Starting program: /home/joel/tmp/test/tablen-test

Program received signal SIGSEGV, Segmentation fault.
0x0000000000400535 in main () at tablen-test.c:14
14          tab[i] = i;
```

Backtrace

```
(gdb) bt
#0 0x0000000000400535 in main () at tablen-test.c:14
```

- Except that here, it's not much of help...

Inspect variables

- Display index `i` so that we know which index in the array was being accessed:

```
(gdb) print i
$1 = 4294967295
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Segmentation faults

Fix...

- Problem is a case of overflow
 - An `unsigned int` type automatically wraps from 0 to 4294967295

```
#include<stdio.h>
#include<stdlib.h>
```

```
const static int len = 10;
```

```
int main(void)
{
```

```
    int *tab;
```

```
    int i;
```

```
    tab = malloc(len * sizeof(int));
```

```
    for (i = len - 1; i >= 0; i--)
        tab[i] = i;
```

```
    free(tab);
```

```
    return 0;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Tracking bugs

Behavior bugs

- Behavioral bugs more complicated to find because program doesn't crash
- It's just that the output is wrong

```
#include <ctype.h>
#include <stdio.h>
#include <string.h>
```

```
int main(void)
```

```
{
```

```
    int i;
```

```
    char str[] = "Tracking bugs is my passion";
```

```
    printf("Before: %s\n", str);
```

```
    for (i = 0; i < strlen(str) - 1; i++)
```

```
        str[i] = toupper(str[i]);
```

```
    printf("After: %s\n", str);
```

```
    return 0;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Execution

Before: Tracking bugs is my passion

After: TRACKING BUGS IS MY PASSION

Tracking bugs

Setting breakpoints

- Stop the program during the execution at a designated point
- Set as many breakpoints as necessary
- GDB will always stop the execution when reaching them

Breaking at exact location in code

```
(gdb) break string-test.c:13
```

```
Breakpoint 1 at 0x4005ef: file string-test.c, line 13.
```

```
(gdb) r
```

```
Starting program: /home/joe1/tmp/test/string-test
```

```
Before: Tracking bugs is my passion
```

```
Breakpoint 1, main () at string-test.c:13
```

```
13          str[i] = toupper(str[i]);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Tracking bugs

Breaking at a particular function

```
(gdb) b main
Breakpoint 1 at 0x40059f: file string-test.c, line 8.

(gdb) r
Starting program: /home/joel/tmp/test/string-test

Breakpoint 1, main () at string-test.c:8
8          char str[] = "Tracking bugs is my passion";
```

Assignment Project Exam Help

Breaking only if condition is satisfied

```
(gdb) b string-test.c:13 if i==5
Breakpoint 1 at 0x4005ef: file string-test.c, line 13.

(gdb) r
Starting program: /home/joel/tmp/test/string-test
Before: Tracking bugs is my passion

Breakpoint 1, main () at string-test.c:13
13          str[i] = toupper(str[i]);

(gdb) print i
$1 = 5
```

<https://powcoder.com>

Add WeChat powcoder

Tracking bugs

Dealing with breakpoints

- Set at least one breakpoint before running the program
 - Otherwise the program will run until completion
- Once the program stops and the gdb shell is available, a few options:
 1. Continue the execution until hitting the same or another breakpoint

```
(gdb) continue      # or just 'c'
```

2. Execute only the next line of code and break again

```
(gdb) step          # or just 's'
```

Careful, `step` enters function calls

3. Jump over function calls

```
(gdb) next          # or just 'n'
```

Tip: typing `<enter>` in the interactive GDB shell repeats the last command

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Tracking bugs

Printing variables

```
int a = 2;
char b = 'x';
int *c = &a;
char *s = "A string";
// <= breaking here
...
```

- Inspect the value of all your variables with command `print`

Assignment Project Exam Help

Default

- By default, prints variables according to their type

Tweak

- Can tweak both the way `print` prints and what it prints

<https://powcoder.com>

Add WeChat powcoder

```
(gdb) print a
$1 = 2
(gdb) p b
$2 = 120 'x'
(gdb) p c
$3 = (int *) 0x7fffffffdb65c
(gdb) p s
$4 = 0x40070b "A string"
```

```
(gdb) print /x a
$1 = 0x2
(gdb) p /c b+2
$2 = 122 'z'
(gdb) p *c
$3 = 2
(gdb) p s[0]
$4 = 65 'A'
```

Tracking bugs

Printing data structures

```
struct entry {  
    int    key;  
    char   *name;  
} obj = {  
    .key    = 2,  
    .name   = "toto",  
};
```

```
struct entry *e = &obj;
```

Assignment Project Exam Help

- With `print`, you can access the pointer and the object it's pointing to:

```
(gdb) print e  
$1 = (struct entry *) 0x7fffffff640  
(gdb) print &obj  
$2 = (struct entry *) 0x7fffffff640  
(gdb) p *e  
$3 = {key = 2, name = 0x400734 "toto"}  
(gdb) p e->key  
$4 = 2  
(gdb) p obj.name  
$5 = 0x400734 "toto"
```

<https://powcoder.com>

Add WeChat powcoder

Misc

Setting watchpoint

- Breakpoints are for interrupting the execution flow at a specific location
- Watchpoints are for interrupting the program when a variable is modified

```
(gdb) watch i  
Hardware watchpoint 2: i
```

```
(gdb) c  
Continuing.  
Before: Tracking bugs is my passion
```

```
Hardware watchpoint 2: i
```

```
Old value = 0
```

```
New value = 1
```

```
0x0000000000400612 in main (0) at string-test.c:12  
12          for (i = 0; i < strlen(str) - 1; i++)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Misc

Other useful commands

- `finish`
 - Runs until the current function is finished
- `until`
 - When executed in a loop, continues the execution until the loop ends
- `info breakpoints`
 - Shows informations about all declared breakpoints
- `delete`
 - Deletes a breakpoint

```
(gdb) info b
Num      Type           Disp Enb Address            What
1        breakpoint     keep y   0x000000000040059f  in main at string-test.c:8
breakpoint already hit 1 time
2        hw watchpoint keep y           i
breakpoint already hit 2 times
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Valgrind

Example

```
#include <stdlib.h>
```

```
void f(void)
```

```
{
```

```
    int *x = malloc(10 * sizeof(int));
```

```
    x[10] = 0;
```

```
}
```

```
int main(void)
```

```
{
```

```
    f();
```

```
    return 0;
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Valgrind

Run

```
$ valgrind --leak-check=full ./valgrind_example
...
==31134== Invalid write of size 4
==31134==    at 0x108668: f (in /home/joel/work/ecs150/slides/tuto_gdb/code/valgrind_example)
==31134==    by 0x108679: main (in /home/joel/work/ecs150/slides/tuto_gdb/code/valgrind_example)
==31134== Address 0x51f0068 is 0 bytes after a block of size 40 alloc'd
==31134==    at 0x4C2CEDF: malloc (vg_replace_malloc.c:299)
==31134==    by 0x10865B: f (in /home/joel/work/ecs150/slides/tuto_gdb/code/valgrind_example)
==31134==    by 0x108679: main (in /home/joel/work/ecs150/slides/tuto_gdb/code/valgrind_example)
==31134==
==31134== HEAP SUMMARY:
==31134==    in use at exit: 40 bytes in 1 blocks
==31134==    total heap usage: 1 allocs, 0 frees, 40 bytes allocated
==31134==
==31134== 40 bytes in 1 blocks are definitely lost in loss record 1 of 1
==31134==    at 0x4C2CEDF: malloc (vg_replace_malloc.c:299)
==31134==    by 0x10865B: f (in /home/joel/work/ecs150/slides/tuto_gdb/code/valgrind_example)
==31134==    by 0x108679: main (in /home/joel/work/ecs150/slides/tuto_gdb/code/valgrind_example)
==31134==
==31134== LEAK SUMMARY:
==31134==    definitely lost: 40 bytes in 1 blocks
==31134==    indirectly lost: 0 bytes in 0 blocks
==31134==    possibly lost: 0 bytes in 0 blocks
==31134==    still reachable: 0 bytes in 0 blocks
==31134==    suppressed: 0 bytes in 0 blocks
==31134==
==31134== For counts of detected and suppressed errors, rerun with: -v
==31134== ERROR SUMMARY: 2 errors from 2 contexts (suppressed: 0 from 0)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder