## **Project 4**

Due May 24, 2019 at 11:59 PM

This project specification is subject to change at any time for clarification. For this project you will be working with a partner. You will be developing C++ wrappers for two C libraries. The wrappers will allow for reading and writing of both CSV and XML files. You have been provided headers for the CSV and XML wrapper types. You must keep the public interface but may develop the private implementation however you wish. The two libraries that you will be wrapping are libcsv (for CSV) and libexpat (for XML). Fortunately, libexpat is installed on the CSIF, but libcsv is not. The source code for libcsv has been provided for you and you will need to build it in order to include it in your project. After you have created your wrapper classes, you will be developing a program that will convert files between CSV and XML. The files that your program will need to convert are course grade files described later in this project. Make sure to add the temporary files created for your projects (\*.o, \*.lo, \*.la, etc.) to your .qitignore file.

Create a Makefile to configure, make, and install libcsv. Open source libraries for Linux typically follow the same pattern for being built. The typical workflow is to configure, make, and then install (Auxyllle installing into the library source directory and executing the command:

./configure --prefix=INSTALLPATH

The INSTALLPATH is the prefix of where you would like to install the headers and the libraries. On a typical system this is in library / professional form. You will be just "installing" into your local project which should be the directory containing libcsv-3.0.3 directory. You can get the absolute path of the Makefile with the command \$ (shell pwd). They should be done next with executing the command: make

This should also output a lot of lines but should complete successfully. Next the library should be installed by executing the command:

make install

This should install the libraries into the lib directory in the INSTALLPATH, and move the header file into the include directory of the INSTALLPATH. After you build the library correctly there should be a libcsv.a file (this is the static library you will link against) in your lib directory, and a csv.h in in your include directory.

Once the library is built, add to your Makefile to build your CSVReader and CSVWriter object files and to build and run your google test for the CSV. The CCSVReader and CCSVWriter classes have simple interfaces.

```
// Constructor for CSV reader, CCSVReader should have a
// std::istream & as part of it
CCSVReader(std::istream &in);
// Destructor for CSV reader
```

```
~CCSVReader();
// Returns true if all rows have been read from the CSV
bool End() const;

// Returns true if the row is successfully read, one string will
// be put in the row per column
bool ReadRow(std::vector< std::string > &row);

// Constructor for CSV writer, CCSVWriter should have a
// std::ostream & as part of it
CCSVWriter(std::ostream &ou);

// Destructor for CSV writer
~CCSVWriter();

// Returns true if the row is successfully written, one string
// per column should be put in the row vector
bool WritesSigningenter(i) the row vector
bool WritesSigningenter(i)
```

Once your CSV wrappers are complete, add to your Makefile to build your XMLReader and XMLWriter object files and to build and run your google test for the XML. The CXMLReader and CXMLWriter classes have simple interfaces. The SXMLEHTITY struct is used by both classes and has been provided. You will want to build programs with your wrappers by linking in libexpat with -lexpat as a linker option.

```
Add WeChat powcoder
```

```
SXMLEntity{
    EType DType; // Type of entity start/end/complete element
    std::string DNameData;
    std::vector< TAttribute > DAttributes;
}
// returns true if the attribute name is in the DAttributes
bool AttributeExists(const std::string &name) const;
// returns the value of the attribute, or empty string if
// doesn't exist
std::string AttributeValue(const std::string &name) const;
// Sets the attribute name to the value
bool SetAttribute(const std::string &name, const std::string
&value);
// Constructor for XML reader, CXMLReader should have a
// std::istream & as part of it
CXMLReader(std::istream &is);
```

```
// Destructor for XML reader
~CXMLReader();

// Returns true if all entities have been read from the XML
bool End() const;

// Returns true if the entity is successfully read if skipcdata
// is true only element type entities will be returned
bool ReadEntity(SXMLEntity &entity, bool skipcdata = false);

// Constructor for XML writer, CXMLWriter should have a
// std::ostream & as part of it
CXMLWriter(std::ostream &ou);

// Destructor for XML writer
~CXMLWriter();

// Output SSI grantents Project LEXIAM belong ted
bool Flush();

// Writes out the entity to the output stream
bool WriteEntity Lapse SXN DATAY COLORY.
```

Once you have completed writing the XML wrapper classes, you will be ready to begin developing the student file converted fourse information is in two different systems, one uses CSV, the other uses XML. You are tasked with writing a program that will take in any number of CSV or XML files as arguments and converting each of them to the other type. The CSV files will have the following naming convention SUBJ\_CRSE\_SEC.csv where SUBJ is the course subject, CRSE is the course number, and SEC is the section number. Inside each CSV file there will be a header with the following column headings, though not guaranteed to be in any particular order.

```
SEAT – The seat number of the student
SID – The student ID
SURNAME – The last name of the student
PREFNAME – The student's preferred first name
LEVEL – The student's level UG for undergrad, etc.
UNITS – The number of units the student received
CLASS – The student's class standing
MAJOR – The student's major code
GRADE – The grade the student received in the course
STATUS – The student's registration status
EMAIL – The student's e-mail address
There will be one row for each student that was part of the course.
```

The XML files will contain the SUBJ, CRSE, and SEC information inside them. The elements in the XML file will be an outer course element with inner student elements. The SUBJ, CRSE, and SEC are attributes of the course element. The CSV headings are the attributes of the student elements.

The output file must be put in the same directory as the input file and must have name of the form SUBJ\_CRSE\_SEC.EXT where SUBJ is the course subject, CRSE is the course number, SEC is the section number, and EXT is the extension (either csv or xml).

An example program can be found in /home/cjnitta/ecs34/studconv, and sample files for conversion can be found in /home/cjnitta/ecs34/proj4samples/.

You can unzip the given tgz file with utilities on your local machine, or if you upload the file to the CSIF, you can unzip it with the command:

tar -xzvf proj4given.tgz

You **must** submit the source file(s), the Makefile, .git files, and README.txt file, in a tgz archive. Do a make, clean prior to zipping up your files so the size will be smaller. You can tar gzip a directory-name Project Exam Help tar -zcvf archive-name.tgz directory-name

Provide your interactive grading timeslot csy file in the tsz. The directions for filling it out have been posted. Make sure to include you of Villetto yellow. Com

You should avoid using existing source code as a primer that is currently available on the Internet. You **must** specify in courteache file any sources of code that you have viewed to help you complete this project. All class projects will be submitted to MOSS to determine if students have excessively collaborated. Excessive collaboration, or failure to list external code sources will result in the matter being referred to Student Judicial Affairs.

## **Helpful Hints**

- Read through the guides that are provided on Canvas.
- See <a href="http://www.cplusplus.com/reference/">http://www.cplusplus.com/reference/</a>, it is a good reference for C++ built in functions and classes.
- You may find the following line helpful for debugging your code:
   std::cout<<"In "<<\_\_FILE\_\_<<" @ "<<\_\_LINE\_\_<<std::endl;
   It will output the line string "In F @ line: X" where F is the name of the file and X is the line number the code is on. You can copy and paste it in multiple places and it will output that particular line number when it is on it.</li>
- Make sure to use a tab and not spaces with the Makefile commands for the target
- Use a .gitignore file to ignore your object files, and output binaries.
- Do not wait to the end to merge with you partner. You should merge your work together on a somewhat regular basis.

• Use std::stringstream to test your reader and writer wrappers for CSV and XML.

- You may find some useful CSV tests in the test\_csv.c file that you can implement in your google tests.
- Look at the test csv.c for examples of using the libcsv library functions.
- You will probably want to use static functions in your classes for the callbacks to the library calls that require callbacks. The call data (void \*) parameter that the functions take and the callbacks pass back as a parameter, should be this from your object.
- You may find <a href="https://www.xml.com/pub/1999/09/expat/index.html">https://www.xml.com/pub/1999/09/expat/index.html</a> helpful for describing the libexpat functions.
- You are not going to need to use every function in each library.

## Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder