

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 14

Context-Free Languages and Pushdown Automata

<https://powcoder.com>

slides by Graham Farr

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Assignment Project Exam Help

- ▶ CFL \rightarrow PDA
- ▶ PDA \rightarrow CFL

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

We will show

$$\{ \text{CFLs} \} = \{ \text{languages recognised by a PDA} \}$$

... in two parts

1. $\{ \text{CFLs} \} \subseteq \{ \text{languages recognised by a PDA} \}$

2. $\{ \text{languages recognised by a PDA} \} \subseteq \{ \text{CFLs} \}$

<https://powcoder.com>
Add WeChat powcoder

CFL \longrightarrow PDA

Theorem.

$\{ \text{CFLs} \} \subseteq \{ \text{languages recognised by a PDA} \}$

Assignment Project Exam Help

Proof outline and main ideas:

Let L be a CFL

Let G be a CFG for L

<https://powcoder.com>

We need to show that there is a PDA that recognises L .

If $w \in L$ then w has a leftmost derivation.

Add WeChat powcoder

Idea: leftmost derivation may be viewed as

- ▶ growing a prefix of w that we know to be correct, and
- ▶ managing the rest of w (including all nonterminals) with a stack.

Leftmost derivation: stack view

S

pearcey

Grammar fragment:

...
S	→	peX
X	→	YcZ
Y	→	ar
Z	→	ey
...

\Rightarrow peX pearcey X

\Rightarrow peYcZ pearcey YcZ

\Rightarrow pearcZ pearcey cZ

\Rightarrow pearcey pearcey Z

\Rightarrow pearcey pearcey

CFL \longrightarrow PDA

Assignment Project Exam Help

We construct the required PDA as follows.

We start with four basic states, then add more states for each production rule ...


<https://powcoder.com>

We'll need a new character (not currently a terminal or non-terminal),
to mark the end of our stack.


We'll use \$.

Add WeChat powcoder


CFL \longrightarrow PDA



CFL \longrightarrow PDA



CFL \longrightarrow PDA



CFL \longrightarrow PDA



<https://powcoder.com>

If a terminal is on top of stack:
everything before it in target string
must have been read in.

$a, a \rightarrow \epsilon$

$b, b \rightarrow \epsilon$

$c, c \rightarrow \epsilon$

\vdots

So we need loop transitions
to check such letters off ...

For terminals

CFL \longrightarrow PDA

This construction gives a PDA that accepts precisely those strings with a leftmost derivation by G ,

i.e., precisely those strings with a derivation by G ,

i.e., precisely those strings in L .

<https://powcoder.com>

Full formal proof: see Sipser, Ch. 2, Section 2.2.

Add WeChat powcoder

Now for the other way round ...

PDA \longrightarrow CFL

Theorem.

$\{\text{languages recognised by a PDA}\} \subseteq \{\text{CFLs}\}$

Assignment Project Exam Help

Proof ideas:

Let L be a language recognised by some PDA M .
We need to show that \exists a CFG G that generates L .

First, we make some simple modifications to M .


Then we give productions that describe certain ways of going through the PDA ...

First, modifications to M :

Ensure it has just one Final State,

and that the stack is empty when it reaches the Final State.

PDA \longrightarrow CFL



PDA \longrightarrow CFL

More modifications: ensure that each transition *either* pushes or pops, but *not both*.

Assignment Project Exam Help

These are ok:



<https://powcoder.com>

These are *not*:



So we change them ...

PDA \longrightarrow CFL



<https://powcoder.com>

Add WeChat powcoder



PDA \longrightarrow CFL

A string is accepted by this (modified) M if one of its paths through M

- ▶ starts in the Start State s ,
- ▶ finishes in the Final State t ,
- ▶ with the stack empty at start and finish.

For every pair of states p, q , define a non-terminal symbol A_{pq} .

- ▶ intended to generate all strings which, starting at p with an empty stack, can take some path through M which ends at q with an empty stack.

Aim: a grammar such that, for every string,

it is accepted by $M \iff$ it can be derived from A_{st} .

PDA \longrightarrow CFL

Consider how a computation in M , for a string w , moves from p to q , with empty stack at start and finish.

We have two cases:

Assignment Project Exam Help

Case 1:

The computation also has an empty stack at some other state r on the path.


Then we can break the computation from p to q into two parts:

- ▶ the first part, going from p to r (starting and ending with empty stack),
- ▶ the second part, going from r to q (starting and ending with an empty stack).

We model this with the production

$$A_{pq} \longrightarrow A_{pr}A_{rq}$$

PDA \longrightarrow CFL



$$A_{pq} \longrightarrow A_{pr}A_{rq}$$

PDA \longrightarrow CFL


Case 2:

The computation never has an empty stack, except at p and q .

Because it starts and finishes with an empty stack:

- ▶ the first transition must push a symbol onto the stack,
- ▶ the last transition must pop a symbol from the stack,
- ▶ the two symbols must be the same (call it z)
 - ▶ ... else the stack would have to have been emptied at some stage to remove the first symbol before the last symbol arrives.
- ▶ and this symbol stays at the bottom of the stack the whole time.

PDA \longrightarrow CFL



$$A_{pq} \longrightarrow xA_{p'q'}y$$

PDA \longrightarrow CFL

In the computation from p' to q' , the stack is not empty, but it always has z sitting at the bottom.

Assignment Project Exam Help

The “substack” above z is empty at p' and q' .

The computation path from p' to q' starts and ends with a stack containing just z , with z on the bottom of every stack along the way.

<https://powcoder.com>

This is equivalent to starting and ending with an empty stack.

Add WeChat powcoder

We model this with the production

$$A_{pq} \longrightarrow xA_{p'q'}y$$

PDA \longrightarrow CFL

Also, for each state p , add the production

Assignment Project Exam Help
 $A_{pp} \longrightarrow \varepsilon$

Finally, add the production

<https://powcoder.com>
 $S \longrightarrow A_{st}$

where, as usual, the non-terminal S is the Start symbol.

This set of productions give a CFG for L .
Add WeChat powcoder

For formal proof (making good use of induction), see Sipser.

Some things to think about:

- ▶ $\text{CFG} \rightarrow \text{PDA}$:
 - ▶ What conditions would the CFG have to satisfy, so that the PDA we construct is *deterministic*?
 - ▶ If the PDA produced by this construction *only has the four states we started with* — so that the extra transitions we added are *all loops* — what can we say about the language we started with?
- ▶ $\text{CFG} \rightarrow \text{PDA} \rightarrow \text{CFG}$:
 - ▶ If you start with a CFG and then do the construction both ways to get another CFG, will it ever be the same as the CFG you started with?

Reading: Sipser, pp. 117–125