

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 2

Propositional Logic

<https://powcoder.com>

slides by Graham Farr

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

- ▶ Propositions
- ▶ Logical operations
- ▶ Tautologies, logical equivalence
- ▶ Disjunctive Normal Form
- ▶ Conjunctive Normal Form
- ▶ Representing logical statements

<https://powcoder.com>

Add WeChat powcoder

Propositions

Definition: A **proposition** is a statement which is either true or false.

Examples

$$1 + 1 = 2$$

The earth is flat.

It will rain tomorrow.

'Twas brillig, and the slithy toves
did gyre and gimble in the wabe.

From: Lewis Carroll, *Through the Looking Glass, and What Alice
Found There*, Macmillan, London, 1871.

Come and work for us!

This statement is false.

- a proposition which is **true**.
- a proposition which is **false**.
- a proposition.

— *not* a proposition.

— *not* a proposition.

— *not* a proposition.

For brevity, a proposition may be given a name, which has a **truth value**, True or False.
For example, let X be the proposition $1 + 1 = 2$. Then the truth value of X is True.

Assignment Project Exam Help

Not \neg (\sim , $-$, $=$)

And \wedge ($\&$)

Or \vee

Implies \Rightarrow (\rightarrow)

Equivalence \Leftrightarrow (\leftrightarrow)

<https://powcoder.com>

A **connective** is a binary logical operation. E.g.: \wedge , \vee , \Rightarrow , \Leftrightarrow .

Add WeChat powcoder

Negation

P : You have prepared for next week's tutorial.
 $\neg P$: You have not prepared for next week's tutorial.

Other notation: $\sim P$, \overline{P} , $-P$

Truth table:

P	$\neg P$
F	T
T	F

<https://powcoder.com>

Add WeChat powcoder

Conjunction

P Radhanath was a computer.
 Q Radhanath was a person.



$P \wedge Q$ Radhanath was a computer and a person.

Radhanath Sikdar (1813–1870)

http://news.bbc.co.uk/2/hi/south_asia/1113576.stm

Truth table:

P	Q	$P \wedge Q$
F	F	F
F	T	F
T	F	F
T	T	T

Add WeChat powcoder

Disjunction

P I will study FIT3155 Advanced Data Structures & Algorithms.

Q I will study MTH3170 Network Mathematics.

$P \vee Q$ I'll study FIT3155 *or* I'll study MTH3170.

I'll study *at least one of* FIT3155 and MTH3170.

Disjunction is sometimes called *inclusive OR*, and sometimes written as $+$.

Truth table:

P	Q	$P \vee Q$
F	F	F
F	T	T
T	F	T
T	T	T

Add WeChat powcoder

De Morgan's Laws

Assignment Project Exam Help

$$\neg(P \vee Q) = \neg P \wedge \neg Q$$
$$\neg(P \wedge Q) = \neg P \vee \neg Q$$

Can be proved using truth tables:

P	Q	$P \vee Q$	$\neg(P \vee Q)$	$\neg P$	$\neg Q$	$\neg P \wedge \neg Q$
F	F	F	T	T	T	T
F	T	T	F	T	F	F
T	F	T	F	F	T	F
T	T	T	F	F	F	F



Augustus De Morgan
(1806–1871)

https://mathshistory.st-andrews.ac.uk/Biographies/De_Morgan/

Add WeChat powcoder

Conditional

P Stars are visible.

Q The sun has set.

Assignment Project Exam Help

$P \Rightarrow Q$ If stars are visible then the sun has set.

Stars being visible implies the sun has set.

Stars are visible only if the sun has set.

Stars are visible is sufficient for the sun to have set.

$Q \Leftarrow P$ same as $P \Rightarrow Q$

Add WeChat powcoder

Also called *implication*.

Conditional

Truth table:

P	Q	$P \Rightarrow Q$
F	F	T
F	T	T
T	F	F
T	T	T



Grace Hopper (1906–1992)
<https://www.cs.vassar.edu/history/hopper>

P Grace is a COBOL expert.
 Q Grace can program.


$P \Rightarrow Q$ **If** Grace is a COBOL expert **then** she can program.

Biconditional


P The triangle is right-angled.

Q The side lengths satisfy


$$a^2 + b^2 = c^2$$



$$a^2 + b^2 < c^2$$



$$a^2 + b^2 = c^2$$



$$a^2 + b^2 > c^2$$

$P \Leftrightarrow Q$

The triangle is right-angled **if and only if**
 $a^2 + b^2 = c^2$.

The triangle being right-angled is a
necessary and sufficient condition
for $a^2 + b^2 = c^2$.

$Q \Leftrightarrow P$

$a^2 + b^2 = c^2$ is a
necessary and sufficient condition
for the triangle being right-angled.

Truth table:

P	Q	$P \Leftrightarrow Q$
F	F	T
F	T	F
T	F	F
T	T	T

Tautologies, logical equivalence

Definitions

A **tautology** is a statement that is always true.

In other words, the right-hand column of its truth table has every entry True.

Two statements P and Q are **logically equivalent** if their truth tables are identical.

In other words, $P \Leftrightarrow Q$ is a tautology.

Examples

$$\neg\neg P$$

is logically equivalent to

$$P$$

$$\neg(P \vee Q)$$

is logically equivalent to

$$\neg P \wedge \neg Q$$

$$\neg(P \wedge Q)$$

is logically equivalent to

$$\neg P \vee \neg Q$$

$$P \Rightarrow Q$$

is logically equivalent to

$$\neg P \vee Q$$

$$P \Leftrightarrow Q$$

is logically equivalent to

$$(P \Rightarrow Q) \wedge (P \Leftarrow Q)$$

and to

$$(\neg P \vee Q) \wedge (P \vee \neg Q)$$

These can all be proved using truth tables.

We usually denote logical equivalence by “ $=$ ”. So we write $\neg\neg P = P$, etc.


<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



George Boole (1815–1864)

<https://mathshistory.st-andrews.ac.uk/Biographies/Boole/>

Assignment Project Exam Help

$$P \wedge (Q \vee R) = (P \wedge Q) \vee (P \wedge R)$$

$$P \vee (Q \wedge R) = (P \vee Q) \wedge (P \vee R)$$

<https://powcoder.com>

Compare with ordinary algebra:

Add WeChat powcoder

but

$$p + (q \times r) \neq (p + q) \times (p + r)$$

Laws of Boolean algebra

$$\neg\neg P = P$$

$$\neg\text{True} = \text{False}$$

$$\neg\text{False} = \text{True}$$

Assignment Project Exam Help

$$(P \wedge Q) \wedge R = P \wedge (Q \wedge R)$$

$$(P \vee Q) \vee R = P \vee (Q \vee R)$$

$$P \wedge P = P$$

$$P \vee P = P$$

$$P \wedge \neg P = \text{False}$$

$$P \vee \neg P = \text{True}$$

$$P \wedge \text{True} = P$$

$$P \vee \text{False} = P$$

$$P \wedge \text{False} = \text{False}$$

$$P \vee \text{True} = \text{True}$$

Add WeChat powcoder

Distributive Laws

$$P \wedge (Q \vee R) = (P \wedge Q) \vee (P \wedge R)$$

$$P \vee (Q \wedge R) = (P \vee Q) \wedge (P \vee R)$$

De Morgan's Laws

$$\neg(P \vee Q) = \neg P \wedge \neg Q$$

$$\neg(P \wedge Q) = \neg P \vee \neg Q$$

Disjunctive Normal Form (DNF)

X	Y	P
F	F	T
F	T	T
T	F	F
T	T	T

$$\neg X \wedge \neg Y$$

$$\neg X \wedge Y$$

$$X \wedge Y$$

Assignment Project Exam Help

<https://powcoder.com>

$$P = \overbrace{(\neg X \wedge \neg Y)}^{\text{conjunction}} \vee \overbrace{(\neg X \wedge Y)}^{\text{conjunction}} \vee \overbrace{(X \wedge Y)}^{\text{conjunction}}$$

Add WeChat disjunction powcoder

Exercise: simplify this as much as possible, using Boolean algebra.

Disjunctive Normal Form (DNF)

X	Y	Z	P
F	F	F	T
F	F	T	F
F	T	F	T
F	T	T	F
T	F	F	F
T	F	T	T
T	T	F	T
T	T	T	F

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$P = (\neg X \wedge \neg Y \wedge \neg Z) \vee (\neg X \wedge Y \wedge \neg Z) \vee (X \wedge \neg Y \wedge Z) \vee (X \wedge Y \wedge \neg Z)$$

Disjunctive Normal Form (DNF)

$$P = (\neg X \wedge \neg Y \wedge Z) \vee (\neg X \wedge Y \wedge \neg Z) \vee (X \wedge \neg Y \wedge Z) \vee (X \wedge Y \wedge \neg Z)$$

- ▶ A **literal** is an appearance of a variable in which it is either unnegated or negated just once.
 - ▶ Example: there are 12 literals in the above expression.
- ▶ A logical expression is in **DNF** if it is a **dis**junction of **con**junctions of literals.
- ▶ Every logical expression is equivalent to one in DNF.
 - ▶ To see this: “just” use the truth table.
 - ▶ BUT this can be exponentially large (in # of variables).
- ▶ In effect, DNF enumerates all situations in which P is True.
- ▶ There is another Normal Form that is much more useful for us ...

Conjunctive Normal Form (CNF)

- ▶ A logical expression is in **CNF** if it is a **con**junction of **dis**junctions of literals.
 - ▶ E.g.:

Assignment Project Exam Help

$$\underbrace{(\neg P \vee Q) \wedge (P \vee \neg Q)}_{\text{conjunction}}$$

The diagram shows the expression $(\neg P \vee Q) \wedge (P \vee \neg Q)$. Above the first disjunction $(\neg P \vee Q)$ is a bracket labeled "disjunction". Above the second disjunction $(P \vee \neg Q)$ is a bracket labeled "disjunction". Below the entire expression is a bracket labeled "conjunction".

- ▶ Each disjunction of literals is called a **clause**.
- ▶ Every logical expression is equivalent to one in CNF.
- ▶ One way to see this:

Given P ,

find the DNF of its negation, $\neg P$,

then negate it

and use De Morgan's Laws.

- ▶ BUT it is usually *much faster*, and *much less error-prone*, to work directly from the stated conditions that P must satisfy.
- ▶ In this unit, CNF will be *much* more important than DNF.

Representing logical statements

Example:

You are planning a dinner party. Your guest list must have:

- ▶ at least one of: Harry, Ron, Hermione, Ginny

$$\text{Harry} \vee \text{Ron} \vee \text{Hermione} \vee \text{Ginny}$$

- ▶ Hagrid *only if* it also has Norberta

$$\text{Hagrid} \Rightarrow \text{Norberta} \quad \dots \text{can rewrite as:} \quad \neg \text{Hagrid} \vee \text{Norberta}$$

- ▶ none, or both, of Fred and George

$$\text{Fred} \Leftrightarrow \text{George} \quad \dots \text{can rewrite as:} \quad (\neg \text{Fred} \vee \text{George}) \wedge (\text{Fred} \vee \neg \text{George})$$

- ▶ no more than one of: Voldemort, Bellatrix, Dolores.

$$(\text{not both Voldemort \& Bellatrix}) \wedge (\text{not both Voldemort \& Dolores}) \wedge (\text{not both Bellatrix \& Dolores})$$

$$(\neg \text{Voldemort} \vee \neg \text{Bellatrix}) \wedge (\neg \text{Voldemort} \vee \neg \text{Dolores}) \wedge (\neg \text{Bellatrix} \vee \neg \text{Dolores})$$

Representing logical statements

$(\text{Harry} \vee \text{Ron} \vee \text{Hermione} \vee \text{Ginny})$
 $\wedge (\neg \text{Hagrid} \vee \neg \text{Norberta})$
 $\wedge (\neg \text{Fred} \vee \text{George}) \wedge (\text{Fred} \vee \neg \text{George})$
 $\wedge (\neg \text{Voldemort} \vee \neg \text{Bellatrix}) \wedge (\neg \text{Voldemort} \vee \neg \text{Dolores}) \wedge (\neg \text{Bellatrix} \vee \neg \text{Dolores})$

<https://powcoder.com>

This is now in CNF.

Challenge: how long would an equivalent DNF expression be?

Reading

See Sipser, pp. 14–15, and top paragraph of p. 302.