

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 19

Universal Turing Machines

<https://powcoder.com>

slides by Graham Farr

based in part on previous slides by David Albrecht

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Assignment Project Exam Help

- ▶ Tables for Turing Machines

- ▶ Encoding

- ▶ Decoding

- ▶ Definition of a Universal Turing Machine

- ▶ Algorithm for a Universal Turing Machine

- ▶ Existence of Universal Turing Machines

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Input Alphabet: $\{a,b\}$
- ▶ Tape Alphabet: $\{a,b,\#\}$
- ▶ Start State: numbered 1
- ▶ Accept State: numbered 2

<https://powcoder.com>

Add WeChat powcoder




<https://powcoder.com>

Add WeChat powcoder

From	To	Read	Write	Move
1	3	a	a	R
1	3	b	b	R
3	4	b	b	R
4	2	Δ	Δ	R

TM for $\{a^n b^n a^n : n \geq 0\}$



Table

From	To	Read	Write	Move
1	3	a	#	R
3	3	a	a	R
3	4	b	b	R
4	4	b	b	R
4	5	a	a	L
5	6	a	a	R
6	6	a	a	R
6	7	Δ	Δ	L
7	8	a	Δ	L
8	9	a	Δ	L
9	9	a	a	L
9	9	b	b	L
9	1	#	#	R
1	2	Δ	Δ	R

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Check whether there is a row with a 1 in the From column.

Check that there is no row with a 2 in the From column.

Check there are no two rows with the same numbers in the From and the same letter in the Read column.

<https://powcoder.com>
Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

State number	Code
-----------------	------

a	a
b	b

Letter	Code
--------	------

a	aa
b	ab

b	ab
Δ	ba

Δ	ba
#	bb

#	bb
---	----

Direction	Code
-----------	------

L	a
R	b

R	b
---	---

Coding the Table

From	To	Read	Write	Move	Code
1	3	a	#	R	abaaabaabbb
3	3	a	a	R	aaabaabaab
3	4	b	b	R	aaabaabaababb
4	4	b	b	R	aaabaaaabababb
4	5	a	a	L	aaaabaaaaabaaaaa
5	6	a	a	R	aaaaabaaaaababab
6	6	a	a	R	aaaaaabaabaaaaab
6	7	Δ	Δ	L	aaaaaabaabaaaaabbabaa
7	8	a	Δ	L	aaaaaabaabaaaaaabaabaa
8	9	a	Δ	L	aaaaaabaabaaaaaabaabaa
9	9	a	a	L	aaaaaaaaabaaaaaaaaabaaaaa
9	9	b	b	L	aaaaaaaaabaaaaaaaaabababa
9	1	#	#	R	aaaaaaaaababbbbbbb
1	2	Δ	Δ	R	abaabbabab

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Code Word Language (CWL)

The **Code-Word Language (CWL)** is the regular language defined by the regular expression

Assignment Project Exam Help

Words which encode a TM belong to CWL.

BUT: **Not** all words in CWL encode a TM.

<https://powcoder.com>

Quantifier practice:

Add WeChat powcoder

$\neg \forall w \in \text{CWL} \exists M : w \text{ encodes } M$

$\exists w \in \text{CWL} \neg \exists M : w \text{ encodes } M$

$\exists w \in \text{CWL} \forall M : \neg (w \text{ encodes } M)$

$\exists w \in \text{CWL} \forall M : w \text{ does not encode } M$

abaaabaaababbaababbaabababbaabababbaababab

Assignment Project Exam Help

From	To	Read	Write	Move
1	3	a	a	R
1	3	b	b	R
3	4	b	b	R
4	2	Δ	Δ	R

https://powcoder.com

Add WeChat powcoder

Algorithm

While there are unread letters

1. Read and count the next clump of a's, then read the b after it.
 - ▶ Interpret clump of a's as the state number, in unary, that this transition goes from.
2. Read and count the next clump of a's, then read the b after it.
 - ▶ Interpret clump of a's as the state number, in unary, that this transition goes to.
3. Read the next two letters.
 - ▶ Interpret it as the letter to be read for this transition.
4. Read the next two letters.
 - ▶ Interpret it as the letter to be written for this transition.
5. Read the next letter.
 - ▶ Interpret it as the direction for this transition.

Assignment Project Exam Help

Definition

A **Universal Turing Machine (UTM)** is a Turing Machine that takes, as input,


- ▶ an encoding of some Turing Machine M , together with
- ▶ a string x , to be used as input to M

and simulates the execution of M on x .

<https://powcoder.com>

Add WeChat powcoder

Example



<https://powcoder.com>

Suppose we want a UTM to simulate the execution of this TM on the string `bbbaa`.

Input to the UTM:

Turing Machine: `abaaabaaaabababababbbaaabaabaaaab`

Data: `bbbaa`

Input for UTM

input for the UTM

Assignment Project Exam Help

Turing Machine (encoded)

input for the
encoded TM

a	b	a	a	a	b	a	a	a	a	b	a	b	a	b	a	b	b	a	b	a	a	a	b	a	a	a	a	b	\$	b	b	b	a	a	Δ	Δ	Δ	...
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	----	---	---	---	---	---	---	---	---	-----

<https://powcoder.com>

Add WeChat powcoder

marks end of
TM encoding
and start of
its input

Algorithm for a UTM

1. Move rightwards to first letter of the encoded TM's input.
Read it. Mark it, so we can come back to it (e.g., $a \mapsto A$, $b \mapsto B$).
Remember it (in choice of state).
2. Move leftwards to first instruction.
3. If the next state in current instruction in encoded TM is the Accept state
Find (from current instruction) what to write and direction of next move.
Remember it (in choice of state).
Move rightwards back to current position in encoded TM's input.
Write the required letter, move in the required direction, and Accept.
else
Find (from current instruction) what to write and direction of next move.
Remember it (in choice of state).
Move rightwards back to current position in encoded TM's input.
Write the required letter, move in the required direction.
Read current letter in encoded TM's input. Mark it, so we can come back to it.
Remember it (in choice of state).
Move leftwards to find the next instruction (using remembered letter).

Exercise

Suppose:

- ▶ U is a UTM,
- ▶ T is a TM
- ▶ x is an input string for T , with $|x| = n$.
- ▶ When T is run on input x , it takes time t and visits at most s tape cells.

Using the algorithm outline of the previous slide, and the encoding scheme for TMs given in this lecture:

- ▶ Determine an upper bound for the time taken by U to simulate the running of T on input x .
- ▶ Give the bound in terms of t , s and n .

Assignment Project Exam Help

- ▶ theoretical model of one computer simulating another
- ▶ Stored-program computer
- ▶ von Neumann architecture

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Know how to encode a Turing Machine.
- ▶ Know how to decode Turing Machine representation.
- ▶ Know what a Universal Turing Machine is, and what it does.
- ▶ Understand why UTMs exist.

<https://powcoder.com>

Add WeChat powcoder