

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 17

The Pumping Lemma for Context-Free Languages

<https://powcoder.com>

slides by Graham Farr

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.


all languages

Assignment Project Exam Help

- ▶ Pumping Lemma for CFLs
- ▶ Proof
- ▶ application:
showing that some languages
are *not* context-free

<https://powcoder.com>

Add WeChat powcoder



Pumping Lemma for Regular Languages (paraphrased)

Recall:

If a Finite Automaton with N states

accepts

a sufficiently long string,
then the path taken by the string
in the FA

contains a repeated state.


This enables us to “pump” the string
by repeating one substring —
to generate an infinite family
of members of the language.

<https://powcoder.com>
Add WeChat powcoder


- # Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder




Nonterminal repetition in parse tree paths



$uvxyz$



uv^2xy^2z





uv^3xy^3z

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Nonterminal repetition in parse tree paths



<https://powcoder.com>

Add WeChat powcoder

$uvxyz$

uxz

Nonterminal repetition in parse tree paths

Nonterminals: S, E, T, F


In a parse tree:

If

length of a root-to-leaf path $>$ # nonterminals

then

some nonterminal appears twice on that path.



Nonterminal repetition in parse tree paths

How can we *ensure* that this happens?

How to guarantee that the parse tree for a *sufficiently long* string has a path with a repeated state?

Assignment Project Exam Help

Consider:

length of a path from root to leaf = # non-leaf nodes in that path.

<https://powcoder.com>

Each non-leaf node has a nonterminal symbol.

If

max root-to-leaf path length $>$ # nonterminal symbols in the grammar

then **some nonterminal symbol occurs twice on that path.**

How to guarantee that the parse tree for a *sufficiently long* string has a *sufficiently long* root-to-leaf path?

Nonterminal repetition in binary parse tree paths

Let's use *binary* parse trees

Binary parse tree:

$$2^{\text{max path length}} \geq \# \text{ leaves} = \text{word length}$$

If


$$\text{word length} > 2^{\# \text{ nonterminals}}$$

then

$$2^{\text{max path length}} > 2^{\# \text{ nonterminals}},$$

$$\therefore \text{max path length} > \# \text{ nonterminals}$$

and so there will be a repeated symbol
in a root-to-leaf path.



Nonterminal repetition in binary parse tree paths

Let's use *binary* parse trees, **from Chomsky Normal Form grammars!**

Binary **CNF** parse tree:

$$2^{\text{max path length} - 1} \geq \# \text{ leaves} = \text{word length}$$

If


$$\text{word length} > 2^{\# \text{ nonterminals} - 1}$$

then

$$2^{\text{max path length} - 1} > 2^{\# \text{ nonterminals} - 1},$$

$$\therefore \text{max path length} > \# \text{ nonterminals}$$

and so there will be a repeated symbol
in a root-to-leaf path.



Pumping Lemma for CFLs

Let L be any context-free language that has a CFG in CNF with k non-terminal symbols.

Then for every word $w \in L$ with $|w| > 2^{k-1}$ letters,

there exist strings u, v, x, y, z with $vy \neq \varepsilon$
(i.e., v, y not both ε)

such that

▶ $w = uvxyz$

▶ $|vxy| \leq 2^k$, and

▶ for all $i \geq 0$, $uv^i xy^i z \in L$,

i.e.,

$uxz, uvxyz, uvvxyyz, \dots, uv^n xy^n z, \dots \in L.$

Add WeChat powcoder

Symbolically:

$$\forall w \in L : |w| > 2^{k-1} \Rightarrow (\exists u, v, x, y, z : (w = uvxyz) \wedge (vy \neq \varepsilon) \wedge (|vxy| \leq 2^k) \\ \wedge (\forall i \geq 0 : uv^i xy^i z \in L))$$

Pumping Lemma for CFLs

Proof. (outline)

Take any word $w \in L$ with $|w| \geq 2^{k-1}$ letters.

Let T be a parse tree for w , using the CNF CFG for L .

By our earlier Observations on root-to-leaf paths in CNF parse trees, some root-to-leaf path P in T contains a repeated nonterminal symbol.

Among all pairs of nodes in P containing the same nonterminals, choose the pair q, r , with q above r , such that q is as far as possible down the path P . This ensures all nonterminals below q on P are distinct.
(Reason to be revealed later.)


Pumping Lemma for CFLs

Reading the letters of w from left to right, from the leaves of the tree, define:

- u be the letters of w to the left of the subtree T_q rooted at node q .
- v be the letters at the leaves of T_q that are to the left of the subtree T_r rooted at r .
- x be the letters at the leaves of T_r .
- y be the letters of T_q that are to the right of the subtree T_r .
- z be the remaining letters of w , i.e., those to the right of T_q .

<https://powcoder.com>

Add WeChat powcoder



We have.

- ▶ $w = uvxyz$ by construction.
- ▶ Since q, r are distinct nodes of the path P with q above r , the tree T_r is a proper subtree of T_q .
- ▶ Furthermore, since the grammar is in CNF, q has two children, and only one of them is above r , so T_q has some leaves that do not belong to T_r .
- ▶ Therefore $vy \neq \epsilon$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- ▶ By our choice of q and d , all nonterminals appearing below q on P are distinct.
- ▶ Since we have k nonterminals altogether, the subpath of P from q downwards has $\leq k + 2$ nodes (being q , then at most k nonterminals, then the leaf).
- ▶ Therefore it has length $\leq k + 1$.
Therefore T_q has $\leq 2^k$ leaves.
These leaves are the strings v, x, y in order.
- ▶ Therefore $|vxy| \leq 2^k$.

- # Assignment Project Exam Help
- ▶ Replacement of T_q by T_r gives a parse tree for u^2xz .
 - ▶ Replacement of T_r by T_q in T gives a parse tree for $uvvxyyz$.
 - ▶ The new copy of T_q contains a copy of T_r .
Replacing that copy of T_r by T_q gives a parse tree for $uvvvvxyyz$.
 - ▶ Any parse tree with a copy of T_r can be enlarged, to be a parse tree of a longer string, by replacing T_r by T_q .
 - ▶ These observations can be turned into a full formal proof by induction. □
- # Add WeChat powcoder

A Tale of Two Pumping Lemmas

If a Finite Automaton with N states accepts a sufficiently long string, then the path taken by the string in the FA contains a repeated state.

This enables us to “pump” the string — by repeating one substring — to generate an infinite family of members of the language.

If a Context-Free Grammar in CNF with k nonterminals generates a sufficiently long string, then some root-to-leaf path in the parse tree contains a repeated nonterminal.

This enables us to “pump” the string — by repeating two substrings — to generate an infinite family of members of the language.

Pumping Lemma for CFLs: application

Consequence

Using the Pumping Lemma for CFLs we can show there are non-context-free languages.

Method

Assume L is context-free.

Then it has a Context-Free Grammar in CNF.

Let k be the number of nonterminal symbols in this CFG.

Choose a suitable word $w \in L$, of length $> 2^{k-1}$.

Show that, for any u, v, x, y, z such that $w = uvxyz$ and $vy \neq \varepsilon$ and $|vxy| \leq 2^k \dots$

\dots there exists $i \geq 0$ s.t. $uv^ixy^iz \notin L$.

Contradiction.

Compare quantifiers above with those in the Pumping Lemma for CFLs.

Non-context-free languages

$$L := \{a^n b^n a^n : n \geq 0\} = \{\varepsilon, aba, aabbaa, aaabbbbaaa, \dots\}.$$

Theorem.

L is not context-free.

Proof. (by contradiction)

Assume that L is context-free. Then it has a CFG.

Then there is a CFG in Chomsky Normal Form that generates $L \setminus \{\varepsilon\}$.

Let $k = \#$ nonterminals in this CNF CFG.

Take $N > 2^{k-1}/3$.

Choose $w = a^N b a^N$.

Consider any u, v, x, y, z such that

- ▶ $vy \neq \varepsilon$,
- ▶ $|vxy| \leq 2^k$, and
- ▶ $w = uvxyz$.

Think: are $uxz, uvxyz, uvvxyyz, \dots, uv^i xy^i z, \dots$ all in L ?

Non-context-free languages

Case 1: v and y are each all a's, or all b's, or empty.

For example, 

Then uv^2xy^2z can no longer have three equal-length stretches of a's and b's, since:

- ▶ The two strings v, y must each lie entirely within one stretch, and there are three stretches, so one of these stretches is unaltered by pumping.
- ▶ But at least one of the other stretches is lengthened, because $v, y \neq \epsilon$.

So $uv^2xy^2z \notin L$.

Non-context-free languages

Case 2: Either v or y contains ab .

For example: $aaa \dots aabbb \dots bbaa \dots aa$

Assignment Project Exam Help

Then $uvvxy^2z$ has two occurrences of ab .

This cannot happen for strings in L . So $uv^2xy^2z \notin L$.

Case 3: Either v or y contains ba .

<https://powcoder.com>

For example: $aaa \dots aabbb \dots bbaa \dots aa$

Add WeChat powcoder

Similar argument to Case 2.

In every possible case, we have found an i such that $uv^ixy^iz \notin L$.

This violates the conclusion of the Pumping Lemma for CFLs.

Contradiction. \square

all languages

Assignment Project Exam Help

<https://powcoder.com>

Reading: Sipser, pp. 125–129.

Add WeChat powcoder

