

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 7

Finite Automata

<https://powcoder.com>

slides by Graham Farr

based in part on previous slides by David Albrecht

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Assignment Project Exam Help

- ▶ Definition
- ▶ How they are used to define languages
- ▶ Representations
- ▶ Complement Languages
- ▶ Comparison with Regular Expressions

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

- ▶ Sometimes known as a **Deterministic Finite Automaton (DFA)**.
- ▶ Used for determining whether a word does or does not belong to a Regular Language.
- ▶ Used for defining a Regular Language.
- ▶ Used in Lexical Analysers.

<https://powcoder.com>

Add WeChat powcoder




- ▶ **Assignment Project Exam Help**
- ▶ A finite set of **states**
 - ▶ One called the Start State
 - ▶ Some (maybe none) called Final States
- ▶ An alphabet of possible input letters
- ▶ A finite set of **transitions**
 - ▶ that tell, for each state and each letter in the alphabet, which state to go to next.
 - ▶ There is a unique transition from any state for each letter in the alphabet.

<https://powcoder.com>

Add WeChat powcoder

Finite automaton: representations



		a	b
Start	1	1	2
	2	3	3
Final	3	3	2

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Every string traces a unique path in the automaton, starting from the Start State and following the transitions, letter by letter.

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

		a	b
Start	1	1	2
	2	3	3
Final	3	3	2

Add WeChat powcoder

Algorithm 1: Execution of a Finite Automaton

Input: a string

Begin at the Start State.

while *there is another input letter* **do**

 | Read the next letter of the input string.

 | Move along the directed edge labelled by this letter.

if *you're in a Final State* **then**

 | Accept input string.

else

 | Reject input string.

Assignment Project Exam Help

Every string traces a unique path in the automaton, starting from the Start State and following the transitions, letter by letter.

Definitions

A string is **accepted** by a FA if its path ends on a Final State.


Otherwise the string is **rejected**.

The **language recognised** by a FA is the set of all strings it accepts.

We say the FA **recognises** the language or **accepts** the language.

<https://powcoder.com>

Add WeChat powcoder




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

		a	b
Start	1	1	2
	2	3	3
Final	3	3	2



		a	b
Start	1	2	3
	2	4	3
	3	2	5
Final	4	4	5
Final	5	4	5

Assignment Project Exam Help

- ▶ All words accepted.
- ▶ No words accepted.
- ▶ Only the empty word accepted.
- ▶ Only non-empty words accepted.
- ▶ A single word accepted.

<https://powcoder.com>

Add WeChat powcoder

Complements

If L is a language over an alphabet, then its **complement** \bar{L} is the set of words over the alphabet that are not in L .

The complement of L is sometimes denoted by L' or L^c .

Assignment Project Exam Help

Examples

$$\bar{\emptyset} = \Sigma^*$$

<https://powcoder.com>


$$\bar{\Sigma^*} = \emptyset$$

$$\overline{\{\text{words of } \leq 3 \text{ letters}\}} = \{\text{words of } \geq 4 \text{ letters}\}$$

EVEN-EVEN $:=$ {strings that contain an **even** number of a's **and** an **even** number of b's}
 $=$ { ϵ , aa, bb, aaaa, aabb, abab, abba, baab, ... }.

$\overline{\text{EVEN-EVEN}}$ $:=$ {strings which contain an **odd** number of a's **or** an **odd** number of b's}
 $=$ {a, b, ab, ba, aaa, aab, aba, abb, baa, ... }

EVEN-EVEN



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Complement Finite Automaton (FA)


Suppose some FA accepts the language L .

Change all the final states in this FA to non-final states,
and all the non-final states to final states.

This new FA now accepts all the strings not accepted by the original FA
(i.e., all the words in \bar{L}),
and rejects all the words that the original accepted
(i.e., the words in L).

So the new FA accepts \bar{L} .

EVEN-EVEN



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Comparison with Regular Expressions

It is (usually) easier

than to write down a **regular expression** that defines a language
to design a **FA** to accept this language.

It is easier

than to check whether a given string is accepted by a **FA**
to see whether it matches a **regular expression**.

It is easier

than to find complements using a **FA**
by using a **regular expression**.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Some Generalizations of Finite Automata

This week:

- ▶ It is *not* required that, for every state and letter, there is a *unique* transition.
- ▶ It can change state *without* reading a letter.
- ▶ It can read *more than one letter* at a time.

Next week:

<https://powcoder.com>

- ▶ It can read strings which match *regular expressions*, not just single letters.

Later:

Add WeChat powcoder

- ▶ Each transition can produce *output letters* as well as changing state. (*transducer*)
- ▶ Transitions can *read and write* letters from some kind of *memory*.
- ▶ For a given state and letter, the next state is chosen *probabilistically*.

Nondeterministic Finite Automaton (NFA)

NFA are defined like a Finite Automaton (FA) except for transitions.

Transitions

- ▶ For some states and letters there is a transition.
- ▶ The labels may include the empty word ϵ .

So for a given letter and state there may be:


- ▶ No transition
- ▶ More than one transition

For a given string, the path it takes ...


- ▶ might not exist
- ▶ might not be unique

aba


FA




NFA



$ab \cup abb \cup baa$



Is abbbabbbabba accepted?




Assignment Project Exam Help

- ▶ If there is ~~no~~ transition for the current letter and state the machine crashes.
- ▶ Paths from the Start State to a Final State for a given input:
 - ▶ One
 - ▶ None
 - ▶ Several (Nondeterministic)
- ▶ **Accept** a string if there is **at least one** path from the Start State to a Final State.
- ▶ **Reject** a string if there are ~~no~~ paths from the Start State to a Final State.

<https://powcoder.com>

Add WeChat powcoder

$a(aa \cup bb)^*b$



Finite Automata (FA)

- ▶ Definition. How to use them.
- ▶ How to construct a Finite Automaton to accept a language.

Complement Languages

- ▶ What they are. Designing FA to accept them.

Nondeterministic Finite Automata (NFA)

- ▶ Definition. How to use them.
- ▶ How to construct a Nondeterministic Finite Automaton to accept a language.

Reading: Sipser Ch 1.