

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 13

(A) Regular Grammars,
(B) Pushdown Automata
<https://powcoder.com>

Add WeChat: [powcoder](https://powcoder.com)
slides by Graham Farr
based in part on previous slides by David Albrecht

COMMONWEALTH OF AUSTRALIA
Copyright Regulations 1969
Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Assignment Project Exam Help

- ▶ $\{\text{Regular Languages}\} \subseteq \{\text{CFLs}\}$
- ▶ Pushdown Automaton (PDA)
- ▶ Constructing PDA to accept a Regular Grammar

<https://powcoder.com>

Add WeChat powcoder

all languages

Assignment Project Exam Help
Is every Regular Language
a Context-Free Language?

<https://powcoder.com>

Add WeChat powcoder

regular
languages

CFLs

?

?


NFA to CFG

Input: an NFA

1. Name all the states in the NFA by a symbol.
 - Call the Start State S .
2. For each ordered pair of states X, Y linked by an arc labelled z , create production rule $X \rightarrow zY$.
3. For each Final State X , create production rule $X \rightarrow \epsilon$.

Output: the CFG consisting of

- terminals: the alphabet of the NFA;
- non-terminals: the symbols representing the states of the NFA;
- all the production rules we have created.




$X \rightarrow zY$

$X \rightarrow zX$

$X \rightarrow Y$

$X \rightarrow \epsilon$

NFA to CFG: Example



$S \rightarrow aS$

$S \rightarrow bX$

$S \rightarrow bY$

$X \rightarrow bY$

$Y \rightarrow aY$

$X \rightarrow \epsilon$

$Y \rightarrow \epsilon$

Add WeChat powcoder

Assignment Project Exam Help

Definitions

Semiwords are of the form:

terminal terminal . . . terminal Nonterminal

A CFG is called a **Regular Grammar** if all its production rules are in one of the following forms:

Nonterminal \rightarrow semiword

or

Nonterminal \rightarrow string of terminals

<https://powcoder.com>

Add WeChat powcoder

Theorem.

Every Regular Language can be generated by a Regular Grammar.

Proof idea:

A regular language is recognised by some NFA


Observe that our construction $NFA \rightarrow CFG$ produces a regular grammar. \square

Theorem.

Every Regular Grammar generates a Regular Language.

Proof: Exercise.

all languages



Assignment Project Exam Help

Is there a state machine for Context Free Languages?

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ A Nondeterministic Finite Automaton (NFA) with a **Stack**.


- ▶ Can be used to represent Context Free Languages

- ▶ Many parsers use a Pushdown Automaton

- ▶ ... including the parsers generated by some compiler-compilers.

<https://powcoder.com>
Add WeChat powcoder

Pushdown Automaton (PDA)



Assignment Project Exam Help

The Stack

- ▶ storage for letters
 - ▶ serves as ϵ -memory
- ▶ two operations:
 - ▶ **Push**: puts a letter on the top of the stack
 - ▶ **Pop**: takes a letter off the top of the stack.

<https://powcoder.com>

Add WeChat powcoder

Pushdown Automaton (PDA)

Transitions

Assignment Project Exam Help

$$x, y \longrightarrow z$$

which means when the machine is reading x , if there is a y on top of the stack, it is replaced by z .

<https://powcoder.com>


► If x is ε then no letter is read from the tape.

► If y is ε then no letter is popped from the stack.

Add WeChat powcoder

► If z is ε then no letter is pushed onto the stack.

Pushdown Automaton (PDA)



Pushdown Automaton (PDA)

A **Pushdown Automaton** consists of:

- ▶ an **input alphabet**: the set of possible input letters.
- ▶ a **stack alphabet**: the set of possible stack letters.
- ▶ a stack
- ▶ a finite set of states
 - ▶ One called the **Start State**
 - ▶ Some (maybe none) called **Final States**
- ▶ A set of transitions between states

$x, y \rightarrow z$

which means when the machine is reading x , if there is a y on top of the stack, it is replaced by z .

Assignment Project Exam Help

Definitions

A string is **accepted** by a PDA if there exists at least one path through the PDA for this string that ends in a Final State.

A string is **rejected** by a PDA if for all paths through the PDA for this string, the PDA either crashes or ends in a non-Final State.

The set of strings accepted by the PDA is called the **language accepted** by the PDA.

Assignment Project Exam Help

$$\text{HALF-AND-HALF} := \{a^n b^n : n \geq 0\}$$

$$= \{\varepsilon, ab, aabb, aaabbb, \dots\}$$

<https://powcoder.com>


Using the Pumping Lemma we showed that this language was non-regular.


Consider:

Add WeChat powcoder


So it is a Context-Free Language.

PDA for HALF-AND-HALF





PDA for PARENTHESES



Regular Languages \subseteq languages accepted by PDAs

Assignment Project Exam Help

Exercise:

- What do you have to do to restrict a PDA so that it is just an NFA?

An NFA is a special case of a PDA.

So

$\{\text{regular languages}\} \subseteq \{\text{languages recognised by a PDA}\}$

Add WeChat powcoder


Regular Languages \subseteq languages accepted by PDAs

$$S \rightarrow aS \mid bY \mid bX$$
$$X \rightarrow bY$$
$$Y \rightarrow aY \mid \epsilon$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Things to think about:

- ▶ Which of the PDAs we've met are *deterministic*?
- ▶ Suppose we plot **stack height** against **time** for our PDA for the Dyck language. What would it look like?
- ▶ How can we construct, from a given CFG, a PDA for the same language?
- ▶ How can we construct, from a given PDA, a CFG for the same language?

<https://powcoder.com>
Add WeChat powcoder

Reading: Sipser, Section 2.2, pp. 111–116.