

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 23

Recursively enumerable languages

<https://powcoder.com>

slides by Graham Farr

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Assignment Project Exam Help

- ▶ recursively enumerable (r.e.) languages
- ▶ relationship with decidability
- ▶ enumerators
- ▶ non-r.e. languages

<https://powcoder.com>

Add WeChat powcoder

Recall Assignment Project Exam Help

A language L is decidable if and only if there exists a Turing machine T such that

<https://powcoder.com>

$$\text{Accept}(T) = L$$

$$\text{Reject}(T) = \bar{L}$$

$$\text{Loop}(T) = \emptyset.$$

Add WeChat powcoder

Reminder: $\bar{L} = \Sigma^* \setminus L$, where Σ is the alphabet.

Assignment Project Exam Help

A language L is **recursively enumerable** if there exists a Turing machine T such that

$\text{Accept}(T) = L$
<https://powcoder.com>

Strings outside L may be *rejected*, or may make T *loop forever*.

Add WeChat powcoder

Recursively enumerable: synonyms

Assignment Project Exam Help

= recursively enumerable (r.e.)

= computably enumerable

= partially decidable

<https://powcoder.com>

= Turing recognizable (used in Sipser)

= type 0 (in Chomsky hierarchy)

Add WeChat powcoder

= *computable*

...but risk of confusion, as “computable” is sometimes used for “decidable”.

Decidable versus r.e.

Every decidable language is recursively enumerable.

Assignment Project Exam Help

Is every recursively enumerable language decidable?

Consider:

<https://powcoder.com>

$HALT = \{ \langle T \rangle : T \text{ halts, if input is } T \}$

This is the language corresponding to the Halting Problem.

We know it's not decidable.

Add WeChat powcoder

Is it recursively enumerable?

Decidable versus r.e.

Let M be a Turing machine which takes, as input, a Turing machine T and

- ▶ simulates what happens when T is run with *itself* as its input.
- ▶ If T stops (in any state), M accepts.

Here, M could be obtained by modifying a UTM.

Accept(M) = HALT

Reject(M) = \perp

Loop(M) = $\overline{\text{HALT}}$

Decidable versus r.e.

Assignment Project Exam Help

So HALT is recursively enumerable.

So some recursively enumerable languages are not decidable.

<https://powcoder.com>

Consider the list of undecidable languages given in Lecture 22.

Which ones are recursively enumerable?

Add WeChat powcoder

Decidable versus r.e.

Theorem.

A language is decidable if and only if both it and its complement are r.e.

Proof.

(\Rightarrow)

Let L be any decidable language.

We have seen that every decidable language is r.e. So L is r.e.

Now, the complement of a decidable language is also decidable.

(See Lecture 20, comments on closure properties of the class of decidable languages.)

So \bar{L} is also decidable, and therefore also r.e.

So L and \bar{L} are both r.e.

Decidable versus r.e.

(\Longleftarrow)

Let L be any language such that both L and \bar{L} are both r.e.

Since they are each r.e., there exist Turing machines M_1 and M_2 such that

$$\text{Accept}(M_1) = L$$

$$\text{Accept}(M_2) = \bar{L}$$

Note, each of these TMs might *loop forever* for inputs they don't accept.

Construct a new Turing machine M that simulates both M_1 and M_2 :

Input: x

Repeatedly:

Do one step of M_1 . If it **accepts**, then Accept.

Do one step of M_2 . If it **accepts**, then Reject.

Decidable versus r.e.

M' is a decider:

- ▶ every string belongs to either L or \bar{L} ,
- ▶ therefore is accepted by either M_1 or M_2 ,
- ▶ therefore will eventually be either accepted or rejected by M' .

Furthermore, M' accepts x if and only if M_1 accepts x .

So M' is a decider for L .

So L is decidable.



A non-r.e. language

Is every language recursively enumerable?

Consider:

$\text{HALT} = \{ \langle T \rangle : T \text{ loops forever if input is } \langle T \rangle \}$

Assume $\overline{\text{HALT}}$ is r.e.

We already know that HALT is r.e.

So, both HALT and its complement are r.e.

Therefore, by the previous theorem, HALT is decidable.

Contradiction!

Therefore $\overline{\text{HALT}}$ is not r.e.

Definition

An **enumerator** is a Turing machine which outputs a sequence of strings.

This can be a finite or infinite sequence.

If it's infinite, then the enumerator will never halt.

It never accepts or rejects; it just keeps outputting strings, one after another.

- ▶ If the sequence is finite, then the enumerator may stop once it has finished outputting. But the state it enters doesn't matter.

Definition

Assignment Project Exam Help

A language L is **enumerated** by an enumerator M if

$$L = \{\text{all strings in the sequence outputted by } M\}$$

<https://powcoder.com>

Members of L may be outputted in any order by M , and repetition is allowed.

Theorem

Add WeChat powcoder

A language is recursively enumerable if and only if it is enumerated by some enumerator.

Enumerators and r.e. languages

Theorem

A language is recursively enumerable if and only if it is enumerated by some enumerator.

Proof.

(\Leftarrow)

Let L be a language, and let M be an enumerator for it.

Construct a Turing machine M' as follows:

Input: a string x

Simulate M , and for each string y it generates:

Test if $x = y$. If so, accept; otherwise, continue.

A string x is accepted by M' if and only if it is in L .

So $\text{Accept}(M') = L$. So L is r.e.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Enumerators and r.e. languages

(\implies) Let L be r.e. Then there is a TM M such that $\text{Accept}(M) = L$. Take all strings in order:
 $\epsilon, a, b, aa, ab, ba, bb, aaa, aab, aba, \dots$

Simulate the execution of M on each of these strings, in parallel.

As soon as any of them stops and accepts its string,
we pause our simulation, output that string, and then resume the simulation.

CAREFUL: Add WeChat powcoder

Infinitely many executions to simulate, but we only have finite time!
How do we schedule all these simulations?

Denote the strings by $x_1, x_2, \dots, x_i, \dots$

Algorithm:

For each $k = 1, 2, \dots$

For each $i = 1, \dots, k$:

Simulate the next step of the execution of M on x_i
(provided that execution hasn't already stopped).

If this makes M accept, then

output x_i and skip in all further iterations

else if this makes M reject, then

output nothing, and skip i in all further iterations.

This algorithm can be implemented by a Turing machine.
Any string accepted by M will eventually be outputted.

So this is an enumerator for L . □

<https://powcoder.com>

This result explains the term “recursively enumerable” (and “computably enumerable”).

It also explains why r.e. languages are sometimes called *computable*, since there is a computer that can *compute* all its members (i.e., can generate them all).

Exercises

Theorem.

A language L is r.e. if and only if there is a decidable two-argument predicate P such that

$$x \in L \iff \exists y : P(x, y).$$

<https://powcoder.com>

This P is a *verifier*:

if you are given y then you can use P to *verify* that x is in L (if it is).

But it may be hard to find such a y .

Add WeChat powcoder


Theorem.


If $K \leq_m L$ and L is r.e. then K is r.e.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





- ▶ definition of recursively enumerable languages
- ▶ relationship between decidability and recursive enumerability
- ▶ enumerators and their relationship with r.e. languages
- ▶ a language that is r.e. but not decidable, with proof
- ▶ a language that is not r.e., with proof

Reading: Sipser, pp. 170, 209–211.

Preparation: Sipser, pp. 275–286.