

FIT2014 Theory of Computation

# Assignment Project Exam Help

Lecture 10

Simplifying Finite Automata, and Lexical Analysis

<https://powcoder.com>

slides by Graham Farr

based in part on previous slides by David Albrecht

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University  
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Assignment Project Exam Help

- ▶ Simplifying Finite Automata
- ▶ Implementing Finite Automata
- ▶ Lexical Analyzer
- ▶ Tokens and lexemes

<https://powcoder.com>

Add WeChat powcoder

## Matching a Regular Expression


Write a program which reads in a character string, over alphabet  $\{a,b\}$ , one character at a time and identifies whether or not the string matches the following regular expression.

$(a \cup bb \cup baa^*b)^* baa^*$   
<https://powcoder.com>

1. Convert regular expression to NFA.
2. Convert NFA to DFA
3. **Simplify DFA.**

Add WeChat powcoder

NFA



# Assignment Project Exam Help

		a	b
Start	{1,2,8}	{2,8}	{3,4,9}
	{2,8}	{2,8}	{3,4,9}
	{3,4,9}	{5,6,7,10,11,12}	{2,8}
Final	{5,6,7,10,11,12}	{6,7,11,12}	{2,8}
Final	{6,7,11,12}	{6,7,11,12}	{2,8}

Add WeChat powcoder

<https://powcoder.com>

A **Final State** and a **non-Final State** are *fundamentally different*.

They *cannot be combined*.

So: **Assignment Project Exam Help**

- ▶ Give all **Final States** one colour.
- ▶ Give all **non-Final States** a *different* colour.

**<https://powcoder.com>**

*Different colours  $\implies$  different states.*

- ▶ They cannot be combined.

**Add WeChat powcoder**

*Same colours  $\nRightarrow$  same states.*

- ▶ The states *may or may not* be combined.
- ▶ We have not yet ruled out combining them.

# Assignment Project Exam Help

		a	b
Start	$\{1,2,8\}$	$\{2,8\}$	$\{3,4,9\}$
	$\{2,8\}$	$\{2,8\}$	$\{3,4,9\}$
	$\{3,4,9\}$	$\{5,6,7,10,11,12\}$	$\{2,8\}$
Final	$\{5,6,7,10,11,12\}$	$\{6,7,11,12\}$	$\{2,8\}$
Final	$\{6,7,11,12\}$	$\{6,7,11,12\}$	$\{2,8\}$

Add WeChat powcoder


# Assignment Project Exam Help

		a	b
Start	$\{1,2,8\}$	$\{2,8\}$	$\{3,4,9\}$
	$\{2,8\}$	$\{2,8\}$	$\{3,4,9\}$
	$\{3,4,9\}$	$\{5,6,7,10,11,12\}$	$\{2,8\}$
Final	$\{5,6,7,10,11,12\}$	$\{6,7,11,12\}$	$\{2,8\}$
Final	$\{6,7,11,12\}$	$\{6,7,11,12\}$	$\{2,8\}$

Add WeChat powcoder



## Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder

## Minimum DFA

---

**Algorithm:** FA simplification

---

**Input:** a FA

Colour all Final States with one colour, and all non-Final States with a different colour.  
**repeat**

**for** *each colour used so far* **do**

        Consider all states with that colour.

**if** *their rows do not have the same pattern of colours* **then**

*/\*\* States with different colour patterns along their rows must get different colours. So ... \*/*

            Give each different row pattern a different colour, using new colours.

*/\*\* Each set of states having the same row pattern gets the colour for that row pattern. \*/*

**until** *no new colour has been added in this iteration;*

Give each colour a unique number, and use these numbers to form the transition table.

**Output:** an equivalent FA with fewest states

---

# Assignment Project Exam Help

There are algorithms that can take a regular expression and produce a minimum state DFA without constructing a NFA.

<https://powcoder.com>

There are algorithms that produce fast and more compact representations of a DFA transition table than the straightforward two-dimensional table.

Add WeChat powcoder

# Assignment Project Exam Help

Once we have a Finite Automaton for a regular expression,  
we can write a program for it.

<https://powcoder.com>

Add WeChat powcoder

---

**Algorithm:** detecting strings accepted by an FA given by a table.

---

**Input:** a string

currentState := 1;

table = table with rows (1,2), (3,1), (3,1);

nextLetter := next character of input;

**while** nextLetter exists **do**

**switch** nextLetter **do**

**case** 'a' **do**

            currentState := table[currentState][0];

**break**;

**case** 'b' **do**

            currentState := table[currentState][1];

**break**;

    nextLetter := next character of input;

**if** currentState == 3 **then** print "Match"; **else** print "No Match";

---

## Application: Lexical Analysis

Many situations require text to be divided into substrings that match various *patterns*.

Calculator:  $\exp(\sqrt{-1}) * 3.14159265) + 1$

Programming languages:

```
read(n); sum := 0; i := 1; while(1 <= n) {sum += 1.0/i; i++} write(sum).
```

Personnel records:

```
//Employer:  Harvard College Observatory.// Annie Jump Cannon,  
11/12/1863.  Williamina Paton Stevens Fleming, 15/5/1857.  Henrietta  
Swan Leavitt 4/7/1868.  Edward Charles Pickering, 19/7/1846.
```

## Application: Lexical Analysis

Many situations require text to be divided into substrings that match various *patterns*.

Calculator:

`exp ( sqrt ( (-1) * 3.14159265 ) + 1`

Programming languages:

```
read ( n ); sum := 0; i := 1;
while ( i <= n ) { sum += 1.0 / i; i++; } write ( sum );
```

Personnel records:

```
//Employer: Harvard College Observatory.// Annie Jump Cannon ,
11/12/1863 . Williamina Paton Stevens Fleming , 15/5/1857 .
Henrietta Swan Leavitt , 4/7/1868 . Edward Charles Pickering ,
19/7/1846 .
```

A **pattern** is specified by a regular expression.

A **token** is a name of a pattern.

- ▶ It may also have an attribute value associated with it.

A **lexeme** is a sequence of characters that matches the pattern corresponding to a token.

So a pattern describes the form that the lexemes of a token may take.



# Assignment Project Exam Help

A lexical analyzer:

- ▶ reads the input one character at a time, and
- ▶ splits the input up into lexemes with their associated tokens,
- ▶ where each token corresponds to a specific regular language.
- ▶ It outputs a sequence of tokens  
(along with any attribute values that any tokens have).
- ▶ It is implemented using a Finite Automaton.

<https://powcoder.com>

Add WeChat powcoder


# Assignment Project Exam Help

Write a program which reads in a character string, over alphabet  $\{a,b\}$ , one character at a time and identifies whether or not the string matches one the following regular expressions, and which one.

<https://powcoder.com>

a, abb,  $a^*bb^*$

Add WeChat powcoder



Convert to FA, giving:

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

	a	b
Start	{1,2,4,8}	{3,5,8} {9}
Final a	{3,5,8}	{8} {6,9}
Final a*bb*	{9}	{9}
Final a	{8}	{9}
Final a*bb*	{6,9}	{7,9}
Final abb	{7,9}	{9}
	{9}	{9}

## Conventions

Often it is possible to split a sequence of characters up into tokens in more than one way.

- ▶ Consider abbbb
- ▶ **Convention:** Match the largest possible lexeme at each stage.

Often a sequence of characters can match more than one token.

- ▶ Consider abb
- ▶ **Convention:** If the lexemes are the same length, choose the first token that is listed.

# Assignment Project Exam Help

- ▶ Know how to find the DFA with the minimum number of states
- ▶ Know how to implement a finite automaton
- ▶ Understand what a lexical analyzer does.

<https://powcoder.com>

Add WeChat powcoder