

FIT2014 Theory of Computation

# Assignment Project Exam Help

Lecture 6

Regular Expressions

<https://powcoder.com>

slides by Graham Farr

based in part on previous slides by David Albrecht

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University  
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Assignment Project Exam Help

- ▶ Some Problems
- ▶ Applications of Regular Expressions
- ▶ Regular Expressions
- ▶ Regular Languages

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

- ▶ Find all the files which contain old subject course codes.
- ▶ Find all the e-mail addresses in a set of mail files.
- ▶ Change the way comments in programs are formatted in your web pages.
- ▶ Using web server access files, record how many times each page is visited, and how many times each link is used.

<https://powcoder.com>  
Add WeChat powcoder

# Assignment Project Exam Help

- ▶ Useful way to describe simple patterns.
- ▶ Used in several programs:
- ▶ Editors: vi, emacs
- ▶ Filters: egrep, sed, gawk
- ▶ Programming languages: JFlex, CUP, Perl

<https://powcoder.com>

Add WeChat powcoder

egrep **Assignment Project Exam Help**  
▶ A program which searches a file for a pattern described by a regular expression.

sed **<https://powcoder.com>**  
▶ A program which enables stream editing of files.

awk, nawk, gawk **Add WeChat powcoder**  
▶ Programming languages which enable text manipulation.

JFlex, flex, lex

# Assignment Project Exam Help

- ▶ Languages used to generate lexical analysers.

CUP, bison, yacc

# <https://powcoder.com>

- ▶ Languages used to generate compilers.

Perl

# Add WeChat powcoder

- ▶ A powerful scripting language, developed in the 1980s by Larry Wall.

## Regular Expressions for Small Languages

The empty language

$\emptyset$

Language  $\{\epsilon\}$  consisting only of the empty word

$\epsilon$

Language  $\{w\}$  consisting only of the single word  $w$

$w$

E.g.:

the language  $\{abbab\}$

$abbab$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Alternatives, Grouping

### Alternatives

are indicated by  $\cup$ .

E.g.:

$1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9$

is a regular expression for:

$\{1, 2, 3, 4, 5, 6, 7, 8, 9\}$

### Grouping

is indicated by  $( )$ .

E.g.:

$(ab \cup ba)(c \cup g)$

is a regular expression for:

$\{abe, abg, bae, bag\}$



consist of finite number of words.

E.g.:

$\{abaaba, abbbbba, abbaba\}$

Regular Expression:

$abaaba \cup abbbbba \cup abbaba$

... or:

$ab(aa \cup bb \cup ba)ba$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Matching an expression *zero or more times* is indicated by  $*$

# Assignment Project Exam Help

For example:

$a^*$  represents  $\{\epsilon, a, aa, aaa, aaaa, \dots\}$

$(ab)^*$  represents  $\{\epsilon, ab, abab, ababab, \dots\}$

$ab^*$  represent  $\{a, ab, abb, abbb, abbbb, \dots\}$

Note:  $ab^* \neq (ab)^*$

# Assignment Project Exam Help

$$(aa \cup bb)^* = (aa \cup bb)^0 \cup (aa \cup bb)^1 \cup (aa \cup bb)^2 \cup \dots$$
$$= \epsilon \cup (aa \cup bb) \cup (aa \cup bb)(aa \cup bb) \cup \dots$$

<https://powcoder.com>

represents:

[Add WeChat powcoder](#)

$$\{ \epsilon, aa, bb, aaaa, aabb, bbaa, bbbb, aaaaaa, aaaaab, aaabba, \dots \}$$

Assignment Project Exam Help


$(a \cup \varepsilon)b^*$

$(a \cup \varepsilon)$

$b^*$

<https://powcoder.com>

Add WeChat powcoder



## Definition

1.  $\emptyset$  and  $\varepsilon$  are regular expressions

2. All letters in the alphabet are regular expressions.

3. If  $R$  and  $S$  are regular expressions, then so are:

(i)  $(R)$

(ii)  $RS$

(iii)  $R \cup S$

(iv)  $R^*$

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

A language which can be described by a *regular expression* is called a **regular language**.

<https://powcoder.com>

If a word belongs to the language described by a regular expression, then we say it is **matched** by the regular expression.

Add WeChat powcoder

## Example: EVEN-EVEN

Recall **Assignment Project Exam Help**

EVEN-EVEN = { All strings in which a and b each occur an *even* number of times }  
= {  $\epsilon$ , aa, bb, aaaa, aabb, abab, abba, ... }.

<https://powcoder.com>

Regular Expression:

**Add WeChat powcoder**  
 $((aa \cup bb \cup (ab \cup ba)(aa \cup bb)^*(ab \cup ba))^*)$

## Things to think about ...

Is the set of all English words (in some standard dictionary) a regular language?

Is DOUBLEWORD (see Lecture 1) a regular language?

Is PALINDROME a regular language?

Is the set of all grammatical English sentences a regular language?

How would you determine, for a given string and regular expression, whether the string matches the regular expression?



## Example: Floating Point Number

# Assignment Project Exam Help

A floating point number has one or more digits, which may begin with a minus sign (—), and which may contain a decimal point.

E.g.,

<https://powcoder.com>

0   1.2   — 3   — 4.675   002   023.50

## Add WeChat powcoder

## Sequence of Digits

One Digit

$0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9$

Two Digits

$(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)$

Three Digits

$(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)$

One or more Digits

$(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)(0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)^*$

## Sequences of Digits

Digit **Assignment Project Exam Help**  
 $D = (0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9)$

Two Digits

$DD$  or  $D^2$   
**<https://powcoder.com>**

Three Digits

$DDD$  or  $D^3$

One or more Digits

**Add WeChat powcoder**  
 $DD^*$

# Numbers

One Digit

$$D = \{0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9\}$$

Nonnegative Integers

$$N = DD^* \quad \text{e.g.:} \quad 1 \quad 123 \quad 1209 \quad 002 \quad 020$$

Integers

$$Z = N \cup (-N)$$

Floating Point Number

$$F = Z \cup (Z.) \cup (.N) \cup (-.N) \cup (Z.N)$$

## Other Notations

	alternative notation
$R \cup S$	$R \mid S$
$0 \cup 1 \cup 2 \cup 3 \cup 4 \cup 5 \cup 6 \cup 7 \cup 8 \cup 9$	$[0-9]$
any letter a to z	$[a-z]$
$RR^*$	$R^+$
$\epsilon \cup R$	$R?$

Assignment Project Exam Help

<https://powcoder.com>

*Be careful!* Many variations exist. Tools that use regexps differ in many details:

- ▶ whether or not they use the above special meanings of  $+$  and  $?$ ;
- ▶ how they handle the parentheses and vertical bar for alternatives
  - ▶ sometimes  $(\dots | \dots)$
  - ▶ sometimes  $\backslash(\dots \backslash | \dots \backslash)$
- ▶ how they use full stop (often represents any non-newline character);
- ▶ how they represent newline characters
- ▶ ...

Add WeChat powcoder

- ▶ Regular Expressions
- ▶ Definitions
- ▶ How to use them to define languages
- ▶ Regular languages

# Assignment Project Exam Help

<https://powcoder.com>

Read Sipser, §1.3, pp 63–66.

Additional Reading

Add WeChat powcoder

- ▶ Jeffrey E.F. Friedl, *Mastering Regular Expressions: Powerful Techniques for Perl and Other Tools*, O'Reilly, 1997.