

FIT2014 Theory of Computation

Assignment Project Exam Help

Lecture 20

Decidability

<https://powcoder.com>

slides by Graham Farr

based in part on previous slides by David Albrecht

Add WeChat powcoder

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.

Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Assignment Project Exam Help

- ▶ Decision problems
- ▶ Decidable problems and languages
- ▶ Deciders
- ▶ Closure

<https://powcoder.com>

Add WeChat powcoder

Deciders

Reminder:

A decider is a Turing Machine that halts for every input.

A language is decidable if it is $\text{Accept}(L)$ for some decider.

... in which case, its complement is $\text{Reject}(L)$ for the same decider.

Examples:

- ▶ Regular Languages
- ▶ Context Free Languages
- ▶ $\{a^n b^n a^n : n \geq 0\}$

Decidable: synonyms

Assignment Project Exam Help

decidable

= recursive

= solvable

<https://powcoder.com>

Add WeChat powcoder

computable

...sometimes, though “computable” has
been used with other meanings too.

Decision Problems

INPUT: an integer

QUESTION: Is it even?

INPUT: a string

QUESTION: Is it a palindrome?

INPUT: an expression in propositional logic

QUESTION: Is it ever True?

INPUT: a graph G , and two vertices s and t

QUESTION: is there a path from s to t in G ?

INPUT: a Python program

QUESTION: is it syntactically correct?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

INPUT: a Finite Automaton

QUESTION: Does it define the empty language?

INPUT: two Regular Expressions

QUESTION: Do they define the same language?

INPUT: a Finite Automaton

QUESTION: Does it define an infinite language?

INPUT: a Context Free Grammar

QUESTION: Does it define the empty language?

INPUT: a Context Free Grammar

QUESTION: Does it generate an infinite language?

INPUT: a Context Free Grammar and a string w

QUESTION: Can w be generated by the grammar?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Decision Problems

A **decision problem** is a problem where, for each input, the answer is Yes or No.

A decider **solves** a decision problem if it

- ▶ Accepts an input for which the answer is Yes, and
- ▶ Rejects any input for which the answer is No.

Decision problem \rightarrow language

- ▶ { YES-inputs }

Language \rightarrow decision problem

- ▶ INPUT: a string
(over some alphabet, usually representing some object)

QUESTION: Is the string in the Language?

Thus, a decider solves a decision problem if and only if it is a decider for its corresponding language.

Assignment Project Exam Help

The input and output for a Turing Machine is always a string.

For any object, O , $\langle O \rangle$ will denote encoding of the object as a string.

If we have several objects, O_1, \dots, O_n , we denote their encoding into a single string by $\langle O_1, \dots, O_n \rangle$.

Add WeChat powcoder

Testing Emptiness of Regular Languages

Decision Problem:

INPUT: a Finite Automaton

QUESTION: Does it define the empty language?

Language:

<https://powcoder.com>

$\text{FA-Empty} := \{ \langle A \rangle : A \text{ is a FA and } L(A) = \emptyset \}$

Theorem.

FA-Empty is decidable.

Add WeChat powcoder

Testing Emptiness of Regular Languages

Theorem.

FA-Empty is decidable.

Proof. (outline)

Algorithm:

Input: $\langle A \rangle$ where A is a Finite Automaton.

1. Mark the Start State of A .
2. Repeat until no new states get marked:
 - ▶ Mark any state that has a transition coming into it from any state that is already marked.
 - ▶ If no final state is marked, Accept; otherwise Reject.



Testing Equivalence of Regular Expressions

Decision Problem:

REGULAR EXPRESSION EQUIVALENCE
Assignment Project Exam Help

INPUT: two Regular Expressions

QUESTION: Do they define the same language?

For a Regular expression R , let $L(R)$ be the language defined by R .
<https://powcoder.com>

Language:

$\text{RegExpEquiv} = \{ \langle A, B \rangle : A, B \text{ are regular expressions and } L(A) = L(B) \}$
Add WeChat powcoder

Theorem.

RegExpEquiv is decidable.

Testing Equivalence of Regular Expressions

Proof

Algorithm.

Input: $\langle A, B \rangle$ where A and B are regular expressions

1. Construct a FA, C , that defines the language

$$(L(A) \cap \overline{L(B)}) \cup (\overline{L(A)} \cap L(B)).$$

2. Run the previous Turing Machine, T , on C .

3. If T accepts C , then Accept, else Reject.



Testing Emptiness of Context Free Language

Decision Problem:

Assignment Project Exam Help

INPUT: a Context Free Grammar

QUESTION: Does it define the empty language?

Language: <https://powcoder.com>

CFG-Empty := $\{G : G \text{ is a CFG and } G \text{ defines the empty language}\}$

Theorem. **Add WeChat powcoder**

CFG-Empty is decidable.

Assignment Project Exam Help

Algorithm:

Input: $\langle A \rangle$ where A is a Context Free Grammar.

1. Mark all the terminal symbols in A .
2. Repeat until no new symbols get marked.
 - ▶ Mark any non-terminal X that has a production which has all the right-hand symbols marked.
 - ▶ If Start Symbol is not marked, Accept. Else Reject.

Some Decidable Problems

INPUT: a Finite Automaton

QUESTION: Does it define the empty language?

INPUT: two Regular Expressions

QUESTION: Do they define the same language?

INPUT: a Finite Automaton

QUESTION: Does it define an infinite language?

INPUT: a Context Free Grammar

QUESTION: Does it define the empty language?

INPUT: a Context Free Grammar

QUESTION: Does it generate an infinite language?

INPUT: a Context Free Grammar and a string w

QUESTION: Can w be generated by the grammar?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment [?] Project Exam Help

Decidable

<https://powcoder.com>

Add WeChat powcoder

CFL

regular
languages

Closure properties

If L is decidable, then \bar{L} is decidable.

If L_1 and L_2 are decidable, then so are

- ▶ $L_1 \cup L_2$
- ▶ $L_1 \cap L_2$
- ▶ $L_1 L_2$
- ▶ ...

Exercise:

Formulate and prove more closure results.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- # Assignment Project Exam Help
- ▶ Decidable Problems, decidable languages, and the link between them.
 - ▶ Decision problems, relationship with languages
 - ▶ Examples of Decidable Problems.
 - ▶ Closure properties
- <https://powcoder.com>

Reading: Sipser, Section 4.1, pp. 190–201.

Add WeChat powcoder

Preparation: Sipser, Section 4.2, pp. 201–213, especially pp. 207–209.