



MONASH
University

MONASH
INFORMATION
TECHNOLOGY

Assignment Project Exam Help
Database Design II: Logical Modelling
<https://powcoder.com>

Add WeChat powcoder



Reference

Several of the examples and diagrams used this session have been taken from:

Hoffer, J. A. , Prescott, M. B. & McFadden, F. R. “Modern Database Management”

<https://powcoder.com>
Add WeChat powcoder



Step 2 (and 3) of the Design Process

- Step 1 Conceptual Model (session 2)
 - Database Model independent
- Step 2 Logical Model (this session)
 - Select which type (model) of database you wish to implement your conceptual model in
 - Network, Relational, OO, XML, NoSQL, ...
 - Database model dependent
- Step 3 Physical Model
 - Select which specific vendor for your chosen model you will implement in
 - Oracle, MySQL, IBM DB2, SQL Server, ...
 - Database vendor dependent
 - Final output schema file to implement model (for relational model a set of tables)



Summary of Terminologies at Different Levels

Conceptual	Logical (Relational)	Physical (Relational)
Entity	Relation	Table
Attribute	Attribute	Column
Instance	Tuple	Row
Identifier	Primary Key	Primary Key
Relationship	---	---
---	Foreign Key	Foreign Key

Recap Session 3 Relational Model Characteristics

- Each relation must have a unique name
- Each attribute of a relation must have a distinct name within the relation
- An attribute cannot be multivalued (consist of repeating values)
- All values of an attribute need to be from the same domain
- The order of attributes and tuples in a relation is immaterial
- Each relation must have a primary key
- Logical (not physical) connections are made between relations by virtue of primary/foreign keys

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Q1. The relational model requires that each cell in a relation is single-valued (atomic). Considering this requirement, what construct in an ER diagram cannot be implemented directly (for example, without adding further entities) in the relational model (logical level)?

Assignment Project Exam Help

- a. Composite key.
- b. Composite attribute.
- c. Multi-valued attribute.
- d. Dependent attribute.
- e. More than one option is correct.

<https://powcoder.com>

Add WeChat powcoder


Revisit - Session 2 Conceptual Model

*All required
attributes shown*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Transforming ER diagrams into relations (mapping conceptual level to logical level)

- Essentially
 - KEY to PK
 - Represent relationships with PK/FK pairs
- The steps are:
 - Map strong (regular) entities
 - Map weak entities
 - Map binary relationships
 - Map associative entities
 - Map unary relationships
 - Map ternary relationships
 - *Map supertype/subtype relationships (is not part of this unit).*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Map Regular Entities

- Composite Attributes

- When the regular entity type contains a composite attribute, only the simple component attributes of the composite attribute are included in the new relation.
- Compared to composite attributes, simple attributes not only improve data accessibility but also help in maintaining data quality
- Client input needed in some cases to determine if to be left as simple or broken into components


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Mapping a Composite Attribute



Monash Software Case Study

* = not null (must have value)




Map Regular Entities

- Multivalued Attribute

- When the regular entity type contains a multivalued attribute, two new relations are created.
- The first relation contains all the attributes of the entity type except the multivalued attribute itself.
- The second relation contains two attributes that form the PK. One of the attributes is the PK from the first relation, which becomes the FK in the second relation and the other is the multivalued attribute.
- There can also be non key attributes in the second relation depending upon the data requirements.

Mapping a Multi valued Attribute



Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder



Is there a better solution than the one shown above?


What are the issues here - this was partially discussed in session 2

Revisit - Session 2 Conceptual Model - IMPROVED

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Note: Surrogate key of skill_code has been added



Mapping a Weak Entity

- For each weak entity type, create a new relation and include all of the simple attributes as attributes of this relation. The PK of the identifying relation is also included as the FK in this new relation.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




*** Note: logical model must have verbs on relationships, excluded on slides for clarity*

Conceptual


Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder




Logical



Mapping a 1:M Binary Relationship



Q2. Where would you place the Foreign Key when you map this ER diagram into the relational model?



Assignment Project Exam Help

<https://powcoder.com>

- A. CUSTOMER
- B. ORDER
- C. Both CUSTOMER and ORDER
- D. None, no FK is needed.

Map Binary Relationships (1:M)



<https://powcoder.com>

Add WeChat powcoder

For each 1:M binary relationship, first create a relation for each of the two entity types participating in the relationship. Then include the PK attribute (or attributes) of the entity on the one-side of the relationship as the FK on the many-side of the relationship.

Conceptual

Logical


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Mapping a M:N Binary Relationship



Q3. What will be the Primary Key of the new created relation resulting from mapping this ER model at the conceptual level into a relational model?




- A. The primary key of the ORDER table.
- B. The primary key of the PRODUCT table.
- C. The combination of primary keys of ORDER and PRODUCT.

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder




Map Binary Relationship (M:N)

- For a M:N binary relationship
 - First create a relation for each of the two entity types participating in the relationship.
 - Then create a new relation and include as foreign key attributes, the PK attribute (or attributes) for each of the two participating entity types. These attributes become the PK of the new relation.
 - If there are any nonkey attributes associated with the M:N relationship, they are also included in the new relation.

Conceptual



Logical




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Mapping an associative entity with an Identifier



Add WeChat powcoder



Mapping a 1:1 Binary Relationship



Add WeChat powcoder




Q4. Where would you place the Foreign Key when mapping this ER diagram into a relational model?



<https://powcoder.com>

- A. NURSE
- B. CARE CENTRE
- C. Both NURSE and CARE CENTRE
- D. No FK is needed.

Relationship Participation Mandatory vs Optional



<https://powcoder.com>

Add WeChat powcoder


NURSE participation *in this relationship?*

CARECENTRE participation *in this relationship?*


Map Binary Relationship (1:1)

- Create two relations, one for each of the participating entity types.
 - The primary key (PK) on the mandatory side of the relationship becomes the foreign key (FK) on the optional side of the relationship.
 - where both are optional place the FK on the side which causes the fewest nulls
 - Special case: 1:1 total relationship (mandatory participation from both sides)
 - Consider consolidating the two entity types into one relation
- <https://powcoder.com>
Add WeChat powcoder

Conceptual



Logical



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder


Map unary relationships

- Unary Relationship is a relationship between the instances of a single entity type.
- Unary 1:M Relationship – A relation is created for the entity type. Add a FK within the same relation that references the PK of the relation. A recursive foreign key is a FK in a relation that references the PK values of the same relation.
- Unary M:N Relationship – Two relations are created, one for the entity type in the relationship and the other as the associative relation to represent the M:N relationship itself. The PK of the associative relation consists of two attributes (with different names) taking their values from the PK of the other relation.


Mapping a 1:M Unary Relationship



Conceptual



Logical




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Q5. How many relations/tables and relationships do we need to implement the model below into a relational model?

- A. 2 tables, 1 relationship
- B. 2 tables, 2 relationships
- C. 3 tables, 2 relationships
- D. 4 tables, 3 relationships




Add WeChat powcoder

Mapping a M:N Unary Relationship



SQL Developer Data Modeler




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Adding surrogate keys



Surrogate PK's may be added **ONLY** on the logical model provided they are justified (include in documentation / assumptions).

Potential problem:

Need to ensure that the identified key from the conceptual model - the natural key: (emp_no, training_code, et_date_completed)

will still remain unique

Solution, where needed:

Define a unique index on the attributes of natural key

Assignment Project Exam Help



MANUALLY add new PK attribute (here et_no), **DO NOT USE** SQL Developers "Create Surrogate Key" option

<https://powcoder.com>

et_no	emp_no	training_code	et_date_completed
1	101	ORA01	1-Oct-2016
2	101	ORA01	1-Oct-2016
3	101	ORA01	1-Oct-2016

Add WeChat powcoder


Unique Identifiers
Relationships
Subtypes
Volume Properties
Engineer To
Comments
Comments in RDBMS
Overlapping Attributes
Notes
Impact Analysis
Measurements
Change Requests



Ternary Relationships

Ternary


modelled as binary:



Ternary Relationships – model as binary relationships?

- Ternary represents more information than three binary relationships
- For example - Supplier 1 supplies Project 2 with Part 3 -
 - ternary **Assignment Project Exam Help**
 - instance (supplier 1, project 2, part 3) exists
 - binaries **<https://powcoder.com>**
 - instances
 - (supplier 1, project 2) (project 2, part 3) (supplier 1, part 3)
 - BUT does not imply (supplier 1, project 2, part 3)
- How then do we map such relationships?

Mapping a Ternary Relationship



Map Ternary (and n-ary) Relationships

- Ternary relationship should be converted to an associative entity.
 - To map an associative entity type that links three regular entity types, an associative relation is created.
 - The default FK of this relation consists of the three PK attributes for the participating entity types.
 - Any attributes of the associative entity type become attributes of the new relation.


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Mapping a Ternary Relationship




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Monash Software Amalgamation

Session 5 Final Logical Model - conversion from Session 2 Conceptual Model



Session 4 Final Normalisation Result - EMPLOYEE Form

3NF

EMPLOYEE (emp_no, emp_fname, emp_lname, emp_dob, emp_street_no, emp_street, emp_town, emp_pcode)

EMP_PHONE (emp_no, phone_no, phone_type)

EMP_QUALIFICATION (emp_no, degree_name, degree_institution, degree_year)

FAMILY_MEMBER (emp_no, fmemb_no, fmemb_name, fmemb_dob)

EMPLOYEE_SKILL (emp_no, skill_name)

Full dependencies:

emp_no -> emp_fname, emp_lname, emp_dob, emp_street_no, emp_street, emp_town, emp_pcode

emp_no, phone_no -> phone_type

emp_no, degree_name, degree_institution -> degree_year

emp_no, fmemb_no -> fmemb_name, fmemb_dob

