



MONASH  
University


MONASH  
INFORMATION  
TECHNOLOGY

**Assignment Project Exam Help**  
**Structured Query Language (SQL) – Part 1**  
**<https://powcoder.com>**

**Add WeChat powcoder**



# Anatomy of an SQL SELECT Statement



# SQL SELECT Statement - Usage

What column/s to display

What table(s) the data come from?

```
SELECT stu_id, stu_fname, stu_lname  
FROM student  
WHERE stu_fname = 'Maria';
```

Add WeChat powcoder

What row/s to retrieve – the  
RESTRICTION on the select

# SQL Predicates or Search Conditions

- The search conditions are applied on each row, and the row is returned if the search conditions are evaluated to be TRUE for that row.
- **Comparison**
  - Compare the value of one expression to the value of another expression.
  - Operators: =, !=, <, >, <=, >=
  - Example: salary > 5000
- **Range**
  - Test whether the value of an expression falls within a specified range of values.
  - Operator: BETWEEN
  - Example: salary BETWEEN 1000 AND 3000 (both are inclusive)

# SQL Predicates or Search Conditions

## ■ Set Membership

- To test whether the value of expression equals one of a set of values.
- Operator: IN
- Example : `city IN ('Melbourne' 'Sydney')`

## ■ Pattern Match

- To test whether a string (text) matches a specified pattern.
- Operator: LIKE
- Patterns:
  - % character represents any sequence of zero or more character.
  - \_ character represents any single character.
- Example:
  - `WHERE city LIKE 'M%'`
  - `WHERE unit_code LIKE 'FIT20__'`

# SQL Predicates or Search Conditions

- **NULL**

- To test whether a column has a NULL (unknown) value.
- Example: WHERE grade IS NULL.

- Use in subquery (to be discussed in the future)

- ANY, ALL
- EXISTS

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## What row will be retrieved?

- Predicate evaluation is done using three-valued logic.
  - **TRUE**, **FALSE** and **UNKNOWN**
- DBMS will evaluate the predicate against each row.
- Row that is evaluated to be **TRUE** will be retrieved.
- NULL is considered to be UNKNOWN.

# Combining Predicates

- Logical operators
  - AND, OR, NOT
- Rules:
  - An expression is evaluated LEFT to RIGHT
  - Sub-expression in brackets are evaluated first
  - NOTs are evaluated before AND and OR
  - ANDs are evaluated before OR
  - Use of BRACKETS better alternative

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Truth Table

- **AND** is evaluated to be TRUE if and only if **both** conditions are TRUE
- **OR** is evaluated to be TRUE if and only if at least one of the conditions is TRUE

AND

A \ B	T	U	F
T	T	U	F
U	U	U	F
F	F	F	F

OR

A \ B	T	U	F
T	T	T	T
U	T	U	U
F	T	U	F

T = TRUE

F = FALSE


U = Unknown

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Unknown = NULL in  
relational database



**SELECT \* FROM UNIT;**

Script Output x Query Result x

SQL | All Rows Fetched: 3 in 0.015 seconds

	UNIT_CODE	UNIT_NAME
1	FIT1001	Computer Systems
2	FIT1002	Computer Programming
3	FIT1004	Database

**SELECT \* FROM STUDENT;**

Script Output x Query Result x

SQL | All Rows Fetched: 4 in 0.022 seconds

	STU_NBR	STU_LNAME	STU_FNAME	STU_DOB
1	11111111	Bloggs	Fred	01/JAN/90
2	11111112	Nice	Nick	10/OCT/94
3	11111113	Wheat	Wendy	05/MAY/90
4	11111114	Sheen	Cindy	25/DEC/96

**SELECT \* FROM ENROLMENT;**

Script Output x Query Result x

SQL | All Rows Fetched: 8 in 0.016 seconds

	STU_NBR	UNIT_CODE	ENROL_YEAR	ENROL_SEMESTER	ENROL_MARK	ENROL_GRADE
1	11111111	FIT1001	2012	1	78	D
2	11111111	FIT1002	2013	1	(null)	(null)
3	11111111	FIT1004	2013	1	(null)	(null)
4	11111112	FIT1001	2012	1	35	N
5	11111112	FIT1001	2013	1	(null)	(null)
6	11111113	FIT1001	2012	2	65	C
7	11111113	FIT1004	2013	1	(null)	(null)
8	11111114	FIT1004	2013	1	(null)	(null)

# Arithmetic Operations

- Can be performed in SQL.
- For example:

```
SELECT stu_nbr, enrol_mark/10  
FROM enrolment;
```

<https://powcoder.com>

Add WeChat powcoder

STU_NBR	ENROL_MARK
1 11111111	7.8
2 11111111	(null)
3 11111111	(null)
4 11111112	3.5
5 11111112	(null)
6 11111113	6.5
7 11111113	(null)
8 11111114	(null)



# Oracle NVL function

- It is used to replace a NULL with a value.

```
SELECT stu_nbr,  
       NVL(enrol_mark,0),  
       NVL(enrol_grade,'WH')  
FROM enrolment;
```

	STU_NBR	NVL(ENROL_MARK,0)	NVL(ENROL_GRADE,'WH')
1	11111111	78	D
2	11111111	0	WH
3	11111111	0	WH
4	11111112	35	N
5	11111112	0	WH
6	11111113	65	C
7	11111113	0	WH
8	11111114	0	WH

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Renaming Column

- Note column headings on slide 16
- Use the word "AS"
  - New column name in " " to maintain case or spacing
- Example

<https://powcoder.com>  
SELECT stu\_nbr, enrol\_mark/10 AS new\_mark  
FROM enrolment;

Add WeChat powcoder  
SELECT stu\_nbr, enrol\_mark/10 AS "New Mark"  
FROM enrolment;

# Sorting Query Result

- "ORDER BY" clause – *tuples have no order*
  - Must be used if more than one row may be returned
- Order can be ASCending or DESCending. The default is ASCending.
  - NULL values can be explicitly placed first/last using "NULLS LAST" or "NULLS FIRST" command
- Sorting can be done for multiple columns.
  - order of the sorting is specified for each column.

- Example:

```
SELECT stu_nbr, enrol_mark  
FROM enrolment  
ORDER BY enrol_mark DESC
```

	STU_NBR	ENROL_MARK
1	11111111	(null)
2	11111111	(null)
3	11111114	(null)
4	11111112	(null)
5	11111113	(null)
6	11111111	78
7	11111113	65
8	11111112	35



# Removing Duplicate Rows in the Query Result

- Use "DISTINCT" as part of SELECT clause
  - *use with care*

Assignment Project Exam Help

<https://powcoder.com>

```
SELECT DISTINCT stu_nbr  
FROM enrolment  
WHERE enrol_mark IS NULL;
```

Add WeChat powcoder

	STU_NBR
1	111111114
2	111111111
3	111111112
4	111111113



# SQL NATURAL JOIN

STUDENT

sno	name
1	alex
2	maria
3	bob

QUALIFICATION

sno	degree	year
1	bachelor	1990
1	master	2000
2	PhD	2001

**Assignment Project Exam Help**  
**SELECT \***  
**FROM student JOIN qualification**  
**ON student.sno = qualification.sno**  
**ORDER BY student.sno**

**https://powcoder.com**  
**Add WeChat powcoder**

sno	name	degree	year
1	alex	bachelor	1990
1	alex	master	2000
2	maria	PhD	2001





# SQL JOIN

- For database students are **required to use ANSI JOINS**
  - placing the join in the where clause is **not acceptable** and will be *marked as incorrect for all assessment purposes*
    - such a join is sometimes known as "implicit join notation" - effectively a cross product and then restricted by the where clause
- ANSI JOINS
  - ON
    - the general form which always works, hence the syntax we tend to use
    - FROM student JOIN qualification ON student.sno = qualification.sno
  - USING
    - requires matching attribute names for the PK and FK
    - FROM student JOIN qualification USING (sno)
  - NATURAL
    - requires matching attribute names for the PK and FK
    - FROM student NATURAL JOIN qualification

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



# JOIN-ing Multiple Tables

Pair the PK and FK in the JOIN condition  
Note table aliasing e.g. unit u in FROM clause



**Add WeChat powcoder**

```
SELECT s.stu_nbr, s.stu_fname, s.stu_lname, u.unit_name
FROM ((unit u JOIN enrolment e ON u.unit_code=e.unit_code)
      JOIN student s ON e.stu_nbr=s.stu_nbr)
ORDER BY s.stu_nbr, u.unit_name;
```

Table1		
P *	T1_attributte1	CHAR (4)
P *	T1_attribute2	CHAR (6)
	T1_attribute3	VARCHAR (100)
{entity} PK (T1_attributte1, T1_attribute2)		

Table 2		
P *	T2_attribute1	NUMERIC (8)
F *	T1_attributte1	CHAR (4)
F *	T1_attribute2	CHAR (6)
{entity} PK (T2_attribute1)		



## Assignment Project Exam Help

How many conditions will be used to join the two tables?

<https://powcoder.com>

SELECT \*

FROM table1 t1 JOIN table2 t2 ON

(t1.T1\_attribute1 = t2.T1\_attribute1

AND

t1.T1\_attribute2 = t2.T1\_attribute2)

ORDER BY t1.T1\_attribute1, t1.T1\_attribute2;



# Summary

- SQL statement, clause, predicate.
- Writing SQL predicates.
  - Comparison, range, set membership, pattern matching, is NULL
  - Combining predicates using logic operators (AND, OR, NOT)
- Arithmetic operation
  - NVL function
- Column alias.
- Ordering (Sorting) result.
- Removing duplicate rows.
- JOIN-ing tables

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Oracle Date Data Type <https://powcoder.com>

Add WeChat powcoder

# Oracle Data Datatype

- Dates are stored differently from the SQL standard
  - standard uses two different types: date and time
  - Oracle uses one type: DATE
    - Stored in internal format contains date and time
      - Julian date as number (can use arithmetic)
    - Output is controlled by formatting
      - select `to_char(sysdate,'dd-Mon-yyyy')` from dual;  
» 04-May-2020
      - select  
`to_char(sysdate,'dd-Mon-yyyy hh:mi:ss PM')` from dual;  
» 04-May-2020 02:51:24 PM

- DATE data type should be formatted with **TO\_CHAR** when selecting for **display**.
- Text representing date **must be formatted** with **TO\_DATE** when comparing or inserting/updating.
- Example: <https://powcoder.com>

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
select studid,  
       studfname || ' ' || studlname as StudentName,  
       to_char(studdob,'dd-Mon-yyyy') as StudentDOB  
from uni.student  
where studdob > to_date('01-Apr-1991','dd-Mon-yyyy')  
order by studdob;
```




## Current Date

- Current date can be queried from the DUAL table using the **SYSDATE** attribute.
  - SELECT **sysdate** FROM dual;
- Oracle internal attributes include:
  - **sysdate**: current date/time
  - **systimestamp**: current date/time as a timestamp
  - **user**: current logged in user



# Uni Data Model



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Putting this to Work

- Q1. Show the ids, names of students as a single column called NAME and their DOBs. Order the output in date of birth order
- Q2. Show the ids, names of students as a single column called NAME, unit code, and year and semester of enrolment where the mark is NULL. Order the output by student id, within unit code order

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder