



MONASH
University

MONASH
INFORMATION
TECHNOLOGY


Creating & Populating the Database – Data
Definition Language

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





SQL general syntax

- A single statement is ended with SEMICOLON.
- Predefined KEYWORDS represent clauses (components) of a statement.
- Keywords are NOT case sensitive.
- Examples:

```
CREATE TABLE unit
(
    unit_code    CHAR(7) NOT NULL,
    unit_name    VARCHAR2(50) CONSTRAINT uq_unit_name UNIQUE NOT NULL,
    CONSTRAINT pk_unit PRIMARY KEY (unit_code)
);

SELECT * FROM student;
```

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

SQL Statements

- Data Definition Language (DDL)
 - Creating database structure
 - CREATE TABLE, ALTER TABLE, DROP TABLE
 - Data Manipulation Language (DML)
 - Adding and Manipulating database contents (rows)
 - INSERT, UPDATE, DELETE
 - Retrieving data from database
 - SELECT
 - Data Control Language (DCL)
 - Set permissions on objects
 - GRANT
- Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder



Q1. There are a number of business rule represented by the above model. Choose true statement(s) according to the diagram.



- A. A student enrolls in a maximum of one unit.
- B. An enrolment record is created for a particular student of a unit in a given semester and year.
- C. A student can have more than one grade for a given unit.
- D. A unit can only have a single student enrolled.
- E. More than one option in a to d is correct.

Assignment Project Exam Help

CREATE A TABLE (DDL)

<https://powcoder.com>

Add WeChat powcoder

Q2. What relational model component(s) is/are defined in this create table statement?

```
CREATE TABLE STUDENT (  
    stu_nbr      NUMBER(6)      NOT NULL,  
    stud_lname   VARCHAR2(50)  NOT NULL,  
    stud_fname   VARCHAR2(50)  NOT NULL,  
    stu_dob       DATE          NOT NULL,  
    CONSTRAINT STUDENT_PK PRIMARY KEY (stu_nbr)  
);
```

A. Relation, Attribute Domain

B. Primary Key

C. Foreign Key

D. Referential Integrity constraint

E. All of the options in a-d are correct.

F. Some of the options in a-d are correct.

Common ORACLE data types

- **Text:** CHAR(size), VARCHAR2(size)

- e.g., CHAR(10), VARCHAR2(10)

- CHAR(10) → 'apple' = 'apple '

- VARCHAR2(10) → 'apple' = 'apple'

Assignment Project Exam Help

- **Numbers:** NUMBER(precision, scale)

- Weight NUMBER(7) or NUMBER(7,0) → Weight = 7456123

- Weight NUMBER(9,2) → Weight = 7456123.89

- Weight NUMBER(8,1) → Weight = 7456123.9

<https://powcoder.com>

Add WeChat powcoder

- **Data/Time:** DATE, TIMESTAMP

- DATE can store a date and time (time to seconds), stored as Julian date


- TIMESTAMP can store a date and a time (up to fractions of a second)

- TIMESTAMP WITH TIME ZONE




Column VS Table Level Constraints

```
CREATE TABLE STUDENT (  
  stu_nbr NUMBER(6) NOT NULL,  
  stud_lname VARCHAR2(50) NOT NULL,  
  stud_fname VARCHAR2(50) NOT NULL,  
  stu_dob DATE NOT NULL,  
  CONSTRAINT STUDENT_PK PRIMARY KEY (stu_nbr)  
);
```



Q3. What would be the order of the CREATE TABLE statements in the schema script to successfully create a database based on the below diagram? (assuming that we will define the FK as part of the create table statement)



A. UNIT, ENROLMENT, STUDENT


B. ENROLMENT, STUDENT, UNIT

C. STUDENT, UNIT, ENROLMENT

D. UNIT, STUDENT, ENROLMENT

E. More than one option is correct


Q4. How many foreign key/s (FK) will be in the database when the three tables are created?



Assignment Project Exam Help

- A. 1.
- B. 2. <https://powcoder.com>
- C. 3.
- D. 4. **Add WeChat powcoder**

During answering, identify the attribute(s) that will be assigned as FK and what table(s) would it “link”?



CREATE TABLE student

```

(
  stu_nbr      NUMBER(8)      NOT NULL,
  stu_lname    VARCHAR(50)    NOT NULL,
  stu_fname    VARCHAR(50)    NOT NULL,
  stu_dob      DATE           NOT NULL,
  CONSTRAINT pk_student PRIMARY KEY (stu_nbr)
);

```

Assignment Project Exam Help

<https://powcoder.com>

CREATE TABLE unit


```

(
  unit_code    CHAR(8)        NOT NULL,
  unit_name    VARCHAR(50)    CONSTRAINT uq_unit_name UNIQUE NOT NULL,
  CONSTRAINT pk_unit PRIMARY KEY (unit_code)
);

```

Add WeChat powcoder





CREATE

TABLE enrolment

(

stu_nbr NUMBER(8) NOT NULL,

unit_code CHAR(8) NOT NULL,

enrol_year NUMBER(4) NOT NULL,

enrol_semester CHAR(2) NOT NULL,

enrol_mark NUMBER(3),

enrol_grade CHAR(2),

CONSTRAINT pk_enrolment PRIMARY KEY (stu_nbr, unit_code, enrol_year, enrol_semester),

CONSTRAINT fk_enrolment_student FOREIGN KEY (stu_nbr) REFERENCES student (stu_nbr),

CONSTRAINT fk_enrolment_unit FOREIGN KEY (unit_code) REFERENCES unit (unit_code)

);

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Alternative method of defining FKs

```
CREATE TABLE enrolment
(
  stu_nbr          NUMBER(8)    NOT NULL,
  unit_code        CHAR(8)      NOT NULL,
  enrol_year       NUMBER(4)    NOT NULL,
  enrol_semester   CHAR(2)      NOT NULL,
  mark             NUMBER(3),
  grade            CHAR(2),
  CONSTRAINT pk_enrolment PRIMARY KEY (stu_nbr, unit_code, enrol_year, enrol_semester)
);
```

```
ALTER TABLE enrolment
ADD
  ( CONSTRAINT fk_enrolment_student FOREIGN KEY (stu_nbr)
    REFERENCES student ( stu_nbr),
    CONSTRAINT fk_enrolment_unit FOREIGN KEY (unit_code)
    REFERENCES unit (unit_code));
```


Referential Integrity

- To ensure referential integrity, SQL defines three possible actions for FKs in relations when a deletion of a primary key occurs:
 - RESTRICT (Oracle No Action basically equivalent)
 - Deletion of tuples is NOT ALLOWED for those tuples in the table referred by the FK (the table containing PK) if there is corresponding tuple in the table containing the FK.
 - CASCADE
 - A deletion of a tuple in the table referred by the FK (the table containing PK) will result in the deletion of the corresponding tuples in the table containing the FK.
 - NULLIFY
 - A deletion of a tuple in the table referred by the FK (the table containing PK) will result in the update of the corresponding tuples in the table containing the FK to NULL.



Referential Constraints SQL Data Modeller

52 UTC
48 UTC



Relation Properties - team_employee

General

Name: team_employee

Use surrogate keys: ☐

Source Cardinality

Source: TEAM

Source Key: TEAM.M_TEAM PK

Name on Source: consists

Source Entity Synonym: TEAM

Source to Target Cardinality: 1..*

Source Optional: ☐

Transferable: ☒

Identifying: ☐

Delete Rule: NO ACTION

NO ACTION
CASCADE
SET NULL
RESTRICT

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



What Referential Integrity Constraint to implement?


- Use the model to decide on what referential integrity constraint to implement.
 - Mandatory vs Optional participation.
- The constraints must be decided at the design phase.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Q5. Assume that the table ENROLMENT contains enrolment details for students in FIT9132 and FIT9001. The referential integrity constraint is CASCADE. What would happen to tuples in ENROLMENT with the unit_code='FIT9132' when we delete the FIT9132 record from UNIT?



<https://powcoder.com>

- A. They will be deleted.
- B. The value of unit_code will be updated to NULL.
- C. The deletion is not possible, the DBMS will prevent the deletion.
- D. None of the above.

Q6. What would happen to the student record with `stu_nbr='1234'` in the STUDENT table when we delete all tuples with `stu_nbr='1234'` in the ENROLMENT table? (Assume referential integrity is CASCADE constraints)



- <https://powcoder.com>
- [Add WeChat powcoder](#)
- Student record with `stu_nbr='1234'` in the STUDENT table will be deleted.
 - Nothing will happen to the STUDENT table.
 - The `stu_nbr='1234'` in the STUDENT table will be updated to NULL.
 - Deletion will not be permitted by the DBMS.

Q7. What referential integrity constraint could be implemented according to the above model for the FKs in the PROJECT table without violating the business rules depicted in the model?



- <https://powcoder.com>
- Add WeChat powcoder**
- A. NULLIFY
 - B. CASCADE
 - C. RESTRICT
 - D. b and c are correct.
 - E. a, b and c are correct.

ALTER TABLE

- Used to change a tables structure.
- For example:

- Adding column(s).
- Removing column(s).
- Adding constraint(s).
- Removing constraint(s).

Assignment Project Exam Help

<https://powcoder.com>

```
ALTER TABLE student
```

Add WeChat powcoder

```
ADD (stu_address varchar(200),  
     status char(1) DEFAULT 'C',  
     constraint status_chk CHECK (status in ('G','C'))  
);
```



Referential Integrity Definition - Example

```
ALTER TABLE enrolment  
  DROP CONSTRAINT fk_enrolment_student;
```

```
ALTER TABLE enrolment  
  DROP CONSTRAINT fk_enrolment_unit;
```

```
ALTER TABLE enrolment  
  ADD  
    ( CONSTRAINT fk_enrolment_student FOREIGN KEY (stu_nbr)  
      REFERENCES student ( stu_nbr) ON DELETE CASCADE,
```

```
    CONSTRAINT fk_enrolment_unit FOREIGN KEY (unit_code) REFERENCES unit  
      (unit_code) ON DELETE CASCADE  
  );
```

DELETING A TABLE

- Use the DROP statement.
- Examples:

- `DROP TABLE enrolment PURGE;`
- `DROP TABLE student CASCADE CONSTRAINTS PURGE;`

Add WeChat powcoder

Assignment Project Exam Help
ADDING TUPLES/ROWS TO A TABLE (DML)
<https://powcoder.com>

Add WeChat powcoder

INSERT

- Adding data to a table in a database.
- SYNTAX:

```
INSERT INTO table [(column [, column...])]
```

```
VALUES (value [, value...]);
```

Assignment Project Exam Help


<https://powcoder.com>

```
INSERT INTO unit VALUES ('FIT9132', 'Databases');
```

```
INSERT INTO student VALUES (112233, 'Willa', 'Wilbur',  
'01-Jan-1995')
```

Role of: *to_date* and *to_char*

Q8. Assume the tables have been created with primary and foreign key constraints and there is no data currently in the tables. In what order should we populate the table?



<https://powcoder.com>

- A. UNIT- > ENROLMENT -> STUDENT
- B. STUDENT > ENROLMENT -> UNIT
- C. STUDENT -> UNIT -> ENROLMENT
- D. More than one option is correct.

COMMIT and ROLLBACK

```
INSERT INTO enrolment VALUES (112233,  
                                'FIT9132',1,2018,45,'N');  
INSERT INTO enrolment VALUES (112233,  
                                'FIT9001',1,2018,80,'HD');  
COMMIT;
```

<https://powcoder.com>

COMMIT makes the changes to the database permanent.

ROLLBACK will undo the changes.

Using a SEQUENCE

- Oracle supports auto-increment of a numeric PRIMARY KEY.
 - SEQUENCE.
- Steps to use:
 - Create sequence

```
CREATE SEQUENCE sno_seq  
INCREMENT BY 1
```

- Access the sequence using two built-in variables (pseudocolumns):
 - NEXTVAL and CURRVAL

- INSERT INTO student
VALUES(sno_seq.nextval, 'Bond', 'James', '01-Jan-1994');
- INSERT INTO enrolment
VALUES(sno_seq.currval, 'FIT9132', ...');



Q9. Two new students and their enrolment details need to be added, James Bond wants to enrol in FIT9132 and FIT9001, Bruce Lee only wants to enrol in FIT9132. The sequence for sno is called sno_seq. What problems, if any, exist with this script:

```
-- Add two students
INSERT INTO student VALUES (sno_seq.nextval,'Bond','James','01-Jan-1994');
INSERT INTO student VALUES (sno_seq.nextval,'Lee','Bruce','01-Feb-1994');
-- Add the enrolments
INSERT INTO enrolment VALUES (sno_seq.currval,1,2018,'FIT9132',0,'NA');
INSERT INTO enrolment VALUES (sno_seq.currval,1,2018,'FIT9001',0,'NA');
INSERT INTO enrolment VALUES (sno_seq.currval,1,2018,'FIT9132',0,'NA');
COMMIT;
```

Assignment Project Exam Help

<https://powcoder.com>


- A. There will be an error message. It states that a violation of primary key constraints in the ENROLMENT has occurred.
- B. Bruce Lee will be enrolled in FIT9001.
- C. There will be NO enrolment record for James Bond.
- D. All of the options a-c are problems that will be caused by the script.
- E. Some of the options in a-c are problems that will be caused by the script.
- F. There will be no problem caused by the script.



Assignment Project Exam Help
PUTTING THIS TO WORK

<https://powcoder.com>

Add WeChat powcoder



```
CREATE TABLE employee (  
    emp_no        NUMBER(5) NOT NULL,  
    emp_fname     VARCHAR2(30),  
    emp_lname     VARCHAR2(30),  
    emp_street    VARCHAR2(50) NOT NULL,  
    emp_town      VARCHAR2(30) NOT NULL,  
    emp_pcode     CHAR(4) NOT NULL,  
    emp_dob       DATE NOT NULL,  
    emp_taxno     VARCHAR2(10),  
    team_no       NUMBER(3),  
    mentor_no     NUMBER(5)  
);
```

Assignment Project Exam Help

<https://powcoder.com>

```
ALTER TABLE employee ADD CONSTRAINT employee_pk PRIMARY KEY ( emp_no );
```

Add WeChat powcoder

```
CREATE TABLE team (  
    team_no       NUMBER(3) NOT NULL,  
    emp_no        NUMBER(5)  
);
```

```
ALTER TABLE team ADD CONSTRAINT team_pk PRIMARY KEY ( team_no );
```




```
ALTER TABLE employee
  ADD CONSTRAINT emp_mentors_emp FOREIGN KEY ( mentor_no )
    REFERENCES employee ( emp_no )
    ON DELETE SET NULL;
```

Assignment Project Exam Help

```
ALTER TABLE employee
  ADD CONSTRAINT team_has_employee FOREIGN KEY ( team_no )
    REFERENCES team ( team_no )
    ON DELETE SET NULL;
```

<https://powcoder.com>

```
ALTER TABLE team
  ADD CONSTRAINT emp_leads_team FOREIGN KEY ( emp_no )
    REFERENCES employee ( emp_no )
    ON DELETE SET NULL;
```

Add WeChat powcoder