

Assignment Project Exam Help

Data Reshaping

<https://powcoder.com>

Faculty of Information Technology, Monash University, Australia

Add WeChat powcoder

1 Data Transformation

- Data Normalisation/scaling
 - Transformation by generating new features
 - Nominal to Numeric Transformation

2 Data Discretisation

3 Feature Engineering & Data Sampling

4 Summary

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Outline

Assignment Project Exam Help

- Data Normalisation/Scaling
- Transformation by generating new features
- Nominal to Numeric Transformation

<https://powcoder.com>

2 Data Discretisation

3 Feature Engineering & Data Sampling

Add WeChat powcoder





4 Summary

Data Transformation

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Data Transformation

- Why: Raw attributes are usually not good enough to obtain accurate predictive model.

Assignment Project Exam Help

- k-nearest neighbours (K-NN) with an Euclidean distance measure if want all features to contribute equally

$$d(\mathbf{p}, \mathbf{q}) = \sqrt{(p_1 - q_1)^2 + (p_2 - q_2)^2 + \cdots + (p_n - q_n)^2} = \sqrt{\sum_i (p_i - q_i)^2}$$

- logistic regression, SVMs, perceptrons, neural networks etc. if you are using gradient descent/ascent-based optimisation, otherwise some weights will update much faster than others

Add WeChat powcoder

so that $w_j := w_j + \Delta w_j$

- linear discriminant analysis, principal component analysis, kernel principal component analysis since you want to find directions of maximising the variance (under the constraints that those directions/eigenvectors/principal components are orthogonal); you want to have features on the same scale since you'd emphasise variables on "larger measurement scales" more.

Data Transformation

- Data transformation

- ▶ A series of manipulation steps to transform the original attributes or to generate new attributes with better properties that will help the predictive power of the model.
- ▶ To achieve properties that enhance the modelling and analysis (linearity, statistical or visual interpretability).
- ▶ Methods
 - Normalisation/Scaling methods
 - Transformation by generating new features (i.e., variables or attributes)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Outline

Assignment Project Exam Help

1 Data Transformation

- Data Normalisation/Scaling
- Transformation by generating new features
- Nominal to Numeric Transformation

<https://powcoder.com>

2 Data Discretisation

3 Feature Engineering & Data Sampling

Add WeChat powcoder

4 Summary

Data Transformation — Normalisation

There are two types of data normalisation:

- Standardisation (z-score normalisation): where the focus is on shifting the distribution of data to have mean of 0 and standard deviation of 1.
- Scaling: where the focus is on rescaling data value range to a specific interval.
 - Min-Max normalisation
 - Decimal scaling

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Data Normalisation — Standardisation

Z-score Normalisation

- Rescale the features (or variables) so that they will have the properties of a standard normal distribution with

$$\mu = 0 \text{ \& } \sigma = 1.0$$

- How?

$$x' = \frac{x - \mu}{\sigma}$$


where

$$\mu = \frac{1}{n} \sum_i x_i$$

$$\sigma = \sqrt{\frac{1}{n} \sum_i (x_i - \mu)^2}$$



Data Normalisation — Standardisation

Z-score Normalisation



Data Normalisation — Standardisation

Z-score Normalisation



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Data Normalisation — Min-Max Scaling

Min-Max Scaling

- Rescale the features (or variables) that their values are in a specific range $[X'_{min}, X'_{max}]$
- How?

$$X_{scaled} = \frac{X - X_{min}}{X_{max} - X_{min}} (X'_{max} - X'_{min}) + X'_{min}$$

If the fixed range is $[0,1]$

$$X_{scaled} = \frac{X - X_{min}}{X_{max} - X_{min}}$$


Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Data Normalisation — Min-Max Scaling



Min-Max Scaling



We will end up with smaller standard deviations, which can suppress the effect of outliers

Data Normalisation — Min-Max Scaling


Min-Max Scaling



Data Normalisation — Standardisation vs Min-Max

“Standardisation or Min-Max scaling?": depends on the application


Assignment Project Exam Help




- PCA: standardisation
- Image processing: pixel intensities have to be normalised to fit within a certain range (i.e., 0 to 255 for the RGB colour range)
- ANN: data that on a 0-1 scale

Data Normalisation — Standardisation vs Min-Max

Transformed NON-standardized training dataset after PCA




Transformed standardized training dataset after PCA




Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Data Normalisation — Standardisation vs Min-Max

Transformed NON-standardized training dataset after PCA



Transformed min_max scaled training dataset after PCA



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Data Normalisation — Decimal Scaling

- Shift the decimal place of a numeric value such that the maximum absolute value will be always less than 1

- How:

$$x' = \frac{x}{10^c}$$

where c is the smallest integer such that $\max(|x'|) < 1$.

- Example:

- $-500 \leq x \leq 45 \Rightarrow -0.500 \leq x \leq 0.045$
- How to convert?

Add WeChat powcoder

Data Normalisation — Decimal Scaling

- Shift the decimal place of a numeric value such that the maximum absolute value will be always less than 1

- How:

$$x' = \frac{x}{10^c}$$

where c is the smallest integer such that $\max(|x'|) < 1$.

- Example:

- $-500 \leq x \leq 45 \Rightarrow -0.500 \leq x \leq 0.045$
 - How to convert?

$$x_{max} = \max(\text{abs}(x)) = 500$$

$$c = \text{ceil}(\log_{10}(x_{max})) = 3.0$$

$$x' = 10.0^{3.0} = x / 1000.0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Outline

Assignment Project Exam Help

1 Data Transformation

- Data Normalisation/Scaling
- Transformation by generating new features
- Nominal to Numeric Transformation

<https://powcoder.com>

2 Data Discretisation

3 Feature Engineering & Data Sampling

Add WeChat powcoder

4 Summary

Data Transformation

Data Transformation is a process of re-expressing data in a form that is more suitable for analysis.

- Reasons for data transformation

- ▶ Fix skewness in data
- ▶ Enhance data visualisation
- ▶ Better interpretability
- ▶ Improve the compatibility of data with assumptions underlying a modelling process

- Methods: different mathematical formulas from statistical analysis

- ▶ linear transformation
- ▶ log transformation
- ▶ Power transformation
- ▶ Box-Cox Transformation
- ▶ others: Quadratic transformation, (non-)polynomial approximation of transformation, rank transformation

Data Transformation

Linear Transformation

- Linear transformation preserves the linear relationship between the features.
- Aggregate the information contained in various features
- Linear transformation function: Given a subset of the complete set of attributes, X_1, X_2, \dots, X_m ,

$$X_{agg} = w_0 + \sum_{i=1}^m w_i X_i$$

- Examples:
 - ▶ Celsius to Fahrenheit
 - ▶ Miles to Kilometers
 - ▶ Inches to Centimeters



Data Transformation

Log transformation makes highly skewed distributions less skewed

Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder



Data Transformation

Log transformation makes highly skewed distributions less skewed

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder


Data Transformation

Power Transformation

- Tukey and Mosteller's Bulging Rule:* The idea is that it might be interesting to transform x and y at the same time using some power functions:

$$Y_i^q = \beta_0 + \beta_1 X_i^p + \eta_i$$

<https://powcoder.com>



Data Transformation





Power Transformation

Assignment Project Exam Help

<https://powcoder.com>

$$Y_i^q = \beta_0 + \beta_1 X_i^p + \eta_i$$



Add WeChat powcoder



More information can be found <https://www.r-bloggers.com/tukey-and-mostellers-bulging-rule-and-ladder-of-powers/>



Data Transformation

Power Transformation




Data Transformation

Power Transformation



Data Transformation

Power Transformation



- Seek optimal transformations: learnt p and q with L-BFGS

Data Transformation

The Box-Cox Transformation: transforms a continuous variable into an almost normal distribution.

Assignment Project Exam Help


$$y = \begin{cases} x^\lambda & \text{if } \lambda \neq 0 \\ \log(x) & \text{if } \lambda = 0 \end{cases}$$


Figure: Examples of the Box-Cox transformation x'_λ versus x for $\lambda = -1, 0, 1$. In the second row, x'_λ is plotted against $\log(x)$. The red point is at $(1, 0)$.

Data Transformation


The Box-Cox Transformation: transforms a continuous variable into an almost normal distribution.

Assignment Project Exam Help

$$y = \begin{cases} x^\lambda & \text{if } \lambda \neq 0 \\ \log(x) & \text{if } \lambda = 0 \end{cases}$$

<https://powcoder.com>


Add WeChat powcoder



Data Transformation

The Box-Cox Transformation: transforms a continuous variable into an almost normal distribution.


Assignment Project Exam Help

$$y = \begin{cases} x^\lambda - 1 & \text{if } \lambda \neq 0 \\ \log(x) & \text{if } \lambda = 0 \end{cases}$$


Data Transformation

The Box-Cox Transformation: transforms a continuous variable into an almost normal distribution.


Assignment Project Exam Help

$$y = \begin{cases} x^\lambda - 1 & \text{if } \lambda \neq 0 \\ \log(x) & \text{if } \lambda = 0 \end{cases}$$


Data Transformation

The Box-Cox Transformation: transforms a continuous variable into an almost normal distribution.

Assignment Project Exam Help

$$y = \begin{cases} x^{\lambda} & \text{if } \lambda \neq 0 \\ \log(x) & \text{if } \lambda = 0 \end{cases}$$


Data Transformation

The Box-Cox Transformation: transforms a continuous variable into an almost normal distribution.

- With negative values in the attributes

$$y = \begin{cases} \frac{(x+c)^{\lambda-1}}{g^{\lambda}} & \text{if } \lambda \neq 0 \\ \frac{\log(x+c)}{g} & \text{if } \lambda = 0 \end{cases}$$

<https://powcoder.com>

where

- ▶ A parameter c : offset the negative values
- ▶ g : scale the resulting values, often considered as the geometric mean of the data.
- ▶ λ : greedily search λ so that the resulting attribute is as close as possible to the normal distribution.

Outline

Assignment Project Exam Help

- Data Transformation
 - Data Normalisation/Scaling
 - Transformation by generating new features
 - Nominal to Numeric Transformation

<https://powcoder.com>

2 Data Discretisation

3 Feature Engineering & Data Sampling

Add WeChat powcoder

4 Summary



Nominal to Numeric Transformation

- Why?

- ▶ Many machine learning algorithms only accept numeric value, while in many applications we have nominal attributes.

- How?

- ▶ Integer substitution: map each nominal value in the domain to numeric value
- ▶ Example: assume we have a color attribute with Red, Green, Blue and Yellow value

- Red \Rightarrow 1
- Green \Rightarrow 2
- Blue \Rightarrow 3
- Yellow \Rightarrow 4

- ▶ What's the problem?

- Implies a sort of ranking that doesn't actually exist in the original data.
- The outcome of the mining algorithms would be sensitive to the numeric values we choose to use.

Nominal to Numeric Transformation

- Why?

- Many machine learning algorithms only accept numeric value, while in many applications we have nominal attributes.

- How?

- Integer substitution: map each nominal value in the domain to numeric value
- Example: assume we have a color attribute with Red, Green, Blue and Yellow value
- One-hot encoding

Colour	Red	Green	Blue	Yellow
Yellow	0	0	0	1
Blue	0	0	1	0
Red	1	0	0	0
Yellow	0	0	0	1
Green	0	1	0	0
Red	1	0	0	0

Add WeChat powcoder

Outline

Assignment Project Exam Help

1 Data Transformation

2 Data Discretisation

3 Feature Engineering & Data Sampling

4 Summary

<https://powcoder.com>

Add WeChat powcoder

Data Discretisation

- The process of converting or partitioning continuous variables to discretised or nominal variables.

- ▶ Find concise data representation as categories which are adequate for the learning task retaining as much information in the original continuous attribute as possible
- ▶ Effects of discretisation

<https://powcoder.com>

- Smooth data
- Reduce noisy
- Reduce data size
- Enable specific methods using nominal data

Add WeChat powcoder

Data Discretisation

- Methods

- ▶ Binning
- ▶ Entropy discretisation
- ▶ Concept hierarchy

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Data Discretisation — Binning

- An unsupervised algorithm (doesn't care about the dependent variable) that splits ordered data into predefined number of bins.

- Two approaches

- ▶ Equal-width binning

- Given a range of values, $[x_{min}, x_{max}]$, we divide the value range into intervals with approximately same width, w

$$w = \frac{x_{max} - x_{min}}{n}$$

where n is the number of bins. Or you can specify the value of w

- ▶ Equal-depth binning

Divides the range into n intervals, each containing approximately same number of samples.

- Binning with

- ▶ mean value
 - ▶ median values
 - ▶ bin boundaries

Data Discretisation — Binning

- Task: discretise {34, 64, 88, 55, 94, 59, 10, 25, 44, 48, 69, 15}

- sort the values in ascending order

{10, 15, 25, 34, 44, 48, 55, 59, 64, 69, 88, 94}

- Equal-width binning with $n = 4$

{10, 15, 25}, {34, 44, 48}, {55, 59, 64, 69}, {88, 94}

- mean value

{16.6, 16.6, 16.6}, {42, 42, 42}, {61.75, 61.75, 61.75, 61.75}, {91, 91}

- median value

{15, 15, 15}, {44, 44, 44}, {61.5, 61.5, 61.5, 61.5}, {91, 91}

- boundaries

{10, 10, 25}, {34, 48, 48}, {55, 55, 69, 69}, {88, 94}

Data Discretisation — Binning

- Task: discretise {34, 64, 88, 55, 94, 59, 10, 25, 44, 48, 69, 15}

- sort the values in ascending order

{10, 15, 25, 34, 44, 48, 55, 59, 64, 69, 88, 94}

- Equal-depth binning with $n = 4$

{10, 15, 25}, {34, 44, 48}, {55, 59, 64}, {69, 88, 94}

- mean value

{16.6, 16.6, 16.6}, {42, 42, 42}, {59.3, 59.3, 59.3}, {83.6, 83.6, 83.6}

- median value

{15, 15, 15}, {44, 44, 44}, {59, 59, 59}, {88, 88, 88}

- boundaries

{10, 10, 25}, {34, 48, 48}, {55, 55, 64}, {69, 94, 94}

Data Discretisation — Binning

Advantage/disadvantage of each method:

- Equal-width binning
 - ▶ Is simple but sensitive to outliers
 - ▶ Not well handles skewed data
- Equal-depth binning
 - ▶ Scales well by keeping the distribution of the data

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Data Discretisation — Entropy Discretisation

- Entropy

Assignment Project Exam Help

$$H(X) = - \sum_{i=1}^n p(x_i) \log_b(p(x_i))$$

- ▶ Coin toss: $p(\text{head}) = p(\text{tail}) = 1/2$

$$H(X) = -p(\text{head}) \log_2(p(\text{head})) - p(\text{tail}) \log_2(p(\text{tail})) = -1 \times \frac{1}{2} \log_2(1/2) = 1$$

- ▶ Coin toss: $p(\text{head}) = 0.7$ and $p(\text{tail}) = 0.3$

$$H(X) = -0.7 \log_2(0.7) - 0.3 \log_2(0.3) = 0.881 < 1$$

- Entropy discretisation: a method takes into account the class labels in discretisation.

Data Discretisation — Entropy Discretisation

- Entropy discretisation: a method takes into account the class labels in discretisation.

► Ideas

- Data should be split into intervals that maximise the information, measured by Entropy,
- Partitioning should not be too fine-grained, to avoid over-fitting.

► Algorithm

<https://powcoder.com>

1. Calculate Entropy for your data...

2. For each potential split in your data...

- Calculate Entropy in each potential bin

Find the net entropy for your split

Calculate entropy gain

Add WeChat powcoder

3. Select the split with the highest entropy gain

4. Recursively (or iteratively in some cases) perform the partition on each split until a termination criteria is met

- Terminate once you reach a specified number of bins
- Terminate once entropy gain falls below a certain threshold.

Figure is adapted from <http://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

Data Discretisation — Entropy Discretisation

Hours Studied

A on Test

4	N
5	Y
8	N
12	Y
15	Y

<https://powcoder.com>

Figure is adapted from <https://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- Entropy of the data:

$$H(X) = -\frac{3}{5} \log_2\left(\frac{3}{5}\right) - \frac{2}{5} \log_2\left(\frac{2}{5}\right) = 0.529 + 0.442 = 0.971$$

Data Discretisation — Entropy Discretisation

Hours Studied

A on Test

4

N

5

Y

6

N

12

Y

15

Y

Assignment Project Exam Help

<https://powcoder.com>

Figure is adapted from <http://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- Split at 4.5

$$H(X \leq 4.5) = -\frac{1}{1} \log_2(1) - \frac{0}{1} \log_2(0) = 0 + 0 = 0$$

$$H(X > 4.5) = -\frac{3}{4} \log_2\left(\frac{3}{4}\right) - \frac{1}{4} \log_2\left(\frac{1}{4}\right) = 0.311 + 0.5 = 0.811$$

$$H(X_{new}) = H(X \leq 4.5) + H(X > 4.5) = \frac{1}{5}0 + \frac{4}{5}0.811 = 0.6488$$

$$G(X_{new}) = 0.971 - 0.6488 = 0.322$$

Data Discretisation — Entropy Discretisation

Hours Studied

A on Test

4

N

5

Y

6

N

12

Y

15

Y

Assignment Project Exam Help

<https://powcoder.com>

Figure is adapted from <http://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- Split at 6.5

$$H(X \leq 6.5) = -\frac{1}{2} \log_2\left(\frac{1}{2}\right) - \frac{1}{2} \log_2\left(\frac{1}{2}\right) = 1$$

$$H(X > 6.5) = -\frac{2}{3} \log_2\left(\frac{2}{3}\right) - \frac{1}{3} \log_2\left(\frac{1}{3}\right) = 0.918$$

$$H(X_{new}) = H(X \leq 6.5) + H(X > 6.5) = \frac{2}{5}1 + \frac{3}{5}0.917 = 0.951$$

$$G(X_{new}) = 0.971 - 0.951 = 0.02$$

Data Discretisation — Entropy Discretisation

Hours Studied

A on Test

4

N

5

Y

6

N

12

Y

15

Y

Assignment Project Exam Help

<https://powcoder.com>

Figure is adapted from <http://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- Split at 10

$$H(X \leq 10) = -\frac{1}{3} \log_2\left(\frac{1}{3}\right) - \frac{2}{3} \log_2\left(\frac{2}{3}\right) = 0.918$$

$$H(X > 10) = -\frac{2}{2} \log_2\left(\frac{2}{2}\right) - \frac{0}{2} \log_2\left(\frac{0}{2}\right) = 0$$

$$H(X_{new}) = H(X \leq 10) + H(X > 10) = \frac{3}{5} 0.917 + \frac{2}{5} 0 = 0.551$$

$$G(X_{new}) = 0.971 - 0.551 = 0.42$$

Data Discretisation — Entropy Discretisation

Hours Studied

A on Test

4	N
5	Y
8	N
12	Y
15	Y

Assignment Project Exam Help

<https://powcoder.com>

Figure is adapted from <http://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- Split at 13.5

$$H(X \leq 13.5) = -\frac{3}{4} \log_2\left(\frac{3}{4}\right) - \frac{1}{4} \log_2\left(\frac{1}{4}\right) = 1.0$$

$$H(X > 13.5) = -\frac{1}{1} \log_2\left(\frac{1}{1}\right) - \frac{0}{1} \log_2\left(\frac{0}{1}\right) = 0$$

$$H(X_{new}) = H(X \leq 13.5) + H(X > 13.5) = \frac{4}{5} 1.0 + \frac{1}{5} 0 = 0.8$$

$$G(X_{new}) = 0.971 - 0.8 = 0.171$$

Data Discretisation — Entropy Discretisation

Hours Studied	A on Test
4	N
5	Y
8	N
12	Y
15	Y

<https://powcoder.com>

Figure is adapted from <https://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- Split at 4.5: $G(X_{new}) = 0.322$
- Split at 5.5: $G(X_{new}) = 0.02$
- Split at 10: $G(X_{new}) = 0.42$
- Split at 13.5: $G(X_{new}) = 0.171$

Add WeChat powcoder

Data Discretisation — Entropy Discretisation

Hours Studied

A on Test

4	N
5	Y
8	N
12	Y
15	Y

<https://powcoder.com>

Figure is adapted from <https://kevinmeurer.com/a-simple-guide-to-entropy-based-discretization/>

- When to stop the algorithm

- ▶ Terminate when a specified number of bins has been reached
- ▶ Terminate when information gain falls below a certain threshold.

Concept Hierarchy for numerical data

A simple 3-4-5 rule can be used to segment numeric data (attribute values) into relatively uniform, “natural” intervals.


- If an interval covers 3, 6, 7 or 9 distinct values at the most significant digit, partition the range into 3 equi-width.
- If it covers 2, 4, or 8 distinct values at the most significant digit, partition the range into 4 intervals
- If it covers 1, 5, or 10 distinct values at the most significant digit, partition the range into 5 intervals

<https://powcoder.com>

Add WeChat powcoder

Segmentation by natural partitioning

Assignment Project Exam Help




Step 2 $\text{msd} = 1,000,000$ $\text{LOW}' = -\$1,000,000$ $\text{HIGH}' = \$2,000,000$

Step 3 $(-\$1,000,000 \dots \$2,000,000)$

$(-\$1,000,000 \dots \$0]$ $(\$0 \dots \$1,000,000]$ $(\$1,000,000 \dots \$2,000,000]$

Step 4 $(-\$1,000,000 \dots \$5,000,000)$

$(-\$400,000 \dots \$0]$ $(\$0 \dots \$1,000,000]$ $(\$1,000,000 \dots \$2,000,000]$ $(\$2,000,000 \dots \$5,000,000]$



Outline

Assignment Project Exam Help

1 Data Transformation

2 Data Discretisation

3 Feature Engineering & Data Sampling

4 Summary

<https://powcoder.com>

Add WeChat powcoder

Feature Engineering

- Feature extraction (or generation)

- ▶ Generate new features from raw data or other features

- ▶ Goals

- Produce more meaningful/descriptive/discriminant features

- Feature selection

- ▶ Select a subset of available features based on some criteria

- ▶ Goals

- Remove irrelevant data
- Increase predictive accuracy of learned models
- Improve learning efficiency
- Reduce the model complexity and increase its interpretability

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Feature Subset Selection

Feature subset selection reduces the data set size by removing irrelevant or redundant features.

- Goal: find a minimum set of attributes such that the resulting probability distribution of the data classes is as close as possible to the original distribution obtained using all attributes

- Methods

- ▶ Stepwise forward selection
- ▶ Stepwise backward elimination.
- ▶ Combination of forward selection and backward elimination
- ▶ Decision tree induction.

<https://powcoder.com>
Add WeChat powcoder

Feature Subset Selection


Forward selection	Backward elimination	Decision tree induction
<p>Initial attribute set: $\{A_1, A_2, A_3, A_4, A_5, A_6\}$</p> <p>Initial reduced set: $\{\}$ $\Rightarrow \{A_1\}$ $\Rightarrow \{A_1, A_4\}$ \Rightarrow Reduced attribute set: $\{A_1, A_4, A_6\}$</p>	<p>Initial attribute set: $\{A_1, A_2, A_3, A_4, A_5, A_6\}$</p> <p>$\Rightarrow \{A_1, A_3, A_4, A_5, A_6\}$ $\Rightarrow \{A_1, A_4, A_5, A_6\}$ \Rightarrow Reduced attribute set: $\{A_1, A_4, A_6\}$</p>	<p>Initial attribute set: $\{A_1, A_2, A_3, A_4, A_5, A_6\}$</p>  <pre> graph TD A4["A4?"] -- Y --> A1["A1?"] A4 -- N --> A6["A6?"] A1 -- Y --> C1_1((Class 1)) A1 -- N --> C1_2((Class 2)) A6 -- Y --> C2_1((Class 1)) A6 -- N --> C2_2((Class 2)) </pre> <p>\Rightarrow Reduced attribute set: $\{A_1, A_4, A_6\}$</p>

Figure is from "Data mining: know it all"

Data Sampling Methods

- Sampling methods are used to choose a representative subset of the data

- Why?

- ▶ Reduce the volume of data
- ▶ Fix imbalance distribution
- ▶ Creating training, validation, testing sets.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Data Sampling Methods

- Methods: Suppose that a large dataset, D , contains N tuples, the ways we can used to do data reduction:

- Simple random sample without replacement (**SRSWOR**) of size s :

Draw s of the N tuples from D ($s < N$), where the probability of drawing any tuple in D is $1/N$

- Simple random sample with replacement (**SRSWR**) of size s .

Similar to SRSWOR, except that after a tuple is drawn, it is placed back in D so that it may be drawn again.




Figure is from "Data mining: know it all"

Data Sampling Methods

- Methods: Suppose that a large dataset, D , contains N tuples, the ways we can used to do data reduction:

Stratified sample

If D is divided into mutually disjoint parts called strata, a stratified sample of D is generated by obtaining an SRS at each stratum

T38	youth
T256	youth
T307	youth
T391	youth
T96	middle_aged
T117	middle_aged
T138	middle_aged
T263	middle_aged
T290	middle_aged
T308	middle_aged
T326	middle_aged
T387	middle_aged
T69	senior
T284	senior

T38	youth
T391	youth
T117	middle_aged
T138	middle_aged
T290	middle_aged
T326	middle_aged
T69	senior

Figure is from "Data mining: know it all"

Summary

- Data transformation:
 - ▶ Normalisation/Scaling
 - ▶ Data transformation generating new features
 - ▶ Nominal to numerical transformation
- Data Discretization
- Feature selection and data sampling

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder