



MONASH
University

Assignment Project Exam Help

MONASH
INFORMATION
TECHNOLOGY

Add WeChat powcoder

Database Design II: Logical Modelling

Lindsay Smith

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Add WeChat powcoder

Revisit - Week 3 Conceptual Model

Keys only



Assignment Project Exam Help


Revisit - Week 3 Conceptual Model

All attributes

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Add WeChat powcoder

Summary of Terminologies at Different Levels

Conceptual	Logical	Physical
Entity	Relation	Table
Attribute	Attribute	Column
Instance	Tuple	Row
Identifier	Primary Key	Primary Key
Relationship	---	---
---	Foreign Key	Foreign Key

Assignment Project Exam Help

Add WeChat powcoder

Properties of Relations

- Some properties to be considered:
 - Each relation has a unique name in the database.
 - Each row is unique - i.e. duplicate tuples are not allowed.
 - Each column has a (meaningful) name.
 - The order of attributes is immaterial.
 - The order of tuples is immaterial.
 - The entries are single-valued (**atomic**) - each cell contains a single entry.
 - **Multi-valued** and **composite attributes**???

Assignment Project Exam Help

Add WeChat powcoder

Transforming ER diagrams into relations (mapping conceptual level to logical level)

- **The steps are:**
 - Map strong (regular) entities
 - Map weak entities
 - Map binary relationships
 - Map associative entities
 - Map unary relationships
 - Map ternary relationships
 - Map supertype/subtype relationships (is not part of this unit).

Assignment Project Exam Help

Add WeChat powcoder

Q1. The relational model requires that each cell in a relation is single-valued (atomic). Considering this requirement, what construct in an ER diagram cannot be implemented directly (without further steps) in the relational model (logical level)?

- <https://powcoder.com>
- Add WeChat powcoder
- a. Composite key.
 - b. Composite attribute.
 - c. Multi-valued attribute.
 - d. Dependent attribute.
 - e. More than one option is correct.

Assignment Project Exam Help

Add WeChat powcoder


Map Regular Entities

▪ Composite Attributes

- When the regular entity type contains a **composite attribute**, only the simple component attributes of the composite attribute are included in the new relation.
- Compared to composite attributes, simple attributes not only improve data accessibility but also help in maintaining data quality

Assignment Project Exam Help

Add WeChat powcoder Mapping a Composite Attribute



CUSTOMER	
P	* cust_id
	* cust_name
	* cust_street
	* cust_city
	* cust_state
	* cust_zip

EMPLOYEE	
P	* emp_no
	emp_fname
	emp_lname
	* emp_street
	* emp_town
	* emp_pcode
	* emp_dob
	emp_taxno

Monash Software Case Study

* = not null (must have value)

Assignment Project Exam Help

Add WeChat powcoder

Map Regular Entities


▪ Multivalued Attribute

- When the regular entity type contains a **multivalued attribute**, two new relations are created.
- The first relation contains all the attributes of the entity type except the multivalued attribute itself.
- The second relation contains two attributes that form the PK. One of the attributes is the PK from the first relation, which becomes the FK in the second relation and the other is the multivalued attribute.
- There can also be non key attributes in the second relation depending upon the data requirements.

Assignment Project Exam Help

Add WeChat powcoder

Mapping a Multi valued Attribute



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Is there a better solution than the one shown above?


Assignment Project Exam Help

Revisit - Week 3 Conceptual Model - IMPROVED

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





All attributes

Assignment Project Exam Help

Add WeChat powcoder Mapping a Weak Entity

- For each weak entity type, create a new relation and include all of the simple attributes as attributes of this relation. The PK of the identifying relation is also included as the FK in this new relation.



Assignment Project Exam Help

Add WeChat powcoder


Conceptual

Logical

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Assignment Project Exam Help

Add WeChat powcoder

Mapping a 1:M Binary Relationship



Assignment Project Exam Help

Add WeChat powcoder

Q2. Where would you place the Foreign Key when you map this ER diagram into the relational model?



<https://powcoder.com>

- a. CUSTOMER
- b. ORDER
- c. Both CUSTOMER and ORDER.
- d. None, no FK is needed.

Assignment Project Exam Help

Add WeChat powcoder

Map Binary Relationships (1:M)



<https://powcoder.com>

Add WeChat powcoder

For each 1:M binary relationship, first create a relation for each of the two entity types participating in the relationship. Then include the PK attribute (or attributes) of the entity on the one-side of the relationship as the FK on the many-side of the relationship.

Assignment Project Exam Help

Add WeChat powcoder


Conceptual

Logical

Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder



Assignment Project Exam Help

Add WeChat powcoder


Mapping a M:N Binary Relationship



Assignment Project Exam Help

Add WeChat powcoder

Q3. What will be the Primary Key of the new created relation resulting from mapping this ER model at the conceptual level into a relational model?



Add WeChat powcoder

- The primary key of the ORDER table.
- The primary key of the PRODUCT table.
- The combination of primary keys of ORDER and PRODUCT.


Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Add WeChat powcoder

Map Binary Relationship (M:N)

- For a M:N binary relationship
 - First create a relation for each of the two entity types participating in the relationship.
 - Then create a new relation and include as foreign key attributes, the PK attribute (or attributes) for each of the two participating entity types. These attributes become the PK of the new relation.
 - If there are any nonkey attributes associated with the M:N relationship, they are also included in the new relation.

Assignment Project Exam Help

Add WeChat powcoder


Conceptual

Logical

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Assignment Project Exam Help

Add WeChat powcoder


Mapping an associative entity with an Identifier




Assignment Project Exam Help

Add WeChat powcoder


Mapping a 1:1 Binary Relationship



NURSE



CARE CENTRE



Assignment Project Exam Help

Add WeChat powcoder

Q4. Where would you place the Foreign Key when mapping this ER diagram into a relational model?



Add WeChat powcoder

- A. NURSE
- B. CARE CENTRE
- C. Both NURSE and CARE CENTRE
- D. No FK is needed.

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help



Assignment Project Exam Help

Add WeChat powcoder

Map Binary Relationship (1:1)

- Create two relations, one for each of the participating entity types.
 - The primary key (PK) on the mandatory side of the relationship becomes the foreign key (FK) on the optional side of the relationship.
 - where both are optional place the FK on the side which causes the fewest nulls
 - Special case: *1:1 total* relationship (mandatory participation on both sides)
 - Consider consolidating the two entity types into one relation

Assignment Project Exam Help

Add WeChat powcoder


Conceptual

Logical

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Assignment Project Exam Help

Map unary relationships

- Unary Relationship is a relationship between the instances of a single entity type.
- **Unary 1:M Relationship** – A relation is created for the entity type. Add a FK within the same relation that references the PK of the relation. A recursive foreign key is a FK in a relation that references the PK values of the same relation.
- **Unary M:N Relationship** – Two relations are created, one for the entity type in the relationship and the other as the associative relation to represent the M:N relationship itself. The PK of the associative relation consists of two attributes (with different names) taking their values from the PK of the other relation.

Assignment Project Exam Help

Add WeChat powcoder Mapping a 1:M Unary Relationship



Assignment Project Exam Help

Add WeChat powcoder


Conceptual

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Logical



Assignment Project Exam Help

Add WeChat powcoder

Q5. How many relations/tables and relationships do we need to implement the model below into a relational model?





- a. 2 tables, 1 relationship
- b. 2 tables, 2 relationships
- c. 3 tables, 2 relationships
- d. 4 tables, 3 relationships

Assignment Project Exam Help

Add WeChat powcoder

Mapping a M:N Unary Relationship



Assignment Project Exam Help

SQL Developer Data Modeler

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


The screenshot displays the SQL Developer Data Modeler interface. On the left, the 'Browser' pane shows the project structure for 'MonashSoftware', including Logical Models, Relational Models, and Domains. The main workspace is divided into two panes: 'Logical (MonashSoftware)' and 'Relational_1 (MonashSoftware)'. The 'Logical' pane shows a logical model with entities 'TEAM', 'EMPLOYEE_SKILL', and 'SKILL'. The 'Relational_1' pane shows a relational model with tables 'TEAM', 'EMPLOYEE_SKILL', 'SKILL', 'TRAINING', 'EMPLOYEE', and 'FAMILY_MEMBER'. The 'DDL File Editor - Oracle Database 11g' pane on the right shows the DDL code for the 'employee' table, including constraints and comments.

```
DDL File Editor - Oracle Database 11g
Oracle Database 11g Relational_1 Generate

11 DROP TABLE employee_training CASCADE CONSTRAINTS;
12 DROP TABLE family_member CASCADE CONSTRAINTS;
13 DROP TABLE skill CASCADE CONSTRAINTS;
14 DROP TABLE team CASCADE CONSTRAINTS;
15 DROP TABLE training CASCADE CONSTRAINTS;
16
17 CREATE TABLE employee (
18   emp_no NUMBER(5) NOT NULL,
19   emp_fname VARCHAR2(30),
20   emp_lname VARCHAR2(30),
21   emp_street VARCHAR2(50) NOT NULL,
22   emp_town VARCHAR2(30) NOT NULL,
23   emp_pcode CHAR(4) NOT NULL,
24   emp_dob DATE NOT NULL,
25   emp_taxno VARCHAR2(20),
26   team_no NUMBER(3),
27   mentor_no NUMBER(5),
28 );
29
30 COMMENT ON COLUMN employee.emp_no IS
31 'Employee identifier';
32
33 COMMENT ON COLUMN employee.emp_fname IS
34 'Employees first name';
35
```

Assignment Project Exam Help

Adding surrogate keys



Surrogate PK's may be added on the logical model provided they are justified (include in documentation / assumptions)

<https://powcoder.com>

Potential problem:

Need to ensure that the identified key from the conceptual model (emp_no, training_code, et_date_completed) will still remain unique

- define a unique index on attributes of key


et_no	emp_no	training_code	et_date_completed
1	101	ORA01	1-Oct-2016
2	101	ORA01	1-Oct-2016
3	101	ORA01	1-Oct-2016

Assignment Project Exam Help

Add WeChat powcoder

Ternary Relationships

Ternary




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

modelled as

binary:



Assignment Project Exam Help

Add WeChat powcoder


Ternary Relationships – model as binary relationships?

- Ternary represents more information than three binary relationships
- For example - Supplier 1 supplies Project 2 with Part 3 -
 - ternary <https://powcoder.com>
 - instance (supplier 1, project 2, part 3) exists
 - binaries Add WeChat powcoder
 - instances
 - (supplier1, project 2) (project 2, part 3) (supplier 1, part 3)
 - BUT does not imply (supplier 1, project 2, part 3)
- How then do we map such relationships?

Assignment Project Exam Help

Add WeChat powcoder

Mapping a Ternary Relationship



Assignment Project Exam Help


Add WeChat powcoder

Map Ternary (and n-ary) Relationships

- Ternary relationship should be converted to an associative entity.
 - To map an associative entity type that links three regular entity types, an associative relation is created.
 - The default PK of this relation consists of the three PK attributes for the participating entity types.
 - Any attributes of the associative entity type become attributes of the new relation.

Assignment Project Exam Help

Add WeChat powcoder Mapping a Ternary Relationship



Assignment Project Exam Help

Add WeChat powcoder

Reference

Hoffer, J. A. , Prescott, M. B. & McFadden, F. R.

“Modern Database Management”

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder