

Assignment Project Exam Help

Graphs Traversal and Topological Sort
<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Goal: visit each node in a graph in a systematic way

Non trivial because:

- Non-linear
- Non-hierarchical

<https://powcoder.com>

Add WeChat powcoder

Breadth-first Search

Exploring one layer at a time

- Nodes are visited in order of increasing distance from s
 - First visit nodes at distance 1 from s
 - Then visit nodes at distance 2 from s
 - Continue until all nodes have been visited.

How can this be achieved?

- Put nodes that have been discovered but not yet explored in a **queue**
- Keep a record of which nodes have been discovered
- Construct a search tree that records search

Breadth-first Search

BFS(G, s) :

let Q be a queue containing just the node s

let $discovered(s) = true$

let $discovered(v) = false$ for all $v \in V - \{s\}$

let $T = (V, \{\})$

while Q is not empty

remove v from the front of Q

for each edge $\{v, w\}$ in E where not $discovered(w)$

let $discovered(w) = true$

add w to the back of Q


add edge $\{v, w\}$ to edges in T

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Illustration of BFS




Run BFS starting at v_7

Illustration of BFS




Initialize Q

Illustration of BFS




Let $discovered(v_7) = true$

Illustration of BFS




Remove v_7 from front of Q

Illustration of BFS




Consider edge $\{v_7, v_4\}$ since v_4 not yet discovered

Illustration of BFS




Let $discovered(v_4) = true$, add $\{v_7, v_4\}$ to T and v_4 to Q

Illustration of BFS




Consider edge $\{v_7, v_5\}$ since v_5 not yet discovered

Illustration of BFS




Let $discovered(v_5) = true$, add $\{v_7, v_5\}$ to T and v_5 to Q

Illustration of BFS




No more edges from v_7

Illustration of BFS




Remove v_4 from front of Q

Illustration of BFS




Consider edge $\{v_4, v_6\}$ because v_6 not yet discovered

Illustration of BFS




Let $discovered(v_6) = true$, add $\{v_4, v_6\}$ to T and v_6 to Q

Illustration of BFS




Don't consider $\{v_4, v_7\}$ because v_7 already discovered

Illustration of BFS




No more edges from v_4

Illustration of BFS




Remove v_5 from front of Q

Illustration of BFS




Consider edge $\{v_5, v_2\}$ because v_2 not yet discovered

Illustration of BFS




Let $discovered(v_2) = true$, add $\{v_5, v_2\}$ to T and v_2 to Q

Illustration of BFS




Consider $\{v_5, v_8\}$ because v_8 not yet discovered

Illustration of BFS




Let $discovered(v_8) = true$, add $\{v_5, v_8\}$ to T and v_8 to Q

Illustration of BFS




Don't consider $\{v_5, v_7\}$ because v_7 already discovered

Illustration of BFS




No more edges from v_5

Illustration of BFS




Remove v_6 from front of Q

Illustration of BFS




Consider edge $\{v_6, v_3\}$ because v_3 not yet discovered

Illustration of BFS




Let $discovered(v_3) = true$, add $\{v_6, v_3\}$ to T and v_3 to Q

Illustration of BFS




Don't consider $\{v_6, v_4\}$ because v_4 already discovered

Illustration of BFS




Don't consider $\{v_6, v_8\}$ because v_8 already discovered

Illustration of BFS




No more edges from v_6

Illustration of BFS




Remove v_2 from front of Q

Illustration of BFS




Consider edge $\{v_2, v_1\}$ because v_1 not yet discovered

Illustration of BFS




Let $discovered(v_1) = true$, add $\{v_2, v_1\}$ to T and v_1 to Q

Illustration of BFS




Don't consider $\{v_2, v_3\}$ because v_3 already discovered

Illustration of BFS




Don't consider $\{v_2, v_5\}$ because v_5 already discovered

Illustration of BFS




No more edges from v_2

Illustration of BFS




Remove v_8 from front of Q

Illustration of BFS




Don't consider $\{v_8, v_5\}$ because v_5 already discovered

Illustration of BFS




Don't consider $\{v_8, v_6\}$ because v_6 already discovered

Illustration of BFS




No more edges from v_8

Illustration of BFS



Remove v_3 from front of Q

Illustration of BFS



Don't consider $\{v_3, v_1\}$ because v_1 already discovered

Illustration of BFS






Illustration of BFS




No more edges from v_3

Illustration of BFS




Remove v_1 from front of Q

Illustration of BFS




Don't consider $\{v_1, v_2\}$ because v_2 already discovered

Illustration of BFS




Don't consider $\{v_1, v_3\}$ because v_3 already discovered

Illustration of BFS




No more edges from v_1

Illustration of BFS




Q is empty so traversal complete

Illustration of BFS




Here is the breadth first search tree for this run

Illustration of BFS



Same tree, but arranged in more usual way

Assignment Project Exam Help




Draw the breadth-first search tree
Consider vertices in order of subscript
Begin traversal at v_1

<https://powcoder.com>

Add WeChat powcoder

Example for You

Draw the breadth-first search tree
Consider vertices in order of subscript
Begin traversal at v_1



Breadth-first Search

BFS(G, s) :

let Q be a queue containing just the node s

let $discovered(s) = true$

let $discovered(v) = false$ for all $v \in V - \{s\}$

let $T = (V, \{\})$

while Q is not empty

remove v from the front of Q

for each edge $\{v, w\}$ in E where not $discovered(w)$

let $discovered(w) = true$

add w to the back of Q


add edge $\{v, w\}$ to edges in T

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Components of Graphs



Is this one or two graphs?

Components of Graphs




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


This is one of the components

Components of Graphs



And this is the other components

Components of Graphs



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


But remember, its all one graph

Assignment Project Exam Help


Definition of a component of a graph $G = (V, E)$

- A subset of the vertices in G and all associated edges from G
- Must be connected
 - path between any pair of vertices
- Must be maximal
 - cannot be enlarged and remain connected

<https://powcoder.com>
Add WeChat powcoder



Question: Suppose BFS run on this graph starting at v_3 ?



Answer: BFS would find only nodes in the component containing v_3

Assignment Project Exam Help

BFS(G) :

let discovered(v) = false for all $v \in V$

let $T = (V, \{\})$

for each $v \in V$

if not discovered(v)

BFS(G, v)

Add WeChat powcoder

Revised BFS Algorithm (cont.)

BFS(G, s):

let Q be a queue containing just the node s

let $discovered(s) = true$

while Q is not empty

remove v from the front of Q

for each edge $\{v, w\}$ in E where not $discovered(w)$

let $discovered(w) = true$

add w to the back of Q

add edge $\{v, w\}$ to edges in E

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- T can consist of more than one tree
- One tree in T for each component of G
- T is actually Breadth-First Search Forest
- Number of edges in T will be $n - k$
— where G contains k components

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- What is a good measure of progress?
- Number of vertices whose edges have been considered
- Increases by 1 on each iteration of the *while* loop
- This means that there n iterations of the loop
- How much time spent on each iteration?
- Depends on number of edges to be considered

<https://powcoder.com>

Add WeChat powcoder

Running Time of BFS (cont.)

Assignment Project Exam Help

- Number of steps within loop is $\Theta(\max(1, \text{outdegree}(v)))$
- $\text{outdegree}(v)$ is number of edges from v to some other vertex w
- We know that in total there are m edges to consider
- Total across all iterations of loop:

<https://powcoder.com>

$$\sum_{v \in V} \max(1, \text{outdegree}(v)) = \Theta(n + m)$$

Add WeChat powcoder

Depth-first Search

A different strategy for systematic exploration of a graph

- Uses a **stack** to hold discovered nodes
- Record nodes as *explored* once popped from stack
- Only explore nodes taken from stack that haven't already been explored
- Record edges in search tree by remembering the latest parent of each node
- Parent of a node can change up to the point it is explored

Depth-first Search

DFS(G, s) :

let S be a stack containing just the node s

let $\text{explored}(v) = \text{false}$ for all $v \in V$

while S is not empty

pop v from the top of S

if not $\text{explored}(v)$ then

for each edge $\{v, w\}$ in E where not $\text{explored}(w)$

push w onto S

let $\text{parent}(w) = v$


let $\text{explored}(v) = \text{true}$

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Illustration of DFS




Run DFS starting at v_7

Illustration of DFS




Initialize S

Illustration of DFS




Pop v_7 from top of S

Illustration of DFS




v_7 not yet explored so let's explore it

Illustration of DFS




Consider edge $\{v_7, v_4\}$ since v_4 not yet explored

Illustration of DFS




Push v_4 onto S and let $parent(v_4) = v_7$

Illustration of DFS




Consider edge $\{v_7, v_5\}$ since v_5 not yet explored

Illustration of DFS




Push v_5 onto S and let $parent(v_5) = v_7$

Illustration of DFS




No more edges from v_7

Illustration of DFS




Let $explored(v_7) = true$

Illustration of DFS




Pop v_5 from top of S

Illustration of DFS




v_5 not yet explored so let's explore it

Illustration of DFS




Consider edge $\{v_5, v_2\}$ since v_2 not yet explored

Illustration of DFS




Push v_2 onto S and let $parent(v_2) = v_5$

Illustration of DFS




Consider $\{v_5, v_8\}$ since v_8 not yet explored

Illustration of DFS




Push v_8 onto S and let $parent(v_8) = v_5$

Illustration of DFS




Don't consider $\{v_5, v_7\}$ because v_7 already explored

Illustration of DFS




No more edges from v_5

Illustration of DFS




Let $explored(v_5) = true$

Illustration of DFS




Pop v_8 from top of S

Illustration of DFS




v_8 not yet explored so let's explore it

Illustration of DFS




Don't consider $\{v_8, v_5\}$ because v_5 already explored

Illustration of DFS




Consider edge $\{v_8, v_6\}$ since v_6 not yet explored

Illustration of DFS




Push v_6 onto S and let $parent(v_6) = v_8$

Illustration of DFS




No more edges from v_8

Illustration of DFS




Let $explored(v_8) = true$

Illustration of DFS




Pop v_6 from top of S

Illustration of DFS




v_6 not yet explored so let's explore it

Illustration of DFS




Consider edge $\{v_6, v_4\}$ since v_4 not yet explored

Illustration of DFS




Push v_4 onto S and let $parent(v_4) = v_6$

Illustration of DFS




Don't consider $\{v_6, v_8\}$ because v_8 already explored

Illustration of DFS




No more edges from v_6

Illustration of DFS




Let $explored(v_6) = true$

Illustration of DFS



Pop v_4 from top of S


Illustration of DFS



Add WeChat powcoder


v_4 not yet explored so let's explore it

Illustration of DFS




Don't consider $\{v_4, v_6\}$ because v_6 already explored

Illustration of DFS




Don't consider $\{v_4, v_7\}$ because v_7 already explored

Illustration of DFS




No more edges from v_4

Illustration of DFS




Let $explored(v_4) = true$

Illustration of DFS




Pop v_2 from top of S

Illustration of DFS




v_2 not yet explored so let's explore it

Illustration of DFS




Consider edge $\{v_2, v_1\}$ since v_1 not yet explored

Illustration of DFS




Push v_1 onto S and let $parent(v_1) = v_2$

Illustration of DFS




Consider edge $\{v_2, v_3\}$ since v_3 not yet explored

Illustration of DFS




Push v_3 onto S and let $parent(v_3) = v_2$

Illustration of DFS




Don't consider $\{v_2, v_5\}$ because v_5 already explored

Illustration of DFS



No more edges from v_2


Illustration of DFS



Add WeChat powcoder


Let $explored(v_2) = true$

Illustration of DFS




Pop v_3 from top of S

Illustration of DFS



v_3 not yet explored so let's explore it


Illustration of DFS



Add WeChat powcoder


Consider edge $\{v_3, v_1\}$ since v_1 not yet explored

Illustration of DFS



Push v_1 onto S and let $parent(v_1) = v_3$

Illustration of DFS



Don't consider $\{v_3, v_2\}$ because v_2 already explored

Illustration of DFS






Illustration of DFS




Let $explored(v_3) = true$

Illustration of DFS




Pop v_1 from top of S

Illustration of DFS




v_1 not yet explored so let's explore it

Illustration of DFS



Don't consider $\{v_1, v_2\}$ because v_2 already explored

Illustration of DFS



Don't consider $\{v_1, v_3\}$ because v_3 already explored

Illustration of DFS






Illustration of DFS




Let $explored(v_1) = true$

Illustration of DFS




Pop v_1 from top of S

Illustration of DFS




v_1 already explored so no need to consider it

Illustration of DFS




Pop v_4 from top of S

Illustration of DFS




v_4 already explored so no need to consider it

Illustration of DFS



S is empty so search is complete

Illustration of DFS




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Obtain tree by reversing directionality of all parent edges

Illustration of DFS



Re-position nodes for clarity

Illustration of DFS




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help



Draw the depth-first search tree

Consider vertices in order of subscript

Begin traversal at v_1


<https://powcoder.com>

Add WeChat powcoder

Example for You

Draw the depth-first search tree

Consider vertices in order of subscript
Begin traversal at v_1



DFS Algorithm

DFS(G, s):

let S be a stack containing just the node s

let $\text{explored}(v) = \text{false}$ for all $v \in V$

while S is not empty

pop v from the top of S

if not $\text{explored}(v)$ then

for each edge $\{v, w\}$ in E where not $\text{explored}(w)$

push w onto S

let $\text{parent}(w) = v$

let $\text{explored}(v) = \text{true}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- What is a good measure of progress?
 - Number of vertices whose edges have been considered not adequate
 - For some iterations this will not increase — when explored vertex removed from stack
 - Number of edge **destinations** considered always increases
 - Each directed edge is directed into the destination vertex
 - Increases by at least 1 on each iteration of the *while* loop

<https://powcoder.com>

Add WeChat powcoder

Running Time of DFS (cont.)


- This means that there are $\Theta(m)$ iterations of the loop
- How much time spent on each iteration?
- Depends on number of edges to be considered
- Number of steps within loop is $\Theta(\max(1, \text{outdegree}(v)))$
- We know that in total there are m edges to consider
- Total across all iterations of loop:

$$\sum_{v \in V} \max(1, \text{outdegree}(v)) = \Theta(n + m)$$


Assignment Project Exam Help

Topological Sorting
<https://powcoder.com>


Add WeChat powcoder




Directed Graphs often used to encode **dependencies**




Nodes correspond to tasks




Edges encode constraints on order in which tasks can be scheduled



Task *E* must be completed before task *G* is started



Cycles are undesirable



No scheduling would be possible that satisfies constraints

Topological Sorting of DAGs

Topological Sorting Problem:

Given a DAG, $G = (V, E)$, find a topological sort of G .


Topological Ordering:

A topological ordering of a DAG, $G = (V, E)$, is a permutation of the vertices in V that is compatible with each edge in E

A permutation (v_1, \dots, v_n) is **compatible** with edge (v, w) if


$$v = v_i, \quad w = v_j \quad \text{and} \quad i < j$$

Examples of Topological Sorts




Let's find a topological sort of this DAG

Examples of Topological Sorts



We could schedule C or E , let's choose to schedule E

Examples of Topological Sorts




Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Examples of Topological Sorts




Now we could schedule G or C , let's choose G

Examples of Topological Sorts




Now let's schedule *C*

Examples of Topological Sorts




Now let's schedule A

Examples of Topological Sorts




Now let's schedule *B*

Examples of Topological Sorts




Now let's schedule F

Examples of Topological Sorts




Now let's schedule *D*

Examples of Topological Sorts



Finally, let's schedule *H*


Examples of Topological Sorts



So the topological sort is: (E, G, C, A, B, F, D, H)

Assignment Project Exam Help

- Give all topological sorts of this graph




<https://powcoder.com>

Add WeChat powcoder

Question for you

- Give all topological sorts of this graph



<https://powcoder.com>

- ▶ Add WeChat powcoder
- ▶ (A, B, C)
- ▶ (B, A, C)

Assignment Project Exam Help

- Give a graph containing 5 vertices with exactly one topological sort

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- Give a graph containing 5 vertices with exactly one topological sort

<https://powcoder.com>



Add WeChat powcoder

Assignment Project Exam Help

- Give a graph containing 3 vertices with no topological sorts

<https://powcoder.com>

Add WeChat powcoder


Question for you

Assignment Project Exam Help

- Give a graph containing 3 vertices with no topological sorts

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Question: When can a task be safely scheduled?

Answer: when everything that it depends on has already been scheduled

<https://powcoder.com>

- We need to start with a task that depends on nothing
- This corresponds to a node without any **incoming** edges

Add WeChat powcoder

The Incoming Edge Count

Assignment Project Exam Help

For each node the total incoming edge count is a measure of how “close” it is to a task that is ready to be scheduled

Once a task X is scheduled, can reduce incoming edge count for all tasks that depend on X .

In effect, the edges out of X are deleted once X has been scheduled.

Once incoming edge count for a node reduces to 0 it can be scheduled

Topological Sort Algorithm

TopologicalSort(G) :

*let S be an empty stack
for each vertex $v \in V$*

compute $\text{indegree}(v)$

if $\text{indegree}(v) = 0$ then push v onto S

while S is not empty

pop u from S

schedule u

for each $(v, w) \in E$

decrement $\text{indegree}(w)$ by 1

if $\text{indegree}(w) = 0$ then


push w onto S

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Illustration of Topological Sort Algorithm




Compute indegree of each vertex

Illustration of Topological Sort Algorithm




Push vertices with 0 indegree on stack

Illustration of Topological Sort Algorithm




Push vertices with 0 indegree on stack

Illustration of Topological Sort Algorithm




Pop E from stack

Illustration of Topological Sort Algorithm




Schedule E

Illustration of Topological Sort Algorithm




“Remove” all edges out of E , updating indegree values

Illustration of Topological Sort Algorithm




Push G onto stack

Illustration of Topological Sort Algorithm




Pop G from stack

Illustration of Topological Sort Algorithm




Schedule G

Illustration of Topological Sort Algorithm



“Remove” all edges out of G , updating indegree values

Illustration of Topological Sort Algorithm




Add WeChat powcoder

$$S = (C)$$


Pop C from stack

Illustration of Topological Sort Algorithm




Schedule C

Illustration of Topological Sort Algorithm




“Remove” all edges out of C , updating indegree values

Illustration of Topological Sort Algorithm




Push both A and F onto stack

Illustration of Topological Sort Algorithm




Pop F from stack

Illustration of Topological Sort Algorithm




Schedule F

Illustration of Topological Sort Algorithm




“Remove” all edges out of F , updating indegree values

Illustration of Topological Sort Algorithm




Push both D and H onto stack

Illustration of Topological Sort Algorithm




Pop H from stack

Illustration of Topological Sort Algorithm




Schedule H

Illustration of Topological Sort Algorithm




No edges out of H to “remove” — no indegree values to update

Illustration of Topological Sort Algorithm




Pop D from stack

Illustration of Topological Sort Algorithm




Schedule D

Illustration of Topological Sort Algorithm




No edges out of D to “remove” — no indegree values to update

Illustration of Topological Sort Algorithm




Pop A from stack

Illustration of Topological Sort Algorithm




Schedule A

Illustration of Topological Sort Algorithm




“Remove” all edges out of A and update indegree values

Illustration of Topological Sort Algorithm




Push B onto stack

Illustration of Topological Sort Algorithm




Pop B from stack

Illustration of Topological Sort Algorithm




Schedule B

Illustration of Topological Sort Algorithm



No edges out of B to “remove” — no indegree values to update

Illustration of Topological Sort Algorithm



All done!

Assignment Project Exam Help

- What would happen if this topological sort algorithm was given a cyclic graph as input?

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- What would happen if this topological sort algorithm was given a cyclic graph as input?

<https://powcoder.com>

The algorithm would terminate without scheduling any of the edges within a cycle.

Add WeChat powcoder

Assignment Project Exam Help

- What would happen when the algorithm is run on a graph with just one topological sort?

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- What would happen when the algorithm is run on a graph with just one topological sort?

<https://powcoder.com>

Throughout the execution of the algorithm, the stack would contain no more than one element.

Add WeChat powcoder

Topological Sort Algorithm (again)

TopologicalSort(G) :

*let S be an empty stack
for each vertex $v \in V$*

compute $\text{indegree}(v)$

if $\text{indegree}(v) = 0$ then push v onto S

while S is not empty

pop u from S

schedule u

for each $(v, w) \in E$

decrement $\text{indegree}(w)$ by 1

if $\text{indegree}(w) = 0$ then

push w onto S

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Running Time

- Time to compute initial indegree values is $\Theta(n + m)$
 - traverse all adjacency lists
- How many times is the *while* loop executed?
- Measure of progress is number of scheduled vertices
 - always increases by 1 for each iteration
- Number of steps within loop is $\Theta(\max(1, \text{outdegree}(v)))$
- We know that in total there are m edges to consider
- Total across all iterations of loop:

$$\sum_{v \in V} \max(1, \text{outdegree}(v)) = \Theta(n + m)$$

Assignment Project Exam Help

- Would the algorithm be correct if a queue rather than a stack was used to hold the schedulable vertices?

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- Would the algorithm be correct if a queue rather than a stack was used to hold the schedulable vertices?

<https://powcoder.com>

Yes, the order of elements within the stack (or the queue) is irrelevant

Add WeChat powcoder

Assignment Project Exam Help

- Would the use of queues rather than stacks have an impact on the asymptotic running time of the algorithm?

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- Would the use of queues rather than stacks have an impact on the asymptotic running time of the algorithm?

<https://powcoder.com>

No, though stacks are slightly more efficient to implement.

Add WeChat powcoder

Assignment Project Exam Help

- How could the algorithm be adapted to cater for a scenario where some jobs are more urgent than others?

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- How could the algorithm be adapted to cater for a scenario where some jobs are more urgent than others?

<https://powcoder.com>

Use a priority queue rather than a stack.

Add WeChat powcoder