



Murdoch
UNIVERSITY

Topic 3

Basic of OOP

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

ICT167 Principles of
Computer Science

© Published by Murdoch University, Perth, Western Australia, 2020.

Assignment Project Exam Help

This publication is copyright. Except as permitted by the Copyright Act no part of it may in any form or by any electronic, mechanical, photocopying, recording or any other means be reproduced, stored in a retrieval system or be broadcast or transmitted without the prior written permission of the publisher

Objectives

- Define and appreciate the use of **information hiding**
- Use **pre-conditions** and **post-conditions** correctly
- Understand the use of **assertions** in programs
- Only use **private** instance variables
- Use **accessor** methods and **mutator** methods correctly

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Objectives

- Define Abstract Data Types (ADT), user interfaces, and ADT implementation
- Define data abstraction and encapsulation
- Use javadoc for program document purposes <https://powcoder.com>
- Know how to change a class implementation
- Use **new** correctly
- Understand assignment with class type variables
- Explain references and memory addresses

Objectives

- Use `==` with class types
- Define a class equality test
- Use parameters of class type
- Understand the null reference

Reading

Savitch: Chapters 5.2, 5.3

Information Hiding

- Information hiding:
 - Involves designing a method so that in order to use it, a client does not need to look at the code in the method body
 - A comment at the beginning of the method should tell the client what the method does
 - Allows client to understand the **what** (i.e. what the method does) without worrying about the **how** (i.e. how the method does what it does)
 - Is related to abstraction

Information Hiding

- Allows a team of implementers to easily divide up their work
- Requires a good clear description of what the method is supposed to do
- Allows implementers to make better, more efficient implementations even after clients have started using the class:
 - The client does not need to change her/his program just because the body of the method is changed
- The same idea of information hiding applies to whole classes as well as methods

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Pre- + Post-Condition Comments

- The client (user of a method of a class) will want to know:
 - the name
 - return type
 - Number, type and order of parameters of the method
- They will also want a clear, precise and complete description of what it is supposed to do
 - Eg: see the on-line documentation for the library class methods (eg: those of [String class](#))

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Pre- + Post-Condition Comments

- It is very common to present these comments in the form of a **contract** between the creator of a class and the user (client) of the class.
- The client supplies some arguments satisfying certain conditions, the **pre-conditions**
- The pre-condition for a method states the conditions that must be true before the method is invoked
- The creator promises to bring about some changes to the calling object and/or some properties of the return value, the **post-conditions**

Pre- + Post-Condition Comments

10

- The post-condition describes the effect of the method call. That is, it tells what will be true after the method is executed

- Eg: this is all the client needs to know ...

```
/**
```

<https://powcoder.com>

Pre-condition: years is a non-negative number

Post-condition: Returns the projected population of the calling (receiving) object after the specified number of years.

```
*/
```

```
public int predictPopulation(int years)
```

Pre- + Post-Condition Comments

11

- According to the contract, if the pre-condition is satisfied, the creator of the class guarantees that the post-condition will be satisfied

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assertions

- An assertion is a statement about the state of the program:
 - It can be true or false
 - It should be true when there are no mistakes in running the program
- Pre-condition and post-condition comments are examples of assertions

Assertions

- Assertions can occur anywhere in programs, such as after a block (`{...}`)
- A check can be inserted to determine if an assertion is true and, if not, to stop the program and output an error message
- An *assertion check* has the following form:
`assert Boolean_Expression;`
- If the `Boolean_Expression` evaluates to false, the program ends and outputs an error message saying that an assertion failed

Assertions

- Eg:

```
assert n == 1;
while (n < limit) {
    n = 2 * n;
}
```

Assignment Project Exam Help

<https://powcoder.com>

```
assert n >= limit;
```

Add WeChat powcoder

- // n is the smallest power of 2 \geq limit

- Assertion checking can be turned on or off

- They can be turned on during the program testing stage so that a failed assertion will stop the program and display an error message

Assertions

- A class containing assertions would need to be compiled differently. Eg:

```
javac -source 1.8 -enableassertions MyProg.java
```

- To run a program with assertion checking turned on, use:

```
java -enableassertions MyProg
```

- The normal way of running the program has assertion checking turned off – to make it run more efficiently
- Check how to do this in NetBeans?

Making Instance Variables Private

- Recall that if instance variables are declared public in a class, such as:

```
public String name;
```

- in the class `SpeciesFirstTry`, then the client can directly access the instance variable. Eg:

```
speciesOfTheMonth.name = "Klingon ox";
```

- The modifier ***public*** means that any other class/program can directly access/change the instance variable

Making Instance Variables Private

- Allowing direct access to instance variables is bad for information hiding
- The instance variables are the real substance of a class and once clients are using them, they can not be changed by the implementer
- Therefore, **HIDE THEM**
- This is achieved by declaring instance variables using the **private** modifier
- An example soon, but first ...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Making Instance Variables Private

- An analogy:
 - An ATM permits deposits and withdrawals, both of which affect the account balance however, it does not permit an account balance to be accessed and changed **directly**
 - If an account balance could be accessed and changed directly, a bank would be at the mercy of ignorant and unscrupulous users

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Making Instance Variables Private

- For example, in `SpeciesThirdTry` class:

```
private String name;  
private int population;  
private double growthRate;
```

- Then, they can still be used inside the class `SpeciesThirdTry` but not by its clients, like `SpeciesThirdTryDemo`

Making Instance Variables Private

- If an instance variable (or method) is declared to be **private** inside a class then it can not be directly referred to by name outside its class definition
- Normally:
 - All instance variables are marked **private**
 - All methods are marked public (except for helper methods - see later)

Accessor and Mutator Methods

- An **accessor** method is a method that accesses an object and returns some information about it, without changing the state of that object (its instance variables)
- Eg: the following methods of the class `SpeciesFourthly` are accessor methods:
 - `writeOutput()`, `predictPopulation(int years)`, `getName()`, `getPopulation()`, `getGrowthRate()`
- Accessor methods are also called ***get methods*** or ***getters***

Accessor and Mutator Methods

- A ***mutator*** method is a method that modifies the state of an object
- Eg: the `SpeciesFourthTry` class methods
`void readInput()` and
`void setSpecies(String newName,
int newPopulation, double
newGrowthRate)`
- are mutator methods

Accessor and Mutator Methods

- As a rule of thumb, it is best to separate accessors and mutators:
 - If a method returns a value to the client program then it should not modify the object
 - Conversely, mutators should have a return type of void

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Accessor and Mutator Methods

- Since instance variables (i.e. the state of an object) do need to be looked at, initialized or changed, this can be achieved as follows:

1. If the value of an instance variable may be needed by a client then supply a **public** "get" method (accessor method) for the variable
2. If the value of an instance variable might need to be initialized or changed by a client then supply a **public** "set" method (mutator method) for the variable, or if convenient, for a whole lot of instance variables at once

Accessor and Mutator Methods

- Advantages of this design:
 - Inside a set method you can check whether the new value is legitimate
 - Some variables may not be allowed to be set by clients
 - Some groups of variables may have to be updated together
 - The implementer can even change the real instance variables and keep the old set and get methods to make the class work the same for clients

Immutable Classes

- Some classes have been designed to have only accessor methods and no mutator methods at all
- These are called *immutable* classes
- Eg: the String class:
 - once a string object has been constructed, its contents (state) never change
 - no method in the String class can modify the contents of a string
 - The **StringBuffer** class is available for modification

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example Class

```
import java.util.Scanner;

public class SpeciesFourthTry {
    private String name;
    private int population;
    private double growthRate;

    public void writeOutput() {
        System.out.println("Name = " + name);
        System.out.println("Population = " +
                           population);
        System.out.println("Growth rate = " +
                           growthRate + "%");
    }
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example Class

```
public void readInput() {  
    Scanner keyboard = new Scanner(System.in);  
    System.out.println("What species' name?");  
    name = keyboard.nextLine( );  
    System.out.println("Population of species?");  
    population = keyboard.nextInt( );  
    while (population < 0) {  
        System.out.println("No negative population");  
        System.out.println("Re-enter population:");  
        population = keyboard.nextInt( );  
    }  
    System.out.println("Growth rate (%/yr):");  
    growthRate = keyboard.nextDouble( );  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example Class

```
/** Pre-condition: years is a nonnegative number.  
Post-condition: Returns projected population of  
calling object after specified number of years. */  
public int predictPopulation(int years) {  
    int result = 0;  
    double populationAmount = population;  
    int count = years;  
    while ((count > 0) && (populationAmount > 0)) {  
        populationAmount = (populationAmount +  
            (growthRate/100) * populationAmount);  
        count--;  
    }  
    if (populationAmount > 0)  
        result = (int)populationAmount;  
    return result;  
}
```


Example Class

```
public void setSpecies(String newName,
    int newPopulation, double newGrowthRate) {
    name = newName;
    if (newPopulation >= 0)
        population = newPopulation;
    else
    {
        System.out.println("ERROR: negative
        population.");
        System.exit(0);
    }
    growthRate = newGrowthRate;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example Class

```
public String getName()  
{  
    return name;  
}  
public int getPopulation()  
{  
    return population;  
}  
public double getGrowthRate()  
{  
    return growthRate;  
}  
} // end class SpeciesFourthTry
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Example Client

```
import java.util.*;

/** Demonstrates the use of the mutator method
    setSpecies*/

public class SpeciesFourthTryDemo {
    public static void main(String[] args) {
        SpeciesFourthTry speciesOfTheMonth =
            new SpeciesFourthTry();

        int numYears, futurePopulation;
        System.out.println("No. of years to project:");
        Scanner keyboard = new Scanner(System.in);
        numYears = keyboard.nextInt( );
        System.out.println("Enter data on the Species
                           of the Month:");
        speciesOfTheMonth.readInput();
    }
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example Client

```
speciesOfTheMonth.writeOutput();
futurePopulation =
speciesOfTheMonth.predictPopulation(numYears);
System.out.println("In " + numYears + " years
                    the population will be " +
                    futurePopulation);
speciesOfTheMonth.setSpecies("Klingon ox",
                             10,15);
System.out.println("The new Species of the
                    Month:");
speciesOfTheMonth.writeOutput();
System.out.println("In " + numYears + " years
                    the population will be " +
                    speciesOfTheMonth.predictPopulation(numberOfYears));
} //end main
} //end class
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Abstract Data Types (ADTs)

- A **data type** is a set of values together with a collection of operations that can be performed on these values
- An **abstract data type** (ADT) is a data type defined so that the clients who use the type do not have access to the details of how the values and operations are implemented

Abstract Data Types (ADTs)

- An ADT or a class can be divided into two parts: [Assignment Project Exam Help](https://powcoder.com)
 - **Class interface:** <https://powcoder.com>
 - Defines what the client of a class needs to know in order to use the class [Add WeChat powcoder](https://powcoder.com)
 - A client of a class just needs to know its name and about what public methods it has available
 - This is (loosely) called the user ***interface*** of the class

Abstract Data Types (ADTs)

- An ADT or a class can be divided into two parts:
 - **Class Implementation:**
 - Tells how the class interface is realised as Java code
 - All the details like (private) instance variables, private methods and all method bodies can be kept hidden (to avoid confusion and allow for changes etc)
 - This is the *implementation* of the class

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Abstract Data Types (ADTs)

- For example, you have been clients of the String class without knowing its implementation details
- Rival teams of developers can supply several versions of common and useful classes (eg: String), and, provided the same methods are available and do the same things, then we think of all of these as the same class

Abstract Data Types (ADTs)

- To be more correct, we use the term **Abstract Data Type** to refer to a class of Objects with certain standard public methods available
- Eg: we might say that the String ADT is implemented in many ways, some more efficient than others

Guidelines for Making Class Definitions into ADTs

- Place a comment before the class definition that describes what the class does, and how the client should think about the class data and methods
- Declare the instance variables in the class as ***private***
- Provide ***public*** accessor and/or mutator methods to read data and output data/results (eg: getter and setter methods)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Guidelines for Making Class Definitions into ADTs

- Also provide basic methods that a client needs to manipulate data in an object
- Specify how to use each public method with a comment placed before the method heading
- Make any helper methods ***private***

Encapsulation + Data Abstraction

41

- **Data abstraction** = lumping a bunch of related values together and calling it by one name
 - Assignment Project Exam Help
 - Eg: three related values to do with Species are put together as one `SpeciesFourthTry` object
 - <https://powcoder.com>
- **Encapsulation** = lumping related data values and actions (i.e. methods) together in one item
 - Add WeChat powcoder
 - Eg: making a class to deal with the three Species data values and all related methods

Encapsulation + Data Abstraction

- If implementers follow these ideas then one programmer can easily manage whole lists of species without troubling themselves with the details within an individual species
- Another team can deal with details at the species level

Encapsulation + Data Abstraction

- Another example:
 - One team implements methods to do with enrolment and personal details of individual *students*
 - Another team implements methods to do with enrolment and results etc., of all students in a particular *unit*
 - Another team implements methods to do with organizing the rooms and exams for all the units on *campus*

Javadoc

- The **javadoc** program (supplied with the JDK) automatically produces an HTML document that describes your class in a form extremely useful for client users of the class (i.e. with private implementation details hidden)

Javadoc

- The implementer of the class just needs to follow two simple rules about the internal comments which they want to be picked up by javadoc:
 - Put the comment immediately before a public class definition or a public method definition (or other public item)
 - start the comment with `/**` and end with `*/`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Javadoc

- Then type:

`javadoc MyClassName.java`

in the directory in which `MyClassName.java`
resides; this will create a new file
`MyClassName.html`

- Try it with `SpeciesFourthTry` class or your own class

Javadoc

- You can also javadoc all classes in a NetBeans project by selecting Run|Generate Javadoc from the NetBeans tool bar
<https://powcoder.com>
Add WeChat powcoder
- There are plenty of features for more sophisticated use:
 - See Appendix 5 of Savitch for further details
- You should use javadoc for your assignment classes

Changing the Implementation

- One of the most important reasons for information hiding is to allow implementers to improve their implementation even after clients have started using it
- See the case study on pages 350-354 (*page numbers could be different depending of the edition*) of the textbook – **A Purchase class**

Objects and References

- The way Java handles class type values, as opposed to primitive values, affects:
 - The use of `new`
 - Assignment of class type variables
 - References and memory addresses
 - Testing for equality
 - Class type parameters

Objects and References

- We already know that to create an object of class type we need to use the keyword **new**. Eg:

```
SpeciesFourthTry speciesOfTheMonth = new
SpeciesFourthTry();
```

- This sets aside just enough memory (in a special area of memory called the heap) to store a `SpeciesFourthTry` object with all its data values (the values of its instance variables)
- It also stores the memory address of this area in the memory location used by the variable `speciesOfTheMonth`

Objects and References

- We say `speciesOfTheMonth` is a *reference* to this new object
- Thus an **object reference** is information on how to find a particular object
 - The object is a chunk of main memory; a reference to the object is a way to get to that chunk of memory
 - The variable `speciesOfTheMonth` does not actually contain the object, but contains information about where the object is

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment with Class Type Variables

- Compare the output from the two experiments in the following program. They each involve an assignment:
 - one of primitive type
 - one of class type variables
- The difference in output is explained by the difference in behaviour of the assignment operator

Assignment with Class Type Variables

```
n = m;    // n and m are primitive variables
```

- This just means that the value currently stored in `m` is also put in `n`
- There is no lasting association between the two memory locations

- However, both of these are class variables

```
EarthSpecies = klingonSpecies;
```

- This results in the memory address currently being stored in `klingonSpecies` being also stored in `EarthSpecies`

Assignment with Class Type Variables

- So now the two variables refer to the same Object
- If we then make a change to that one Object via the `setSpecies` method, it should not be surprising that the two output calls print out exactly the same information

Example

```
public class AssignDemo {  
    public static void main(String[] args) {  
        System.out.println("Experiment 1: primitives:");  
        int n, m;  
        n = 42;  
        m = n;  
        n = 99;  
        System.out.println( n + " and " + m );  
    }  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example

```
System.out.println("Experiment 2: class
                    types:");
SpeciesFourthTry klingonSpecies, earthSpecies;
klingonSpecies = new SpeciesFourthTry();
earthSpecies = new SpeciesFourthTry();
klingonSpecies.setSpecies("klingon ox",10,15);
earthSpecies = klingonSpecies;
earthSpecies.setSpecies("Elephant",100,12);
System.out.println("earthSpecies:");
earthSpecies.writeOutput();
System.out.println("klingonSpecies:");
klingonSpecies.writeOutput();
} //end of main
} //end of class
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example

```
/* OUTPUT
Experiment 1: primitives
99 and 42
Experiment 2: class types
earthSpecies:
Name = Elephant
Population = 100
Growth rate = 12.0%
klingsonSpecies:
Name = Elephant
Population = 100
Growth rate = 12.0%
*/
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

New Values in Reference Variables

- Consider the following example:

```
// File: referenceString.java
class referenceString {
    public static void main ( String[] args ) {
        String myStr;
        myStr = new String("Computer Science");
        System.out.println(myStr);
        myStr = new String("Games Technology");
        System.out.println(myStr);
    } // end of main
} // end of class referenceString
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

New Values in Reference Variables

- The above program will, as expected, write out
Computer Science
Games Technology
- However, consider some of the details involved:
- The statement
`myStr = new String("Computer Science");`
 - creates the **first** object, and
 - Puts a reference to this object into `myStr`

New Values in Reference Variables

- The statement

```
System.out.println(myStr);
```

- Follows the reference in `myStr` to the **first** object
- Gets the data in the **first** object and prints it

- The statement

```
myStr = new String("Games Technology");
```

- Creates a **second** object
- Puts a reference to the **second** object into `myStr`

New Values in Reference Variables

- **At this point there is no reference to the first object - it is now "garbage"**
Assignment Project Exam Help
- This is a commonly occurring situation in Java, and not a mistake
<https://powcoder.com>
- As the program runs, a part of the Java system called the "garbage collector" reclaims the lost objects (the "garbage") so that their memory can be used again
Add WeChat powcoder

New Values in Reference Variables

- The statement

`System.out.println(myStr);`

- Follows the reference in `myStr` to the **second** object
- Gets the data in the **second** object and prints it

New Values in Reference Variables

- Thus:
 - Each time the **new** operator is used, a new object is created
 - Each time an object is created, a reference to it is saved in a variable
 - The reference in the variable is later used to find the object
 - If another reference is saved in that variable, it replaces the previous reference
 - If no variable holds a reference to an object, the object becomes "garbage"

Testing for Equality of Class Variables

- Be careful of using the comparison operator `==` to test for equality between class type variables
<https://powcoder.com>
- The test will only return true if the two variables both refer to exactly the same Object
Add WeChat powcoder
- It is possible to have a **different** Object with the same values

Testing for Equality of Class Variables

■ Eg:

```
SpeciesFourthTry eS= new SpeciesFourthTry();  
SpeciesFourthTry kS= new SpeciesFourthTry();  
kS.setSpecies("Klingon ox", 10, 15);  
eS.setSpecies("Klingon ox", 10, 15);  
if (eS == kS) System.out.println("EQUAL");  
else System.out.println("Not EQUAL");
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Testing for Equality of Class Variables

- Here the output will be “Not EQUAL” and thus the test of equality will fail
- Would you want to count these two objects as being equal? Probably.
- What about:
 “Klingon ox”, 10, 15 and
 “klingon ox”, 10, 15
- What about:
 “Klingon ox”, 10, 15 and
 “Klingon ox”, 12, 15

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Defining Your Own “Equals”

- Many classes usefully need a test of equality
- Exactly what counts as equal should be defined by the implementer of the class
- Often they supply an equals method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Defining Your Own “Equals”

- Eg:

```
public boolean equals(SpeciesFourthTry otherObject)
{
    return
        ((this.name.equalsIgnoreCase(otherObject.name))
        && (this.population == otherObject.population)
        && (this.growthRate == otherObject.growthRate));
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- This allows for differences in (upper/lower) case in the species name
- This might be used by a client in a test such as:

```
if (klingsonSpecies.equals(earthSpecies))
    System.out.println("EQUAL");
else System.out.println("Not EQUAL");
```


Class Parameters

- Passing a class type argument to a method may change the argument (of primitive types) <https://powcoder.com>
- In general it is not good design to allow this to happen as it may surprise the client but sometimes it has a use

Class Parameters

- Eg:

```
public void makeEqual  
(SpeciesFourthTry otherObject) {  
    otherObject.name=name;  
    otherObject.population=population;  
    otherObject.growthrate=growthRate;  
}
```

- Call by:

```
klingsonSpecies.makeEqual (earthSpecies) ;
```

Class Parameters

- This still allows `earthSpecies` to refer to a different Object in memory but it changes all the data values of `earthSpecies` to be the same as those for `klingsonSpecies`
- Basically the formal parameter `otherObject` is given (by the call) a **reference** to the `earthSpecies` Object and so is able to change it
- You may hear that Java uses ***call-by-reference*** for parameter passing of class type variables

The `null` references

- Note that sometimes a class type variable will refer to no object, especially if it has just been declared and not made to refer to a new object
- You can use `null` to initialize any class type variable to refer to nothing if you don't need particular object. Eg:

```
String line = null;
```
- You might get a `NullPointerException` if you try to call a method on a variable which refers to no Object

The `null` references

- You can test for `null`-ness via

```
if (line == null) ...
```

- You can test for non-`null`-ness via

```
if (line != null) ...
```

The `null` references

■ Another Example:

```
String month = "August";  
String year = "";           // empty string  
// refers to no string at all  
String message = null;  
int len1 = month.length();  // returns 6  
int len2 = year.length();   // returns 0  
// runtime error  
int len3 = message.length();
```

- Note that empty string and a `null` reference are different

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
End of Topic 3