



INFO20003 Database Systems

Assignment Project Exam Help

<https://powcoder.com>

Dr. Renata Borovica-Gajic
Add WeChat powcoder

Lecture 04
Relational Model &
Translating ER diagrams



- Relational Model
- Keys & Integrity Constraints
- Translating ER to Logical and Physical Model

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Readings: Chapter 3, Ramakrishnan & Gehrke, Database Systems



- **Data Model** allows us to translate real world things into structures that a computer can store
- Many models: Relational, ER, O-O, Network, Hierarchical, etc.

Assignment Project Exam Help

- **Relational Model:**

- Rows & Columns (Tuples/records and Attributes/fields)
- Keys & Foreign Keys to link Relations


Add WeChat powcoder

Enrolled

sid	cid	grade
53666	Carnatic101	5
53666	Reggae203	5.5
53650	Topology112	6
53666	History105	5

Students

sid	name	login	age	gpa
53666	Jones	jones@cs	18	5.4
53688	Smith	smith@eecs	18	4.2
53650	Smith	smith@math	19	4.8





- **Relational database**: a set of *relations*.
- **Relation**: made up of 2 parts:
 - **Schema** : specifies name of relation, plus name and type of each column (attribute).
Example: Students(*sid*: string, *name*: string, *login*: string, *age*: integer, *gpa*: real)
<https://powcoder.com>
 - **Instance** : a **table**, with rows and columns.
#rows = *cardinality*
#fields = *degree (or arity)*
Add WeChat powcoder
- You can think of a relation as a set of *rows* or *tuples*.
 - all rows are *distinct*, no order among rows


Students

sid	name	login	age	gpa
53666	Jones	jones@cs	18	3.4
53688	Smith	smith@cecs	18	3.2
53650	Smith	smith@math	19	3.8

Cardinality = 3, degree (arity) = 5, all rows distinct


In logical design **entity** set becomes a **relation**.
Attributes become attributes of the relation.

Conceptual Design: **Logical Design:**



In physical design we choose data types

1. Conceptual Design:



2. Logical Design:

Employee (ssn, name, age)

3. Physical Design:

Employee
(ssn CHAR(11),
name VARCHAR(20),
age INTEGER)

The Entire Cycle

1. Conceptual Design

Assignment Project Exam Help

2. Logical Design

<https://powcoder.com>


3. Physical Design

Add WeChat powcoder

4. Implementation

5. Create Instance

1. Conceptual Design:



4. Implementation:

```
CREATE TABLE Employee
(ssn CHAR(11),
name VARCHAR(20),
age INTEGER,
PRIMARY KEY (ssn))
```

2. Logical Design:

Employee (ssn,
name,
age)

<https://powcoder.com>

5. Instance:

EMPLOYEE

<u>ssn</u>	name	age
0983763423	John	30
9384392483	Jane	30
3743923483	Jill	20

3. Physical Design:

Employee
(ssn CHAR(11),
name VARCHAR(20),
age INTEGER)

Assignment Project Exam Help

Add WeChat [powcoder](https://powcoder.com)

Example: Creating the Students relation.

```
CREATE TABLE Students  
(sid CHAR(20),  
name CHAR(20),  
login CHAR(10),  
age INTEGER,  
gpa FLOAT)
```

The type (domain) of each field is specified, and enforced by the DBMS whenever tuples are added or modified.



REVISION

- Relational Model & SQL overview
- **Keys & Integrity Constraints**
- Translating ER to Logical and Physical Model

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Readings: Chapter 3, Ramakrishnan & Gehrke, Database Systems

- Keys are a way to associate tuples in different relations
- Keys are one form of **integrity constraint (IC)**
- **Example:** *Assignment Project Exam Help* Only students can be enrolled in subjects.

<https://powcoder.com>

Add WeChat powcoder

Enrolled

sid	cid	grade
53666	15-101	C
53666	18-203	B
53650	15-112	A
53666	15-105	B

Students

sid	name	login	age	gpa
53666	Jones	jones@cs	18	3.4
53688	Smith	smith@cs	18	3.2
53650	Smith	smith@math	19	3.8

FOREIGN Key

PRIMARY Key



- A set of fields is a **superkey** if no two distinct tuples can have same values in all key fields
 - A set of fields is a **key** for a relation if it is a superkey and no subset of the fields is a superkey (minimal subset)
 - Out of all keys **one** is chosen to be the **primary key** of the relation. Other keys are called **candidate** keys
 - Each relation has a primary key
- Assignment Project Exam Help**
<https://powcoder.com>
Add WeChat powcoder
- **Your turn:**
 1. Is *sid* a key for Students?
 2. What about *name*?
 3. Is the set {*sid*, *gpa*} a superkey? Is the set {*sid*, *gpa*} a key?
 4. Find a primary key from this set {*sid*, *login*}



- There are possibly many candidate keys (specified using UNIQUE), one of which is chosen as the *primary key*. Keys must be chosen carefully.

Example: **Assignment Project Exam Help**

For a given student and course, there is a single grade.

<https://powcoder.com>

```
CREATE TABLE Enrolled
(sid CHAR(20)
cid CHAR(20),
grade CHAR(2),
PRIMARY KEY (sid,cid))
```

VS.

```
CREATE TABLE Enrolled
(sid CHAR(20)
cid CHAR(20),
grade CHAR(2),
PRIMARY KEY (sid),
UNIQUE (cid, grade))
```

*“Students can take only one course,
and no two students in a course
receive the same grade.”*



- **Foreign key** : A set of fields in one relation that is used to 'refer' to a tuple in another relation. Foreign key must correspond to the primary key of the other relation. **Assignment Project Exam Help**
- If all foreign key constraints are enforced in a DBMS, we say **referential integrity** is achieved. **<https://powcoder.com>**
Add WeChat powcoder



Example: *Only students listed in the Students relation should be allowed to enroll in courses.*

- *sid* is a foreign key referring to Students

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
CREATE TABLE Enrolled  
(sid CHAR(20),  
cid CHAR(20),  
grade CHAR(2),  
PRIMARY KEY (sid,cid),  
FOREIGN KEY (sid) REFERENCES Students )
```

Enrolled

sid	cid	grade
53666	15-101	C
53666	18-203	B
53650	15-112	A
53666	15-105	B

Students

sid	name	login	age	gpa
53666	Jones	jones@cs	18	3.4
53688	Smith	smith@cs	18	3.2
53650	Smith	smith@math	19	3.8

- Consider Students and Enrolled; *sid* in Enrolled is a foreign key that references Students.
- What should be done if an Enrolled tuple with a non-existent student id is inserted? (*Reject it!*)
- What should be done if a Students tuple is deleted?
 - Also delete all Enrolled tuples that refer to it?
 - Disallow deletion of a Students tuple that is referred to?
 - Set *sid* in Enrolled tuples that refer to it to a *default sid*?
 - (In SQL, also: Set *sid* in Enrolled tuples that refer to it to a special value *null*, denoting '*unknown*' or '*inapplicable*'.)
- Note: Similar issues arise if primary key of Students tuple is updated.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- **IC**: condition that must be true for *any* instance of the database; e.g., domain constraints.
 - ICs are specified when schema is defined.
 - ICs are checked when relations are modified.
- A **legal** instance of a relation is one that satisfies all specified ICs.
 - DBMS should not allow illegal instances.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



RELEVANCE

- Relational Model & SQL overview
- Keys & Integrity Constraints
- Translating ER to Logical and Physical Model

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Readings: Chapter 3, Ramakrishnan & Gehrke, Database Systems

In logical design **entity** set becomes a **relation**.
Attributes become attributes of the relation.

Conceptual Design: **Logical Design:**






- Multi-valued attributes need to be unpacked (flattened) when converting to logical design. ** There is an alternative of creating a lookup table discussed in the next lecture.*

Example:

For employees we need to capture their home phone number and work phone number.

Assignment Project Exam Help

Conceptual Design: <https://powcoder.com> **Logical Design:**



Multi-valued attribute



- Composite attributes need to be unpacked (flattened) when converting to logical design.


Example:

For employees we need to capture an address consisting of a postcode, street name and number.

Assignment Project Exam Help


Conceptual Design: <https://powcoder.com> Logical Design:

Add WeChat powcoder



Composite attribute

Conceptual Design:




Logical Design:

Add WeChat powcoder

In translating a **many-to-many** relationship set to a relation, attributes of a *new* relation must include:

1. Keys for each participating entity set (as foreign keys). This set of attributes forms a **superkey** of the relation.
2. All descriptive attributes.

Conceptual Design:



Assignment Project Exam Help

<https://powcoder.com>

Logical Design:

Employee (ssn,
name
age)

Department (did,
dname,
budget)

Works_In (ssn,
did,
since)

Keys from connecting
entities become PFK

This is called an associative entity

Note: Underline = PK,
italic and underline = FK,
underline and bold = PFK

Logical Design:

Employee (ssn, name, age)

Department (did, dname, budget)

Works_In (ssn, did, since)

Note: Underline = PK,
italic and underline = FK,
underline and bold = PFK

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Physical Design:

Employee
(ssn CHAR(11),
name VARCHAR(20),
age INTEGER)

Department
(did INTEGER,
dname VARCHAR(20),
budget FLOAT)

Works_In(
ssn CHAR(11),
did INTEGER,
since DATE)

Logical Design:

Employee (ssn, name, age)

Department (did, dname, budget)

Works_In (**ssn**, **did**, since)

Note: Underline = PK,
italic and underline = FK,
underline and bold = PFK

Assignment Project Exam Help

Implementation:

<https://powcoder.com>

Add WeChat powcoder

```
CREATE TABLE Employee
(ssn CHAR(11),
name VARCHAR(20),
age INTEGER,
PRIMARY KEY (ssn))
```

```
CREATE TABLE Department
(did INTEGER,
dname VARCHAR(20),
budget FLOAT,
PRIMARY KEY (did))
```

```
CREATE TABLE Works_In
(ssn CHAR(11),
did INTEGER,
since DATE,
PRIMARY KEY (ssn, did),
FOREIGN KEY (ssn) REFERENCES Employee,
FOREIGN KEY (did) REFERENCES Department)
```

Employee

<u>ssn</u>	name	age
0983763423	John	30
9384392483	Jane	30
3743923483	Jill	20

Department

<u>did</u>	dname	budget
101	Sales	10K
105	Purchasing	20K
108	Databases	1000K

Works_In

<u>ssn</u>	<u>did</u>	since
0983763423	101	1 Jan 2003
0983763423	108	2 Jan 2003
9384392483	108	1 Jun 2002


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

In translating a **many-to-many** relationship set to a relation, attributes of the relation must include:

- Keys for each participating entity set (as foreign keys). This set of attributes forms a **superkey** for the relation.
- All descriptive attributes



Logical Design:

Contracts (
supplier_id,
part_id,
department_id)

Note: Underline = PK,
 italic and underline = FK,
 underline and bold = PFK

Assignment Project Exam Help
<https://powcoder.com>
 Add WeChat powcoder




Logical Design:

Contracts (
supplier_id,
part_id,
department_id)

Implementation:

```
CREATE TABLE Contracts(  
  supplier_id INTEGER,  
  part_id INTEGER,  
  department_id INTEGER,  
  PRIMARY KEY (supplier_id, part_id, department_id),  
  FOREIGN KEY (supplier_id) REFERENCES Suppliers,  
  FOREIGN KEY (part_id) REFERENCES Parts,  
  FOREIGN KEY (department_id) REFERENCES Departments)
```




Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

- Each department has at most one manager, according to the key constraint on Manages.

Assignment Project Exam Help






<https://powcoder.com>

Logical Design: Add WeChat powcoder

Employee (ssn, name, age) **VS.** Employee (ssn, name, age)
Department (did, dname, budget) Department (did, dname, budget,
Manages (**ssn**, **did**, since) **ssn**, since)

Note: Underline = PK,
italic and underline = FK,
underline and bold = PFK

Implementation:



```
CREATE TABLE Employee
(ssn CHAR(11),
 name VARCHAR(20),
 age INTEGER,
 PRIMARY KEY (ssn))
```

```
CREATE TABLE Manages
(ssn CHAR(11),
 did INTEGER,
 since DATE,
 PRIMARY KEY (ssn, did),
 FOREIGN KEY (ssn)
 REFERENCES Employees,
 FOREIGN KEY (did)
 REFERENCES Departments)
```

```
CREATE TABLE Department
(did INTEGER,
 dname CHAR(20),
 budget FLOAT,
 ssn CHAR(11),
 since DATE,
 PRIMARY KEY (did)
 FOREIGN KEY (ssn)
 REFERENCES Employees)
```

Which one is better?

Assignment Project Exam Help

<https://powcoder.com>

vs.

Add WeChat powcoder



- RULE: *Primary key from the many side becomes a foreign key on the one side*
- This is the way to ensure that the key constraint holds

Assignment Project Exam Help

CREATE TABLE Department

(did INTEGER,

dname CHAR(20),

budget FLOAT,

ssn CHAR(11),

since DATE,

PRIMARY KEY (did)

FOREIGN KEY (ssn)

REFERENCES Employee)

<https://powcoder.com>


Add WeChat powcoder

Each department will
have a *single* manager



- Does every department have a manager?
 - If so, this is a participation constraint: the participation of Departments in Manages is said to be *total*.

Assignment Project Exam Help





- We specify total participation with key words NOT NULL
– **NOT NULL = this field cannot be empty**

```
CREATE TABLE Department (  
  did INTEGER NOT NULL,  
  dname CHAR(20) NOT NULL,  
  budget FLOAT NULL,  
  ssn CHAR(11) NOT NULL,  
  since DATE NULL,  
  PRIMARY KEY (did),  
  FOREIGN KEY (ssn) REFERENCES Employee  
    ON DELETE NO ACTION)
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

NOTE: Every time we create a table or draw a physical design we should specify whether attributes are NULL or NOT NULL. We haven't done it in each slide of this lecture due to clarity and lack of space – but don't forget this in your design/implementation!




- A **weak entity** can be identified uniquely only by considering the primary key of another (*owner*) entity.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- Weak entity set and identifying relationship set are translated into a single table.
 - When the owner entity is deleted, all owned weak entities must also be deleted.

Logical Design: <https://powcoder.com> **Assignment Project Exam Help**
Dependent (dname, age, cost, ssn)
Note: Underline = PK,
italic and underline = FK,
underline and bold = PFK

Implementation:

<https://powcoder.com> **Add WeChat powcoder**
CREATE TABLE Dependent (
 dname CHAR(20) NOT NULL,
 age INTEGER NULL,
 cost DECIMAL(7,2) NOT NULL,
 ssn CHAR(11) NOT NULL,
 PRIMARY KEY (dname, ssn),
 FOREIGN KEY (ssn) REFERENCES Employees
 ON DELETE CASCADE)

- A tabular representation of data.
- Simple and intuitive, currently the most widely used.
- Integrity constraints can be specified based on application semantics. DBMS checks for violations.
 - Two important ICs: primary and foreign keys
 - In addition, we always have domain constraints.
- Rules to translate ER to logical design (relational model)

<https://powcoder.com>
Add WeChat powcoder



- Translate conceptual (ER) into logical & physical design
- Understand integrity constraints
- Use DDL of SQL to create tables with constraints

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- ER Modelling Example with MySQL Workbench
 - You will need this for workshops/labs (and assessment)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder