



THE UNIVERSITY
of EDINBURGH

Text Technologies for Data Science

INFR11145

IR Evaluation

Instructor:
Walid Magdy

Assignment Project Exam Help

21-Oct-2020

1


<https://powcoder.com>

Lecture Objectives

- Learn about how to evaluate IR
 - Evaluation measures
 - P, R, F
 - MAP
 - nDCG
- Implement: (as part of CW2)
 - P, R
 - MAP
 - nDCG




2



3

<https://powcoder.com>



4

Configure your system

- **About the system:**
 - Stopping? Tokenise? Stemming? n-gram char?
 - Use synonyms improve retrieval performance?
- **Corresponding experiment?**
 - Run your search for a set of queries with each setup and find which one will achieve the best performance
- **About the user:**
 - Is letting users weight search terms a good idea?
- **Corresponding experiment?**
 - Build two different interfaces, one with term weighting functionality, and one without; run a user study

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

5

<https://powcoder.com>

Types of Evaluation Strategies

- **System-centered studies:**
 - Given documents, queries, and relevance judgments
 - Try several variations of the system
 - Measure which system returns the “best” hit list
 - Laboratory experiment
- **User-centered studies**
 - Given several users, and at least two retrieval systems
 - Have each user try the same task on both systems
 - Measure which system works the “best”

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

6

Importance of Evaluation

- The ability to measure differences underlies experimental science
 - How well do our systems work?
 - Is A better than B?
 - Is it really?
 - Under what conditions?
- Evaluation drives what to research
 - Identify techniques that work and don't work

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



7

<https://powcoder.com>

The 3-dimensions of Evaluation


- **Effectiveness**
 - How "good" are the documents that are returned?
 - System only, human + system
- **Efficiency**
 - Retrieval time, indexing time, index size
- **Usability**
 - Learnability, flexibility
 - Novice vs. expert users

Walid Magdy, TTDS 2020/2021



8

Cranfield Paradigm (Lab setting)



Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

9

<https://powcoder.com>

Reusable IR Test Collection

- **Collection of Documents**
 - Should be “representative” to a given IR task
 - Things to consider: size, sources, genre, topics, ...
- **Sample of information need**
 - Should be “randomized” and “representative”
 - Usually formalized topic statements (query + description)
- **Known relevance judgments**
 - Assessed by humans, for each topic-document pair
 - Binary/Graded
- **Evaluation measure**

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

10

Good Effectiveness Measures

- Should capture some aspect of what the user wants
 - IR → Do the results satisfy user's information need?
- Should be easily replicated by other researchers
- Should be easily comparable
 - Optimally, expressed as a single number
 - Curves and multiple numbers are still accepted, but single numbers are much easier for comparison
- Should have predictive value for other situations
 - What happens with different queries on a different document collection?

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

11

<https://powcoder.com>

Set Based Measures

Add WeChat powcoder

- Assuming IR system returns sets of retrieved results without ranking
- Suitable with Boolean Search
- No certain number of results per query

Walid Magdy, TTDS 2020/2021




THE UNIVERSITY
of EDINBURGH

12

Which looks the best IR system?

- For query **Q**, collection has **8 relevant documents**:



Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

13



<https://powcoder.com>

Precision and Recall

• Precision:

What fraction of these retrieved docs are relevant?

$$P = \frac{rel \cap ret}{retrieved} = \frac{TP}{TP + FP}$$



relevant irrelevant	FP	TN
	TP	FN
	retrieved	not retrieved

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH



14

Precision and Recall

- Recall:**

What fraction of the relevant docs were retrieved?

$$R = \frac{rel \cap ret}{relevant} = \frac{TP}{TP + FN}$$



relevant irrelevant	FP	TN
	TP	FN
	retrieved	no-retrieved

Walid Magdy, TTDS 2020/2021




THE UNIVERSITY
of EDINBURGH

15

<https://powcoder.com>

Which looks the best IR system?

- For query **Q**, collection has **8 relevant documents**:



Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

16

Trade-off between P & R

- Precision: The ability to retrieve top-ranked docs that are mostly relevant.
- Recall: The ability of the search to find all of the relevant items in the corpus.
- Retrieve more docs:
 - Higher chance to find all relevant docs $\rightarrow R \uparrow$
 - Higher chance to find more irrelevant docs $\rightarrow P \downarrow$

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021




17

<https://powcoder.com>

Trade-off between P & R

Returns relevant documents but misses many useful ones too



Walid Magdy, TTDS 2020/2021




18

What about Accuracy?

- Accuracy:**

What fraction of docs was classified correctly?

$$A = \frac{TP + TN}{TP + FP + TN + FN}$$



relevant	FP	TN
	TP	FN
	retrieved	no-retrieved

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



19

<https://powcoder.com>

One Measure? F-measure

$$F1 = \frac{2 \cdot P \cdot R}{P + R}$$

$$F_{\beta} = \frac{(\beta^2 + 1)P \cdot R}{\beta^2 P + R}$$

- Harmonic mean of recall and precision
 - Emphasizes the importance of small values, whereas the arithmetic mean is affected more by outliers that are unusually large
- Beta (β) controls relative importance of P and R
 - $\beta = 1$, precision and recall equally important $\rightarrow F1$
 - $\beta = 5$, recall five times more important than precision


Walid Magdy, TTDS 2020/2021



20

F-measure?

- For query **Q**, collection has **8 relevant documents**:




21

<https://powcoder.com>

Rank-based IR measures

- Consider systems A & B
 - Both retrieved 10 docs, only 5 are relevant
 - P, R & F are the same for both systems
 - Should their performances considered equal?
- Ranked IR requires taking “ranks” into consideration!
- How to do that?




Valid Magdy, TTDS 2020/2021

THE UNIVERSITY of EDINBURGH

22

Which is the best ranked list?

- For query **Q**, collection has **8 relevant documents**:



Walid Magdy, TTDS 2020/2021



23

<https://powcoder.com>

Precision @ K

Add WeChat powcoder

- k (a fixed number of documents)
- Have a cut-off on the ranked list at rank k , then calculate precision!
- Perhaps appropriate for most of web search: most people only check the top k results
- But: averages badly, Why?

Walid Magdy, TTDS 2020/2021



24

P@5

- For query **Q**, collection has **8 relevant documents**:

	A	B	C	D	E	F	G
1	R		R	R	R		
2			R	R			R
3	R			R	R	R	R
4						R	R
5	R		R	R		R	R
6						R	
7	R	R			R	R	
8		R					
9	R	R	R				
10		R					
11						R	
12			R				

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



25

<https://powcoder.com>

R-Precision

Add WeChat powcoder

- For a query with known r relevant documents
→ R-precision is the precision at rank r ($P@r$)
- r is different from one query to another
- Concept:
It examines the ideal case: getting all relevant documents in the top ranks
- Is it realistic?

Walid Magdy, TTDS 2020/2021



26

R-Precision

- For query **Q**, collection has **8 relevant documents**:

	A	B	C	D	E	F	G
1	R		R	R	R		
2			R	R			R
3	R			R	R	R	R
4						R	R
5	R		R	R		R	R
6		R				R	
7	R	R			R	R	
8		R					
9	R	R	R				
10		R					
11							
12							

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



27

<https://powcoder.com>

User Satisfaction??

- It is assumed that users need to find relevant docs at the highest possible ranks
→ Precision is a good measure
- But, user would cut-off (stop inspecting results) at some point, say rank x
→ $P@x$
- What is the optimal x ?
When you think a user can stop?

Walid Magdy, TTDS 2020/2021



28

When a user can stop?

- IR objective: “satisfy user information need”
- Assumption: a user will stop once his/her information need is satisfied
- How? user will keep looking for relevant docs in the ranked list, read them, then stop once he/she feels satisfied
- $P@x \rightarrow x$ can be any rank where a relevant document appeared (*assume uniform distribution*)

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021




29

<https://powcoder.com>

When to stop? Add WeChat powcoder

- For query **Q**, collection has **8 relevant documents**:



Walid Magdy, TTDS 2020/2021



30

When a user can stop?

- IR objective: “satisfy user information need”
- Assumption: a user will stop once his/her information need is satisfied
- How? user will keep looking for relevant docs in the ranked list, read them, then stop once he/she feels satisfied
- $P@x \rightarrow x$ can be any rank where a relevant document appeared (*assume uniform distribution*)
- What about calculating the averages over all x 's?
- every time you find relevant doc, calculate $P@x$, then take the average at the end

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



31

<https://powcoder.com>

Average Precision (AP)

Q₁
(has 4 rel. docs)

1	R	1/1=1.00
2	R	2/2=1.00
3		
4		
5	R	3/5=0.60
6		
7		
8		
9	R	4/9=0.44
10		

AP = $3.04 / 4$
= **0.76**

Q₂
(has 3 rel. docs)

1		
2		
3	R	1/3=0.33
4		
5		
6		
7	R	2/7=0.29
8		
...		
$\frac{3}{\infty}$		=0

AP = $0.62 / 3$
= **0.207**

Q₃
(has 7 rel. docs)

1		
2	R	1/2=0.50
3		
4		
5	R	2/5=0.40
6		
7		
8	R	3/8=0.375
9		
...		

AP = $1.275 / 7$
= **0.182**

Walid Magdy, TTDS 2020/2021



32

Mean Average Precision (MAP)

Q_1 (has 4 rel. docs)	Q_2 (has 3 rel. docs)	Q_3 (has 7 rel. docs)
1 <input checked="" type="checkbox"/> R 1/1=1.00	1 <input type="checkbox"/>	1 <input type="checkbox"/>
2 <input checked="" type="checkbox"/> R 2/2=1.00	2 <input type="checkbox"/>	2 <input checked="" type="checkbox"/> R 1/2=0.50
3 <input type="checkbox"/>	3 <input checked="" type="checkbox"/> R 1/3=0.33	3 <input type="checkbox"/>
4 <input type="checkbox"/>	4 <input type="checkbox"/>	4 <input type="checkbox"/>
5 <input checked="" type="checkbox"/> R 3/5=0.60	5 <input type="checkbox"/>	5 <input checked="" type="checkbox"/> R 2/5=0.40
6 <input type="checkbox"/>	6 <input type="checkbox"/>	6 <input type="checkbox"/>
7 <input type="checkbox"/>	7 <input checked="" type="checkbox"/> R 2/7=0.29	7 <input type="checkbox"/>
8 <input type="checkbox"/>	8 <input type="checkbox"/>	8 <input checked="" type="checkbox"/> R 3/8=0.375
9 <input checked="" type="checkbox"/> R 4/9=0.44	⋮ $\frac{3}{\infty}=0$	9 <input type="checkbox"/>
10 <input type="checkbox"/>		
AP = 0.76	AP = 0.207	AP = 0.182

Assignment Project Exam Help

$$MAP = (0.76 + 0.207 + 0.182) / 3 = 0.383$$

Walid Magdy, TTDS 2020/2021



33

<https://powcoder.com>

AP & MAP

Add WeChat powcoder

$$AP = \frac{1}{r} \sum_{k=1}^n P(k) \times rel(k)$$

where, r : number of relevant docs for a given query

n : number of documents retrieved

$P(k)$ precision @ k

$rel(k)$: 1 if retrieved doc @ k is relevant, 0 otherwise.

$$MAP = \frac{1}{Q} \sum_{q=1}^Q AP(q)$$

where, Q : number of queries in the test collection

Walid Magdy, TTDS 2020/2021



34

AP/MAP

$$AP = \frac{1}{r} \sum_{k=1}^n P(k) \times rel(k)$$

- A mix between precision and recall
- Highly focus on finding relevant document as early as possible
- When $r=1 \rightarrow MAP = MRR$ (mean reciprocal rank $\frac{1}{k}$)
- MAP is the most commonly used evaluation metric for most IR search tasks
- Uses binary relevance: $rel = 0/1$

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

35

<https://powcoder.com>

MAP

Add WeChat powcoder

- For query **Q**, collection has **8 relevant documents**:

A ³	B ⁶	C ²	D ¹	E ⁷	F ⁴	G ⁵
1 R	1	1 R	1 R	1 R	1	1
2	2	2 R	2 R	2	2	2 R
3 R	3	3	3 R	3 R	3 R	3 R
4	4	4	4	4	4 R	4 R
5 R	5	5 R	5 R	5	5 R	5 R
6	6 R	6	6	6	6 R	
7 R	7 R	7	7	7 R	7 R	
8	8 R	8	8	8	8	
9 R	9 R	9 R	9		9	
10	10 R	10	10		10	
	11 R	11	11		11 R	
	12	12 R	12		12	

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

36

Binary vs. Graded Relevance

- Some docs are more relevant to a query than other relevant ones!
 - We need non-binary relevance
- Binary Relevance:
 - Relevant 1
 - Irrelevant 0
- Graded Relevance:
 - Perfect 4
 - Excellent 3
 - Good 2
 - Fair 1
 - Bad 0

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

37

<https://powcoder.com>

Binary vs. Graded Relevance

- Two assumptions:
 - Highly relevant documents are more useful than marginally relevant
 - The lower the ranked position of a relevant document, the less useful it is for the user, since it is less likely to be examined
- Discounted Cumulative Gain (DCG)
 - Uses graded relevance as a measure of the usefulness
 - The most popular for evaluating web search

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

38

Discounted Cumulative Gain (DCG)

- Gain is accumulated starting at the top of the ranking and may be reduced (discounted) at lower ranks
- Users care more about high-ranked documents, so we discount results by $1/\log_2(rank)$
 - the discount at rank 4 is $1/2$, and at rank 8 is $1/3$
- DCG_k is the total gain accumulated at a particular rank k (sum of DG up to rank k):

$$DCG_k = rel_1 + \sum_{i=2}^k \frac{rel_i}{\log_2(i)}$$

0, 1, 2, 3, ...
(graded)

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

39

<https://powcoder.com>

DCG Add WeChat powcoder

k	G	DG	DCG@k
1	3	3	3
2	2	2	5
3	3	1.89	6.89
4	0	0	6.89
5	0	0	6.89
6	1	0.39	7.28
7	2	0.71	7.99
8	2	0.67	8.66
9	3	0.95	9.61
10	0	0	9.61

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

40

Normalized DCG (nDCG)

- DCG numbers are averaged across a set of queries at specific rank values (DCG@ k)
 - e.g., DCG at rank 5 is 6.89 and at rank 10 is 9.61
 - Can be any positive real number!
- DCG values are often normalized by comparing the DCG at each rank with the DCG value for the perfect ranking
 - makes averaging easier for queries with different numbers of relevant documents
- $nDCG@k = DCG@k / iDCG@k$ (divide actual by ideal)
- $nDCG \leq 1$ at any rank position

To compare DCGs, normalize values so that a ideal ranking would have a normalized DCG of 1.0


Walid Magdy, TTDS 2020/2021



41

<https://powcoder.com>

nDCG Add WeChat powcoder



k	G	DG	DCG@k	iG	iDG	iDCG@k	nDCG@k
1	3	3	3	3	3.00	3	1.00
2	2	2	5	3	3.00	6	0.83
3	3	1.89	6.89	3	1.89	7.89	0.87
4	0	0	6.89	2	1.00	8.89	0.78
5	0	0	6.89	2	0.86	9.75	0.71
6	1	0.39	7.28	2	0.77	10.52	0.69
7	2	0.71	7.99	1	0.36	10.88	0.73
8	2	0.67	8.66	0	0.00	10.88	0.80
9	3	0.95	9.61	0	0.00	10.88	0.88
10	0	0	9.61	0	0.00	10.88	0.88

Walid Magdy, TTDS 2020/2021



42

Summary:

- IR test collection:
 - Document collection
 - Query set
 - Relevant judgements
 - IR measures
- IR measures:
 - R, P, F → not commonly used
 - P@k, R-precision → used sometimes
 - MAP → the most used IR measure
 - nDGC → the most used measure for web search

Assignment Project Exam Help

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

43

<https://powcoder.com>

Resources

- Text book 1: Intro to IR, Chapter 8
- Text book 2: IR in Practice, Chapter 8

Walid Magdy, TTDS 2020/2021



THE UNIVERSITY
of EDINBURGH

44

Add WeChat powcoder