

Assignment Project Exam Help  
Predicate Logic Cntd.

<https://powcoder.com>

Add WeChat powcoder  
Fariba Sadri

# Rules of Inference

## Natural Deduction

All inference rules for propositional logic +  
4 new rules to deal with the quantifiers.

1.  $\forall$ -elimination ( $\forall E$ )

<https://powcoder.com>

$\forall X p(X)$

Add WeChat powcoder

$p(a)$

where  $a$  is any constant.

The constant  $a$  must replace every free occurrence of  $X$  in  $P(X)$ .

E.g.

From  $\forall X \text{ beautiful}(X)$  we can conclude

$\text{beautiful}(\text{https://powcoder.com})$

From

Add WeChat powcoder

$\forall X (\text{lion}(X) \rightarrow \exists Y (\text{lioness}(Y) \wedge \text{provides\_food}(Y, X)))$

We can infer

$\text{lion}(\text{shere\_khan}) \rightarrow$

$\exists Y (\text{lioness}(Y) \wedge \text{provides\_food}(Y, \text{shere\_khan}))$

# Exercise



Formalise the argument below and show that it is valid.

Assignment Project Exam Help

MSc Generalist and MSc Software Engineering students do group projects.

<https://powcoder.com>

Add WeChat powcoder

Martin is either an MSc Generalist or an MSc Software Engineering student.

So Martin does a group project.

## 2. $\forall$ -Introduction ( $\forall I$ )

(Universal generalisation)

If we know all the ground terms and there are a small number of them, e.g.  $a_1, \dots, a_n$ ,  
then to show

$$\forall X p(X)$$

we show  $p(a_1), \dots, p(a_n)$  .

Suppose we wanted to show

$\forall X (\text{student}(X) \rightarrow$   
 $\text{undergrad}(X) \vee \text{postgrad}(X))$

then this approach would mean checking every student.

This approach is not practical in general.

But maybe we know some properties of being a student, e.g.

Assignment Project Exam Help

All students are enrolled on a degree

<https://powcoder.com>

programme. Add WeChat powcoder

Our only degree programmes are UG and PG.

Then we can show that if you pick any student they will be UG or PG.

In general to show

Assignment Project Exam Help  
 $\forall X p(X)$

we show  $p(a)$  <https://powcoder.com>

for an arbitrary constant  $a$  on which there are  
no constraints.  
Add WeChat powcoder



## $\forall$ -Introduction ( $\forall I$ )

$p(a)$  Assignment Project Exam Help

$\forall X p(X)$

<https://powcoder.com>

provided the following conditions are met:

Add WeChat powcoder

- i.  $a$  is an arbitrary constant.
- ii. There are no assumptions involving  $a$ , left undischarged, used to obtain  $p(a)$ .
- iii. Substitution of  $X$  for  $a$  in  $p(X)$  is uniform, i.e.  $X$  is substituted for every occurrence of  $a$ .

E.g.

From

Assignment Project Exam Help

$\forall Y (q(a, Y) \rightarrow \exists Z (r(Z) \wedge t(Z, Y, a)))$

<https://powcoder.com>

we can infer Add WeChat powcoder

$\forall X \forall Y (q(X, Y) \rightarrow \exists Z (r(Z) \wedge t(Z, Y, X)))$

provided  $a$  is an arbitrary constant.

**Note:**

To be on the safe side:

Make sure there is no variable clash when applying the rule.

The safest is to introduce a new variable, i.e. one that does not occur in the original wff.

# Exercise



All messages are encrypted.

Anything that is encrypted is secure.

<https://powcoder.com>

So all messages are secure.

# Exercise



Given

1.  $\forall X (p(X) \rightarrow \exists Y q(X, Y))$
2.  $\forall Z (\exists X q(Z, X) \wedge r(a) \rightarrow s(Z, a))$
3.  $r(a)$

show

$$\forall X (\neg p(X) \vee s(X, a))$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

### 3. $\exists$ -Introduction ( $\exists I$ )

$p(t)$       Assignment Project Exam Help  
 $\exists X p(X)$       <https://powcoder.com>

Add WeChat powcoder

where  $t$  is any term, and  $X$  does not clash with any occurrence of  $X$  in  $p(t)$ .

$X$  is substituted for one or more occurrences of  $t$  in  $p(t)$ .

**Example:** Given

**logician(charles\_dodgson)  $\wedge$**   
**writer(charles\_dodgson)**

**Abbreviated as  $l(cd) \wedge w(cd)$**

we can derive each of the following by an application of the  $\exists I$  rule.

**$\exists X (l(X) \wedge w(X))$        $\exists X (l(X) \wedge w(cd))$**

**$\exists X (l(cd) \wedge w(X))$**

Beware clash of variables:

Example: Assignment Project Exam Help

There is a course that Mary likes.

$\exists X (\text{course}(X) \wedge \text{likes}(\text{mary}, X))$

We can derive: Add WeChat powcoder

$\exists Y \exists X (\text{course}(X) \wedge \text{likes}(Y, X))$

but not

$\exists X \exists X (\text{course}(X) \wedge \text{likes}(X, X))$

(There is a course that likes itself!)



## 4. $\exists$ -Elimination ( $\exists E$ )

Assignment Project Exam Help

$p(a)$  assume

.. <https://powcoder.com>

.. Add WeChat powcoder

$\exists X p(X),$   $W$   
 $W$

where  $W$  is any wff, provided the following conditions are met:

- i.  $a$  is an arbitrary constant.
- ii. In proving  $W$  from  $p(a)$  the only assumption left undischarged in which  $a$  occurs is  $p(a)$ .
- iii.  $a$  does not occur in  $W$  or in  $\exists X p(X)$ .

Note:

$p(a)$  is an assumption, which is discharged by the application of  $\exists E$  rule, above.

**Example:**

Assignment Project Exam Help

Aliens is an exciting film.

All exciting films make a lot of money.

So there is a film that makes a lot of money.

1.  $\text{film}(\text{als}) \wedge \text{exciting}(\text{als})$  given
2.  $\forall X(\text{film}(X) \wedge \text{exciting}(X) \rightarrow \text{makes\_money}(X))$  given
3.  $\text{film}(\text{als}) \wedge \text{exciting}(\text{als}) \rightarrow \text{makes\_money}(\text{als})$  2,  $\forall E$
4.  $\text{makes\_money}(\text{als})$  3, 1,  $\rightarrow E$
5.  $\text{film}(\text{als})$  1,  $\wedge E$
6.  $\text{film}(\text{als}) \wedge \text{makes\_money}(\text{als})$  5, 4,  $\wedge I$
7.  $\exists X (\text{film}(X) \wedge \text{makes\_money}(X))$  6,  $\exists I$

**Compare with:**

Assignment Project Exam Help

There is an exciting film.

All exciting films make a lot of money.

So there is a film that makes a lot of money.

1.  $\exists X (\text{film}(X) \wedge \text{exciting}(X))$  given
2.  $\forall X (\text{film}(X) \wedge \text{exciting}(X) \rightarrow \text{makes\_money}(X))$  given
3.  $\text{film}(a) \wedge \text{exciting}(a)$  assume
4.  $\text{film}(a) \wedge \text{exciting}(a) \rightarrow \text{makes\_money}(a)$  2,  $\forall E$
5.  $\text{makes\_money}(a)$  3,4,  $\rightarrow E$
6.  $\text{film}(a)$  3,  $\wedge E$
7.  $\text{film}(a) \wedge \text{makes\_money}(a)$  5,6,  $\wedge I$
8.  $\exists X (\text{film}(X) \wedge \text{makes\_money}(X))$  7,  $\exists I$
9.  $\exists X (\text{film}(X) \wedge \text{makes\_money}(X))$  1,3,8,  $\exists E$

Example:

$\exists X (\text{manager}(X) \wedge \text{promoted}(X)) \vdash$   
 $\exists X \text{ promoted}(X)$

More generally, the following are useful derivations:

$\exists X (p(X) \wedge q(X)) \vdash \exists X p(X)$

$\exists X (p(X) \wedge q(X)) \vdash \exists X q(X)$

1.  $\exists X (p(X) \wedge q(X))$  given

2.  $p(a) \wedge q(a)$  assume

3.  $q(a)$  2,  $\wedge E$

4.  $\exists X q(X)$  3,  $\exists I$

5.  $\exists X q(X)$  1, 2, 4,  $\exists E$



# Exercise



Formalise the following argument and show that it is valid.

Assignment Project Exam Help

Someone hacked into secure file  $f$  ('finance').

<https://powcoder.com>

Anyone who hacks into a secure file either has stolen its password or has had insider help.

Add WeChat powcoder

So there is someone who has stolen  $f$ 's password or has had insider help.



# Be careful!

- When applying the inference rules identify the dominant connective/quantifier correctly. <https://powcoder.com> Add WeChat powcoder
- Apply the inference rule applicable to that connective.

## Example:

From

$$\forall X (p(X) \rightarrow q(X))$$

we can derive

$$p(a) \rightarrow q(a)$$

by  $\forall E$ .

But

Assignment Project Exam Help

From

$$\neg \forall X (p(X) \rightarrow q(X))$$

<https://powcoder.com>

we cannot derive

$$\neg (p(a) \rightarrow q(a))$$

Add WeChat powcoder

by  $\forall E$ .

The following derivation is wrong:

$$\neg \forall X (\text{business}(X) \rightarrow \text{avoidsTax}(X))$$

$$\neg (\text{business}(\text{amazon}) \rightarrow \text{avoidsTax}(\text{amazon}))$$



# Be careful!

From  $\neg p(a)$   
we can derive  $\exists X \neg p(X)$  by  $\exists I$ .

But from  $\neg p(a)$   
we cannot derive  $\neg \exists X p(X)$  by  $\exists I$ .

From  $\neg \text{happy}(\text{tom})$  we can derive  
 $\exists X \neg \text{happy}(X)$  but not  $\neg \exists X \text{happy}(X)$ .

# Soundness and Completeness

Predicate logic is sound and complete.

**Decidability** Assignment Project Exam Help

**Definition:**

<https://powcoder.com>

A logical system is **decidable** iff it is possible to have an effective method (an algorithm) that is guaranteed to recognise correctly whether a wff is a theorem of the system or not. In other words, a logical system is decidable if it satisfies conditions 1 and 2 below.

- 1) If  $\models W$  then there is an algorithm that recognises that  $W$  is a theorem.
  - 2) If it is not the case that  $\models W$  then there is an algorithm that recognises that  $W$  is not a theorem.
- <https://powcoder.com>  
Add WeChat powcoder

**Propositional logic is decidable.**

**Predicate logic is not - it is semi-decidable, that is, it satisfies condition 1, above, but not condition 2.**