

Programming in Prolog

Assignment Project Exam Help

Aggregates

Romain Barnoud

<https://powcoder.com>

Add WeChat powcoder

Thanks to:

Dr Fariba Sadri

Claudia Schulz

From lists to individuals

Program

```
city(asia, [tokyo, seoul, beijing]).  
city(europe, [berlin, amsterdam, paris, london]).  
city(america, [new_york, vancouver]).
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

From lists to individuals

Program

```
city(asia, [tokyo, seoul, beijing]).  
city(europe, [berlin, amsterdam, paris, london]).  
city(america, [new_york, vancouver]).
```

Queries

```
?- city(america, _List), member(City, _List).  
City = new_york ;  
City = vancouver ;  
no
```

```
?- city(_Continent, _List), member(City, _List).  
City = tokyo ;  
City = seoul ;  
...  
City = vancouver ;  
no
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

All cities in America

All cities in the world

Program

```
city(asia, tokyo).  
city(asia, seoul).  
city(asia, beijing).  
city(europe, berlin).  
city(europe, amsterdam).  
city(europe, paris).  
city(europe, london).  
  
city(america, new_york).  
city(america, vancouver).
```

How to get a list of the cities in
Europe? Or in the entire world?

<https://powcoder.com>

Add WeChat powcoder

Program

```
city(asia, tokyo).  
city(asia, seoul).  
city(asia, beijing).  
  
city(europe, berlin).  
city(europe, amsterdam).  
city(europe, paris).  
city(europe, london).  
  
city(america, new_york).  
city(america, vancouver).
```

How to get a list of the cities in Europe? Or in the entire world?

Prolog has three built-in predicates for this kind of purpose:

- `findall/3`
- `bagof/3`
- `setof/3`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Definition

`findall(+T, +Goal, -List):`
List is the list of all instances of T for which Goal succeeds.

<https://powcoder.com>

Add WeChat powcoder

Definition

Assignment Project Exam Help

`findall(+T, +Goal, -List):`
List is the list of all instances of T for which Goal succeeds.

Examples

```
?- findall(City, city(europe, City), L).  
L = [berlin, amsterdam, paris, london] ;  
no
```

```
?- findall(City, city(Cont, City), L).  
L = [tokyo, seoul, beijing, berlin, amsterdam, paris, london,  
     new_york, vancouver] ;  
no
```

<https://powcoder.com>

Add WeChat powcoder

Definition

Assignment Project Exam Help

`findall(+T, +Goal, -List):`
List is the list of all instances of T for which Goal succeeds.

Examples

```
?- findall(Cont, city(Cont, City), L).  
L = [asia, asia, asia, europe, europe, europe, europe, america,  
     america];
```

no

```
?- findall(City, city(antarctica, City), L).
```

```
L = [] ;
```

no

<https://powcoder.com>

Add WeChat powcoder

Definition

Assignment Project Exam Help

`findall(+T, +Goal, -List):`
List is the list of all instances of T for which Goal succeeds.

Examples

```
?- findall(Cont-City, city(Cont, City), L).  
L = [asia-tokyo, asia-seoul, asia-beijing, europe-berlin,  
     europe-amsterdam, europe-paris, europe-london,  
     america-new_york, america-vancouver] ;  
no
```

```
?- findall(hello, city(asia, City), L).  
L = [hello, hello, hello] ;  
no
```

<https://powcoder.com>

Add WeChat powcoder

Definition

`findall(+T, +Goal, -List):`
List is the list of all instances of T for which Goal succeeds.

Things to be aware of:

- If Goal cannot be proven, List will be unified with the empty list.
- An instance T θ may appear several several times in List if there are different successful paths to prove Goal θ .
- Free variables in Goal are existentially quantified (hence, there are not part of the answer) — more on that later.

<https://powcoder.com>

Add WeChat powcoder

Definition

`bagof(+T, +Goal, -List):`

For a given substitution σ of free variables in `Goal`
(all possible substitutions are generated through backtracking),
`List` is the list of all instances of `T` such that `Goal σ` succeeds.

<https://powcoder.com>

Add WeChat powcoder

Definition

```
bagof(+T, +Goal, -List):
```

For a given substitution σ of free variables in Goal
(all possible substitutions are generated through backtracking),
List is the list of all instances of T such that Goal σ succeeds.

Examples:

```
?- bagof(City, city(europe, City), L).  
L = [berlin, amsterdam, paris, london] ;  
no
```

```
?- bagof(City, city(Cont, City), L).  
Cont = america, L = [new_york, vancouver] ;  
Cont = asia, L = [tokyo, seoul, beijing] ;  
Cont = europe, L = [berlin, amsterdam, paris, london] ;  
no
```

Definition

```
bagof(+T, +Goal, -List):
```

For a given substitution σ of free variables in Goal
(all possible substitutions are generated through backtracking),
List is the list of all instances of T such that Goal σ succeeds.

Examples:

```
?- bagof(Cont, city(Cont, City), L).
```

```
City = amsterdam, L = [europe] ;
```

```
City = beijing, L = [asia] ;
```

```
City = berlin, L = [europe] ;
```

```
...
```

```
City = tokyo, L = [asia] ;
```

```
City = vancouver, L = [america] ;
```

```
no
```

```
?- bagof(City, city(antarctica, City), L).
```

```
no
```

Definition

```
bagof(+T, +Goal, -List):
```

For a given substitution σ of free variables in Goal
(all possible substitutions are generated through backtracking),
List is the list of all instances of T such that Goal σ succeeds.

Examples

```
?- bagof(Cont-City, city(Cont, City), L).
L = [asia-tokyo, asia-seoul, asia-beijing, europe-berlin,
     europe-amsterdam, europe-paris, europe-london,
     america-new_york, america-vancouver] ;
```

```
no
```

```
?- bagof(hello, city(asia, City), L).
```

```
City = beijing, L = [hello] ;
```

```
City = seoul, L = [hello] ;
```

```
City = tokyo, L = [hello] ;
```

```
no
```

Definition

`bagof(+T, +Goal, -List):`

For a given substitution σ of free variables in `Goal`,
(all possible substitutions are generated through backtracking),
`List` is the list of all instances of `T` such that `Goal σ` succeeds.

Things to be aware of:

- If `Goal` cannot be proven, `bagof/3` will fail.
- For a given instantiation σ of the free variables in `Goal`, an instance `T θ` may appear several times in `List` if there are different successful paths to prove `Goal $\sigma\theta$` .
- Free variables in `Goal` are part of the answer.

Definition

`setof(+T, +Goal, -List):`

For a given substitution σ of free variables in `Goal`
(all possible substitutions are generated through backtracking),
`List` is the **sorted set** of all instances of `T` such that `Goal σ` succeeds.

<https://powcoder.com>

Add WeChat powcoder

Definition

```
setof(+T, +Goal, -List):
```

For a given substitution σ of free variables in Goal
 (all possible substitutions are generated through backtracking),
 List is the **sorted set** of all instances of T such that Goal σ succeeds.

Examples:

```
?- setof(City, city(europe, City), L).
L = [amsterdam, berlin, london, paris] ;
no
```

```
?- setof(City, city(Cont, City), L).
Cont = america, L = [new_york, vancouver] ;
Cont = asia, L = [beijing, seoul, tokyo] ;
Cont = europe, L = [amsterdam, berlin, london, paris] ;
no
```

Definition

setof(+T, +Goal, -List):

For a given substitution σ of free variables in Goal
 (all possible substitutions are generated through backtracking),
 List is the **sorted set** of all instances of T such that Goal σ succeeds.

Examples:

```
?- setof(Cont, city(Cont, City), L).
```

```
City = amsterdam, L = [europe] ;
```

```
City = beijing, L = [asia] ;
```

```
City = berlin, L = [europe] ;
```

```
...
```

```
City = tokyo, L = [asia] ;
```

```
City = vancouver, L = [america] ;
```

```
no
```

```
?- setof(City, city(antarctica, City), L).
```

```
no
```

Definition

setof(+T, +Goal, -List):

For a given substitution σ of free variables in Goal
 (all possible substitutions are generated through backtracking),
 List is the **sorted set** of all instances of T such that Goal σ succeeds.

Examples:

```
?- setof(Cont-City, city(Cont, City), L).
```

```
L = [america-new_york, america-vancouver, asia-beijing,  
     asia-seoul, asia-tokyo, europe-amsterdam,  
     europe-berlin, europe-london, europe-paris].
```

```
no
```

```
?- setof(hello, city(asia, City), L).
```

```
City = beijing, L = [hello] ;
```

```
City = seoul, L = [hello] ;
```

```
City = tokyo, L = [hello] ;
```

```
no
```

<https://powcoder.com>

Add WeChat powcoder

Definition

`setof(+T, +Goal, -List):`

For a given substitution σ of free variables in `Goal`,
(all possible substitutions are generated through backtracking),
`List` is the **sorted set** of all instances of `T` such that `Goal` σ succeeds.

Things to be aware of:

- If `Goal` cannot be proven, `setof/3` will fail.
- For any given instantiation σ of the free variables in `Goal`, the elements in `List` are sorted in ascending order and duplicates are removed.
- Free variables in `Goal` are part of the answer.

Standard Order of Terms

① *Variables < Floats < Integers < Atoms < Compound Terms*

② *Variables* are sorted according to their order of appearance.

③ *Numbers* are compared according the natural order (but a float is always smaller than an integer^[*]).

④ *Atoms* are compared alphabetically

⑤ *Compound terms* are compared: by their arity, then by their functor name (alphabetically), then recursively by their arguments from left to right

To compare terms, use the built-in predicates '==', '\==', '@<', '@=<', '@>', '@>=' or 'compare'.

[*] SWI Prolog uses a different ordering for numbers.

See <http://www.swi-prolog.org/pldoc/man?section=compare>

bagof/3 vs. setof/3

Program

foo(2,a).	foo(2,a).	foo(2,a).
foo(1,b).	foo(1,d).	foo(1,d).
foo(3,c).	foo(1,c).	foo(1,a).

<https://powcoder.com>

bagof/3

```
?- bagof(A, foo(N,A), L).  
N = 1, L = [b, d, c, d, a] ;  
N = 2, L = [a, a, a] ;  
N = 3, L = [c] ;  
no
```

setof/3

```
?- setof(A, foo(N,A), L).  
N = 1, L = [a, b, c, d] ;  
N = 2, L = [a] ;  
N = 3, L = [c] ;  
no
```

Existential quantifiers

`bagof(T, V^Goal, L)`: variable `V` is existentially quantified, it will not be bound in `goal` (thus reproducing the behaviour of `findall/3`).

Assignment Project Exam Help

Program

```
bar(a,b,c).
```

```
bar(b,c,e).
```

```
bar(c,c,g).
```

```
bar(r,b,d).
```

```
bar(b,e,f).
```

<https://powcoder.com>

Queries

```
?- bagof(Z, bar(X,Y,Z), L).
```

```
X = a, Y = b, L = [c, d] ;
```

```
X = b, Y = c, L = [e, f] ;
```

```
X = c, Y = c, L = [g] ;
```

```
no
```

```
?- bagof(Z, X^bar(X,Y,Z), L).
```

```
Y = b, L = [c, d] ;
```

```
Y = c, L = [e, f, g] ;
```

```
no
```

```
?- bagof(Z, X^Y^bar(X,Y,Z), L).
```

```
L = [c, d, e, f, g] ;
```

```
no
```

Add WeChat powcoder

Aggregates are powerful, but computationally very expensive as well.

Assignment Project Exam Help

So do not use them if not necessary!!

`setof/3` less efficient than `bagof/3` less efficient than `findall/3`.

<https://powcoder.com>

To avoid

- `findall(X, member(X, L), List)`
(use `L` directly).
- `findall(X, Goal, List), member(Elt, List)`
(call `Goal` directly and use `X` in place of `Elt`).

Add WeChat powcoder

What have we learned today?

Assignment Project Exam Help

- How to collect solutions in a list,
using `findall(1/3, bagoff/3, [dr, setoff/3])`

<https://powcoder.com>

- What are the differences between these three aggregates

Add WeChat powcoder