

# Answers to Some Predicate Logic Formalisation Exercises from the Predicate Logic Notes

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Predicates to be used:

lecTheatre/1

same/2

office/1

phd/1

contains/2

supervises/2

lecturer/1

happy/1

has/2

completePhd/1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1.

311 is a lecture theatre and 447 is an office.

Assignment Project Exam Help

311 is a lecture theatre and 447 is an office

<https://powcoder.com>

^

Add WeChat powcoder

lecTheatre(311) ^ office(447)

2. Every lecture theatre contains a projector.

Every lecture theatre contains a projector.

~~∀~~ ( Assignment Project Exam Help )

Every

Any

All

Everyone

....

<https://powcoder.com>

Add Map to V  
Add Web to V  
Add Chat to V  
Add powcoder

Every lecture theatre contains a projector.

Assignment Project Exam Help

$\forall X (\text{lecTheatre}(X) \rightarrow$   
<https://powcoder.com>  
 $\text{contains}(X, \text{projector}))$

Add WeChat powcoder

Alternatively:

$\forall X (\text{lecTheatre}(X) \rightarrow$   
 $\exists Y (\text{projector}(Y) \wedge \text{contains}(X, Y)))$

A universally quantified wff is usually like this:

$\forall x ($   [Assignment Project Exam Help](https://powcoder.com)  $)$

Or like this:

$\forall x ($   <https://powcoder.com>  $)$   
[Add WeChat powcoder](https://powcoder.com)

That is their principle connective is

$\rightarrow$  or  $\leftrightarrow$ .

3. Every office contains a telephone and either a desktop or a laptop computer.

Every office contains a telephone and either a desktop or a laptop computer.

$\forall X (\text{office}(X) \rightarrow \dots)$   
... contains a telephone and either a desktop or a laptop computer.

$\forall X (\text{office}(X) \rightarrow (\dots \wedge \dots))$   
 $\forall X (\text{office}(X) \rightarrow (\text{contains}(X, \text{telephone}) \wedge (\dots)))$

... either a desktop or a laptop computer.

$\forall X (\text{office}(X) \rightarrow (\text{contains}(X, \text{telephone}) \wedge (\dots \vee \dots)))$

$\forall X (\text{office}(X) \rightarrow (\text{contains}(X, \text{telephone}) \wedge (\text{contains}(X, \text{desktop}) \vee \text{contains}(X, \text{laptop}))))$

4. Every lecturer has at least one office.

Every lecturer has at least one office.

Assignment Project Exam Help

<https://powcoder.com>

$\forall X (\text{lecturer}(X) \rightarrow \dots)$

Add WeChat powcoder

... has at least one office.

$\forall X (\text{lecturer}(X) \rightarrow \exists Y (\text{office}(Y) \wedge \text{has}(X, Y)))$



At least one

Some

One

....

map to  $\exists$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

An existentially quantified wff is usually like this:

$\exists x ( \quad \wedge \quad )$  Assignment Project Exam Help

Or like this: <https://powcoder.com>

$\exists x ( \quad \vee \quad )$  Add WeChat powcoder

That is their principle connective is

$\wedge$  or  $\vee$ .

5. No lecturer has more than one office.

No lecturer has more than one office.

Not any lecturer has more than one office.

(There does not exist a lecturer who has more than one office.)

$\neg \exists L (\text{lecturer}(L) \wedge L \text{ has more than one office})$

$\neg \exists L (\text{lecturer}(L) \wedge L \text{ has at least 2 offices that are not the same})$

$\neg \exists L (\text{lecturer}(L) \wedge \text{there are at least 2 offices that } L \text{ has and are not the same})$

Assignment Project Exam Help

<https://powcoder.com>

$\neg \exists L (\text{lecturer}(L) \wedge$

$\exists O1 \exists O2 (\text{office}(O1) \wedge \text{office}(O2) \wedge$

$\text{has}(L, O1) \wedge \text{has}(L, O2) \wedge$

$\neg \text{same}(O1, O2)))$

There are other ways of doing 5. For example:

$\forall L (\text{lecturer}(L) \rightarrow \neg (\exists O1 \exists O2 (\text{office}(O1) \wedge$   
 $\text{office}(O2) \wedge \text{has}(L, O1) \wedge \text{has}(L, O2) \wedge$   
 $\neg \text{same}(O1, O2)))$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$\forall L \forall O1 \forall O2 (\text{lecturer}(L) \wedge \text{office}(O1) \wedge$   
 $\text{office}(O2) \wedge \text{has}(L, O1) \wedge \text{has}(L, O2) \rightarrow$   
 $\text{same}(O1, O2))$

6. No lecturers share offices with anyone.

Try it .....

Assignment Project Exam Help

7. Some lecturers supervise PhD students and some do not.

<https://powcoder.com>

Add WeChat powcoder

$(\exists L \dots) \wedge (\exists L \dots)$  or

$(\exists L1 \dots) \wedge (\exists L2 \dots)$

Some lecturers supervise PhD students and some do not.

Assignment Project Exam Help

$(\exists L (\text{lecturer}(L) \wedge \text{there is at least one PhD student that } L \text{ supervises})) \wedge$

<https://powcoder.com>

$(\exists L (\text{lecturer}(L) \wedge \text{there is not at least one PhD student that } L \text{ supervises}))$

Add WeChat powcoder

$(\exists L (\text{lecturer}(L) \wedge \exists S (\text{phd}(S) \wedge \text{supervises}(L, S)))) \wedge$

$(\exists L (\text{lecturer}(L) \wedge \neg \exists S (\text{phd}(S) \wedge \text{supervises}(L, S))))$

$(\exists L (\text{lecturer}(L) \wedge \exists S (\text{phd}(S) \wedge \text{supervises}(L,S)))) \wedge$   
 $(\exists L (\text{lecturer}(L) \wedge \neg \exists S (\text{phd}(S) \wedge \text{supervises}(L,S))))$

Assignment Project Exam Help

Drop some unnecessary brackets:

<https://powcoder.com>

$\exists L (\text{lecturer}(L) \wedge \exists S (\text{phd}(S) \wedge \text{supervises}(L,S))) \wedge$

Add WeChat powcoder

$\exists L (\text{lecturer}(L) \wedge \neg \exists S (\text{phd}(S) \wedge \text{supervises}(L,S)))$



8. Each PhD student has an office, but all PhD students share their office with at least one other PhD student.

Assignment Project Exam Help

Try it .....

<https://powcoder.com>

Add WeChat powcoder

9. A lecturer is happy **if** the PhD students he/she supervises successfully complete their PhD.

**Assignment Project Exam Help**  
 $\forall L (\text{lecturer}(L) \wedge \text{his/her PhD students successfully complete} \rightarrow \text{happy}(L))$   
**<https://powcoder.com>**

**Add WeChat powcoder**  
 $\forall L (\text{lecturer}(L) \wedge \text{all his/her PhD students successfully complete} \rightarrow \text{happy}(L))$

$\forall L (\text{lecturer}(L) \wedge \forall S \text{ if } S \text{ is } L\text{'s PhD student then } S \text{ successfully completes} \rightarrow \text{happy}(L))$

$\forall L (\text{lecturer}(L) \wedge$

$\forall S$  *if S is L's PhD student then S successfully completes*  $\rightarrow \text{happy}(L))$

Assignment Project Exam Help

<https://powcoder.com>

$\forall L (\text{lecturer}(L) \wedge$

$\forall S (\text{phd}(S) \wedge \text{supervises}(L, S) \rightarrow \text{completePhD}(S))$   
 $\rightarrow \text{happy}(L))$

Add WeChat powcoder

10. Not all PhD students complete their PhD.

Try it ....

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder