

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

- ▶ Chapter 6 - Model Specification

- ▶ ACF/PACF/EACF for determining  $p, d, q$

- ▶ Chapter 7 - Parameter Estimation

- ▶ We will skip this

- ▶ Chapter 8 - Model Diagnostics

- ▶ Does the model fit well?

- ▶ Which model fits better?

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

1. Plot the time series
2. Determine appropriate transformation for nonconstant variance
3. Difference or detrend as needed
4. Plot ACF, PACF, EACF to help identify appropriate order of  $p$  and  $q$

<https://powcoder.com>  
Add WeChat powcoder

# Assignment Project Exam Help

1. Plot the time series. Looking for

- ▶ trends
- ▶ seasonality
- ▶ nonconstant variance
- ▶ outliers
- ▶ abrupt changes

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

2. Determine appropriate transformation if nonconstant variance exists

<https://powcoder.com>

- ▶ Box-Cox procedure
- ▶ Try several and stick with best

Add WeChat powcoder

# Assignment Project Exam Help

### 3. Difference data as needed to remove trends

- ▶ Will likely notice trend in time series plot
- ▶ Can plot ACF on original series, ACF will decay very slowly
  - ▶ First difference likely sufficient, possibly 2nd order difference
  - ▶ *Rarely*, if ever, will you need to difference more than twice

Add WeChat powcoder

## Strategy

4. Plot sample ACF, PACF, and EACF on the stationary series to determine  $p$  and  $q$

- ▶ Can be original, transformed, differenced, or transformed/differenced series (whichever one is stationary)

- ▶  $p$  and  $q$  are generally never too high, say  $\leq 4$  (excluding seasonal models which we haven't covered yet)

- ▶ Principle of Parsimony

- ▶ Use knowledge of theoretical patterns in ACF, PACF, and EACF to guide selection of  $p$  and  $q$

- ▶ ACF cuts off at  $q$  for  $MA(q)$

- ▶ PACF cuts off at  $p$  for  $AR(p)$

- ▶ Wedge or upper left 0 in EACF table identifies  $p$  and  $q$  for  $ARMA(p, q)$  models

## Identifying Model Order

# Assignment Project Exam Help

- ▶ "The art of model selection is very much like the method of an FBI agent's criminal search. Most criminals disguise themselves to avoid being recognized."
- ▶ Similar for ACF, PACF, and EACF. Sampling variation can disguise theoretical patterns making it difficult to clearly ascertain  $p$  and  $q$
- ▶ At the end of these steps...
  - ▶ probably have multiple candidate models
  - ▶ rare to have one definite model in practice

<https://powcoder.com>

Add WeChat powcoder



## Next Steps (Chapter 8)

# Assignment Project Exam Help

- ▶ Fit candidate models
- ▶ Compare them
- ▶ Diagnose assumptions
- ▶ Determine which seems most appropriate
- ▶ After selecting the “best” model, forecasting becomes the central focus (Chapter 9)

<https://powcoder.com>

Add WeChat powcoder



# Assignment Project Exam Help

- ▶ The supreme court dataset represents the acceptance rate of cases appealed to the Supreme Court during 1926-2004.
- ▶ Convert to stationary, then identify  $p$  and  $q$


Add WeChat powcoder

# Supreme Court Data


Original Data



Log Transformed




Log Transformed and Differenced




## Supreme Court Data

Series diff(log(sc))



Series diff(log(sc))



# Assignment Project Exam Help

AS/ML

0 1 2 3 4 5 6 7 8 9 10 11 12 13

0 x o o o o o o x o x x o o o

1 x o o o o o o x o o x o o o

2 x o o o o o o o o o o o o o

3 x x x o o o o o o o o o o o

4 x o o o o o o o o o o o o o

5 x o x o o o o o o o o o o

6 x x x o x x o o o o o o o o

7 o o x x o o x o o o o o o o

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

- ▶ Based on everything, probably start with an  $IMA(1)$  model
  - ▶ Why?

```
arima(log(sc), order=c(0, 1, 1))$coef
```

$ma_1$   
-0.355319

# Add WeChat powcoder

## Supreme Court Data - MA(1) Model

After fitting an MA(1) model, we find the following regression equation

$$\nabla \log(Y_t) = e_t - 0.356e_{t-1}$$

- ▶ <https://powcoder.com> As with linear regression, we study residuals to determine appropriateness of model
- ▶ In time series, we want the residuals to look like white noise
  - ▶ Normally distributed
  - ▶ Independent
  - ▶ Constant variance (though this should have been taken care of in previous steps. . . )

Add WeChat powcoder

# Assignment Project Exam Help

### ▶ Normality

- ▶ Histogram of residuals
- ▶ Normal QQ plot of residuals
- ▶ Shapiro-Wilk Test

<https://powcoder.com>

### ▶ Independence

- ▶ Runs test
- ▶ Plot of residual ACF
- ▶ Ljung-Box Test

Add WeChat powcoder



Normality


# Assignment Project Exam Help

```
scMA1 <- arima(log(sc), order=c(0, 1, 1) )  
hist(rstandard(scMA1)) # histogram  
qqnorm(rstandard(scMA1)) # qqplot  
qqline(rstandard(scMA1))  
shapiro.test(rstandard(scMA1) ) # shapiro test
```


<https://powcoder.com>  
Add WeChat powcoder

## Histogram and QQ Plot

Histogram of rstandard(scMA1)



Normal Q-Q Plot



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Shapiro-Wilk Test

Assignment Project Exam Help

▶  $H_0$ : The standardized residuals are normally distributed  
▶  $H_a$ : The standardized residuals are not normally distributed

```
shapiro.test(rstandard(scMA1))
```

<https://powcoder.com>

Shapiro-Wilk normality test

```
data:  rstandard(scMA1)
```

```
W = 0.98632, p-value = 0.5639
```

Add WeChat powcoder

Independence

# Assignment Project Exam Help

```
runs(rstandard(scMA1)) # runs test  
acf(lstandard(scMA1)) # residual ACF  
Box.test(residuals(scMA1), lag=k, type='Ljung-Box', fitdf=1)  
tsdiag(scMA1) # produces relevant plots
```

<https://powcoder.com>

## Add WeChat powcoder

## Runs test

- ▶ The **runs test**
  - ▶  $H_0$ : The standardized residuals are independent
  - ▶  $H_a$ : The standardized residuals are independent

```
runs(rstandard(scMA1))
```

```
$pvalue
```

```
[1] 0.864
```

```
$observed.runs
```

```
[1] 37
```

```
$expected.runs
```

```
[1] 38.21519
```

```
$n1
```

```
[1] 49
```

```
$n2
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Residual ACF

- ▶ Under “white noise” assumption, the autocorrelations follow  $N(0, \sigma^2 = 1/n)$ 
  - ▶ Plot them, if many are outside of  $\pm 1.96/\sqrt{(n)}$  then independence appears to be violated



## Ljung-Box Test

# Assignment Project Exam Help

- ▶ In addition to examining lag  $k$  autocorrelation individually, we can assess their magnitude as a group
- ▶ For example, most of the ACFs may be moderate, but, taken as a group might look excessive.
- ▶ Ljung-Box test developed for this scenario
  - ▶  $H_0$ : ARMA( $p, q$ ) model is appropriate
  - ▶  $H_1$ : ARMA( $p, q$ ) model is not appropriate

Add WeChat powcoder

## Ljung-Box Test

Assignment Project Exam Help

```
# tsdiag(scMA1) # runs test for multiple lags, want most p-  
Box.test(residuals(scMA1), lag=10, type='Ljung-Box', fitdf=
```

<https://powcoder.com>

Box-Ljung test

```
data: residuals(scMA1)
```

```
X-squared = 20.484, df = 9, p-value = 0.01515
```

Add WeChat powcoder



## Overfitting

# Assignment Project Exam Help

- ▶ In addition to performing thorough residual analysis, overfitting can be a useful diagnostic technique to further assess the validity of an assumed model.
- ▶ Overfitting involves fitting a model more complicated than the one currently being considered and
  - ▶ examining the significance of the additional terms
  - ▶ examining the change in estimates from the assumed model

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

- ▶ When overfitting an  $\text{ARMA}(p, q)$  model, we consider the following two models

1.  $\text{ARMA}(p + 1, q)$
2.  $\text{ARMA}(p, q + 1)$

Add WeChat powcoder

## Overfitting

Suppose my current model is an MA(1), or an ARMA(0, 1)

► Fit an ARMA(0, 2)

- If additional MA term is insignificant  $\rightarrow$  evidence that more complicated model is not needed
- If additional MA term is significant  $\rightarrow$  evidence that the MA(2) is worth considering
- Residual analysis, see if things improved/worsened

► Fit an ARMA(1, 1)

► Same as above

► Can continue this process

- add  $q$ , add  $p$ , diagnose until you reach a suitable model that fits well

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Model Diagnostics with `sarima()`

# Assignment Project Exam Help

- ▶ Diagnostic plots are provided in output
- ▶ Residual analysis as before

1. Standardized residuals should look random (white noise)
2. ACF of residuals should remain within boundary lines
3. Normal Q-Q plot
4. p values for Ljung-Box statistic

- ▶ Tests for "randomness" of residuals

- ▶ Most points should be above boundary line

- ▶ If many are under it, start "overfitting" and hope for better results

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

- ▶ Several models may look reasonable
  - ▶ Overfit supreme court data, you will find multiple ARIMA models that fit well
- ▶ Common to fit several and accept the model with the lowest AIC or BIC value
  - ▶ AIC - Akaike Information Criterion
  - ▶ BIC - Bayesian Information Criterion

<https://powcoder.com>

Add WeChat powcoder

## Summary

- ▶ We now know how to
  - ▶ specify a model
    - ▶ ACF/PACF/EACF for  $p, d, q$
  - ▶ diagnose how well it fits (are the residuals white noise)
    - ▶ Normality
    - ▶ Independence
  - ▶ Compare models
    - ▶ overfit and diagnose
    - ▶ compare AIC or BIC

- ▶ You are now well versed in modeling time series data in the ARIMA( $p, d, q$ ) family

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Summary

# Assignment Project Exam Help

- ▶ No model is perfect!
- ▶ Model specification and selection is not always clear cut
- ▶ Lots of trial and error

<https://powcoder.com>

- ▶ Not a “black box” exercise
- ▶ In the end, want a simple model that fits data well
- ▶ With this model, we focus on forecasting

Add WeChat powcoder