

Assignment Project Exam Help

ARIMA Models


<https://powcoder.com>

MAS-640


Add WeChat powcoder

1/24/2018

Chicken Price



CREF Data Example



Assignment Project Exam Help

- ▶ MA(q) models have 0 autocorrelation beyond lag q





Add WeChat powcoder

ACF Plots for MA(q) Processes

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder







Assignment Project Exam Help

- ▶ Autocorrelation for AR(p) process decays over time, but does not cut off to 0

Add WeChat powcoder

ACF Plots for AR(p) Processes



Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder

Which Model Generated These Plots?

Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder

Assignment Project Exam Help

	AR(p)	MA(q)
ACF	Tails off	Cuts off after lag q

- ▶ <https://powcoder.com>
 - ▶ If we need MA components in our model (and how many)
 - ▶ If we need AR components
- ▶ Unfortunately, due to the nature of ACF for AR processes, we cannot determine the order, p

Add WeChat powcoder

Assignment Project Exam Help

- ▶ The ACF provides a considerable amount of info about the order of the dependence or MA processes
- ▶ Unfortunately, it doesn't for AR processes
- ▶ Need a new function that behaves like the ACF for MA models, but for use with AR models instead.
 - ▶ This function is called the partial autocorrelation function (PACF).

<https://powcoder.com>
Add WeChat powcoder

Partial Autocorrelation Function (PACF)

Assignment Project Exam Help

- **Basic idea.** What is the correlation between Y_t and Y_{t-k} after taking into account $Y_{t-1}, Y_{t-2}, \dots, Y_{t-k+1}$

- **Technically:**

1. Regress Y_t on $Y_{t-1}, Y_{t-2}, \dots, Y_{t-k+1}$ and find \hat{Y}_t
2. Regress Y_{t-k} on $Y_{t-1}, Y_{t-2}, \dots, Y_{t-k+1}$ and find \hat{Y}_{t-k}
3. Use correlation between \hat{Y}_t and \hat{Y}_{t-k}

- “Partial” because I’m removing everything in the middle.

- `pacf()` for PACF, or `acf2()` for both ACF and PACF

<https://powcoder.com>

Add WeChat powcoder





PACF for AR(p) Models

- Can you guess the AR order, p ?

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder



ACF Plots for MA(q) Processes

- Can you guess the MA order q ?



Determining AR and MA Components

Assignment Project Exam Help

	AR(p)	MA(q)
ACF	Tails off	Cuts off after lag q
PACF	Cuts off after lag p	Tails off

<https://powcoder.com>

- ▶ Now we are comfortable with these!
- ▶ Let's use them to build more complicated models

Add WeChat powcoder

Autoregressive Moving Average (ARMA) Process

Assignment Project Exam Help

Suppose $\{e_t\}$ is a zero mean white noise process with $\text{var}(e_t) = \sigma_e^2$.
The process

<https://powcoder.com>

$$Y_t = \phi_1 Y_{t-1} + \phi_2 Y_{t-2} + \dots + \phi_p Y_{t-p} + e_t + \theta_1 e_{t-1} + \dots + \theta_q e_{t-q}$$

is an autoregressive moving average process with AR order p and MA order q , written as ARMA(p, q).

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Special cases

- ▶ ARMA(0, 0):

<https://powcoder.com>

- ▶ ARMA(p, 0):

- ▶ ARMA(0, q):

Add WeChat powcoder

Assignment Project Exam Help

$$Y_t = \mu_t + \epsilon_t$$

- ▶ We model μ_t with standard linear regression techniques
- ▶ We are left with the error terms
 - ▶ These errors are correlated
 - ▶ We want to model them
- ▶ These errors can be correlated with past values of itself (AR) or past errors (MA)
 - ▶ We just need to determine which components (AR or MA), and how many of each, to include in our model

<https://powcoder.com>

Add WeChat powcoder

Some ARMA(1, 1) Processes


$\phi = 0.9, \theta = 0.9$




$\phi = 0.7, \theta = 0.5$



$\phi = 0.5, \theta = -0.5$



$\phi = -0.5, \theta = -0.5$




Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

ACF for ARMA(1,1) Processes


$\phi = 0.9, \theta = 0.9$




$\phi = 0.7, \theta = 0.5$



$\phi = 0.5, \theta = -0.5$



$\phi = -0.5, \theta = -0.5$




Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

PACF for ARMA(1,1) Processes


phi 0.9, theta 0.9




phi 0.7, theta 0.5



phi 0.5, theta -0.5



phi -0.5, theta -0.5



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Determining Order for ARMA(p , q)

Assignment Project Exam Help

- Unfortunately, no clear “drop-offs” are present in the ACF or PACF plots
- So we can't determine p or q if AR and MA components are both present in model
- We do have the following to guide the process:

<https://powcoder.com>

	AR(p)	MA(q)	ARMA(p,q)
ACF	Tails off	Cuts off after lag q	Tails off
PACF	Cuts off after lag p	Tails off	Tails off

Fitting an ARMA(p, q) Model

Assignment Project Exam Help

- ▶ If the ACF and PACF both tail off, this is evidence of an ARMA model
- ▶ But how to determine p and q ?
 - ▶ “Go fit an ARMA model to this data. . .”

<https://powcoder.com>

Add WeChat powcoder

Fitting ARMA Models in R

Assignment Project Exam Help

- ▶ Previously used `ar()` function to fit an AR model and let it decide the order p by comparing AIC values
- ▶ Need something more comprehensive for ARMA models

<https://powcoder.com>

- ▶ `arma()`
 - ▶ `arima()`
 - ▶ `sarima()`
- ▶ Each of these accomplish the same thing, some are easier to use
- ▶ I will stick with `sarima()` for the remainder of the course

Add WeChat powcoder

The `sarima()` Function

Seasonal **A**utoregressive **I**ntegrated **M**oving **A**verage

`sarima(x, p, d, q, P=0, D=0, Q=0, S=-1, ...)`

► Where

- `x` is the data
- `p` and `q` are the AR and MA orders (note that you now have to specify)
- `d` tells the function to difference the data `d` times (next class, use 0 for now)
- The capital letters are seasonal components that we ignore for now
- `x`, `p`, `d`, and `q` are required

The 'sarima.for()' Function

Assignment Project Exam Help

- ▶ `sarima()` not compatible with `predict()`, but it does come with it's own function for forecasting

<https://powcoder.com>

```
sarima.for(x, n.ahead, p, d, q, ...)
```

Add WeChat powcoder

Examples Using `sarima()`

Write the code for fitting each of the following models to data `x`:

1. AR(1) -

2. MA(3) -

3. AR(2) -

4. ARMA(1, 1) -

5. ARMA(2, 1) -

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples Using `sarima.for()`

Write the code for forecasting the next 6 time periods for each of the following models:

1. AR(1) -

2. MA(3) -

3. AR(2) -

4. ARMA(1, 1) -

5. ARMA(2, 1) -

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder