



UNIVERSITY OF
BIRMINGHAM

Hierarchical Clustering and Expectation-Maximization


Assignment Project Exam Help
<https://powcoder.com>

Shuo Wang

Add WeChat powcoder




AI Taxonomy



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Outline

- Clustering concepts
- Hierarchical clustering
- Gaussian mixture models using EM

Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder


Clustering

- Segment data into clusters, such that there is
 - high intra-cluster similarity
 - low inter-cluster similarity
- Informally, finding natural groupings among objects.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





What is the natural grouping of these objects?




Add WeChat powcoder


What is the natural grouping of these objects?




Simpson's family



School employees



Females



Males



UNIVERSITY OF
BIRMINGHAM

Picture from CMU

Clustering set-up

- Our data are: $D = \{x_1, \dots, x_N\}$.
- Each data point **Assignment Project Exam Help** is m -dimensional i.e. $x_i = \langle x_{i,1}, \dots, x_{i,m} \rangle$
- Define a *distance function* (i.e. *similarity measures*) between data, $d(x_i, x_j)$ **Add WeChat powcoder**
- Goal: segment x_n into k groups **https://powcoder.com**
 $\{z_1, \dots, z_N\}$ where $z_i \in \{1, \dots, K\}$

Similarity Measures

- Between any two data samples p and q , we can calculate their distance $d(p,q)$ using a number of measurements:

Euclidean Assignment Project Exam Help

$$d(p, q) = d(q, p) = \sqrt{(q_1 - p_1)^2 + (q_2 - p_2)^2 + \cdots + (q_n - p_n)^2}$$

Manhattan

<https://powcoder.com>

$$d(p, q) = \sum_{i=1}^n |p_i - q_i|$$

Chebyshev

Add WeChat powcoder

$$d_{\text{Chebyshev}}(p, q) = \max_i(|p_i - q_i|)$$

Minkowski

$$d(p, q) = \left(\sum_{i=1}^n |p_i - q_i|^b \right)^{1/b}$$



UNIVERS
BIRMINGHAM

Types of Clustering Algorithms

- Partitional clustering, e.g. K-means, K-medoids
- Hierarchical clustering
Bottom-up (agglomerative)
Top-down
- Density-based clustering, e.g. DBScan
- Mixture density based clustering
- Fuzzy theory based, graph theory based, grid based, etc.

Hierarchical clustering

- Create a hierarchical decomposition of the set of objects using some criterion [Assignment](#) [Project](#) [Exam](#) [Help](#)
- Produce a dendrogram

<https://powcoder.com>


Add WeChat powcoder




UNIVERSITY OF
BIRMINGHAM

(Bovine, (Spider Monkey, (Gibbon, (Orang, (Gorilla, (Chimp, Human))))));


Hierarchical clustering



Agglomerative clustering illustration



Dendrogram: A visual representation of output



Agglomerative clustering algorithm

1. Place each data point into its own singleton group
2. Repeat: iteratively merge the two closest groups
3. Until: all the data are merged into a single cluster

Add WeChat powcoder

- Output: a dendrogram
- Reply on: a *distance metric* between clusters


Measuring distance between clusters

- Single linkage
the similarity of the closest pair
- Complete linkage
the similarity of the furthest pair
- Group average
the average similarity of all pairs
more widely used
robust against noise


Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



$$d_{SL}(G, H) = \min_{i \in G, j \in H} d_{i,j}$$



$$d_{CL}(G, H) = \max_{i \in G, j \in H} d_{i,j}$$



$$d_{GA} = \frac{1}{N_G N_H} \sum_{i \in G} \sum_{j \in H} d_{i,j}$$



UNIVERSITY OF
BIRMINGHAM

Try your own data here:

<http://jydelort.appspot.com/resources/figue/demo.html>

Strengths, weaknesses, caveats

- Strengths
 - provides deterministic results
 - no need to specify number of clusters beforehand
 - can create clusters of arbitrary shapes
- Weakness <https://powcoder.com>
 - does not scale up for large datasets, time complexity at least $O(n^2)$
- Caveats [Add WeChat powcoder](#)
 - Different decisions about group similarities can lead to vastly different dendograms.
 - The algorithm imposes a hierarchical structure on the data, even data for which such structure is not appropriate.