

# Assignment Project Exam Help

## Predictive Analytics

Week 12: Exponential Smoothing

<https://powcoder.com>

Semester 2, 2018

Discipline of Business Analytics, The University of Sydney Business School

## Add WeChat powcoder

# Assignment Project Exam Help

1. Simple exponential smoothing
2. Trend corrected exponential smoothing
3. Holt winters smoothing
4. Damped trend exponential smoothing

<https://powcoder.com>

Add WeChat powcoder

## Exponential smoothing methods

# Assignment Project Exam Help

**Exponential smoothing** forecasts are weighted averages of past observations, where the weights decay exponentially as we go further into the past.

<https://powcoder.com>

Exponential smoothing can be useful when the time series components are changing over time.

Add WeChat powcoder

# Assignment Project Exam Help

Simple exponential smoothing  
<https://powcoder.com>

Add WeChat powcoder

## Simple exponential smoothing (keyboard)

# Assignment Project Exam Help

The **simple exponential smoothing** method specifies the forecasting rule

$$\hat{y}_{t+1} = \ell_t \quad (\text{forecast equation})$$

$$\ell_t = \alpha y_t + (1 - \alpha)\ell_{t-1} \quad (\text{smoothing equation})$$

**Add WeChat powcoder**  
for an initial value  $\ell_0$  and  $0 \leq \alpha \leq 1$ .

## Exponentially weighted moving average

$$\ell_1 = \alpha y_1 + (1 - \alpha)\ell_0$$

Assignment Project Exam Help

$$\begin{aligned}\ell_2 &= \alpha y_2 + (1 - \alpha)\ell_1 \\ &= \alpha y_2 + (1 - \alpha)\alpha y_1 + (1 - \alpha)^2 \ell_0\end{aligned}$$

<https://powcoder.com>

$$\begin{aligned}\ell_3 &= \alpha y_3 + (1 - \alpha)\ell_2 \\ &= \alpha y_3 + (1 - \alpha)\alpha y_2 + (1 - \alpha)^2 \alpha y_1 + (1 - \alpha)^3 \ell_0\end{aligned}$$

Add WeChat powcoder

$$\begin{aligned}\ell_4 &= \alpha y_4 + (1 - \alpha)\ell_3 \\ &= \alpha y_4 + (1 - \alpha)\alpha y_3 + (1 - \alpha)^2 \alpha y_2 + (1 - \alpha)^3 \alpha y_1 + (1 - \alpha)^4 \ell_0 \\ &\vdots\end{aligned}$$

## Exponentially weighted moving average

# Assignment Project Exam Help

$$\ell_t = \alpha y_t + (1 - \alpha)\ell_{t-1}$$

$$= \alpha y_t + (1 - \alpha)\alpha y_{t-1} + (1 - \alpha)^2 \alpha y_{t-2} + \dots + (1 - \alpha)^{t-1} \alpha y_1 + (1 - \alpha)^t \ell_0.$$

Add WeChat powcoder

Simple exponential smoothing is also known as the **exponentially weighted moving average** (EWMA) method.

## Simple exponential smoothing

Assignment Project Exam Help

- Useful for forecasting time series with changing levels.

- A higher  $\alpha$  gives larger weight to recent observations, making the forecasts more adaptive to recent changes in the series.

<https://powcoder.com>

- A lower  $\alpha$  leads to a larger weights for past observations, making the forecasts smoother.


Add WeChat powcoder

- Initialisation: we typically set  $\ell_0 = y_1$  for simplicity.


Alternatively, we can treat it as a parameter.



## Example: AUD/USD exchange rate



## Example: AUD/USD exchange rate



# Assignment Project Exam Help

We estimate  $\alpha$  by least squares (empirical risk minimisation).

$$\hat{\alpha} = \operatorname{argmin}_{\alpha} \sum_{t=1}^N (y_t - \ell_{t-1})^2$$

<https://powcoder.com>

Each  $\ell_t$  is a nonlinear function of  $\alpha$ , so that there is no formula for  $\hat{\alpha}$ . We use numerical optimisation methods to obtain the solution.

# Assignment Project Exam Help

In order to say more about the simple exponential smoothing method, we need to formulate it as a statistical model. We assume that

<https://powcoder.com>

$$Y_t = \ell_{t-1} + \varepsilon_t,$$

$$\ell_t = \alpha y_t + (1 - \alpha)\ell_{t-1},$$

Add WeChat powcoder

where the errors  $\varepsilon_t$  are i.i.d with constant variance  $\sigma^2$ .

# Assignment Project Exam Help

In forecasting, we want to:

1. To compute point forecasts for multiple forecasting horizons  $h$ .
2. To compute interval forecasts for multiple forecasting horizons  $h$ .

<https://powcoder.com>

## Add WeChat powcoder

In order to this for the exponential smoothing method, we rewrite the model in **error correction form**.

## Error correction form

We obtain the error correction form as

$$\begin{aligned} \ell_t &= \alpha Y_t + (1 - \alpha)\ell_{t-1} \\ &= \ell_{t-1} + \alpha(Y_t - \ell_{t-1}) \\ &= \ell_{t-1} + \alpha\varepsilon_t. \end{aligned}$$

<https://powcoder.com>

Hence, we can rewrite the model as:

$$\begin{aligned} Y_{t+1} &= \ell_t + \varepsilon_{t+1}, \\ \ell_t &= \ell_{t-1} + \alpha\varepsilon_t. \end{aligned}$$

## Error correction form

Using  $\ell_t = \ell_{t-1} + \alpha \varepsilon_t$ ,

$$\ell_{t+1} = \ell_t + \alpha \varepsilon_{t+1}$$

$$\ell_{t+2} = \ell_{t+1} + \alpha \varepsilon_{t+2}$$

$$= \ell_t + \alpha \varepsilon_{t+1} + \alpha \varepsilon_{t+2}$$

$$\ell_{t+3} = \ell_{t+2} + \alpha \varepsilon_{t+3}$$

$$= \ell_t + \alpha \varepsilon_{t+1} + \alpha \varepsilon_{t+2} + \alpha \varepsilon_{t+3}$$

Add WeChat powcoder

$$\ell_{t+h} = \ell_t + \sum_{i=1}^h \alpha \varepsilon_{t+i}$$

## Constant plus noise representation

Using  $Y_t = \ell_{t-1} + \varepsilon_t$  and the previous slide,

$$Y_{t+1} = \ell_t + \varepsilon_{t+1}$$

$$Y_{t+2} = \ell_{t+1} + \varepsilon_{t+2}$$

$$= \ell_t + \alpha \varepsilon_{t+1} + \varepsilon_{t+2}$$

$$Y_{t+3} = \ell_{t+2} + \varepsilon_{t+3}$$

$$= \ell_t + \alpha \varepsilon_{t+1} + \alpha \varepsilon_{t+2} + \varepsilon_{t+3}$$

$$Y_{t+h} = \ell_{t+h-1} + \varepsilon_{t+h}$$

$$= \ell_t + \sum_{i=1}^{h-1} \alpha \varepsilon_{t+i} + \varepsilon_{t+h}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Point forecast

Constant plus noise representation of future observations:

$$Y_{t+h} = \ell_t + \sum_{i=1}^{h-1} \alpha \varepsilon_{t+i} + \varepsilon_{t+h}$$

From the linearity of expectations, the point forecast for any horizon  $h$  is

$$\begin{aligned}\hat{y}_{t+h} &= E(Y_{t+h} | y_{1:t}) \\ &= E\left(\ell_t + \sum_{i=1}^{h-1} \alpha \varepsilon_{t+i} + \varepsilon_{t+h} \mid y_{1:t}\right) \\ &= \ell_t\end{aligned}$$

$\text{Var}(Y_{t+1}|y_{1:t}) = \text{Var}(\ell_t + \varepsilon_{t+1}|y_{1:t})$   
 $= \sigma^2$

Assignment Project Exam Help

$\text{Var}(Y_{t+2}|y_{1:t}) = \text{Var}(\ell_t + \alpha\varepsilon_{t+1} + \varepsilon_{t+2}|y_{1:t})$   
 $= \sigma^2(1 + \alpha^2)$

<https://powcoder.com>

Add WeChat powcoder

$\text{Var}(Y_{t+h}|y_{1:t}) = \text{Var}\left(\ell_t + \sum_{i=1}^h \alpha^i \varepsilon_{t+h-i} + \varepsilon_{t+h} \middle| y_{1:t}\right)$   
 $= \sigma^2(1 + (h-1)\alpha^2)$

Assignment Project Exam Help

$\hat{y}_{t+h} = \ell$   
<https://powcoder.com>

$\text{Var}(Y_{t+h}|y_{1:t}) = \sigma^2(1 + (h-1)\alpha^2)$   
Add WeChat powcoder

## Interval forecast

If we assume that  $\varepsilon_t \sim N(0, \sigma^2)$ ,

$$Y_{t+h} | y_{1:t} \sim N(\ell_t, \sigma^2 [1 + (h-1)\alpha^2]).$$

To compute an interval forecast, we use the estimated values of  $\alpha$  and  $\sigma^2$ .


$$\hat{\ell}_t \pm z_{\text{crit}} \times \sqrt{\hat{\sigma}^2 [1 + (h-1)\hat{\alpha}^2]},$$

where

$$\hat{\sigma}^2 = \frac{\sum_{t=1}^T (y_t - \hat{\ell}_{t-1})^2}{N-1}.$$

If the errors are not normal, you should use the Bootstrap method or other distributional assumptions.

## Example: AUD/USD exchange rate



# Assignment Project Exam Help

Trend corrected exponential  
smoothing <https://powcoder.com>

---

Add WeChat powcoder

## Trend corrected exponential smoothing

# Assignment Project Exam Help

The trend corrected or Holt exponential smoothing method allows for a time-varying trend:

$$\hat{y}_{t-1} = \ell_t + b_t \quad (\text{forecast equation})$$

$$\ell_t = \alpha y_t + (1 - \alpha)(\ell_{t-1} + b_{t-1}) \quad (\text{smoothing equation})$$

$$b_t = \beta(\ell_t - \ell_{t-1}) + (1 - \beta)b_{t-1} \quad (\text{trend equation})$$

# Add WeChat powcoder

for an initial values  $\ell_0$  and  $b_0$ ,  $0 \leq \alpha \leq 1$ , and  $0 \leq \beta \leq 1$ .

## Trend corrected exponential smoothing

# Assignment Project Exam Help

Consider the simple time series trend model

$$\ell_t = a + b \times t$$
$$Y_t = \ell_t + \varepsilon_t.$$

What is  $\ell_t - \ell_{t-1}$  here?

Add WeChat powcoder



## Trend corrected exponential smoothing model

The statistical model is

Assignment Project Exam Help

$$Y_{t+1} = \ell_t + b_t + \varepsilon_{t+1},$$

$$\ell_t = \alpha Y_t + (1 - \alpha)(\ell_{t-1} + b_{t-1}),$$

$$b_t = \beta(\ell_t - \ell_{t-1}) + (1 - \beta)b_{t-1},$$

<https://powcoder.com>

where the errors  $\varepsilon_t$  are i.i.d with constant variance  $\sigma^2$ .

The least squares estimates of  $\alpha$  and  $\beta$  are

Add WeChat powcoder

$$\hat{\alpha}, \hat{\beta} = \operatorname{argmin}_{\alpha, \beta} \sum_{t=1}^N (y_t - \ell_{t-1} - b_{t-1})^2$$

# Assignment Project Exam Help

$$\begin{aligned}\ell_t &= \alpha Y_t + (1 - \alpha)(\ell_{t-1} + b_{t-1}) \\ &= \ell_{t-1} + b_{t-1} + \alpha(Y_t - \ell_{t-1} - b_{t-1})\end{aligned}$$

$$= \ell_{t-1} + b_{t-1} + \alpha \varepsilon_t$$

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}b_t &= \beta(\ell_t - \ell_{t-1}) + (1 - \beta)b_{t-1} \\ &= b_{t-1} + \beta(\ell_t - \ell_{t-1} - b_{t-1}) \\ &= b_{t-1} + \beta\alpha(\ell_{t-1} + b_{t-1} + \alpha \varepsilon_t - \ell_{t-1} - b_{t-1}) \\ &= b_{t-1} + \beta\alpha \varepsilon_t\end{aligned}$$

# Assignment Project Exam Help

$$y_{t+1} = \ell_t + b_t + \varepsilon_{t+1}$$
$$\ell_t = \ell_{t-1} + b_{t-1} + \alpha \varepsilon_t$$
$$b_t = b_{t-1} + \beta \alpha \varepsilon_t$$

<https://powcoder.com>

Add WeChat powcoder

## Constant plus noise representation

$$Y_{t+1} = \ell_t + b_t + \varepsilon_{t+1}$$

$$Y_{t+2} = \ell_{t+1} + b_{t+1} + \varepsilon_{t+2}$$

$$= \ell_t + 2b_t + \alpha(1 + \beta)\varepsilon_{t+1} + \varepsilon_{t+2}$$

$$Y_{t+3} = \ell_{t+2} + b_{t+2} + \varepsilon_{t+3}$$

$$= \ell_{t+1} + 2b_{t+1} + \alpha(1 + \beta)\varepsilon_{t+2} + \varepsilon_{t+3}$$

$$= \ell_t + 3b_t + \alpha(1 + 2\beta)\varepsilon_{t+1} + \alpha(1 + \beta)\varepsilon_{t+2} + \varepsilon_{t+3}$$

$\vdots$

$$Y_{t+h} = \ell_t + hb_t + \alpha \sum_{i=1}^{h-1} (1 + i\beta)\varepsilon_{t+h-i} + \varepsilon_{t+h}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Point forecast

Constant plus noise representation of future observations:

$$Y_{t+h} = \ell_t + hb_t + \alpha \sum_{i=1}^{h-1} (1 + i\beta) \varepsilon_{t+h-i} + \varepsilon_{t+h}$$

From the linearity of expectations, the point forecast for any horizon  $h$  is

$$\begin{aligned}\hat{y}_{t+h} &= E(Y_{t+h} | y_{1:t}) \\ &= E\left(\ell_t + hb_t + \alpha \sum_{i=1}^{h-1} (1 + i\beta) \varepsilon_{t+h-i} + \varepsilon_{t+h} \mid y_{1:t}\right) \\ &= \ell_t + hb_t.\end{aligned}$$

## Forecast variance

$$\text{Var}(Y_{t+1}|y_{1:t}) = \text{Var}(\ell_t + b_t + \varepsilon_{t+1}|y_{1:t})$$

Assignment Project Exam Help

$$\begin{aligned}\text{Var}(Y_{t+2}|y_{1:t}) &= \text{Var}(\ell_t + 2b_t + \alpha(1 + \beta)\varepsilon_{t+1} + \varepsilon_{t+2}|y_{1:t}) \\ &= \sigma^2(1 + \alpha^2(1 + \beta)^2)\end{aligned}$$

$\vdots$

$$\begin{aligned}\text{Var}(Y_{t+h}|y_{1:t}) &= \text{Var}\left(\ell_t + hb_t + \alpha \sum_{i=1}^{h-1} (1 + i\beta)\varepsilon_{t+h-i} + \varepsilon_{t+h}|y_{1:t}\right) \\ &= \sigma^2 \left(1 + \alpha^2 \sum_{i=1}^{h-1} (1 + i\beta)^2\right)\end{aligned}$$

## Forecast equations for the trend corrected smoothing method

Point forecast:

Assignment Project Exam Help

$$\hat{y}_{t+h} = \hat{c}_t + h\hat{b}_t$$

Variance:


<https://powcoder.com>

$\text{Var}(Y_{t+h}|y_{1:t}) = \sigma^2 \left( 1 + \alpha^2 \sum_{i=1}^{h-1} (1 + i\beta)^2 \right)$

Add WeChat powcoder

We compute interval forecasts as before.

## Example: assaults in Sydney






## Example: assaults in Sydney


Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



## Example: visitor arrivals



## Example: visitor arrivals



# Assignment Project Exam Help

~~Holt winters smoothing~~  
<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

The ~~Holt-Winters~~ exponential smoothing method extend the trend corrected method to seasonal data. It allows for additive or multiplicative seasonality.

<https://powcoder.com>  
Add WeChat powcoder

## Additive Holt Winters Smoothing (key concept)

# Assignment Project Exam Help

$$\hat{y}_{t+1} = \ell_t + b_t + S_{t+1-L} \quad (\text{forecast equation})$$

$$\ell_t = \alpha(y_t - S_{t-L}) + (1 - \alpha)(\ell_{t-1} + b_{t-1}) \quad (\text{level})$$

$$b_t = \beta(\ell_t - \ell_{t-1}) + (1 - \beta)b_{t-1}, \quad (\text{trend})$$

$$S_t = \delta(y_t - \ell_t) + (1 - \delta)S_{t-L}, \quad (\text{seasonal indices})$$

## Add WeChat powcoder

for a seasonal frequency  $L$ , initial values  $\ell_0$ ,  $b_0$ , and  $S_{i-L}$  for  $i = 1, \dots, L$ , and parameters  $0 \leq \alpha \leq 1$ ,  $0 \leq \beta \leq 1$ ,  $0 \leq \delta \leq 1$ .

## Multiplicative Holt Winters Smoothing (key concept)

Assignment Project Exam Help

$$\hat{y}_{t+1} = (\ell_t + b_t) \times S_{t+1-L} \quad (\text{forecast equation})$$

$$\ell_t = \alpha(y_t/S_{t-L}) + (1 - \alpha)(\ell_{t-1} + b_{t-1}) \quad (\text{level})$$

$$b_t = \beta(\ell_t - \ell_{t-1}) + (1 - \beta)b_{t-1}, \quad (\text{trend})$$

$$S_t = \delta(y_t/\ell_t) + (1 - \delta)S_{t-L}, \quad (\text{seasonal indices})$$

Add WeChat powcoder

for a seasonal frequency  $L$ , initial values  $\ell_0$ ,  $b_0$ , and  $S_{i-L}$  for  $i = 1, \dots, L$ , and parameters  $0 \leq \alpha \leq 1$ ,  $0 \leq \beta \leq 1$ ,  $0 \leq \delta \leq 1$ .

## Statistical model

As before, we formulate a statistical model by specifying an observation equation.

# Assignment Project Exam Help

**Additive:**

$$Y_{t+1} = \ell_t + b_t + S_{t+1-L} + \varepsilon_{t+1},$$

<https://powcoder.com>

where  $\varepsilon_{t+1}$  is i.i.d with variance  $\sigma^2$

**Multiplicative:** Add WeChat powcoder

$$y_{t+1} = (\ell_t + b_t) \times S_{t+1-L} + \varepsilon_{t+1},$$

where  $\varepsilon_{t+1}$  is i.i.d with variance  $\sigma^2$ .



## Estimation

We estimate  $\alpha$ ,  $\beta$  and  $\delta$  by least squares.

# Assignment Project Exam Help

Additive:

$$\hat{\alpha}, \hat{\beta}, \hat{\delta} = \underset{\alpha, \beta, \delta}{\operatorname{argmin}} \sum_{t=1}^N (y_t - \ell_{t-1} - b_{t-1} - S_{t+1-L})^2$$

<https://powcoder.com>

Multiplicative:

# Add WeChat powcoder

$$\hat{\alpha}, \hat{\beta}, \hat{\delta} = \underset{\alpha, \beta, \delta}{\operatorname{argmin}} \sum_{t=1}^N (y_t - (\ell_t + b_t) \times S_{t+1-L})^2$$

## Forecast equations

### Additive:

$$\hat{y}_{t+h} = \hat{\ell}_t + h\hat{b}_t + S_{t-L+(h \bmod L)}$$

$$\text{Var}(Y_{t+h}|y_{1:t}) = \sigma^2 \left( 1 + \sum_{i=1}^{h-1} [\alpha(1+i\beta) + I_{i,L}\delta(1-\alpha)]^2 \right),$$


where  $\bmod$  is the modulo operator.  $I_{i,L} = 0$  if  $h \bmod L \neq i$  and  $I_{i,L} = 1$  if  $h \bmod L = i$ .

### Multiplicative:

$$\hat{y}_{t+h} = (\hat{\ell}_t + h\hat{b}_t) \times S_{t-L+(h \bmod L)}$$


No simple expression exists for the variance in the multiplicative model.

## Example: assaults in Sydney




The estimated parameters are  $\hat{\alpha} = 0.117$ ,  $\hat{\beta} = 0.023$ , and  $\hat{\delta} = 0.370$ .

## Example: visitor arrivals



The estimated parameters are  $\hat{\alpha} = 0.154$ ,  $\hat{\beta} = 0.088$ , and  $\hat{\delta} = 0.271$ .

## Example: visitor arrivals



# Assignment Project Exam Help

Damped trend exponential

smoothing <https://powcoder.com>

---

Add WeChat powcoder

# Assignment Project Exam Help

Damped trend exponential smoothing addresses the problem that extrapolating trends indefinitely into the future can lead to implausible forecasts.

<https://powcoder.com>  
Add WeChat powcoder

## Model and forecast

Model:

Assignment Project Exam Help

$$y_{t+h} = \ell_t + \phi b_t + \varepsilon_{t+h}$$

$$\ell_t = \alpha y_t + (1 - \alpha)(\ell_{t-1} + \phi b_{t-1}),$$

$$b_t = \beta(\ell_t - \ell_{t-1}) + (1 - \beta)\phi b_{t-1},$$

<https://powcoder.com>

where  $\phi$  is the damping parameter, with  $0 \leq \phi \leq 1$ .

Forecast equation


Add WeChat powcoder

$$\hat{y}_{t+h} = \ell_t + \phi b_t + \phi^2 b_t + \phi^3 b_t + \dots + \phi^h b_t$$

We can extend it to allow for additive or multiplicative seasonality.



## Illustration: visitor arrivals



## Review questions

# Assignment Project Exam Help

- What is exponential smoothing?

- What is the difference between simple, trend corrected, and Holt-Winters exponential smoothing methods?

- Derive the point forecasts and forecast variances for the SES and trend corrected methods, starting from the model equations.

- Explain how to compute forecast intervals based on the SES and trend corrected methods.

<https://powcoder.com>

Add WeChat powcoder