

# AREAL DATA

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

---

*STA465: Theory and Methods for Complex Spatial Data*

*Instructor: Dr. Vianey Leos Barajas*

# ANNOUNCEMENTS

---

- Hwk 1 Solution is online
- Hwk 2 is posted and due on Feb 22nd by 11:59 pm EST  
[Assignment Project Exam Help](#)  
<https://powcoder.com>
- Reading week: February 15-19 (no class)  
[Add WeChat powcoder](#)

# WHAT IS AREAL DATA?

---

- Areal or lattice data — when a fixed domain is partitioned into a finite number of subregions.
- Defined on a finite or countable subset in space — e.g. grid nodes, pixels, polygons, small areas
- Examples:
  - Number of cancer cases in counties (USA)
  - Number of road accidents in provinces
  - Proportion of people living in poverty in census tracts

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

# EXAMPLE DATA

---


Counties in Pennsylvania



# SPATIAL NEIGHBOURS — ADJACENCY

---


Counties in Pennsylvania



# SPATIAL NEIGHBOURS — DISTANCE

---

Counties in Pennsylvania



# SPATIAL NEIGHBORHOOD MATRIX

---

- Spatial neighborhood matrix:  $W$
- $(i,j)$ th element of spatial neighborhood denoted by  $w_{i,j}$   
spatially connects areas  $i$  and  $j$ 
  - Elements can be viewed as ‘weights’  
<https://powcoder.com>
  - More weight is associated with  $j$ ’s closer to  $i$  than those farther away from  $i$   
Add WeChat powcoder

# SPATIAL NEIGHBORHOOD MATRIX

---

- Simplest neighborhood definition:
  - $w_{ij} = 1$  if regions  $i$  and  $j$  share common boundary
  - $w_{ij} = 0$  otherwise
- Customarily,  $w_{ii} = 0$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# ELEMENTS OF A SPATIAL MODEL

---

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# BESAG-YORK-MOLLIÉ MODEL

---

- Takes into account that data may be spatially correlated
- Observations in neighbouring areas may be more similar than observations in areas that are farther away
- Model includes:
  - Spatial random effect that smoothes the data according to a neighborhood structure
  - Unstructured exchangeable component that models uncorrelated noise

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# BESAG-YORK-MOLLIÉ MODEL: EXAMPLE

---

- Assume we are interested in observed counts  $Y_i$  in area  $i$  for spatial small area disease risk estimation
- $Y_i \sim Po(E_i\theta_i), \quad i = 1, \dots, n$
- $\log(\theta_i) = \alpha + u_i + v_i$   

Assignment Project Exam Help  
<https://powcoder.com>
- $v_i \sim N(0, \sigma_v^2)$   

Add WeChat powcoder
- $E_i$  — expected counts
- $\theta_i$  — relative risk in area  $i$

# BESAG-YORK-MOLLIÉ MODEL: CAR

---

- $u_i | \mathbf{u}_{-i} \sim N\left(\bar{u}_{\delta_i}, \frac{\sigma_u^2}{n_{\delta_i}}\right)$
- $\bar{u}_{\delta_i} = n_{\delta_i}^{-1} \sum_{j \in \delta_i} u_j$  **Assignment Project Exam Help**  
<https://powcoder.com>
- $\delta_i$  = set of neighbours **Add WeChat powcoder**
- $n_{\delta_i}$  = number of neighbours over area  $i$

# NEXT TIME

---

- We'll put everything we've learned together:
  - Simulate from model with fixed values for parameters
  - Simulate from prior predictive
  - Fit the model
  - Simulation from posterior predictive
  - + Maps along the way!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder